Package: BASiCStan (via r-universe)

November 25, 2026

Title Stan implementation of BASiCS

Version 1.16.0

Date 2026-06-30

Description Provides an interface to infer the parameters of BASiCS using the variational inference (ADVI), Markov chain Monte Carlo (NUTS), and maximum a posteriori (BFGS) inference engines in the Stan programming language. BASiCS is a Bayesian hierarchical model that uses an adaptive Metropolis within Gibbs sampling scheme. Alternative inference methods provided by Stan may be preferable in some situations, for example for particularly large data or posterior distributions with difficult geometries.

License GPL-3

Encoding UTF-8

VignetteBuilder knitr

Roxygen list(markdown = TRUE)

Biarch true

Depends R (>= 4.2), BASiCS, rstan (>= 2.18.1)

Imports methods, glmGamPoi, scran, scuttle, stats, utils, SingleCellExperiment, SummarizedExperiment, Rcpp (>= 0.12.0), RcppParallel (>= 5.0.1), rstantools (>= 2.1.1)

LinkingTo BH (>= 1.66.0), Rcpp (>= 0.12.0), RcppEigen (>= 0.3.3.3.0), RcppParallel (>= 5.0.1), rstan (>= 2.18.1), StanHeaders (>= 2.18.0)

SystemRequirements GNU make

biocViews ImmunoOncology, Normalization, Sequencing, RNASeq, Software, GeneExpression, Transcriptomics, SingleCell, DifferentialExpression, Bayesian, CellBiology

URL https://github.com/Alanocallaghan/BASiCStan

BugReports https://github.com/Alanocallaghan/BASiCStan/issues

Suggests testthat (>= 3.0.0), knitr, rmarkdown

Config/testthat/edition 3

Config/roxygen2/version 8.0.0

Config/pak/sysreqs cmake libglpk-dev make libicu-dev libuv1-dev libxml2-dev libssl-dev zlib1g-dev

Repository Bioconductor 3.24

Date/Publication 2026-11-23 22:49:28 UTC

RemoteUrl https://github.com/bioc/BASiCStan

RemoteRef RELEASE_3_24

RemoteSha 58da8d84f9efe9d3afb5f971f98052259efeb85a

Contents

BASiCStan-package 2
BASiCStan 3
Stan2BASiCS 4

Index **6**

`BASiCStan-package` *The 'BASiCStan' package.*

Description

Provides an interface to infer the parameters of BASiCS using the variational inference (ADVI), Markov chain Monte Carlo (NUTS), and maximum a posteriori (BFGS) inference engines in the Stan programming language. BASiCS is a Bayesian hierarchical model that uses an adaptive Metropolis within Gibbs sampling scheme. Alternative inference methods provided by Stan may be preferable in some situations, for example for particularly large data or posterior distributions with difficult geometries. See also BASiCS_MCMC

Author(s)

Maintainer: Alan O'Callaghan <alan.ocallaghan@outlook.com>

Authors:

- Alan O'Callaghan <alan.ocallaghan@outlook.com>
- Catalina Vallejos

References

Stan Development Team (2020). RStan: the R interface to Stan. R package version 2.21.2. https://mc-stan.org

Vallejos, Marioni and Richardson (2015). PLoS Computational Biology. https://doi.org/10.1371/journal.pcbi.1004333.

Vallejos, Richardson and Marioni (2016). Genome Biology. https://doi.org/10.1186/s13059-016-0930-3

Eling et al (2018). Cell Systems. https://doi.org/10.1016/j.cels.2018.06.011

See Also

Useful links:

- https://github.com/Alanocallaghan/BASiCStan
- Report bugs at https://github.com/Alanocallaghan/BASiCStan/issues

---

`BASiCStan` *Stan implementation of BASiCS.*

Description

The stan programming language enables the use of MAP, VB, and HMC inference. Only the regression mode featuring a joint prior between mean and overdispersion parameters is implemented

Usage

```
BASiCStan(
  Data,
  Method = c("vb", "sampling", "optimizing"),
  WithSpikes = length(altExpNames(Data)) > 0,
  Regression = TRUE,
  BatchInfo = Data$BatchInfo,
  L = 12,
  PriorMu = c("EmpiricalBayes", "uninformative"),
  NormFactorFun = scran::calculateSumFactors,
  ReturnBASiCS = TRUE,
  Verbose = TRUE,
  ...
)
```

Arguments

`Data`	SingleCellExperiment object
`Method`	Inference method. One of: `"vb"` for Variational Bayes, `"sampling"` for Hamiltonian Monte Carlo, `"optimizing"` for or maximum *a posteriori* estimation.
`WithSpikes`	Do the data contain spike-in genes? See BASiCS for details. When `WithSpikes=FALSE`, the cell-specific scaling normalisation factors are fixed; use `NormFactorFun` to specify how size factors should be generated or extracted.
`Regression`	Use joint prior for mean and overdispersion parameters? Included for compatibility with `BASiCS_MCMC`, but only `TRUE` is supported.
`BatchInfo`	Vector describing which batch each cell is from.
`L`	Number of regression terms (including slope and intercept) to use in joint prior for mu and delta.
`PriorMu`	Type of prior to use for mean expression. Default is "EmpiricalBayes", but "uninformative" is the prior used in Eling et al. and previous work.

NormFactorFun	Function that returns cell-specific scaling normalisation factors. See computeSumFactors for details on the default.
ReturnBASiCS	Should the object be converted into a BASiCS_Chain-class object?
Verbose	Should output of the stan commands be printed to the terminal?
...	Passed to vb or sampling.

Value

An object of class BASiCS_Chain-class.

Examples

```
library("BASiCS")
sce <- BASiCS_MockSCE(NGenes = 10, NCells = 10)

fit_spikes <- BASiCStan(sce, tol_rel_obj = 1)

## uses fixed scaling normalisation factors
fit_nospikes <- BASiCStan(sce, WithSpikes = FALSE, tol_rel_obj = 1)
```

Stan2BASiCS *Convert Stan fits to BASiCS_Chain-class objects.*

Description

Convert Stan fits to BASiCS_Chain-class objects.

Usage

```
Stan2BASiCS(
  x,
  gene_names = attr(x, "gene_names"),
  cell_names = attr(x, "cell_names"),
  size_factors = attr(x, "size_factors")
)
```

Arguments

x	A stan object
gene_names, cell_names	Gene and cell names. The reason this argument exists is that by default, stan fit parameters are not named. NOTE: this must be the same order as the data supplied to BASiCStan.
size_factors	Cell-specific scaling normalisation factors, to be stored as part of the chain object when WithSpikes=FALSE.

Value

A BASiCS_Chain-class object.

Examples

```
library("BASiCS")
sce <- BASiCS_MockSCE(NGenes = 10, NCells = 10)

fit_spikes <- BASiCStan(sce, ReturnBASiCS = FALSE, tol_rel_obj = 1)
summary(fit_spikes)
```

Index

BASiCS_Chain-class, *4*
BASiCS_MCMC, *2, 3*
BASiCStan, 3, *4*
BASiCStan-package, 2

computeSumFactors, *4*

Stan2BASiCS, 4