Package: BiocCheck (via r-universe)

October 31, 2026

Title Bioconductor-specific package checks

Version 1.48.1

Date 2026-06-30

Description BiocCheck guides maintainers through Bioconductor best practicies. It runs Bioconductor-specific package checks by searching through package code, examples, and vignettes. Maintainers are required to address all errors, warnings, and most notes produced.

License Artistic-2.0

URL https://github.com/Bioconductor/BiocCheck

BugReports https://github.com/Bioconductor/BiocCheck/issues

Depends R (>= 4.4.0)

Imports BiocBaseUtils, BiocFileCache, BiocManager, biocViews, callr, cli, codetools, commonmark, graph, httr2, knitr, methods, rvest, stringdist, tools, utils, xml2

Suggests BiocStyle, devtools, gert, jsonlite, rmarkdown, tinytest, usethis

VignetteBuilder knitr

biocViews Infrastructure

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Config/pak/sysreqs make libicu-dev libxml2-dev libssl-dev

Repository Bioconductor 3.23

Date/Publication 2026-06-30 19:34:51 UTC

RemoteUrl https://github.com/bioc/BiocCheck

RemoteRef RELEASE_3_23

RemoteSha 6029e2b898d3f78636a039c5e8f1b6633b3d364e

Contents

BiocCheck 2
BiocCheck-class 5
BiocCheckGitClone 7

Index **9**

`BiocCheck` *Check a package's adherence with the Bioconductor Package Guidelines*

Description

Analyzes an R package for adherence with Bioconductor package guidelines and best practices. The check outputs are categorized into ERROR, WARNING, and NOTE. See the vignette for more details. `BiocCheck` is complementary to `R CMD check`, which should always be run first.

Usage

```
BiocCheck(
  package = getwd(),
  checkDir = dirname(package),
  debug = FALSE,
  callr = FALSE,
  ...
)
```

Arguments

`package`	The path to an R package directory or tarball (`.tar.gz`). The `BiocCheck` function is intended to be run from the package directory; therefore, the current working directory (given by `getwd()`) is the default.
`checkDir`	The directory where the `BiocCheck` output directory will be stored. By default, it will be placed in the same directory as the package directory i.e., `dirname(pkg_dir)`.
`debug`	Whether to append the names of functions that correspond to each condition raised by `BiocCheck` in the written log (i.e., in the `'<package_name>.BiocCheck'` folder). This option is only relevant to developers and contributors to `BiocCheck`.
`callr`	logical(1) Whether to use the `callr` package to run `BiocCheck` in an isolated R session to prevent namespace collisions.
`...`	See the `dot-options` details section for available options.

Details

BiocCheck() reviews R packages for adherence with Bioconductor package guidelines and best practices. See https://contributions.bioconductor.org for the latest guidance for writing Bioconductor software. Some rationale behind these best practices can be seen in the vignette and pages in the references section. The vignette also provides detailed explanations of all the checks performed by BiocCheck.

BiocCheck is called within R with BiocCheck("package") where package points to the source directory or the .tar.gz tarball that was created using R CMD build.

Note that BiocCheck is complementary to R CMD check. R CMD check should always be run first for best results.

To skip installation of the package during the check, set the install option to FALSE or NULL:

```
BiocCheck(package, install=FALSE)
## OR
BiocCheck(package, install=NULL)
```

To re-use an existing installation log file, set the install option to the name of the installation log file. For example, the following will put the install_out.txt log file in the <package_name>.BiocCheck directory: BiocCheck(package, install="check:install_out.txt")

Value

BiocCheck() is chiefly called for the side effect of the check reporting. The function also creates a <package_name>.BiocCheck folder and returns a BiocCheck reference class with three main list elements:

- **error**: Items to address before the package can be accepted
- **warning**: Strongly suggested items that may require attention
- **note**: Items to consider, though not required, before acceptance

dot-options

To use the dot-options, BiocCheck can be called with named arguments corresponding to the options below. Typically, these options are set to TRUE to disable specific checks, e.g., BiocCheck(package, 'no-check-vignettes'=TRUE). Unless otherwise stated, these options can be left unset (i.e., NULL) to enable checks but FALSE can also be used to explicitly enable them. The available options are:

- build-output-file: file containing R CMD build output, for additional analysis
- new-package: enable checks specific to new packages
- no-check-bbs: disable BBS-specific checks (for non-BioC packages). Valid DESCRIPTION
- no-check-bioc-help: disable check for registration on Bioconductor
- no-check-bioc-views: disable biocViews-specific checks (for non-BioC packages) mailing list and support site
- no-check-coding-practices: disable check for some common best coding practices
- no-check-CRAN: disable check for if package exists in CRAN

- `no-check-dependencies`: disable check for bad dependencies
- `no-check-deprecated`: disable check for usage of deprecated packages
- `no-check-description`: disable DESCRIPTION file checks
- `no-check-file-size`: disable check for individual file size
- `no-check-formatting`: disable checks for file formatting
- `no-check-function-len`: disable check for function length
- `no-check-install-self`: disable check for require or library of itself
- `no-check-library-calls`: disable check usage of functions that install or update packages
- `no-check-man-doc`: disable checks for man page documentation
- `no-check-namespace`: disable NAMESPACE file checks
- `no-check-news`: disable checks for NEWS file
- `no-check-pkg-size`: disable check for package tarball size
- `no-check-R-ver`: disable check for valid R version
- `no-check-remotes`: disable check for usage of remote packages other than those hosted on CRAN or Bioconductor
- `no-check-skip-bioc-tests`: disable check for tests that skip when on bioc
- `no-check-unit-tests`: disable checks for unit tests
- `no-check-version-num`: disable check for valid version number
- `no-check-vignettes`: disable vignette checks
- `quit-with-status`: enable exit code option when performing check
- `install`: if `FALSE`, the package is not installed; otherwise, if not specified, the package is installed by default. Optionally, a `check:<file>` key-value pair is provided to identify the name of the installation output file which will be copied to the `<package_name>.BiocCheck` directory.
- `libloc`: when `install` is specified, the library location where the package is installed. By default, this is `.libPaths()[1]`.

Author(s)

Dan Tenenbaum, Lori Shepherd, and Marcel Ramos

References

https://contributions.bioconductor.org

See Also

BiocCheck, Message

Examples

```
packageDir <- system.file("testpackages", "testpkg0", package="BiocCheck")
BiocCheck(packageDir, `quit-with-status`=FALSE)
```

BiocCheck-class *An internal class for composing BiocCheck reports*

Description

The BiocCheck class provides a framework for reporting checks based on Bioconductor guidelines. The class has several methods for working with the provided checks that handle and display messages and the display of the metadata. These methods also record the output of the BiocCheck() report in both plain text and JSON formats.

Note that currently, multiple BiocCheck runs will interfere with each other given that they are implemented via a reference class semantic. When running multiple checks in the same session, you can separate these instances by running them in separate processes (e.g., via BiocParallel).

Arguments

...	character() A vector that makes up the BiocCheck exception message (e.g., 'Vignette must be built by R CMD build'). The character vector is handled with paste0 and made into a list and appended with help_text and messages.
help_text	character(1) Additional text prompting a list of files (e.g,. "Found in files:")
condition	character(1) One of the three conditions handled: error, warning, or note
messages	character() Often a vector of file names where the check was triggered.
debug	logical(1) Whether to append the name of the originating check name into for trace-ability
checkName	character(1) The title of the current group of checks. It can be set with handleCheck, e.g., handleCheck("Checking for version number mismatch..."). Internally, it ' is saved with setCheck and obtained with getLastCheck.
isOnBBS	logical(1) Indicates whether the checks are being run on the Bioconductor Build System (BBS). This is helpful for avoiding the creation of folders in the BBS.
file	character(1) A path to a JSON file for writing or reading as created by toJSON and fromJSON BiocCheck methods.

Details

The metadata includes a number of standard fields to allow easier troubleshooting and display of potentially relevant information. Currently, the fields included are:

- BiocCheckVersion: The version of the BiocCheck package
- BiocVersion: The version of Bioconductor
- Package: The name of the package in check
- PackageVersion: The version of the package in check
- sourceDir: The directory of the package source or tarball in check
- installDir: The directory where the package is installed for testing, a temporary location by default

- BiocCheckDir: The directory where the `<package>.BiocCheck` folder is saved. Usually the same folder as the package in check
- platform: The platform/OS where the check is taking place
- isTarBall: Whether the package in check is a source directory or a tarball

Value

An internal `BiocCheck` R5 Reference Class used to document conditions such as errors, warnings, and notes

Fields

`log list()` A running list of all conditions raised (i.e., notes, warnings, errors)

`check character(1)` The title of the last check used for logging purposes.

`error,warning,note list()` Finer extraction of each condition type

`metadata list()` A list of additional information relevant to the package and its state. See details.

methods

- `add`: Include a condition to the `BiocCheck` report
- `addMetadata`: Add metadata to the `BiocCheck` object from a `BiocPackage` object
- `getLastCheck`: Obtain the name of the last check run
- `setCheck`: Create a new element in the internal list for a check
- `get`: Extract the list of conditions raised by `BiocCheck`
- `getNum`: Tally the number of condition provided by the input
- `zero`: Reset the internal log of the condition provided
- `getBiocCheckDir`: Report and create the `<package>.BiocCheck` directory as obtained from the metadata
- `composeReport`: Simplify the list structure from the `log` and provide a character vector of conditions raised
- `report`: Write the `00BiocCheck.log` report into the `BiocCheck` folder
- `toJSON`: Write a JSON file to the location indicated with the conditions raised
- `fromJSON`: Read a JSON file from the location indicated with the output of previous conditions raised in the check
- `show`: Display the information in the class. Currently empty.
- `show_meta`: Display the metadata information stored in the `metadata` field

See Also

Message, BiocPackage

Examples

```
bc <- BiocCheck:::.BiocCheck
```

`BiocCheckGitClone` *Checks specific to a Git clone of a package repository*

Description

Analyzes an R package for adherence with Bioconductor package guidelines and best practices. The check outputs are categorized into ERROR, WARNING, and NOTE. This function is typically used in the Bioconductor Build System (BBS) and not intended for general use.

Usage

```
BiocCheckGitClone(package = ".", ...)
```

Arguments

`package`	A directory containing an R source package. Not a package tar ball.
`...`	Currently, only `quit-with-status` is available. See `BiocCheck`

Details

`BiocCheckGitClone()` reviews R packages for adherence with Bioconductor package guidelines and best practices. See https://contributions.bioconductor.org for the latest guidance for writing Bioconductor software. This function should only be run on a source directory and not on a tarball.

`BiocCheckGitClone` is called within R with, as `BiocCheckGitClone("package")` where `package` is the source directory containing the `R` package.

Value

`BiocCheckGitClone()` is chiefly called for the side effect of the check reporting. The function returns a `BiocCheck` reference class with three main list elements:

- error: Items to address before the package can be accepted
- warning: Strongly suggested items that may require attention
- note: Items to consider, though not required, before acceptance

Author(s)

Lori Shepherd

References

https://contributions.bioconductor.org

See Also

BiocCheck

Examples

```
packageDir <- system.file("testpackages", "testpkg0", package="BiocCheck")
BiocCheckGitClone(packageDir, `quit-with-status`=FALSE)
```

Index

BiocCheck, 2, *4*, *7*
BiocCheck-class, 5
BiocCheckGitClone, 7
BiocPackage, *6*

Message, *4*, *6*