

Package: ClusterFoldSimilarity (via r-universe)

October 11, 2026

Type Package

Title Calculate similarity of clusters from different single cell samples using foldchanges

Version 1.8.0

Description This package calculates a similarity coefficient using the fold changes of shared features (e.g. genes) among clusters of different samples/batches/datasets. The similarity coefficient is calculated using the dot-product (Hadamard product) of every pairwise combination of Fold Changes between a source cluster i of sample/dataset n and all the target clusters j in sample/dataset m

License Artistic-2.0

Encoding UTF-8

Imports methods, igraph, ggplot2, scales, BiocParallel, graphics, stats, utils, Matrix, cowplot, dplyr, reshape2, Seurat, SeuratObject, SingleCellExperiment, ggdendro

Suggests knitr, rmarkdown, kableExtra, scRNAseq, BiocStyle

RoxygenNote 7.2.3

biocViews SingleCell, Clustering, FeatureExtraction, GraphAndNetwork, GeneTarget, RNASeq

VignetteBuilder knitr

Config/pak/sysreqs cmake libglpk-dev make libicu-dev libpng-dev libuv1-dev libxml2-dev libssl-dev python3 zlib1g-dev

Repository Bioconductor 3.23

Date/Publication 2026-04-28 13:01:59 UTC

RemoteUrl <https://github.com/bioc/ClusterFoldSimilarity>

RemoteRef RELEASE_3_23

RemoteSha ebc46cd2827ca68b358fb4017d2de08b856a1ed6

Contents

clusterFoldSimilarity	2
findCommunitiesSimmilarity	4
plotClustersGraph	5
similarityHeatmap	7
Index	9

clusterFoldSimilarity	<i>Calculate cluster similarity between clusters from different single cell samples.</i>
-----------------------	--

Description

‘clusterFoldSimilarity()’ returns a dataframe containing the best top similarities between all possible pairs of single cell samples.

Usage

```
clusterFoldSimilarity(
  scList = NULL,
  sampleNames = NULL,
  topN = 1,
  topNFeatures = 1,
  nSubsampling = 15,
  parallel = FALSE
)
```

Arguments

scList	List. A list of Single Cell Experiments or Seurat objects. At least 2 are needed. The objects are expected to have cluster or label groups set as identity class.
sampleNames	Character Vector. Specify the sample names, if not a number corresponding with its position on (scList).
topN	Numeric. Specifies the number of target clusters with best similarity to report for each cluster comparison (default 1). If set to Inf, then all similarity values from all possible pairs of clusters are returned.
topNFeatures	Numeric. Number of top features that explains the clusters similarity to report for each cluster comparison (default 1). If topN = Inf then topNFeatures is automatically set to 1.
nSubsampling	Numeric. Number of random sampling of cells to achieve fold change stability (default 15).
parallel	Boolean. Whether to use parallel computing using BiocParallel or not (default FALSE).

Details

This function will calculate a similarity coefficient using the fold changes of shared features (e.g.: genes for a single-cell RNA-Seq, peaks for ATAC-Seq) among clusters, or user-defined-groups, from different samples/batches. The similarity coefficient is calculated using the dotproduct of every pair-wise combination of Fold Changes between a source cluster/group *i* from sample *n* and all the target clusters/groups in sample *j*.

Value

The function returns a `DataFrame` containing the best top similarities between all possible pairs of single cell samples. Column values are:

<code>similarityValue</code>	The top similarity value calculated between <code>datasetL:clusterL</code> and <code>datasetR</code> .
<code>w</code>	Weight associated with the similarity score value.
<code>datasetL</code>	Dataset left, the dataset/sample which has been used to be compared.
<code>clusterL</code>	Cluster left, the cluster source from <code>datasetL</code> which has been compared.
<code>datasetR</code>	Dataset right, the dataset/sample used for comparison against <code>datasetL</code> .
<code>clusterR</code>	Cluster right, the cluster target from <code>datasetR</code> which is being compared with the <code>clusterL</code> from <code>datasetL</code> .
<code>topFeatureConserved</code>	The features (e.g.: genes, peaks...) that most contributed to the similarity between <code>clusterL</code> & <code>clusterR</code> .
<code>featureScore</code>	The similarity score contribution for the specific <code>topFeatureConserved</code> (e.g.: genes, peaks...).

Author(s)

Oscar Gonzalez-Velasco

Examples

```
if (requireNamespace("Seurat") & requireNamespace("SeuratObject")){
  library(ClusterFoldSimilarity)
  library(Seurat)
  library(SeuratObject)
  # data dimensions
  nfeatures <- 2000; ncells <- 400
  # single-cell 1
  counts <- matrix(rpois(n=nfeatures * ncells, lambda=10), nfeatures)
  rownames(counts) <- paste0("gene", seq(nfeatures))
  colnames(counts) <- paste0("cell", seq(ncells))
  colData <- data.frame(cluster=sample(c("Cluster1", "Cluster2", "Cluster3"), size = ncells, replace = TRUE),
                        row.names=paste0("cell", seq(ncells)))
  seu1 <- SeuratObject::CreateSeuratObject(counts = counts, meta.data = colData)
  Idents(object = seu1) <- "cluster"
  # single-cell 2
```

```

counts <- matrix(rpois(n=nfeatures * ncells, lambda=20), nfeatures)
rownames(counts) <- paste0("gene",seq(nfeatures))
colnames(counts) <- paste0("cell",seq(ncells))
colData <- data.frame(cluster=sample(c("Cluster1","Cluster2","Cluster3","Cluster4"),size = ncells,replace = TRUE),
                      row.names=paste0("cell",seq(ncells)))
seu2 <- SeuratObject::CreateSeuratObject(counts = counts, meta.data = colData)
Idents(object = seu2) <- "cluster"
# Create a list with the unprocessed single-cell datasets
singlecellObjectList <- list(seu1, seu2)

similarityTable <- clusterFoldSimilarity(scList=singlecellObjectList, sampleNames = c("sc1","sc2"))
head(similarityTable)
}

```

findCommunitiesSimilarity

Find cell-group communities by constructing and clustering a directed graph using the similarity values calculated by ClusterFoldSimilarity()

Description

‘findCommunitiesSimilarity()’ Find communities by constructing and clustering graph using the similarity values calculated by ClusterFoldSimilarity().

Usage

```
findCommunitiesSimilarity(similarityTable = NULL)
```

Arguments

similarityTable

Dataframe. A table obtained from ClusterFoldSimilarity that contains the similarity values as a column "similarityValue" that represents the similarity of a source cluster to a target cluster.

Details

This function will group together nodes of the network into communities using the InfoMap community detection algorithm.

Value

This function returns a data frame with the community that each node of the network (cell groups defined by the user) belongs to, and plots a graph in which the nodes are clusters from a specific dataset, the edges represent the similarity and the direction of that similarity between clusters.

sample	The sample name.
group	The group/cluster from sample defined by the user.
community	Community group to which the sample:group belongs to.

Author(s)

Oscar Gonzalez-Velasco

Examples

```

if (requireNamespace("Seurat") & requireNamespace("SeuratObject")){
  library(ClusterFoldSimilarity)
  library(Seurat)
  library(SeuratObject)
  # data dimensions
  nfeatures <- 2000; ncells <- 400
  # single-cell 1
  counts <- matrix(rpois(n=nfeatures * ncells, lambda=10), nfeatures)
  rownames(counts) <- paste0("gene",seq(nfeatures))
  colnames(counts) <- paste0("cell",seq(ncells))
  colData <- data.frame(cluster=sample(c("Cluster1","Cluster2","Cluster3"),size = ncells,replace = TRUE),
                        row.names=paste0("cell",seq(ncells)))
  seu1 <- SeuratObject::CreateSeuratObject(counts = counts, meta.data = colData)
  Idents(object = seu1) <- "cluster"
  # single-cell 2
  counts <- matrix(rpois(n=nfeatures * ncells, lambda=10), nfeatures)
  rownames(counts) <- paste0("gene",seq(nfeatures))
  colnames(counts) <- paste0("cell",seq(ncells))
  colData <- data.frame(cluster=sample(c("Cluster1","Cluster2","Cluster3","Cluster4"),size = ncells,replace = TRUE),
                        row.names=paste0("cell",seq(ncells)))
  seu2 <- SeuratObject::CreateSeuratObject(counts = counts, meta.data = colData)
  Idents(object = seu2) <- "cluster"
  # Create a list with the unprocessed single-cell datasets
  singlecellObjectList <- list(seu1, seu2)

  similarityTable <- clusterFoldSimilarity(scList = singlecellObjectList, sampleNames = c("sc1","sc2"))
  head(similarityTable)
  findCommunitiesSimmlarity(similarityTable=similarityTable)
}

```

plotClustersGraph	<i>Creates a graph plot using the similarity values calculated with ClusterFoldSimilarity().</i>
-------------------	--

Description

'plotClustersGraph()' Creates a graph plot using the similarity values calculated with ClusterFoldSimilarity().

Usage

```
plotClustersGraph(similarityTable = NULL)
```

Arguments

similarityTable

Dataframe. A table obtained from ClusterFoldSimilarity that contains the similarity values as a column "similarityValue" that represents the similarity of a source cluster to a target cluster.

Details

This function will calculate a similarity coefficient using the fold changes of shared genes among clusters of different samples/batches. The similarity coefficient is calculated using the dotproduct of every pairwise combination of Fold Changes between a source cluster *i* of sample *n* and all the target clusters in sample *j*.

Value

This function plots a graph in which the nodes are clusters from a specific dataset, the edges represent the similarity and the direction of that similarity between clusters.

Author(s)

Oscar Gonzalez-Velasco

Examples

```
if (requireNamespace("Seurat") & requireNamespace("SeuratObject")){
  library(ClusterFoldSimilarity)
  library(Seurat)
  library(SeuratObject)
  # data dimensions
  nfeatures <- 2000; ncells <- 400
  # single-cell 1
  counts <- matrix(rpois(n=nfeatures * ncells, lambda=10), nfeatures)
  rownames(counts) <- paste0("gene",seq(nfeatures))
  colnames(counts) <- paste0("cell",seq(ncells))
  colData <- data.frame(cluster=sample(c("Cluster1","Cluster2","Cluster3"),size = ncells,replace = TRUE),
    row.names=paste0("cell",seq(ncells)))
  seu1 <- SeuratObject::CreateSeuratObject(counts = counts, meta.data = colData)
  Idents(object = seu1) <- "cluster"
  # single-cell 2
  counts <- matrix(rpois(n=nfeatures * ncells, lambda=10), nfeatures)
  rownames(counts) <- paste0("gene",seq(nfeatures))
  colnames(counts) <- paste0("cell",seq(ncells))
```

```
colData <- data.frame(cluster=sample(c("Cluster1","Cluster2","Cluster3","Cluster4"),size = ncells,replace = TRUE),
                      row.names=paste0("cell",seq(ncells)))
seu2 <- SeuratObject::CreateSeuratObject(counts = counts, meta.data = colData)
Idents(object = seu2) <- "cluster"
# Create a list with the unprocessed single-cell datasets
singlecellObjectList <- list(seu1, seu2)

similarityTable <- clusterFoldSimilarity(scList = singlecellObjectList, sampleNames = c("sc1","sc2"))
head(similarityTable)
plotClustersGraph(similarityTable=similarityTable)
}
```

similarityHeatmap	<i>Plot a heatmap of the similarity values obtained using cluster fold similarity</i>
-------------------	---

Description

‘similarityHeatmap()’ returns a ggplot heatmap representing the similarity values between pairs of clusters as obtained from [clusterFoldSimilarity](#).

Usage

```
similarityHeatmap(
  similarityTable = NULL,
  mainDataset = NULL,
  otherDatasets = NULL,
  highlightTop = TRUE
)
```

Arguments

similarityTable	A DataFrame containing the similarities between all possible pairs of single cell samples obtained with clusterFoldSimilarity using the option <code>n_top=Inf</code> .
mainDataset	Numeric. Specify the main dataset (y axis). It corresponds with the datasetL column from the similarityTable
otherDatasets	Numeric. Specify some specific dataset to be plotted along the mainDataset (x axis, default: all other datasets found on datasetR column from similarity_table).
highlightTop	Boolean. If the top 2 similarity values should be highlighted on the heatmap (default: TRUE)

Details

This function plots a heatmap using ggplot. It is intended to be used with the output table from [clusterFoldSimilarity](#), which includes the columns: datasetL (the dataset used for comparison) datasetR (the dataset against datasetL has been contrasted), clusterL (clusters from datasetL), clusterR (clusters from datasetR) and the similarityValue.

Value

The function returns a heatmap ggplot object.

Author(s)

Oscar Gonzalez-Velasco

Examples

```
if (requireNamespace("Seurat") & requireNamespace("SeuratObject")){
  library(ClusterFoldSimilarity)
  library(Seurat)
  library(SeuratObject)
  # data dimensions
  nfeatures <- 2000; ncells <- 400
  # single-cell 1
  counts <- matrix(rpois(n=nfeatures * ncells, lambda=10), nfeatures)
  rownames(counts) <- paste0("gene",seq(nfeatures))
  colnames(counts) <- paste0("cell",seq(ncells))
  colData <- data.frame(cluster=sample(c("Cluster1","Cluster2","Cluster3"),size = ncells,replace = TRUE),
                        row.names=paste0("cell",seq(ncells)))
  seu1 <- SeuratObject::CreateSeuratObject(counts = counts, meta.data = colData)
  Idents(object = seu1) <- "cluster"
  # single-cell 2
  counts <- matrix(rpois(n=nfeatures * ncells, lambda=10), nfeatures)
  rownames(counts) <- paste0("gene",seq(nfeatures))
  colnames(counts) <- paste0("cell",seq(ncells))
  colData <- data.frame(cluster=sample(c("Cluster1","Cluster2","Cluster3","Cluster4"),size = ncells,replace = TRUE),
                        row.names=paste0("cell",seq(ncells)))
  seu2 <- SeuratObject::CreateSeuratObject(counts = counts, meta.data = colData)
  Idents(object = seu2) <- "cluster"
  # Create a list with the unprocessed single-cell datasets
  singlecellObjectList <- list(seu1, seu2)
  # Using topN = Inf by default plots a heatmap using the similarity values:
  similarityTableAll <- clusterFoldSimilarity(scList=singlecellObjectList, topN=Inf)
  # Using the dataset 2 as a reference on the Y-axis of the heatmap:
  similarityHeatmap(similarityTable=similarityTableAll, mainDataset=2, highlightTop=FALSE)
}
```

Index

`clusterFoldSimilarity`, [2](#), [7](#)

`findCommunitiesSimmilarity`, [4](#)

`plotClustersGraph`, [5](#)

`similarityHeatmap`, [7](#)