Package: CompensAID (via r-universe)

November 2, 2026

Type Package

Title Automated detection tool for spillover errors

Version 1.0.0

Description The CompensAID is an automated quality control tool, which determines for each marker combination in the FCS file, whether there a potential presence of reference errors. Such reference errors, which represent themselves in the form of skewed populations, are detected by integrating the Secondary Stain Index (SSI) score. Marker combinations with an SSI < 1 are flagged by CompensAID.

URL https://github.com/Olsman/CompensAID

BugReports https://github.com/Olsman/CompensAID/issues

Depends R (>= 4.1.0)

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.3

Imports checkmate, dplyr, flowCore, flowDensity, ggcyto, ggplot2 (>= 3.5.2), methods, ParallelLogger, reshape2, rlang, stats, tibble, tidyr, utils

biocViews FlowCytometry, QualityControl, Preprocessing

Suggests knitr, rmarkdown, testthat (>= 3.0.0), BiocStyle

VignetteBuilder knitr

Config/testthat/edition 3

Config/pak/sysreqs cmake make libicu-dev libjpeg-dev libpng-dev libxml2-dev libssl-dev zlib1g-dev

Repository Bioconductor 3.23

Date/Publication 2026-04-28 13:06:16 UTC

RemoteUrl https://github.com/bioc/CompensAID

RemoteRef RELEASE_3_23

RemoteSha 80ad4954699ed0d366cebda295f8e1c7a2a0f80c

Contents

CompensAID 2
PlotDotSSI 3
PlotMatrix 4

Index **5**

`CompensAID` *CompensAID*

Description

Run CompensAID to assess the potential presence of reference errors within the FCS file. The outcome is a list which contains an SSI matrix. The matrix quickly visualizes the marker combinations for each marker combinations. Additional information regarding the number of events per segments, which segments were merged, and the corresponding SSI values can be found in the Info dataframe.

Usage

```
CompensAID(ff, segment.value = 4, events.value = 50)
```

Arguments

`ff`	(FlowFrame): FlowFrame containing the expression matrix, channel names, and marker names.
`segment.value`	(numerical): Numerical value of the number of segments in the primary positive population.
`events.value`	(numerical): Numerical value of the minimum number of events per population/segment.

Value

(list) Returns a list containing the full SSI output and SSI matrix

Examples

```
# Import FCS file
file <- flowCore::read.FCS(system.file("extdata", "68983.fcs", package = "CompensAID"))

# Run CompensAID tool
compensAID.res <- CompensAID(ff = file)
```

PlotDotSSI *Plot dot plot of Secondary Stain Index scores*

Description

This function plots the marker combinations of interest. Additionally, the gating, segmentation, and SSI values can be visualized by setting showScore to TRUE.

Usage

```
PlotDotSSI(output, og, primary, secondary, showScores = TRUE)
```

Arguments

output	(matrix): Matrix containing the SSI output from the CompensAID tool.
og	(flowFrame): FlowFrame containing the expression matrix, channel names, and marker names.
primary	(character): Primary marker (x-axis)
secondary	(character): Seconday marker (y-axis)
showScores	(boolean): Boolean variable determining if scores and gating should be visualized.

Value

(ggplot2) Returns figure containing a dot plot of the CompensAID output.

See Also

CompensAID

Examples

```
# Import FCS file
file <- flowCore::read.FCS(system.file("extdata", "68983.fcs", package = "CompensAID"))

# Run compensAID tool
compensAID.res <- CompensAID(ff = file)

# Marker names
primary.marker <- "CD19"
secondary.marker <- "CD3"

# Plot matrix
figure <- PlotDotSSI(output = compensAID.res,
                     og = file,
                     primary = primary.marker,
                     secondary = secondary.marker,
                     showScores = TRUE)
```

```
plot(figure)
```

`PlotMatrix` *Plot Secondary Stain Index matrix*

Description

This function plot the SSI matrix, quickly allowing the identification of potential reference errors if a SSI < -1 is obtained.

Usage

```
PlotMatrix(output)
```

Arguments

`output`	(matrix): Matrix containing the SSI output.

Value

(ggplot2) Returns figure containing a matrix of the total compensAID output.

See Also

`CompensAID`

Examples

```
# Import FCS file
file <- flowCore::read.FCS(system.file("extdata", "68983.fcs", package = "CompensAID"))

# Run compensAID tool
compensAID.res <- CompensAID(ff = file)

# Plot matrix
figure <- PlotMatrix(output = compensAID.res)
plot(figure)
```

Index

CompensAID, 2, *3*, *4*

PlotDotSSI, 3
PlotMatrix, 4