

Package: DELocal (via r-universe)

October 11, 2026

Title Identifies differentially expressed genes with respect to other local genes

Version 1.12.0

Description The goal of DELocal is to identify DE genes compared to their neighboring genes from the same chromosomal location. It has been shown that genes of related functions are generally very far from each other in the chromosome. DELocal utilizes this information to identify DE genes comparing with their neighbouring genes.

License MIT + file LICENSE

URL <https://github.com/dasroy/DELocal>

BugReports <https://github.com/dasroy/DELocal/issues>

Encoding UTF-8

LazyData false

RoxygenNote 7.2.3

biocViews GeneExpression, DifferentialExpression, RNASeq, Transcriptomics

Imports DESeq2, dplyr, reshape2, limma, SummarizedExperiment, ggplot2, matrixStats, stats

Suggests biomaRt, knitr, rmarkdown, stringr, BiocStyle

VignetteBuilder knitr

Config/pak/sysreqs libicu-dev zlib1g-dev

Repository Bioconductor 3.23

Date/Publication 2026-04-28 13:00:32 UTC

RemoteUrl <https://github.com/bioc/DELocal>

RemoteRef RELEASE_3_23

RemoteSha 4ea3f25a1f0c4de0cb96a94a81de2c63389ad9ba

Contents

DELocal	2
plotNeighbourhood	3
Index	5

DELocal	<i>Finds differentially expressed genes by comparing neighboring genes</i>
---------	--

Description

Finds differentially expressed genes by comparing neighboring genes

Usage

```
DELocal(  
  pSmrExpt,  
  nearest_neighbours,  
  pDesign,  
  pValue_cut = 0.05,  
  pLogFold_cut = 0  
)
```

Arguments

- pSmrExpt SummarizedExperiment object
- nearest_neighbours How many nearest neighbours within 1 Mb window to evaluate?
- pDesign design formula
- pValue_cut cut off value for adjusted p-value
- pLogFold_cut cut off value for relative log fold change compared to neighbouring genes

Value

A data.frame with top significant genes with the following columns:
relative.logFC: relative logFC compared to neighbouring genes
P.Value: raw p-value
adj.P.Value: adjusted p-value
B: log-odds that the gene is differentially expressed

Examples

```

count_matrix <- as.matrix(read.table(file = system.file("extdata",
                                                    "tooth_RNASeq_counts.txt",
                                                    package = "DELocal")))

colData <- data.frame(condition=gsub("\\.*",x=colnames(count_matrix),
                                replacement = ""))
gene_location <- read.table(file = system.file("extdata", "gene_location.txt",
                                package = "DELocal"))
smrExpt <- SummarizedExperiment::SummarizedExperiment(
                                assays=list(counts=count_matrix),
                                rowData = gene_location,
                                colData=colData)

contrast= c("condition","ME13","ME14")
require(dplyr)
x_genes <- SummarizedExperiment::rowData(smrExpt) %>%
  as.data.frame() %>%
  filter(chromosome_name=="X") %>% rownames()
DELocal_result <- DELocal(pSmrExpt = smrExpt[x_genes,],
                          nearest_neighbours = 5, pDesign = ~ condition,
                          pValue_cut = 0.05, pLogFold_cut = 0)

```

plotNeighbourhood	<i>Returns median expression from different conditions of genes from a neighbourhood of a gene of interest</i>
-------------------	--

Description

Returns median expression from different conditions of genes from a neighbourhood of a gene of interest

Usage

```

plotNeighbourhood(
  pSmrExpt,
  pNearest_neighbours = 5,
  pDesign = ~condition,
  colorFactor = "condition",
  pGene_id
)

```

Arguments

pSmrExpt	SummarizedExperiment object
pNearest_neighbours	How many nearest neighbours within 1 Mb window to plot
pDesign	design formula
colorFactor	The coloring factor
pGene_id	The gene of interest

Value

a list which contains both the data from the neighbourhood and a ggplot object

Examples

```
count_matrix <- as.matrix(read.table(file = system.file("extdata",
                                                         "tooth_RNASeq_counts.txt",
                                                         package = "DELocal")))
colData <- data.frame(condition=gsub("\\.\\.*",x=colnames(count_matrix),
                                     replacement = ""))
gene_location <- read.table(file = system.file("extdata", "gene_location.txt",
                                                package = "DELocal"))
smrExpt <- SummarizedExperiment::SummarizedExperiment(assays=list(counts=count_matrix),
                                                       rowData = gene_location,
                                                       colData = colData)

contrast= c("condition","ME13","ME14")
require(dplyr)
x_genes <- SummarizedExperiment::rowData(smrExpt) %>%
  as.data.frame() %>%
  filter(chromosome_name=="X") %>% rownames()
DELocal::plotNeighbourhood(pSmrExpt = smrExpt, pGene_id = "ENSMUSG00000059401")
```

Index

DELocal, [2](#)

plotNeighbourhood, [3](#)