

Package: DegNorm (via r-universe)

May 28, 2026

Type Package

Title DegNorm: degradation normalization for RNA-seq data

Version 1.22.0

Date 2025-08-11

biocViews RNASeq, Normalization, GeneExpression, Alignment,Coverage,
DifferentialExpression, BatchEffect,Software,Sequencing,
ImmunoOncology, QualityControl, DataImport

Description This package performs degradation normalization in bulk
RNA-seq data to improve differential expression analysis
accuracy. It provides estimates for each gene within each
sample.

License LGPL (>= 3)

Depends R (>= 4.0.0), methods

Imports Rcpp (>= 1.0.2),GenomicFeatures, txdbmaker, parallel, foreach,
S4Vectors, doParallel, Rsamtools (>= 1.31.2),
GenomicAlignments, heatmaply, data.table, stats, ggplot2,
GenomicRanges, IRanges, plyr, plotly, utils,viridis

LinkingTo Rcpp, RcppArmadillo,S4Vectors,IRanges

NeedsCompilation yes

Suggests knitr,rmarkdown,formatR

VignetteBuilder knitr

BugReports <https://github.com/jipingw/DegNorm/issues>

Config/pak/sysreqs cmake make libmagick++-dev gsfnts libbz2-dev libicu-dev liblzma-dev libpng-
dev libuv1-dev libxml2-dev libssl-dev xz-utils zlib1g-dev

Repository <https://bioc-release.r-universe.dev>

Date/Publication 2026-04-28 12:52:54 UTC

RemoteUrl <https://github.com/bioc/DegNorm>

RemoteRef RELEASE_3_23

RemoteSha da6503c097fc200ad69e4f2dc68b06f38f3f08d9

Contents

DegNorm-package	2
coverage_res_chr21	3
degnorm	3
DegNorm-plot-functions	4
plot_coverage	5
read_coverage_batch	6
res_DegNorm_chr21	7
summary_CoverageClass	8
summary_DegNormClass	9

Index	10
--------------	-----------

DegNorm-package	<i>DegNorm: degradation normalization for RNA-seq data</i>
-----------------	--

Description

DegNorm is an R package for degradation normalization for bulk RNA-seq data. DegNorm, short for degradation normalization, is a bioinformatics pipeline designed to correct for bias due to the heterogeneous patterns of transcript degradation in RNA-seq data.

Details

DegNorm is a data-driven approach for RNA-Seq normalization resulting in the adjusted read count matrix. This adjustment applies to each gene within each sample, accounting for sample- and gene-specific degradation bias while simultaneously controlling for the sequencing depth. The algorithm at the center of DegNorm is the rank-one over-approximation of a gene's coverage score matrix, which is comprised of the different samples' coverage score curves along the transcript for each gene. For each gene, DegNorm estimates (1) an envelope function representing the ideal shape of the gene's coverage curve when no degradation is present, and (2) scale factors for each sample (for said gene) that indicates the relative abundance of the gene within the sample.

functions: read_coverage_batch, degnorm, plot_coverage, plot_heatmap, plot_corr, plot_boxplot

Author(s)

Bin Xiong, Ji-Ping Wang

Maintainer: Ji-Ping Wang <jzawang@northwestern.edu>

References

DegNorm reference:

Xiong, B., Yang, Y., Fineis, F. Wang, J.-P., DegNorm: normalization of generalized transcript degradation improves accuracy in RNA-seq analysis, *Genome Biology*, 2019,20:75

coverage_res_chr21	<i>Example CoverageClass data</i>
--------------------	-----------------------------------

Description

Example of CoverageClass data from DegNorm package. It is the output from read_coverage_batch function for human chromosome 21.

Usage

```
data(coverage_res_chr21)
```

Format

A coverageClass list of the following

coverage a list of coverage matrices for all genes within each sample

counts a data.frame of read counts for all genes within each sample.

Examples

```
data(coverage_res_chr21)
summary_CoverageClass(coverage_res_chr21)
```

degnorm	<i>Main function to perform degradation normalization.</i>
---------	--

Description

degnorm calculates the degradation index score for each gene within each sample and return the degradation-normalized read counts.

Usage

```
degnorm(read_coverage, counts, iteration, loop, down_sampling=1, grid_size=10,
cores=1)
```

Arguments

read_coverage	a list of coverage matrices, one per gene
counts	dataframe of read counts, each row for one gene, and column for sample. The order and number of genes must match the order in read_coverage matrices.
iteration	iteration number for degnorm algorithm. 5 is sufficient.
loop	iteration number inside of nonnegative matrix factorization-over approximation. Default is 100.

down_sampling	1 for yes (default) and 0 for no. If yes, average coverage score is calculated on a grid of size specified by grid_size argument. The new coverage matrix formed by the grid average score will be used for baseline selection. This increases the efficiency of algorithm while maintaining comparable accuracy.
grid_size	default size is 10 bp.
cores	number of cores. Default number is 1. Users should input the maximum possible number of cores for efficiency.

Value

degnorm outputs a list of following objects:

counts	a data.frame of read counts for each gene within each sample.
counts_normed	a data.frame of degradation-normalized read counts for each gene within each sample.
DI	a matrix of degradation index scores for each gene within each sample.
K	normalizing scale factor for each gene within each sample after accounting for degradation normalization.
convergence	convergence tag; 0 = degnorm was not done on this gene because smaller counts or too short length. 1 = degnorm was done with baseline selection. 2 = degnorm done without baseline selection because gene length (after filtering out low count regions) < 200 bp. 3 = baseline was found, but DI score is too large. 4 = baseline selection didn't converge.
envelop	list of the envelop curves for all genes.

Examples

```
##coverage_res_chr21 is a CoverageClass object from DegNorm Package.
data(coverage_res_chr21)
res_DegNorm = degnorm(read_coverage = coverage_res_chr21[[1]],
                      counts = coverage_res_chr21[[2]],
                      iteration = 2,
                      down_sampling = 1,
                      grid_size=10,
                      loop = 20,
                      cores=2)
```

DegNorm-plot-functions

Degradation index (DI) score plot functions

Description

DegNorm provides three functions for visualization gene-/sample-wise degradation.

Usage

```
plot_corr(DI)
plot_heatmap(DI)
plot_boxplot(DI)
```

Arguments

DI a matrix or data.frame of degradation index (DI) scores with each row corresponding to one gene and each column for a sample.

Details

plot_corr plots the correlation matrix of DI scores between samples. plot_heatmap plots the heatmap of DI scores. Left is plotted in descending order of average DI scores of genes where each row corresponds to one gene. In the right plot, DI scores were sorted within each sample and plotted in descending order. plot_boxplot plots the boxplot of DI scores by samples.

Value

These functions return a boxplot of DI scores by sample, a heatmap of DIS scores of all genes in all samples and a correlation plot of DI scores between samples respectively.

Examples

```
## res_DegNorm_chr21 is degnorm otuput stored in sysdata.Rda
data(res_DegNorm_chr21)
plot_boxplot(res_DegNorm_chr21$DI)
plot_heatmap(res_DegNorm_chr21$DI)
plot_corr(res_DegNorm_chr21$DI)
```

plot_coverage

Coverage plot functions for DegNorm

Description

plot_coverage plots the before- and after-degradation coverage curves

Usage

```
plot_coverage(gene_name, coverage_output, degnorm_output, group=NULL, samples=NULL)
```

Arguments

gene_name the name of the gene whose coverage coverage to be plotted.
coverage_output CoverageClass object, the output from function coverage_cal_batch.
degnorm_output DegNormClass object, the output from function DegNorm.

group	a vector of integers or character strings indicating the biological conditions of the samples. Coverage curves will be plotted in the same color for the same group. Default is NULL. By default all curves will plotted in different colors.
samples	a string vector for the subset of samples to be plotted. NULL means all samples to be plotted. The length of samples must be of the same length of group if both specified.

Details

plot_coverageoutputs the coverage curves before- and after-degradation normalization.

Value

The coverage curve before and after degradation normalization.

Examples

```
## gene named "SOD1",plot coverage curves
data(coverage_res_chr21)
data(res_DegNorm_chr21)
plot_coverage(gene_name="SOD1", coverage_output=coverage_res_chr21,
degnorm_output=res_DegNorm_chr21, group=c(0,1,1))
```

read_coverage_batch *Compute the read coverage score and read counts for all genes in batch mode*

Description

This function calls read_coverage to compute read coverage score and read counts for all genes and samples.

Notes:

1. Coverage score is calculated per gene, i.e., concatenation of all exons from the same gene.
2. We follow the HTseq protocol for counting valid reads or read pairs for each gene.
3. When reading the alignment file, isSecondaryAlignment is set to FALSE to avoid redundant counting.
4. For paired-end data, isPaired is set to TRUE. We do not recommend setting isProperPair to TRUE as some fragment lengths may exceed 200 bp.
5. Users can modify scanBamParam in the R code as needed.

Usage

```
read_coverage_batch(bam_file_list, gtf_file, cores = 1)
```

Arguments

bam_file_list A character vector of BAM file paths.
gtf_file The GTF file that RNA-seq reads were aligned to.
cores Number of processor cores to use. Default = 1.

Value

A list with the following components:

coverage A list of coverage matrices for all genes within each sample.
counts A data.frame of read counts for all genes within each sample.

See Also

[read_coverage](#)

Examples

```
## Read BAM file and GTF file from the package
bam_file_list <- list.files(
  path = system.file("extdata", package = "DegNorm"),
  pattern = ".bam$", full.names = TRUE
)
gtf_file <- list.files(
  path = system.file("extdata", package = "DegNorm"),
  pattern = ".gtf$", full.names = TRUE
)

## Run read_coverage_batch to calculate read coverage curves and read counts
coverage_res <- read_coverage_batch(bam_file_list, gtf_file, cores = 2)
```

res_DegNorm_chr21 *Example DegNormClass data*

Description

Example of DegNormClass data from DegNorm package. It is the output from degnorm function for human chromosome 21.

Usage

```
data("res_DegNorm_chr21")
```

Format

A DegNormClass list of the following items:

counts a data.frame of read counts for each gene within each sample.

counts_normed a data.frame of degradation-normalized read counts for each gene within each sample.

DI a matrix of degradation index scores for each gene within each sample.

K normalizing scale factor for each gene within each sample after accounting for degradation normalization.

convergence convergence tag; 0 = degnorm was not done on this gene because smaller counts or too short length. 1 = degnorm was done with baseline selection. 2 = degnorm done without baseline selection because gene length (after filtering out low count regions) < 200 bp. 3 = baseline was found, but DI score is too large. 4 = baseline selection didn't converge.

envelop a list of the envelop curves for all genes.

Examples

```
data(res_DegNorm_chr21)
summary_DegNormClass(res_DegNorm_chr21)
```

summary_CoverageClass *Summary method for CoverageClass.*

Description

It prints a summary of the data objects contained in the list from read_coverage_batch.

Usage

```
summary_CoverageClass(object)
```

Arguments

object CoverageClass from coderead_coverage_batch.

Value

On-screen plot of summary of CoverageClass object.

Examples

```
## Summary of coverage_cal_batch output (CoverageClass)
data(coverage_res_chr21)
summary_CoverageClass(coverage_res_chr21)
```

summary_DegNormClass *Summary method for DegNormClass.*

Description

It prints a summary of the data objects contained in the list from degnorm function.

Usage

```
summary_DegNormClass(object)
```

Arguments

object DegNormClass from degnorm function.

Value

On-screen summary of DegNormClass object.

Examples

```
## Summary of degnorm output (DegNormlass)
data(res_DegNorm_chr21)
summary_DegNormClass(res_DegNorm_chr21)
```

Index

* RNA-seq, degradation, normalization

DegNorm-package, [2](#)

* datasets

coverage_res_chr21, [3](#)

res_DegNorm_chr21, [7](#)

coverage_res_chr21, [3](#)

degnorm, [3](#)

DegNorm-package, [2](#)

DegNorm-plot-functions, [4](#)

plot_boxplot (DegNorm-plot-functions), [4](#)

plot_corr (DegNorm-plot-functions), [4](#)

plot_coverage, [5](#)

plot_heatmap (DegNorm-plot-functions), [4](#)

read_coverage, [7](#)

read_coverage_batch, [6](#)

res_DegNorm_chr21, [7](#)

summary_CoverageClass, [8](#)

summary_DegNormClass, [9](#)