

Package: ExploreModelMatrix (via r-universe)

June 21, 2026

Type Package

Title Graphical Exploration of Design Matrices

Version 1.24.0

Date 2026-03-16

Description Given a sample data table and a design formula, ExploreModelMatrix generates an interactive application for exploration of the resulting design matrix. This can be helpful for interpreting model coefficients and constructing appropriate contrasts in (generalized) linear models. Static visualizations can also be generated.

License MIT + file LICENSE

Encoding UTF-8

Imports shiny (>= 1.5.0), shinydashboard, DT, cowplot, utils, dplyr, magrittr, tidyr, ggplot2, stats, methods, rintrojs, scales, tibble, MASS, limma, S4Vectors, shinyjs, rlang

RoxygenNote 7.3.3

Suggests testthat (>= 2.1.0), knitr, rmarkdown, htmltools, BiocStyle

VignetteBuilder knitr

URL <https://github.com/csoneson/ExploreModelMatrix>

BugReports <https://github.com/csoneson/ExploreModelMatrix/issues>

biocViews ExperimentalDesign, Regression, DifferentialExpression, ShinyApps

Config/pak/sysreqs cmake make libicu-dev libuv1-dev zlib1g-dev

Repository <https://bioc-release.r-universe.dev>

Date/Publication 2026-04-28 12:52:19 UTC

RemoteUrl <https://github.com/bioc/ExploreModelMatrix>

RemoteRef RELEASE_3_23

RemoteSha fe30945452eb92e8a5bd8f144036b331f4e7f199

Contents

ExploreModelMatrix	2
VisualizeDesign	3
Index	6

ExploreModelMatrix	<i>Explore model matrix</i>
--------------------	-----------------------------

Description

Given a sample data table and a design formula, explore the resulting design matrix graphically in an interactive application.

Usage

```
ExploreModelMatrix(
  sampleData = NULL,
  designFormula = NULL,
  addStopButton = TRUE
)
```

Arguments

sampleData	(optional) A <code>data.frame</code> or <code>DataFrame</code> with sample information. If set to <code>NULL</code> , the user can upload the sample information from a tab-separated text file inside the app, or choose among a collection of example designs provided in the app.
designFormula	(optional) A formula. All components of the terms must be present as columns in <code>sampleData</code> . If set to <code>NULL</code> , the design formula can be specified after launching the app.
addStopButton	Logical scalar. If <code>TRUE</code> (default), will add a button to stop the app (by calling <code>shiny::stopApp</code>).

Value

A Shiny app object

Author(s)

Charlotte Soneson, Federico Marini, Michael I Love, Florian Geier, Michael B Stadler

Examples

```
app <- ExploreModelMatrix(  
  sampleData = data.frame(genotype = rep(c("A", "B"), each = 4),  
                           treatment = rep(c("treated", "untreated"), 4)),  
  designFormula = ~genotype + treatment  
)  
if (interactive()) shiny::runApp(app)
```

VisualizeDesign

Visualize design matrix

Description

Given a sample table and a design formula, generate a collection of static plots for exploring the resulting design matrix graphically. This function is called internally by `ExploreModelMatrix()`, but can also be used directly if interactivity is not required.

Usage

```
VisualizeDesign(  
  sampleData,  
  designFormula = NULL,  
  flipCoordFitted = FALSE,  
  flipCoordCoocc = FALSE,  
  textSizeFitted = 5,  
  textSizeCoocc = 5,  
  textSizeLabsFitted = 12,  
  textSizeLabsCoocc = 12,  
  lineWidthFitted = 25,  
  addColorFitted = TRUE,  
  colorPaletteFitted = scales::hue_pal(),  
  dropCols = NULL,  
  designMatrix = NULL  
)
```

Arguments

`sampleData` A data frame of `DataFrame` with sample information.

`designFormula` A formula. All components of the terms must be present as columns in `sampleData`.

`flipCoordFitted`, `flipCoordCoocc`
A logical, whether to flip the coordinate axes in the fitted values/co-occurrence plot, respectively.

`textSizeFitted`, `textSizeCoocc`
A numeric scalar giving the text size in the fitted values/co-occurrence plot, respectively.

<code>textSizeLabsFitted</code> , <code>textSizeLabsCoocc</code>	A numeric scalar giving the text size for the axis labels in the fitted values/co-occurrence plot, respectively.
<code>lineWidthFitted</code>	A numeric scalar giving the maximal length of a row in the fitted values plot, before it is split and printed on multiple lines
<code>addColorFitted</code>	A logical scalar indicating whether the terms in the fitted values plot should be shown in different colors.
<code>colorPaletteFitted</code>	A function returning a color palette to use for coloring the model coefficients in the fitted values plot.
<code>dropCols</code>	A character vector with columns to drop from the design matrix, or NULL if no columns should be dropped.
<code>designMatrix</code>	A numeric matrix, which can be supplied as an alternative to <code>designFormula</code> . Rows must be in the same order as the rows in <code>sampleData</code> .

Details

Note that if a design matrix is supplied (via the `designMatrix` argument), caution is required in order to interpret especially the cooccurrence plot in the situation where the provided `sampleData` contains additional columns not used to generate the design matrix (or when it does not contain all the relevant columns).

Value

A list with the following elements:

- `sampledata`: A data.frame, expanded from the input `sampleData`
- `plotlist`: A list of plots, displaying the fitted values for each combination of predictor values, in terms of the model coefficients.
- `designmatrix`: The design matrix, after removing any columns in `dropCols`
- `pseudoinverse`: The pseudoinverse of the design matrix
- `vifs`: A data.frame with calculated variance inflation factors
- `colors`: A vector with colors to use for different model coefficients
- `cooccurrenceplots`: A list of plots, displaying the co-occurrence pattern for the predictors (i.e., the number of observations for each combination of predictor values)
- `totnbrrows`: The total number of "rows" in the list of plots of fitted values. Useful for deciding the required size of the plot canvas.

Author(s)

Charlotte Soneson

Examples

```
VisualizeDesign(  
  sampleData = data.frame(genotype = rep(c("A", "B"), each = 4),  
                           treatment = rep(c("treated", "untreated"), 4)),  
  designFormula = ~genotype + treatment  
)
```

Index

ExploreModelMatrix, [2](#)

VisualizeDesign, [3](#)