Package: HiCDCPlus (via r-universe)

November 25, 2026

Type Package

Title Hi-C Direct Caller Plus

Version 1.22.0

Description Systematic 3D interaction calls and differential analysis for Hi-C and HiChIP. The HiC-DC+ (Hi-C/HiChIP direct caller plus) package enables principled statistical analysis of Hi-C and HiChIP data sets – including calling significant interactions within a single experiment and performing differential analysis between conditions given replicate experiments – to facilitate global integrative studies. HiC-DC+ estimates significant interactions in a Hi-C or HiChIP experiment directly from the raw contact matrix for each chromosome up to a specified genomic distance, binned by uniform genomic intervals or restriction enzyme fragments, by training a background model to account for random polymer ligation and systematic sources of read count variation.

License GPL-3

Encoding UTF-8

biocViews HiC, DNA3DStructure, Software, Normalization

RoxygenNote 7.1.1

SystemRequirements JRE 8+

LinkingTo Rcpp

Imports Rcpp,InteractionSet,GenomicInteractions,bbmle,pscl,BSgenome,data.table,dplyr,tidyr,GenomeInfoDb,rlang,splines,MAS

Suggests BSgenome.Mmusculus.UCSC.mm9, BSgenome.Mmusculus.UCSC.mm10, BSgenome.Hsapiens.UCSC.hg19, BSgenome.Hsapiens.UCSC.hg38, RUnit, BiocGenerics, knitr, rmarkdown, HiTC, DESeq2, Matrix, BiocFileCache, rappdirs

Enhances parallel

VignetteBuilder knitr

NeedsCompilation yes

Config/pak/sysreqs cmake libglpk-dev make libbz2-dev libicu-dev libjpeg-dev liblzma-dev libpng-dev libuv1-dev libxml2-dev libssl-dev xz-utils zlib1g-dev

Repository Bioconductor 3.24

Date/Publication 2026-11-23 22:46:30 UTC

RemoteUrl https://github.com/bioc/HiCDCPlus

RemoteRef RELEASE_3_24

RemoteSha c72eeafd13d543d17659f4de987b046bd94d2d03

Contents

add_1D_features . . . 3
add_2D_features . . . 4
add_hic_counts . . . 5
add_hicpro_allvalidpairs_counts . . . 5
add_hicpro_matrix_counts . . . 6
construct_features . . . 7
construct_features_chr . . . 8
construct_features_parallel . . . 9
expand_1D_features . . . 11
extract_hic_eigenvectors . . . 12
generate_binned_gi_list . . . 13
generate_bintolen_gi_list . . . 14
generate_df_gi_list . . . 15
get_chr_sizes . . . 16
get_chrs . . . 16
get_enzyme_cutsites . . . 17
gi_list_binsize_detect . . . 17
gi_list_Dthreshold.detect . . . 18
gi_list_read . . . 19
gi_list_topdom . . . 20
gi_list_validate . . . 21
gi_list_write . . . 21
gi_list2HTClist . . . 22
hic2icenorm_gi_list . . . 23
hicdc2hic . . . 24
hicdcdiff . . . 25
HiCDCPlus . . . 27
HiCDCPlus_chr . . . 29
HiCDCPlus_parallel . . . 30
HTClist2gi_list . . . 32
straw . . . 32
straw_dump . . . 33

Index **35**

add_1D_features *add_1D_features*

Description

Adds 1D features to the gi_list instance. If any bin on gi_list overlaps with multiple feature records, feature values are aggregated for the bin according to the vector valued function agg (e.g., sum, mean)

Usage

```
add_1D_features(gi_list, df, chrs = NULL, features = NULL, agg = mean)
```

Arguments

gi_list	List of GenomicInteractions objects where each object named with chromosomes contains intrachromosomal interaction information (see ?gi_list_validate for a detailed explanation of valid gi_list instances).
df	DataFrame with columns named 'chr', and'start' and features to be added with their respective names.
chrs	a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes specified in the data frame df.
features	features to be added. Needs to be a subset of colnames(df). Defaults to all columns in df other than 'chr','start',and 'end'.
agg	any vector valued function with one data argument: defaults to mean.

Value

a gi_list instance with 1D features stored in regions metadata handle of each list element (e.g., gi_list[[1]]@regions@elementMetadata) in the instance

Examples

```
df<-data.frame(chr='chr9',start=seq(1e6,10e6,1e6),end=seq(2e6,11e6,1e6))
gi_list<-generate_df_gi_list(df)
feats<-data.frame(chr='chr9',start=seq(1e6,10e6,1e6),gc=runif(10))
gi_list<-add_1D_features(gi_list,feats)
```

add_2D_features *add_2D_features*

Description

Adds 2D features to a gi_list instance. If any bin on gi_list overlaps with multiple feature records, features are aggregated among matches according to the univariate vector valued function agg (e.g., sum, mean). For efficient use of memory, using add/expand 1D features (see ?add_1D_features and expand_1D_features) in sequence is recommended instead of using add_2D_features directly for each chromosome.

Usage

```
add_2D_features(gi, df, features = NULL, agg = sum)
```

Arguments

gi	Element of a valid gi_list instance (restricted to a single chromosome e.g., gi_list[['chr9']]—see ?gi_list_validate for a detailed explanation of valid gi_list instances).
df	data frame for a single chromosome containing columns named chr, startI and startJ and features to be added with their respective names (if df contains multiple chromosomes, you can convert it into a list of smaller data.frames for each chromosome and apply this function with sapply).
features	features to be added. Needs to be subset of colnames(df). Defaults to all columns in df other than 'chr','start',and 'end'.
agg	any vector valued function with one data argument: defaults to mean.

Value

a gi_list element with 2D features stored in metadata handle (i.e., mcols(gi)).

Examples

```
df<-data.frame(chr='chr9',start=seq(1e6,10e6,1e6))
gi_list<-generate_df_gi_list(df,Dthreshold=500e3)
feats<-data.frame(chr='chr9',
startI=seq(1e6,10e6,1e6),startJ=seq(1e6,10e6,1e6),counts=rpois(10,lambda=5))
gi_list[['chr9']]<-add_2D_features(gi_list[['chr9']],feats)
```

add_hic_counts *add_hic_counts*

Description

This function adds counts from a .hic file into a valid, binned, gi_list instance.

Usage

```
add_hic_counts(gi_list, hic_path, chrs = NULL, add_inter = FALSE)
```

Arguments

gi_list	valid, uniformly binned gi_list instance. See ?gi_list_validate and gi_list_binsize_detect for details.
hic_path	path to the .hic file
chrs	a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes in the gi_list instance.
add_inter	Interchromosomal interaction counts added as a 1D feature named 'inter' on regions metadata handle of each gi_list element (e.g., gi_list[[1]]@regions@elementMetadata or not; default FALSE

Value

gi_list instance with counts on the metadata (e.g., mcols(gi_list[[1]]) handle on each list element, and 'inter' on regions metadata handle of each element if add_inter=TRUE.

Examples

```
gi_list<-generate_binned_gi_list(50e3,chrs='chr22')
gi_list<-add_hic_counts(gi_list,
hic_path=system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus"))
```

add_hicpro_allvalidpairs_counts *add_hicpro_allvalidpairs_counts*

Description

This function converts HiC-Pro outputs in allValidPairs format into a gi_list instance.

Usage

```
add_hicpro_allvalidpairs_counts(
  gi_list,
  allvalidpairs_path,
  chrs = NULL,
  binned = TRUE,
  add_inter = FALSE
)
```

Arguments

gi_list	valid gi_list instance. See ?gi_list_validate for details. You can also detect whether a gi_list instance is uniformly binned, along with its bin size using gi_list_binsize_detect.
allvalidpairs_path	allValidPairsfile obtained from HiC-Pro (e.g., 'GSM2572593_con_rep1.allvalidPairs.txt')
chrs	a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes in the gi_list instance.
binned	TRUE if the gi_list instance is uniformly binned (helps faster execution). Defaults to TRUE.
add_inter	Interchromosomal interaction counts added as a 1D feature named 'inter' on regions metadata handle of each gi_list element (e.g., gi_list[[1]]@regions@elementMetadata or not; default FALSE

Value

gi_list instance with counts on the metadata (e.g., mcols(gi_list[[1]]) handle on each list element, and 'inter' on regions metadata handle of each element if add_inter=TRUE.

---

add_hicpro_matrix_counts

add_hicpro_matrix.counts

Description

This function converts HiC-Pro matrix and bed outputs into a gi_list instance.

Usage

```
add_hicpro_matrix_counts(
  gi_list,
  absfile_path,
  matrixfile_path,
  chrs = NULL,
  add_inter = FALSE
)
```

Arguments

gi_list	valid, uniformly binned gi_list instance. See ?gi_list_validate and gi_list_binsize_detect for details.
absfile_path	absfile BED out of HiC-Pro (e.g., 'rawdata_10000_abs.bed')
matrixfile_path	matrix count file out of HiC-Pro (e.g., 'rawdata_10000.matrix')
chrs	a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes in the gi_list instance.
add_inter	Interchromosomal interaction counts added as a 1D feature named 'inter' on regions metadata handle of each gi_list element (e.g., gi_list[[1]]@regions@elementMetadata or not; default FALSE

Value

gi_list instance with counts on the metadata (e.g., mcols(gi_list[[1]]) handle on each list element, and 'inter' on regions metadata handle of each element if add_inter=TRUE.

---

construct_features *construct_features*

Description

This function lists all restriction enzyme cutsites of a given genome and genome version with genomic features outlined in Carty et al. (2017) https://www.nature.com/articles/ncomms15454; GC content, mappability, and effective length

Usage

```
construct_features(
  output_path,
  gen = "Hsapiens",
  gen_ver = "hg19",
  sig = "GATC",
  bin_type = "Bins-uniform",
  binsize = 5000,
  wg_file = NULL,
  chrs = NULL,
  feature_type = "RE-based"
)
```

Arguments

output_path	the path to the folder and name prefix you want to place feature files into. The feature file will have the suffix '_bintolen.txt.gz'.
gen	name of the species: e.g., default 'Hsapiens'.

gen_ver	genomic assembly version: e.g., default 'hg19'.
sig	restriction enzyme cut pattern (or a vector of patterns; e.g., 'GATC' or c('GATC','GANTC')).
bin_type	'Bins-uniform' if uniformly binned by binsize in bp, or 'Bins-RE-sites' if binned by number of restriction enzyme fragments.
binsize	binsize in bp if bin_type='Bins-uniform' (or number of RE fragment cut sites if bin_type='Bins-RE-sites'), defaults to 5000.
wg_file	path to the bigWig file containing mappability values across the genome of interest.
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes (except Y and M) in the genome specified.
feature_type	'RE-based' if features are to be computed based on restriction enzyme fragments. 'RE-agnostic' ignores restriction enzyme cutsite information and computes features gc and map based on binwide averages. bin_type has to be 'Bins-uniform' if feature_type='RE-agnostic'.

Value

a features 'bintolen' file that contains GC, mappability and length features.

Examples

```
outdir<-paste0(tempdir(check=TRUE),'/')
construct_features(output_path=outdir,gen='Hsapiens',
gen_ver='hg19',sig=c('GATC','GANTC'),bin_type='Bins-uniform',binsize=100000,
wg_file=NULL,chrs=c('chr21'))
```

---

construct_features_chr

construct_features_chr

Description

This function lists all restriction enzyme cutsites of a given genome and genome version with genomic features outlined in Carty et al. (2017) for a single chromosome. https://www.nature.com/articles/ncomms15454; GC content, mappability, and effective length

Usage

```
construct_features_chr(
  chrom,
  gen = "Hsapiens",
  gen_ver = "hg19",
  sig = "GATC",
  bin_type = "Bins-uniform",
  binsize = 5000,
  wg_file = NULL,
  feature_type = "RE-based"
)
```

Arguments

chrom	select a chromosome.
gen	name of the species: e.g., default 'Hsapiens'.
gen_ver	genomic assembly version: e.g., default 'hg19'.
sig	restriction enzyme cut pattern (or a vector of patterns; e.g., 'GATC' or c('GATC','GANTC')).
bin_type	'Bins-uniform' if uniformly binned by binsize in bp, or 'Bins-RE-sites' if binned by number of restriction enzyme fragments.
binsize	binsize in bp if bin_type='Bins-uniform' (or number of RE fragment cut sites if bin_type='Bins-RE-sites'), defaults to 5000.
wg_file	path to the bigWig file containing mappability values across the genome of interest.
feature_type	'RE-based' if features are to be computed based on restriction enzyme fragments. 'RE-agnostic' ignores restriction enzyme cutsite information and computes features gc and map based on binwide averages. bin_type has to be 'Bins-uniform' if feature_type='RE-agnostic'.

Value

a features 'bintolen' file that contains GC, mappability and length features.

Examples

```
df<-construct_features_chr(chrom='chr22',
gen='Hsapiens', gen_ver='hg19',sig=c('GATC','GANTC'),bin_type='Bins-uniform',
binsize=100000,wg_file=NULL)
```

---

construct_features_parallel

construct_features_parallel

Description

This function lists all restriction enzyme cutsites of a given genome and genome version with genomic features outlined in Carty et al. (2017) https://www.nature.com/articles/ncomms15454; GC content, mappability, and effective length

Usage

```
construct_features_parallel(
  output_path,
  gen = "Hsapiens",
  gen_ver = "hg19",
  sig = "GATC",
  bin_type = "Bins-uniform",
  binsize = 5000,
```

```
  wg_file = NULL,
  chrs = NULL,
  feature_type = "RE-based",
  ncore = NULL
)
```

Arguments

output_path	the path to the folder and name prefix you want to place feature files into. The feature file will have the suffix '_bintolen.txt.gz'.
gen	name of the species: e.g., default 'Hsapiens'.
gen_ver	genomic assembly version: e.g., default 'hg19'.
sig	restriction enzyme cut pattern (or a vector of patterns; e.g., 'GATC' or c('GATC','GANTC')).
bin_type	'Bins-uniform' if uniformly binned by binsize in bp, or 'Bins-RE-sites' if binned by number of restriction enzyme fragments.
binsize	binsize in bp if bin_type='Bins-uniform' (or number of RE fragment cut sites if bin_type='Bins-RE-sites'), defaults to 5000.
wg_file	path to the bigWig file containing mappability values across the genome of interest.
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes (except Y and M) in the genome specified.
feature_type	'RE-based' if features are to be computed based on restriction enzyme fragments. 'RE-agnostic' ignores restriction enzyme cutsite information and computes features gc and map based on binwide averages. bin_type has to be 'Bins-uniform' if feature_type='RE-agnostic'.
ncore	Number of cores to parallelize. Defaults to parallel::detectCores()-1.

Value

a features 'bintolen' file that contains GC, mappability and length features.

Examples

```
outdir<-paste0(tempdir(check=TRUE),'/')
construct_features_parallel(output_path=outdir,gen='Hsapiens',
gen_ver='hg19',sig=c('GATC','GANTC'),bin_type='Bins-uniform',binsize=100000,
wg_file=NULL,chrs=c('chr21'),ncore=2)
```

expand_1D_features *expand_1D_features*

Description

Expands 1D features on the regions metadata handle of each list element (e.g., `gi_list[[1]]@regions@elementMetadata`) to the to 2D metadata e.g., `mcols(gi_list[[1]])`). Two feature values corresponding to each anchor is summarized as a score using a vector valued function agg that takes two vector valued arguments of the same size and outputs a vector of the same size as the input vectors. This defaults to the `transform.vec` function outlined in (Carty et al., 2017). For efficient use of memory, using add/expand 1D features (see `?add_1D_features` and `expand_1D_features`) in sequence is recommended instead of using `add_2D_features` directly for each chromosome.

Usage

```
expand_1D_features(gi_list, chrs = NULL, features = NULL, agg = transform.vec)
```

Arguments

`gi_list`	List of `GenomicInteractions` objects where each object named with chromosomes contains intra-chromosomal interaction information (see `?gi_list_validate` for a detailed explanation of valid `gi_list` instances).
`chrs`	a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes in the `gi_list` instance.
`features`	features to be added. Defaults to all 1D features in elements of `gi_list[[1]]@regions@elementMetadat`
`agg`	any vector valued function with two data arguments: defaults to `transform.vec` described in HiC-DC (Carty et al., 2017).

Value

a gi_list element with 2D features stored in metadata handle (i.e., `mcols(gi)`).

Examples

```
df<-data.frame(chr='chr9',start=seq(1e6,10e6,1e6),end=seq(2e6,11e6,1e6))
gi_list<-generate_df_gi_list(df)
feats<-data.frame(chr='chr9',start=seq(1e6,10e6,1e6),gc=runif(10))
gi_list<-add_1D_features(gi_list,feats)
gi_list<-expand_1D_features(gi_list)
```

extract_hic_eigenvectors *extract_hic_eigenvectors*

Description

This function uses Juicer command line tools to extract first eigenvectors across chromosomes from counts data in a .hic file and outputs them to text file of the structure chr start end score where the score column contains the eigenvector elements.

Usage

```
extract_hic_eigenvectors(
  hicfile,
  mode = "KR",
  binsize = 250e3,
  chrs = NULL,
  gen = "Hsapiens",
  gen_ver = "hg19"
)
```

Arguments

hicfile	path to the input .hic file.
mode	Normalization mode to extract first eigenvectors from Allowable options are: 'NONE' for raw (normalized counts if .hic file is written using `hicdc2hic` or `hic2icenorm_gi_list`), 'KR' for Knight-Ruiz normalization, 'VC' for Vanilla-Coverage normalization and 'VC_SQRT' for square root vanilla coverage. Defaults to 'KR'.
binsize	the uniform binning size for compartment scores in bp. Defaults to 100e3.
chrs	a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes except "Y", and "M" for the specified gen and gen_ver.
gen	name of the species: e.g., default `'Hsapiens'`.
gen_ver	genomic assembly version: e.g., default `'hg19'`.

Value

path to the eigenvector text files for each chromosome containing chromosome, start, end and compartment score values that may need to be flipped signs for each chromosome. File paths follow `gsub('.hic','_<chromosome>_eigenvectors.txt',hicfile)`

Examples

```
eigenvector_filepaths<-extract_hic_eigenvectors(
hicfile=system.file("extdata", "eigenvector_example.hic",
package = "HiCDCPlus"),
chrs=c("chr22"),binsize=250e3,mode="NONE")
```

generate_binned_gi_list *generate_binned_gi_list*

Description

Generates a valid uniformly binned gi_list instance.

Usage

```
generate_binned_gi_list(
  binsize,
  chrs = NULL,
  Dthreshold = 2e+06,
  gen = "Hsapiens",
  gen_ver = "hg19"
)
```

Arguments

binsize	Desired binsize in bp, e.g., 5000, 25000.
chrs	a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes except "Y", and "M" for the specified gen and gen_ver.
Dthreshold	maximum distance (included) to check for significant interactions, defaults to 2e6 or maximum in the data; whichever is smaller.
gen	name of the species: e.g., default 'Hsapiens'.
gen_ver	genomic assembly version: e.g., default 'hg19'.

Value

a valid, uniformly binned gi_list instance.

Examples

```
gi_list<-generate_binned_gi_list(1e6,chrs='chr22')
```

generate_bintolen_gi_list *generate_bintolen_gi_list*

Description

Generates a gi_list instance from a bintolen file generated by `generate.features` (see `?generate.features`) for details).

Usage

```
generate_bintolen_gi_list(
  bintolen_path,
  chrs = NULL,
  Dthreshold = 2e+06,
  binned = TRUE,
  binsize = NULL,
  gen = "Hsapiens",
  gen_ver = "hg19"
)
```

Arguments

`bintolen_path`	path to the flat file containing columns named bins and features
`chrs`	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes specified in the bintolen file.
`Dthreshold`	maximum distance (included) to check for significant interactions, defaults to 2e6 or maximum in the data; whichever is smaller.
`binned`	TRUE if the bintolen file is uniformly binned. Defaults to TRUE.
`binsize`	bin size in bp to be generated for the object. Defaults to the binsize in the bintolen file, if exists.
`gen`	name of the species: e.g., default `'Hsapiens'`
`gen_ver`	genomic assembly version: e.g., default `'hg19'`

Value

a valid gi_list instance with genomic features derived from specified restriction enzyme cut patterns when generating the bintolen file using `construct_features` (see `?construct_features` for help). Genomic 1D features are stored in the regions metadata handle of each list element (e.g., `gi_list[[1]]@regions@elementMetadata`).

Examples

```
chrs<-'chr22'
bintolen_path<-system.file("extdata", "test_bintolen.txt.gz",
package = "HiCDCPlus")
gi_list<-generate_bintolen_gi_list(bintolen_path,chrs)
```

generate_df_gi_list *generate_df_gi_list*

Description

Generates a gi_list instance from a data frame object describing the regions.

Usage

```
generate_df_gi_list(
  df,
  chrs = NULL,
  Dthreshold = 2e+06,
  gen = "Hsapiens",
  gen_ver = "hg19"
)
```

Arguments

df	DataFrame with columns named 'chr', 'start', (and optionally 'end', if the regions have gaps) and 1D features with their respective column names.
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes specified in df.
Dthreshold	maximum distance (included) to check for significant interactions, defaults to 2e6 or maximum in the data, whichever is smaller.
gen	name of the species: e.g., default 'Hsapiens'
gen_ver	genomic assembly version: e.g., default 'hg19'

Value

a valid gi_list instance with genomic features supplied from df. Genomic 1D features are stored in the regions metadata handle of each list element (e.g., gi_list[[1]]@regions@elementMetadata).

Examples

```
df<-data.frame(chr='chr9',start=seq(1e6,10e6,1e6))
gi_list<-generate_df_gi_list(df)
```

get_chr_sizes *get_chr_sizes*

Description

This function finds all chromosome sizes of a given genome, genome version and set of chromosomes.

Usage

```
get_chr_sizes(gen = "Hsapiens", gen_ver = "hg19", chrs = NULL)
```

Arguments

gen	name of the species: e.g., default 'Hsapiens'
gen_ver	genomic assembly version: e.g., default 'hg19'
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes (except Y and M) in the genome specified.

Value

named vector containing names as chromosomes and values as chromosome sizes.

Examples

```
get_chr_sizes('Hsapiens','hg19',c('chr21','chr22'))
```

get_chrs *get_chrs*

Description

This function finds all chromosomes of a given genome and genome version except for Y and M.

Usage

```
get_chrs(gen = "Hsapiens", gen_ver = "hg19")
```

Arguments

gen	name of the species: e.g., default 'Hsapiens'
gen_ver	genomic assembly version: e.g., default 'hg19'

Value

string vector of chromosomes.

Examples

```
get_chrs('Hsapiens','hg19')
```

`get_enzyme_cutsites` *get_enzyme_cutsites*

Description

This function finds all restriction enzyme cutsites of a given genome, genome version, and set of cut patterns

Usage

```
get_enzyme_cutsites(sig, gen = "Hsapiens", gen_ver = "hg19", chrs = NULL)
```

Arguments

`sig`	a set of restriction enzyme cut patterns (e.g., 'GATC' or c('GATC','GANTC'))
`gen`	name of the species: e.g., default `'Hsapiens'`
`gen_ver`	genomic assembly version: e.g., default `'hg19'`
`chrs`	a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes (except Y and M) in the genome specified by `gen` and `gen_ver`.

Value

list of chromosomes.

Examples

```
get_enzyme_cutsites(gen='Hsapiens',gen_ver='hg19',
sig=c('GATC','GANTC'),chrs=c('chr22'))
```

`gi_list_binsize_detect` *gi_list_binsize_detect*

Description

This function finds the bin size of a uniformly binned valid gi_list instance in bp. It raises an error if the gi_list instance is not uniformly binned.

Usage

```
gi_list_binsize_detect(gi_list)
```

Arguments

gi_list	gi_list object to be verified. In order to pass without errors, a gi_list object (1) has to be a list of InteractionSet::GInteractions objects,(2) each list element has to be named as chromosomes and only contain intra-chromosomal interaction information, (3) `mcols(.)` for each list element should at least contain pairwise genomic distances in a column named 'D' and (4) each list element needs to be uniformly binned

Value

uniform binsize in base pairs or an error if the gi_list instance is not uniformly binned.

Examples

```
gi_list<-generate_binned_gi_list(1e6,chrs='chr22')
gi_list_binsize_detect(gi_list)
```

---

gi_list_Dthreshold.detect

gi_list_Dthreshold_detect

Description

This function finds the maximum genomic distance in a valid gi_list object.

Usage

```
gi_list_Dthreshold.detect(gi_list)
```

Arguments

gi_list	A valid gi_list instance. See `?gi_list_validate` for more details about the attributes of a valid gi_list instance.

Value

maximum genomic distance in the object

Examples

```
gi_list<-generate_binned_gi_list(1e6,chrs='chr22')
gi_list_Dthreshold.detect(gi_list)
```

gi_list_read *gi_list_read*

Description

Reads a written gi_list instance using `gi_list_write` into a valid gi_list instance.

Usage

```
gi_list_read(
  fname,
  chrs = NULL,
  Dthreshold = NULL,
  features = NULL,
  gen = "Hsapiens",
  gen_ver = "hg19"
)
```

Arguments

`fname`	path to the file to read from (can end with .txt, .rds, or .txt.gz).
`chrs`	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes contained in the `fname`.
`Dthreshold`	maximum distance (included) to check for significant interactions, defaults to the maximum in the data.
`features`	Select the subset of features (1-D or 2-D) to be added to the gi_list instance (without the trailing I or J), defaults to all features (score column gets ingested as 'score').
`gen`	name of the species: e.g., default `'Hsapiens'`
`gen_ver`	genomic assembly version: e.g., default `'hg19'`

Value

A valid gi_list instance with 1D features stored in regions metadata handle of each list element (e.g., `gi_list[[1]]@regions@elementMetadata`) in the instance and with 2D features stored in metadata handle (i.e., `mcols(gi)`).

Examples

```
outputdir<-paste0(tempdir(check=TRUE),'/')
gi_list<-generate_binned_gi_list(1e6,chrs='chr22')
gi_list_write(gi_list,paste0(outputdir,'testgiread.txt'))
gi_list2<-gi_list_read(paste0(outputdir,'testgiread.txt'))
```

gi_list_topdom *gi_list_topdom*

Description

This function converts a gi_list instance with ICE normalized counts into TAD annotations through an implementation of TopDom v0.0.2 (https://github.com/HenrikBengtsson/TopDom) adapted as `TopDom` at this package. If you're using this function, please cite TopDom according to the documentation at https://github.com/HenrikBengtsson/TopDom/blob/0.0.2/docs/

Usage

```
gi_list_topdom(
  gi_list,
  chrs = NULL,
  file_out = FALSE,
  fpath = NULL,
  window.size = 5,
  verbose = FALSE
)
```

Arguments

`gi_list`	List of `GenomicInteractions` objects where each object named with chromosomes contains intrachromosomal interaction information (see `?gi_list_validate` for a detailed explanation of valid `gi_list` instances).
`chrs`	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to chromosomes in `gi_list`.
`file_out`	If true, outputs TAD annotations into files with paths beginning with `fpath`. Defaults to FALSE
`fpath`	Outputs TAD annotations into files with paths beginning in `fpath`.
`window.size`	integer, number of bins to extend. Defaults to 5.
`verbose`	TRUE if you would like to troubleshoot TopDom.

Value

a list instance with TAD annotation reporting for each chromosome

Examples

```
hic_path<-system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus")
gi_list<-hic2icenorm_gi_list(hic_path,binsize=50e3,chrs='chr22')
tads<-gi_list_topdom(gi_list)
```

gi_list_validate *gi_list_validate*

Description

This function validates a gi_list instance.

Usage

```
gi_list_validate(gi_list)
```

Arguments

gi_list	gi_list object to be verified. In order to pass without errors, a gi_list object (1) has to be a list of InteractionSet::GInteractions objects, (2) each list element has to be named as chromosomes and only contain intra-chromosomal interaction information, (3) `mcols(.)` for each list element should at least contain pairwise genomic distances in a column named 'D'.

Value

invisible value if the gi_list instance is valid. Otherwise, an error is raised.

Examples

```
gi_list<-generate_binned_gi_list(1e6,chrs='chr22')
gi_list_validate(gi_list)
```

gi_list_write *gi_list_write*

Description

Writes a valid gi_list instance into a file.

Usage

```
gi_list_write(
  gi_list,
  fname,
  chrs = NULL,
  columns = "minimal",
  rows = "all",
  significance_threshold = 0.05,
  score = NULL
)
```

Arguments

gi_list	List of GenomicInteractions objects where each object named with chromosomes contains intra-chromosomal interaction information (see ?gi_list_validate for a detailed explanation of valid gi_list instances).
fname	path to the file to write to (can end with .txt, or .txt.gz).
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes in the gi_list.
columns	Can be 'minimal', which is just distance and counts (and HiCDCPlus result columns 'qvalue','pvalue','mu',and 'sdev', if exists; see ?HiCDCPlus) information, 'minimal_plus_features', which is distance, counts, and other calculated 2D features, 'minimal_plus_score', which generates a .hic pre compatible text file, or 'all', which is distance, counts, calculated 2D features, as well as all 1D features. Defaults to 'minimal'.
rows	Can be 'all' or 'significant', which filters rows according to FDR adjusted pvalue column 'qvalue' (this has to exist in mcols(.)) at significance_threshold. Defaults to 'all'.
significance_threshold	Row filtering threshold on 'qvalue'. Defaults to 0.05.
score	Score column to extract to .hic pre compatible file. See mode options in ?hicdc2hic for more details.

Value

a tab separated flat file concatenating all intra-chromosomal interaction information.

Examples

```
outputdir<-paste0(tempdir(check=TRUE),'/')
gi_list<-generate_binned_gi_list(1e6,chrs='chr22')
gi_list_write(gi_list,paste0(outputdir,'test.txt'))
```

---

gi_list2HTClist *gi_list2HTClist*

Description

This function converts a gi_list instance into a HTClist instance compatible for use with the R Bioconductor package HiTC https://bioconductor.org/packages/HiTC/

Usage

```
gi_list2HTClist(gi_list, chrs = NULL)
```

Arguments

gi_list	List of GenomicInteractions objects with a counts column where each object named with chromosomes contains intra-chromosomal interaction information (minimally containing counts and genomic distance in mcols(gi_list)— see ?gi_list_validate for a detailed explanation of valid gi_list instances).
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to chromosomes in gi_list.

Value

a HTClist instance compatible for use with HiTC

Examples

```
gi_list<-generate_binned_gi_list(50e3,chrs=c('chr22'))
gi_list<-add_hic_counts(gi_list,
hic_path<-system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus"))
htc_list<-gi_list2HTClist(gi_list)
```

---

hic2icenorm_gi_list *hic2icenorm_gi_list*

Description

This function converts a .hic file into a gi_list instance with ICE normalized counts on the counts column for TAD annotation using a copy of TopDom (see ?TopDom_0.0.2) as well as an (optional) .hic file with ICE normalized counts for visualization with Juicebox. This function requires installing the Bioconductor package HiTC.

Usage

```
hic2icenorm_gi_list(
  hic_path,
  binsize = 50000,
  chrs = NULL,
  hic_output = FALSE,
  gen = "Hsapiens",
  gen_ver = "hg19",
  Dthreshold = Inf
)
```

Arguments

hic_path	Path to the .hic file.
binsize	Desired bin size in bp (default 50000).
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to chromosomes in gen and gen_ver except 'chrY' and 'chrM'.
hic_output	If TRUE, a .hic file with the name gsub("\.hic$","_icenorm.hic",hic_path) is generated containing the ICE normalized counts under 'NONE' normalization.
gen	name of the species: e.g., default 'Hsapiens'
gen_ver	genomic assembly version: e.g., default 'hg19'
Dthreshold	maximum distance (included) to check for significant interactions, defaults to maximum in the data.

Value

a thresholded gi_list instance with ICE normalized intra-chromosomal counts for further use with this package, HiCDCPlus.

Examples

```
hic_path<-system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus")
gi_list=hic2icenorm_gi_list(hic_path,binsize=50e3,chrs=c('chr22'))
```

---

hicdc2hic *hicdc2hic*

Description

This function converts various modes from HiCDCPlus gi_list (uniformly binned) instance back into a .hic file with the mode passed as counts that can be retrieved using Juicer Dump (https://github.com/aidenlab/juicer/wiki/ Extraction) with 'NONE' normalization.

Usage

```
hicdc2hic(
  gi_list,
  hicfile,
  mode = "normcounts",
  chrs = NULL,
  gen_ver = "hg19",
  memory = 8
)
```

Arguments

gi_list	List of GenomicInteractions objects where each object named with chromosomes contains intra-chromosomal interaction information (minimally containing counts and genomic distance in mcols(gi_list)— see ?gi_list_validate for a detailed explanation of valid gi_list instances).
hicfile	the path to the .hic file
mode	What to put to the .hic file as score. Allowable options are: 'pvalue' for -log10 significance p-value, 'qvalue' for -log10 FDR corrected p-value, 'normcounts' for raw counts/expected counts, and 'zvalue' for standardized counts (raw counts-expected counts)/modeled standard deviation of expected counts and 'raw' to pass-through 'raw counts. Defaults to 'normcounts'.
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to chromosomes in gi_list.
gen_ver	genomic assembly version: e.g., default 'hg19'
memory	Java memory to generate .hic files. Defaults to 8. Up to 64 is recommended for higher resolutions.

Value

path of the .hic file.

Examples

```
outdir<-paste0(tempdir(check=TRUE),'/')
gi_list<-generate_binned_gi_list(50e3,chrs='chr22')
gi_list<-add_hic_counts(gi_list,
hic_path=system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus"))
hicdc2hic(gi_list,hicfile=paste0(outdir,'out.hic'),
mode='raw')
```

---

hicdcdiff *hicdcdiff*

Description

This function calculates differential interactions for a set of chromosomes across conditions and replicates. You need to install DESeq2 from Bioconductor to use this function.

Usage

```
hicdcdiff(
  input_paths,
  filter_file,
  output_path,
  bin_type = "Bins-uniform",
```

```
  binsize = 5000,
  granularity = 5000,
  chrs = NULL,
  Dmin = 0,
  Dmax = 2e+06,
  diagnostics = FALSE,
  DESeq.save = FALSE,
  fitType = "local"
)
```

Arguments

input_paths	a list with names as condition names and values as paths to gi_list RDS objects (see ?gi_list_validate for a detailed explanation of valid gi_list instances) saved with saveRDS or paths to .hic files for each replicate. e.g.,list(CTCF=c('~/Downloads/GM_CTCF_rep1_MAPQ30_10kb.rds','~/Downloads/GM_CTCF_rep2_MAPQ30_1
filter_file	path to the text file containing columns chr', startI, and startJ denoting the name of the chromosomes and starting coordinates of 2D interaction bins to be compared across conditions, respectively.
output_path	the path to the folder and name prefix you want to place DESeq-processed matrices (in a .txt file), plots (if diagnostics=TRUE) and DESeq2 objects (if DESeq.save=TRUE). Files will be generated for each chromosome.
bin_type	'Bins-uniform' if uniformly binned by binsize in bp, or 'Bins-RE-sites' if binned by number of restriction enzyme fragment cutsites!
binsize	binsize in bp if bin_type='Bins-uniform' (or number of RE fragments if bin_type='Bins-RE-sites'), e.g., default 5000
granularity	Desired distance granularity to base dispersion parameters on in bp. For uniformly binned analysis (i.e., bin_type=='Bins-uniform'), this defaults to the bin size. Otherwise, it is 5000.
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes (except Y and M) in the filter_file.
Dmin	minimum distance (included) to check for significant interactions, defaults to 0. Put Dmin=1 to ignore D=0 bins in calculating normalization factors.
Dmax	maximum distance (included) to check for significant interactions, defaults to 2e6 or maximum in the data; whichever is minimum.
diagnostics	if TRUE, generates diagnostic plots of the normalization factors, geometric means of such factors by distance bin, as well as MA Plots (see DESeq documentation for details about MA plots). Defaults to FALSE.
DESeq.save	if TRUE, saves the DESeq objects for each chromosome as an .rds file in the output_path. Defaults to FALSE.
fitType	follows fitType in DESeq2::estimateDispersions. Allowable options are 'parametric' (parametric regression),'local' (local regression), and 'mean' (constant across interaction bins). Default is 'local'.

Value

paths of a list of three entities. `outputpaths` will have differential bins among those in filter_file. `deseq2paths` will have the DESeq2 object stored as an .rds file. Available if `DESeq.save=TRUE` `plotpaths` will have diagnostic plots (e.g., MA, dispersion, PCA) if `diagnostics=TRUE`.

Examples

```
outputdir<-paste0(tempdir(check=TRUE),'/')
hicdcdiff(input_paths=list(NSD2=c(
system.file("extdata", "GSE131651_NSD2_LOW_arima_example.hic",
package = "HiCDCPlus"),
system.file("extdata", "GSE131651_NSD2_HIGH_arima_example.hic",
package = "HiCDCPlus")),
TKO=c(system.file("extdata", "GSE131651_TKOCTCF_new_example.hic",
package = "HiCDCPlus"),
system.file("extdata", "GSE131651_NTKOCTCF_new_example.hic",
package = "HiCDCPlus"))),
filter_file=system.file("extdata", "GSE131651_analysis_indices.txt.gz",
package = "HiCDCPlus"),
         chrs='chr22',
         output_path=outputdir,
         fitType = 'mean',
         binsize=50000,
         diagnostics=FALSE)
```

`HiCDCPlus` *HiCDCPlus*

Description

This function finds significant interactions in a HiC-DC readable matrix and expresses statistical significance of counts through the following: 'pvalue': significance *P*-value, 'qvalue': FDR corrected *P*-value, mu': expected counts, 'sdev': modeled standard deviation of expected counts.

Usage

```
HiCDCPlus(
  gi_list,
  covariates = NULL,
  chrs = NULL,
  distance_type = "spline",
  model_distribution = "nb",
  binned = TRUE,
  df = 6,
  Dmin = 0,
  Dmax = 2e+06,
  ssize = 0.01,
  splineknotting = "uniform",
```

```
  model_filepath = NULL
)
```

Arguments

gi_list	List of GenomicInteractions objects where each object named with chromosomes contains intrachromosomal interaction information (minimally containing counts and genomic distance in mcols(gi_list[[1]])—see ?gi_list_validate for a detailed explanation of valid gi_list instances).
covariates	covariates to be considered in addition to genomic distance D. Defaults to all covariates besides 'D','counts','mu','sdev',pvalue','qvalue' in mcols(gi_list[[1]])
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes in the gi_list.
distance_type	distance covariate form: 'spline' or 'log'. Defaults to 'spline'.
model_distribution	'nb' uses a Negative Binomial model, 'nb_vardisp' uses a Negative Binomial model with a distance specific dispersion parameter inferred from the data, 'nb_hurdle' uses the legacy HiCDC model.
binned	TRUE if uniformly binned or FALSE if binned by restriction enzyme fragment cutsites
df	degrees of freedom for the genomic distance spline function if distance_type='spline'. Defaults to 6, which corresponds to a cubic spline as explained in Carty et al. (2017)
Dmin	minimum distance (included) to check for significant interactions, defaults to 0
Dmax	maximum distance (included) to check for significant interactions, defaults to 2e6 or maximum in the data; whichever is minimum.
ssize	Distance stratified sampling size. Can decrease for large chromosomes. Increase recommended if model fails to converge. Defaults to 0.01.
splineknotting	Spline knotting strategy. Either "uniform", uniformly spaced in distance, or placed based on distance distribution of counts "count-based" (i.e., more closely spaced where counts are more dense).
model_filepath	Outputs fitted HiC-DC model object as an .rds file per chromosome. Defaults to NULL (no output).

Value

A valid gi_list instance with additional mcols(.) for each chromosome: pvalue': significance *P*-value, 'qvalue': FDR corrected *P*-value, mu': expected counts, 'sdev': modeled standard deviation of expected counts.

Examples

```
gi_list<-generate_binned_gi_list(50e3,chrs='chr22')
gi_list<-add_hic_counts(gi_list,
hic_path<-system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus"))
gi_list<-HiCDCPlus(gi_list)
```

HiCDCPlus_chr *HiCDCPlus_chr*

Description

This function finds significant interactions in a HiC-DC readable matrix restricted to a single chromosome and expresses statistical significance of counts through the following: 'pvalue': significance *P*-value, 'qvalue': FDR corrected *P*-value, mu': expected counts, 'sdev': modeled standard deviation of expected counts.

Usage

```
HiCDCPlus_chr(
  gi,
  covariates = NULL,
  distance_type = "spline",
  model_distribution = "nb",
  binned = TRUE,
  df = 6,
  Dmin = 0,
  Dmax = 2e+06,
  ssize = 0.01,
  splineknotting = "uniform",
  model_filepath = NULL
)
```

Arguments

gi	Instance of a single chromosome `GenomicInteractions` object containing intra-chromosomal interaction information (minimally containing counts and genomic distance).
covariates	covariates to be considered in addition to genomic distance D. Defaults to all covariates besides 'D','counts','mu','sdev',pvalue','qvalue' in `mcols(gi)`
distance_type	distance covariate form: 'spline' or 'log'. Defaults to 'spline'.
model_distribution	'nb' uses a Negative Binomial model, 'nb_vardisp' uses a Negative Binomial model with a distance specific dispersion parameter inferred from the data, 'nb_hurdle' uses the legacy HiC-DC model.
binned	TRUE if uniformly binned or FALSE if binned by restriction enzyme fragment cut sites.
df	degrees of freedom for the genomic distance spline function if `distance_type='spline'`. Defaults to 6, which corresponds to a cubic spline as explained in Carty et al. (2017)
Dmin	minimum distance (included) to check for significant interactions, defaults to 0

Dmax	maximum distance (included) to check for significant interactions, defaults to 2e6 or maximum in the data; whichever is minimum.
ssize	Distance stratified sampling size. Can decrease for large chromosomes. Increase recommended if model fails to converge. Defaults to 0.01.
splineknotting	Spline knotting strategy. Either "uniform", uniformly spaced in distance, or placed based on distance distribution of counts "count-based" (i.e., more closely spaced where counts are more dense).
model_filepath	Outputs fitted HiC-DC model object as an .rds file with chromosome name indicatd on it. Defaults to NULL (no output).

Value

A valid gi instance with additional mcols(.): pvalue': significance *P*-value, 'qvalue': FDR corrected *P*-value, mu': expected counts, 'sdev': modeled standard deviation of expected counts.

Examples

```
gi_list<-generate_binned_gi_list(50e3,chrs='chr22')
gi_list<-add_hic_counts(gi_list,
hic_path<-system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus"))
gi<-HiCDCPlus_chr(gi_list[[1]])
```

HiCDCPlus_parallel *HiCDCPlus_parallel*

Description

This function finds significant interactions in a HiC-DC readable matrix and expresses statistical significance of counts through the following with a parallel implementation (using sockets; compatible with Windows): 'pvalue': significance *P*-value, 'qvalue': FDR corrected *P*-value, mu': expected counts, 'sdev': modeled standard deviation of expected counts.

Usage

```
HiCDCPlus_parallel(
  gi_list,
  covariates = NULL,
  chrs = NULL,
  distance_type = "spline",
  model_distribution = "nb",
  binned = TRUE,
  df = 6,
  Dmin = 0,
  Dmax = 2e+06,
  ssize = 0.01,
  splineknotting = "uniform",
  ncore = NULL
)
```

Arguments

gi_list	List of GenomicInteractions objects where each object named with chromosomes contains intrachromosomal interaction information (minimally containing counts and genomic distance in mcols(gi_list[[1]])—see ?gi_list_validate for a detailed explanation of valid gi_list instances).
covariates	covariates to be considered in addition to genomic distance D. Defaults to all covariates besides 'D','counts','mu','sdev',pvalue','qvalue' in mcols(gi)
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes in the gi_list.
distance_type	distance covariate form: 'spline' or 'log'. Defaults to 'spline'.
model_distribution	'nb' uses a Negative Binomial model, 'nb_vardisp' uses a Negative Binomial model with a distance specific dispersion parameter inferred from the data, 'nb_hurdle' uses the legacy HiC-DC model.
binned	TRUE if uniformly binned or FALSE if binned by restriction enzyme fragment cutsites
df	degrees of freedom for the genomic distance spline function if distance_type='spline'. Defaults to 6, which corresponds to a cubic spline as explained in Carty et al. (2017)
Dmin	minimum distance (included) to check for significant interactions, defaults to 0
Dmax	maximum distance (included) to check for significant interactions, defaults to 2e6 or maximum in the data; whichever is minimum.
ssize	Distance stratified sampling size. Can decrease for large chromosomes. Increase recommended if model fails to converge. Defaults to 0.01.
splineknotting	Spline knotting strategy. Either "uniform", uniformly spaced in distance, or placed based on distance distribution of counts "count-based" (i.e., more closely spaced where counts are more dense).
ncore	Number of cores to parallelize. Defaults to parallel::detectCores()-1.

Value

A valid gi_list instance with additional mcols(.) for each chromosome: pvalue': significance *P*-value, 'qvalue': FDR corrected *P*-value, mu': expected counts, 'sdev': modeled standard deviation of expected counts.

Examples

```
gi_list<-generate_binned_gi_list(50e3,chrs='chr22')
gi_list<-add_hic_counts(gi_list,
hic_path=system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus"))
gi<-HiCDCPlus_parallel(gi_list,ncore=1)
```

HTClist2gi_list *HTClist2gi_list*

Description

This function converts a HTClist instance into a gi_list instance with counts for further use with this package, HiCDCPlus

Usage

```
HTClist2gi_list(htc_list, chrs = NULL, Dthreshold = 2e+06)
```

Arguments

htc_list	A valid HTClist instance (see vignette("HiTC"))
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to chromosomes in htc_list.
Dthreshold	maximum distance (included) to check for significant interactions, defaults to 2e6 or maximum in the data; whichever is smaller.

Value

a thresholded gi_list instance with intra-chromosomal counts for further use with HiCDCPlus

Examples

```
gi_list<-generate_binned_gi_list(50e3,chrs=c('chr22'))
gi_list<-add_hic_counts(gi_list,
hic_path=system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus"))
htc_list<-gi_list2HTClist(gi_list)
gi_list2<-HTClist2gi_list(htc_list,Dthreshold=Inf)
```

straw *straw*

Description

Adapted C++ implementation of Juicer's dump. Reads the .hic file, finds the appropriate matrix and slice of data, and outputs as an R DataFrame.

Usage

```
straw(norm, fn, ch1, ch2, u, bs)
```

Arguments

norm	Normalization to apply. Must be one of NONE/VC/VC_SQRT/KR. VC is vanilla coverage, VC_SQRT is square root of vanilla coverage, and KR is Knight-Ruiz or Balanced normalization.
fn	path to the .hic file
ch1	first chromosome location (e.g., "1")
ch2	second chromosome location (e.g., "8")
u	BP (BasePair) or FRAG (restriction enzyme FRAGment)
bs	The bin size. By default, for BP, this is one of <2500000, 1000000, 500000, 250000, 100000, 50000, 25000, 10000, 5000> and for FRAG this is one of <500, 200, 100, 50, 20, 5, 2, 1>.

Details

Usage: straw <NONE/VC/VC_SQRT/KR> <hicFile(s)> <chr1>[:x1:x2] <chr2>[:y1:y2] <BP/FRAG> <binsize>

Value

Data.frame of a sparse matrix of data from hic file. x,y,counts

---

straw_dump *straw_dump*

Description

Interface for Juicer's dump in case C++ straw fails (known to fail on Windows due to zlib compression not being OS agnostic and particularly not preserving null bytes, which .hic files are delimited with). This function reads the .hic file, finds the appropriate matrix and slice of data, writes it to a temp file, reads and modifies it, and outputs as an R DataFrame (and also deletes the temp file).

Usage

```
straw_dump(norm, fn, ch1, ch2, u, bs)
```

Arguments

norm	Normalization to apply. Must be one of NONE/VC/VC_SQRT/KR. VC is vanilla coverage, VC_SQRT is square root of vanilla coverage, and KR is Knight-Ruiz or Balanced normalization.
fn	path to the .hic file
ch1	first chromosome location (e.g., "1")
ch2	second chromosome location (e.g., "8")
u	BP (BasePair) or FRAG (restriction enzyme FRAGment)
bs	The bin size. By default, for BP, this is one of <2500000, 1000000, 500000, 250000, 100000, 50000, 25000, 10000, 5000> and for FRAG this is one of <500, 200, 100, 50, 20, 5, 2, 1>.

Details

Usage: straw_dump <oe/observed> <NONE/VC/VC_SQRT/KR> <hicFile(s)> <chr1>[:x1:x2] <chr2>[:y1:y2] <BP/FRAG> <binsize> <outfile>

Value

Data.frame of a sparse matrix of data from hic file. x,y,counts

Index

add_1D_features, 3
add_2D_features, 4
add_hic_counts, 5
add_hicpro_allvalidpairs_counts, 5
add_hicpro_matrix_counts, 6

construct_features, 7
construct_features_chr, 8
construct_features_parallel, 9

expand_1D_features, 11
extract_hic_eigenvectors, 12

generate_binned_gi_list, 13
generate_bintolen_gi_list, 14
generate_df_gi_list, 15
get_chr_sizes, 16
get_chrs, 16
get_enzyme_cutsites, 17
gi_list2HTClist, 22
gi_list_binsize_detect, 17
gi_list_Dthreshold.detect, 18
gi_list_read, 19
gi_list_topdom, 20
gi_list_validate, 21
gi_list_write, 21

hic2icenorm_gi_list, 23
hicdc2hic, 24
hicdcdiff, 25
HiCDCPlus, 27
HiCDCPlus_chr, 29
HiCDCPlus_parallel, 30
HTClist2gi_list, 32

straw, 32
straw_dump, 33