

Package: HoloFoodR (via r-universe)

June 2, 2026

Type Package

Version 1.6.0

Title R interface to EBI HoloFood resource

Description Utility package to facilitate integration and analysis of EBI HoloFood data in R. This package streamlines access to the resource, allowing for direct loading of data into formats optimized for downstream analytics.

biocViews Software, Infrastructure, DataImport, Microbiome, MicrobiomeData

License Artistic-2.0 | file LICENSE

Encoding UTF-8

Depends R(>= 4.4.0), MultiAssayExperiment, TreeSummarizedExperiment

Imports dplyr, httr2, jsonlite, S4Vectors, stringi, stats, SummarizedExperiment, utils

Suggests BiocStyle, DT, ggh4x, ggsignif, knitr, MGNifyR, mia, miaViz, MOFA2, patchwork, reticulate, rmarkdown, scater, shadowtext, testthat, UpSetR

URL <https://github.com/EBI-Metagenomics/HoloFoodR>

BugReports <https://github.com/EBI-Metagenomics/HoloFoodR/issues>

VignetteBuilder knitr

RoxygenNote 7.3.2

Config/pak/sysreqs cmake make libicu-dev libuv1-dev libssl-dev zlib1g-dev

Repository <https://bioc-release.r-universe.dev>

Date/Publication 2026-04-28 13:03:20 UTC

RemoteUrl <https://github.com/bioc/HoloFoodR>

RemoteRef RELEASE_3_23

RemoteSha a27e366f64e946deb3d128ba808953959280b115

Contents

addMGnify	2
doQuery	4
getData	5
getMetaboLights	6
getResult	8
HoloFoodR	9
Index	10

addMGnify	<i>Add results from MGnifyR to HoloFoodR results</i>
-----------	--

Description

Add results from MGnifyR to HoloFoodR results

Usage

```
addMGnify(x, y, ...)
```

```
## S4 method for signature 'SummarizedExperiment,MultiAssayExperiment'
```

```
addMGnify(
  x,
  y,
  exp.name1 = "metagenomic",
  exp.name2 = "metagenomic_amplicon",
  replace = TRUE,
  ...
)
```

```
## S4 method for signature 'SummarizedExperiment,SummarizedExperiment'
```

```
addMGnify(x, y, ...)
```

```
## S4 method for signature 'SummarizedExperiment,ANY'
```

```
addMGnify(x, y, id.col1 = "sample_biosample", id.col2 = "accession", ...)
```

Arguments

x	SummarizedExperiment. Results from MGnifyR::getResult().
y	MultiAssayExperiment or SummarizedExperiment or data.frame-like table. Results from HoloFoodR::getResult() or sample metadata from it.
...	optional arguments not used currently.
exp.name1	Character scalar. Specifies the name of experiment that will be added to y. (Default: "metagenomic")

exp.name2	Character scalar. Specifies the name of experiment from HoloFoodR results. This experiment is used to match IDs with MGnify data. (Default: "metagenomic_amplicon")
replace	Logical scalar. Whether to replace the template experiment. (Default: TRUE)
id.col1	Character scalar. Specifies the name of column from colData(x) that includes HoloFood identifiers. (Default: "sample_biosample")
id.col2	Character scalar. Specifies the name of column from colData(y[[exp.name2]]) that includes HoloFood identifiers. (Default: "accession")

Details

Metagenomic data is found in MGnify rather than HoloFoodR, and the two databases use different sample identifiers. However, MGnify's sample metadata includes references to the identifiers used in the HoloFood database, making it straightforward to convert sample IDs for alignment with HoloFood data. Despite this, HoloFood contains additional metadata not available in MGnify. Moreover, integrating data into a `MultiAssayExperiment` while maintaining accurate sample and system matches can be challenging.

This function is designed to simplify these tasks, enabling seamless integration of MGnify data with HoloFood data after retrieval from the database. You need only to input the returned data from `MGnifyR::getResult()` and `HoloFoodR::getResult()` functions.

Value

`MultiAssayExperiment`

Examples

```
## Not run:
# Get data from HoloFood database
mae <- HoloFoodR::getResult(
  salmon_sample_ids,
  use.cache = TRUE
)

# Get data from MGnify database
mg <- MgnifyClient(
  useCache = TRUE,
  cacheDir = ".MGnifyR_cache"
)
tse <- MGnifyR::getResult(
  mg,
  accession = mgnify_analyses_ids,
  get.func = FALSE
)

# Add MGnify data to HoloFood data
mae <- addMGnify(tse, mae)

## End(Not run)
```

doQuery	<i>Search HoloFood database for animals, genome catalogues, samples, or viral catalogues</i>
---------	--

Description

Search HoloFood database for animals, genome catalogues, samples, or viral catalogues

Usage

```
doQuery(type, flatten = TRUE, ...)
```

Arguments

type	Character scalar specifying the type of data to query. Must be one of the following options: "animals", "genome-catalogues", "samples" or "viral-catalogues".
flatten	Logical scalar specifying whether to flatten the resulting data.frame. This means that columns with multiple values are separated to multiple columns. (Default: TRUE)
...	optional arguments: <ul style="list-style-type: none"> • max.hits NULL or integer scalar specifying the maximum number of results to fetch. When NULL, all results are fetched. (Default: NULL) • spread.sample.types Logical scalar specifying whether to create spread sample types column of animals data. In animals data, sample types column might have multiple values that might be hard to explore. This argument specifies whether to create presence/absence table from sample types. (Default: TRUE) • use.cache Logical scalar specifying whether to use cache. (Default: FALSE) • cache.dir Character scalar specifying cache directory. (Default: tempdir()) • clear.cache Logical scalar specifying whether to remove and clear cache (Default: FALSE)

Details

doQuery is a flexible query function which can be utilized to search available animals, genome catalogues, samples, or viral catalogues. Search results can be filtered; for example, animals can be filtered based on available samples. See [Api browser](https://www.holofooddata.org/api/docs) for information on filters. You can find help on customizing queries from [here](https://emg-docs.readthedocs.io/en/latest/api.html#customising-queries).

Value

data.frame

Examples

```
# Find animals results. The maximum amount of results is 100. Use filter
# so that only chicken is searched. (See details on customizing queries)
res <- doQuery("animals", max.hits = 100, system = "chicken")
head(res)
```

getData

Get data from HoloFood database

Description

Get data from HoloFood database

Usage

```
getData(
  type = NULL,
  accession.type = NULL,
  accession = NULL,
  flatten = FALSE,
  ...
)
```

Arguments

type	NULL or character scalar specifying the type of data to query. Must be one of the following options: "analysis-summaries", "animals", "genome-catalogues", "samples", "sample_metadata_markers" or "viral-catalogues". When genome or viral catalogues is fetched by their accession ID, the type can also be "genomes" or "fragments". (Default: NULL)
accession.type	NULL or character scalar specifying the type of accession IDs. Must be one of the following options: "animals", "genome-catalogues", "samples" or "viral-catalogues". (Default: NULL)
accession	NULL or character vector specifying the accession IDs of type accession.type. (Default: NULL)
flatten	Logical scalar specifying whether to flatten the resulting data.frame. This means that columns with multiple values are separated to multiple columns. (Default: FALSE)
...	optional arguments: <ul style="list-style-type: none"> • max.hits NULL or integer scalar specifying the maximum number of results to fetch. When NULL, all results are fetched. (Default: NULL) • use.cache Logical scalar specifying whether to use cache (Default: FALSE) • cache.dir Character scalar specifying cache directory. (Default: tempdir()) • clear.cache Logical scalar specifying whether to remove and clear cache (Default: FALSE)

Details

With `getData`, you can fetch data from the database. Compared to `getResult`, this function is more flexible since it can fetch any kind of data from the database. However, this function returns the data without further wrangling as `list` or `data.frame` which are not optimized format for fetching data on samples.

Search results can be filtered; for example, animals can be filtered based on available samples. See [Api browser](https://www.holofooddata.org/api/docs) for information on filters. You can find help on customizing queries from [here](https://emg-docs.readthedocs.io/en/latest/api.html#customising-queries).

Value

`list` or `data.frame`

See Also

[getResult](#)

Examples

```
# Find genome catalogues
catalogues <- getData(type = "genome-catalogues")
head(catalogues)

# Find genomes based on certain genome catalogue id
res <- getData(
  type = "genomes", accession.type = "genome-catalogues",
  accession = catalogues[1, "id"], max.hits = 100)
# See the data.
head(res)
# It includes for instance summary of the CAZy
# (Carbohydrate-Active enZymes) annotations as a counts per category
cazy <- res[, grepl("annotations.cazy", colnames(res)), drop = FALSE]
head(cazy)
# Moreover, it includes a sample list. This sample list represents a
# collection of samples where the MAG was identified. Thr data has also the
# completeness of MAG in a sample.
head(res[ c("metadata.Sample_accession", "metadata.Completeness")])
```

getMetaboLights

Get metabolomic data from MetaboLights database

Description

Get metabolomic data from MetaboLights database

Usage

```
getMetaboLights(study.id, output = "list", ...)
```

```
getMetaboLightsFile(study.id, file, ...)
```

Arguments

study.id	character vector specifying the study identifier of data that is going to be fetched from the MetaboLights database.
output	character scalar specifying output format. Must be "list", "TreeSE" (TreeSummarizedExperiment) or "SE" (SummarizedExperiment). (Default: "list")
...	optional arguments: <ul style="list-style-type: none">• cache.dir Character scalar specifying directory where downloaded file is stored. (Default: tempdir())• timeout Integer scalar specifying timeout in seconds for loading a file. (Default: 5*60)• ion.mode Character scalar specifying metabolite assignment files to fetch. If "positive" only positive ions are fetched. Similarly "negative" means that negative ions are fetched if such data exists. By selecting "both", one can fetch both positive and negative ions. (Default: "both")
file	character vector specifying the files that are being fetched.

Details

The HoloFood database primarily comprises targeted metabolomic data, omitting non-targeted metabolomic information. Nonetheless, it features URLs linking to studies within the MetaboLights database. This functionality enables users to access non-targeted metabolomic data. The `getMetaboLights` function returns a structured list encompassing processed data in `data.frame` format for study metadata, assay metadata, and assay.

The metadata includes the file names of spectra data. Those files can be loaded with `getMetaboLightsFile`. Alternatively, once you've identified the study and files to fetch, you can refer to this [vignette](https://rformassspectrometry.github.io/data-from-metabolights/)(<https://rformassspectrometry.github.io/data-from-metabolights/>) for instructions on loading the data directly into an `MsExperiment` object, specifically designed for metabolomics spectra data.

Value

list, SummarizedExperiment or TreeSummarizedExperiment

See Also

[getResult](#) [getData](#)

Examples

```
# This example is not run, because the server fails to respond sometimes.
if( FALSE ){
  res <- getMetaboLights("MTBLS4381")
}
```

```

file_paths <- getMetaboLightsFile(
  study.id = "MTBLS4381",
  file = res[["assay_meta"]][["Raw Spectral Data File"]]
)
# Get data as SummarizedExperiment
se <- getMetaboLights("MTBLS3540", output = "SE")
}

```

getResult

Get data on samples from HoloFood database

Description

Get data on samples from HoloFood database

Usage

```
getResult(accession, ...)
```

Arguments

accession	Character vector specifying the accession IDs of type samples.
...	optional arguments: <ul style="list-style-type: none"> • use.cache Logical scalar specifying whether to use cache. Note that when <code>get.metabolomic = TRUE</code> is specified, the file from the <code>MetaboLights</code> is stored in the local system to the location specified by <code>cache.dir</code> despite of the value of <code>use.cache</code>. (Default: FALSE) • cache.dir Character scalar specifying cache directory. (Default: <code>tempdir()</code>) • clear.cache Logical scalar specifying whether to use <code>cache</code> (Default: FALSE) • assay.type Character scalar specifying the name of assay in resulting <code>TreeSummarizedExperiment</code> object. (Default: "counts") • get.metabolomic Logical scalar specifying whether to retrieve processed metabolomic data from <code>MetaboLights</code> database. For retrieving spectra data, refer to getMetaboLights documentation. (Default: FALSE)

Details

With `getResult`, you can fetch data on samples from the HoloFood database. Compared to `getData`, this function is more convenient for fetching the samples data because it converts the data to `MultiAssayExperiment` where different omics are stored as `TreeSummarizedExperiment` objects which are optimized for downstream analytics. Columns of returned `MultiAssayExperiment` are individual animals. These columns are linked with individual samples that are stored in `TreeSummarizedExperiment` objects.

The HoloFood database lacks non-targeted metabolomic data but they can be fetched from `MetaboLights` resource. Certain datasets include processed features. Those datasets can be retrieved with the function `getResult` which integrates metabolomic data with other datasets from HoloFood.

Furthermore, while the HoloFoodR database does not include metagenomic assembly data, users can access such data from the MGnify database. The MGnifyR package provides a convenient interface for accessing this database. By employing `MGnifyR::getResult()`, users can obtain data formatted as a `MultiAssayExperiment` object, containing multiple `TreeSummarizedExperiment` objects. Consequently, data from both HoloFood and MGnify databases are inherently compatible for subsequent downstream analysis.

Value

`MultiAssayExperiment`

See Also

[getData TreeSummarizedExperiment MultiAssayExperiment MGnifyR:getResult](#)

Examples

```
# Find samples on certain animal
samples <- doQuery("samples", animal_accession = "SAMEA112904746")

# Get the data
mae <- getResult(samples[["accession"]])
mae
```

HoloFoodR

HoloFoodR *package*

Description

HoloFoodR implements an interface to the EBI HoloFood database. See the vignette for a general introduction to this package, [about HoloFood](https://www.holofood.eu/) for general HoloFood information, and [API documentation](https://docs.holofooddata.org/api.html) for details on the JSONAPI implementation.

Author(s)

Maintainer: Tuomas Borman <tuomas.v.borman@utu.fi> ([ORCID](#))

Authors:

- Artur Sannikov <arsann@utu.fi> ([ORCID](#))
- Leo Lahti <leo.lahti@iki.fi> ([ORCID](#))

See Also

[TreeSummarizedExperiment MultiAssayExperiment](#)

Index

addMGnify, [2](#)
addMGnify, SummarizedExperiment, ANY-method
 ([addMGnify](#)), [2](#)
addMGnify, SummarizedExperiment, MultiAssayExperiment-method
 ([addMGnify](#)), [2](#)
addMGnify, SummarizedExperiment, SummarizedExperiment-method
 ([addMGnify](#)), [2](#)

doQuery, [4](#)

getData, [5](#), [7](#), [9](#)
getMetaboLights, [6](#), [8](#)
getMetaboLightsFile ([getMetaboLights](#)), [6](#)
getResult, [6](#), [7](#), [8](#)

HoloFoodR, [9](#)
HoloFoodR-package ([HoloFoodR](#)), [9](#)

MGnifyR:getResult, [9](#)
MultiAssayExperiment, [9](#)

TreeSummarizedExperiment, [9](#)