

Package: IntramiRExploreR (via r-universe)

June 2, 2026

Title Predicting Targets for Drosophila Intragenic miRNAs

Version 1.34.0

Author Surajit Bhattacharya and Daniel Cox

Maintainer Surajit Bhattacharya <sbhattach2@childrensnational.org>

Description Intra-miR-ExploreR, an integrative miRNA target prediction bioinformatics tool, identifies targets combining expression and biophysical interactions of a given microRNA (miR). Using the tool, we have identified targets for 92 intragenic miRs in *D. melanogaster*, using available microarray expression data, from Affymetrix 1 and Affymetrix2 microarray array platforms, providing a global perspective of intragenic miR targets in *Drosophila*. Predicted targets are grouped according to biological functions using the DAVID Gene Ontology tool and are ranked based on a biologically relevant scoring system, enabling the user to identify functionally relevant targets for a given miR.

Depends R (>= 3.4)

Imports igraph (>= 1.0.1), FGNet (>= 3.0.7), knitr (>= 1.12.3), stats, utils, grDevices, graphics

Suggests gProfileR, topGO, org.Dm.eg.db, rmarkdown, testthat

VignetteBuilder knitr

License GPL-2

biocViews Software, Microarray, GeneTarget, StatisticalMethod, GeneExpression, GenePrediction

Encoding UTF-8

LazyData true

RoxygenNote 7.1.2

URL <https://github.com/VilainLab/IntramiRExploreR>

BugReports <https://github.com/VilainLab/IntramiRExploreR>

Config/pak/sysreqs libgplk-dev libicu-dev libpng-dev libxml2-dev

Repository <https://bioc-release.r-universe.dev>
Date/Publication 2026-04-28 12:56:59 UTC
RemoteUrl <https://github.com/bioc/IntramiRExploreR>
RemoteRef RELEASE_3_23
RemoteSha 51681e8f3685e90466fbabd83e9daed259fe0e8e

Contents

| | |
|----------------------------------|-----------|
| Affy1_Distance_Final | 2 |
| Affy1_Pearson_Final | 3 |
| Affy2_Distance_Final | 3 |
| Affy2_Pearson_Final | 4 |
| extract_HostGene | 5 |
| extract_intragenic_miR | 5 |
| Gene_Visualisation | 6 |
| genes_Stat | 7 |
| GetGOS_ALL | 8 |
| IntramiRExploreR | 9 |
| miRNA_ID_to_Function | 9 |
| miRNA_summary_DB | 10 |
| miRTargets_Stat | 10 |
| Visualisation | 11 |
| Index | 13 |

Affy1_Distance_Final *Targets for the microRNA analyzed from Affy1 platform using Distance.*

Description

A precomputed dataset containing the targets, scores and other attributes of 83 intragenic microRNAs using Distance Correlation for platform Affymetrix 1.

Usage

```
Affy1_Distance_Final
```

Format

A data frame with 53399 rows and 8 variables:

miRNA miRNA name, miRNA symbol
GeneSymbol Gene name, in Gene Symbol
FBN Gene name, in FlybaseID
CGID Gene name, in CGID

Score Computed Score, in float
GeneFunction Gene Functions, from Flybase
experiments Experiments, from ArrayExpress
TargetDatabases Target Database Name, from TargetDatabases

Affy1_Pearson_Final *Targets for the microRNA analyzed from Affy1 platform using Pearson.*

Description

A precomputed dataset containing the targets, scores and other attributes of 83 intragenic microRNAs using Pearson Correlation for platform Affymetrix 1.

Usage

Affy1_Pearson_Final

Format

A data frame with 41845 rows and 8 variables:

miRNA miRNA name, miRNA symbol
GeneSymbol Gene name, in Gene Symbol
FBGN Gene name, in FlybaseID
CGID Gene name, in CGID
Score Computed Score, in float
GeneFunction Gene Functions, from Flybase
experiments Experiments, from ArrayExpress
TargetDatabases Target Database Name, from TargetDatabases

Affy2_Distance_Final *Targets for the microRNA analyzed from Affy2 platform using Distance.*

Description

A precomputed dataset containing the targets, scores and other attributes of 83 intragenic microRNAs using Distance Correlation for platform Affymetrix 1.

Usage

Affy2_Distance_Final

Format

A data frame with 73374 rows and 8 variables:

miRNA miRNA name, miRNA symbol

GeneSymbol Gene name, in Gene Symbol

FBGN Gene name, in FlybaseID

CGID Gene name, in CGID

Score Computed Score, in float

GeneFunction Gene Functions, from Flybase

experiments Experiments, from ArrayExpress

TargetDatabases Target Database Name, from TargetDatabases

Affy2_Pearson_Final *Targets for the microRNA analyzed from Affy2 platform using Pearson.*

Description

A precomputed dataset containing the targets, scores and other attributes of 83 intragenic microRNAs using Pearson Correlation for platform Affymetrix 1.

Usage

Affy2_Pearson_Final

Format

A data frame with 52913 rows and 8 variables:

miRNA miRNA name, miRNA symbol

GeneSymbol Gene name, in Gene Symbol

FBGN Gene name, in FlybaseID

CGID Gene name, in CGID

Score Computed Score, in float

GeneFunction Gene Functions, from Flybase

experiments Experiments, from ArrayExpress

TargetDatabases Target Database Name, from TargetDatabases

extract_HostGene *Extract Host Gene for a given Intragenic miRNA.*

Description

Extract Host Gene for a given Intragenic miRNA.

Usage

```
extract_HostGene(miRNA)
```

Arguments

miRNA A String containing the miRNA name.

Value

genf, a character string or vector containing Host gene for the Intragenic miRNA.

Examples

```
miRNA="dme-miR-12"  
extract_HostGene(miRNA)
```

extract_intragenic_miR *Extract Intragenic miRNA for a given Host gene.*

Description

Extract Intragenic miRNA for a given Host gene.

Usage

```
extract_intragenic_miR(gene)
```

Arguments

gene character. Gene Symbol.

Value

miRf, a character string or vector containing Intragenic miRNA for the Host Gene.

Examples

```
gene="Gmap"  
extract_intragenic_miR(gene)
```

Gene_Visualisation *Visualises the targetGene:miRNA network using Cytoscape and igraph*

Description

Visualises the targetGene:miRNA network using Cytoscape and igraph .

Usage

```
Gene_Visualisation(
  mRNA,
  mRNA_type = c("GeneSymbol", "FBGN", "CGID"),
  method = c("Pearson", "Distance", "Both"),
  platform = c("Affy1", "Affy2"),
  visualisation = c("igraph", "Cytoscape", "text", "console"),
  path = tempdir(),
  layout = c("kamadakawai", "reingold.tilford", "fruchterman.reingold", "interactive")
)
```

Arguments

| | |
|---------------|--------------------------------------------------------------------------------------------------------------------|
| mRNA | character. gene Identifier. |
| mRNA_type | character. mRNA id type. The choices are 'GeneSymbol','FBID' and 'CGID'. |
| method | character. Statistical Methods. Choices are 'Pearson','Distance','Both' |
| platform | character. Affymetrix Platforms. Choices are 'Affy1','Affy2'. |
| visualisation | character. Visualisation type. Choices are 'igraph','Cytoscape','text' and "console" |
| path | character. Path where data.frame is saved when visualisation is text. Default is tempdir(). |
| layout | character. Network choices. Choices are 'kamadakawai','reingold.tilford','fruchterman.reingold' and 'interactive'. |

Value

Depending upon the output choice network image or dataframe containing miRNAs that target the query gene are output.

Examples

```
mRNA='Syb'
Gene_Visualisation(mRNA,mRNA_type=c('GeneSymbol'),method=c('Pearson'),
  platform=c('Affy1'), visualisation = "console")
```

| | |
|------------|----------------------------------------------------|
| genes_Stat | <i>Extracting miRNAs that target a query gene.</i> |
|------------|----------------------------------------------------|

Description

Extracting miRNAs that target a query gene.

Usage

```
genes_Stat(  
  gene,  
  geneIDType = c("GeneSymbol", "FBGN", "CGID"),  
  method = c("Pearson", "Distance", "Both", "BothIntersect"),  
  Platform = c("Affy1", "Affy2"),  
  Text = FALSE,  
  outpath = tempdir()  
)
```

Arguments

| | |
|------------|------------------------------------------------------------------------------|
| gene | character. gene Identifier. |
| geneIDType | character. GeneIDType choices are 'GeneSymbol', 'FBGN', 'CGID' |
| method | character. Choices are 'Pearson', 'Distance', 'Both' and 'BothIntersected' |
| Platform | character. Choices are 'Affy1', 'Affy2'. |
| Text | logical . To choose between storing the data as text file. Default is FALSE. |
| outpath | character. The path where the data is stored if TEXT=TRUE. Default is |

Value

Outputs the miRNA information, Target Prediction Score, miRNA miRNA function and Target Database that predicts the interaction in a dataframe. Depending upon the output choice data is stored in the path specified. Default option prints output to the console.

Examples

```
gene="Syb"  
genes_Stat(gene, geneIDType="GeneSymbol", method=c("Pearson"),  
           Platform=c("Affy1"), Text=FALSE)
```

GetGOS_ALL *Gene ontology for Target Genes.*

Description

Gene ontology for Target Genes.

Usage

```
GetGOS_ALL(
  gene,
  GO = c("topGO"),
  term = c("GOTERM_BP_ALL", "GOTERM_MF_ALL", "GOTERM_CC_ALL"),
  geneIdType = "ALIAS",
  path = tempdir(),
  ontology = c("GO_BP", "GO_MF", "GO_CC"),
  filename
)
```

Arguments

| | |
|------------|---------------------------------------------------------------------------------------------------|
| gene | List A String or vector containing the Gene names. |
| GO | A String depicting the chosen GO tool. Choice is "topGO" |
| term | A String depicting the chosen term. Choices are "GOTERM_BP_ALL","GOTERM_MF_ALL", "GOTERM_CC_ALL". |
| geneIdType | Type of gene Id given as input. Default "ALIAS" |
| path | String. The path where the data is stored if TEXT=TRUE. |
| ontology | Ontology selection for topGO. Choices are "GO_BP","GO_MF","GO_CC". |
| filename | Name of the file to store Gene Ontology. |

Value

Depending upon the output choice data is stored in the path specified. Default option prints output to the console.

Examples

```
## Not run:
miR="dme-miR-12"
a<-Visualisation(miR,mRNA_type=c("GeneSymbol"),method=c("Both"),
  platform=c("Affy1"),thresh=100)
genes<-a$Target_GeneSymbol
GetGOS_ALL(genes,GO=c("topGO"),term=c("GO_BP"),path=tempdir(),
  filename="test")

## End(Not run)
```

| | |
|------------------|------------------------------------------------------------------------------------|
| IntramiRExploreR | <i>IntramiRExploreR: Prediction of targets for Intragenic miRNA in Drosophila.</i> |
|------------------|------------------------------------------------------------------------------------|

Description

Prediction of targets for Drosophila Intragenic microRNAs and Integrated approach using Gene Ontology and Networking tools.

Examples

```
## Not run:  
gene='Gmap'  
extract_intragenic_miR(gene)  
  
## End(Not run)
```

| | |
|----------------------|-----------------------------------------------------------------------|
| miRNA_ID_to_Function | <i>Contains the miRNA function information from Flybase database.</i> |
|----------------------|-----------------------------------------------------------------------|

Description

A dataset containing the function for the intragenic miRNA.

Usage

```
miRNA_ID_to_Function
```

Format

A data frame with 66 rows and 4 variables:

miRNA miRNA name, miRNA symbol

FBGN target gene name, gene symbol

miRNAFunction miRNA function, from Flybase

Source

<http://flybase.org/>

| | |
|------------------|-------------------------------------------------------|
| miRNA_summary_DB | <i>Contains the summary for the intragenic miRNA.</i> |
|------------------|-------------------------------------------------------|

Description

A dataset containing the summary for the intragenic miRNA.

Usage

```
miRNA_summary_DB
```

Format

A data frame with 257 rows and 6 variables:

miRNA miRNA name, miRNA symbol

Intragenic Responsee, in boolean

Intergenic Responsee, in boolean

Gene miRNA name, miRNA symbol

Type.of.HostGene.mRNA.lncRNA. Type of Hostgene

Notes Comments about the miRNA

| | |
|-----------------|----------------------------------------------------|
| miRTargets_Stat | <i>Extracting miRNAs that target a query gene.</i> |
|-----------------|----------------------------------------------------|

Description

Extracting miRNAs that target a query gene.

Usage

```
miRTargets_Stat(
  miR,
  method = c("Pearson", "Distance", "Both", "BothIntersect"),
  Platform = c("Affy1", "Affy2"),
  outpath = tempdir(),
  Text = FALSE
)
```

Arguments

| | |
|----------|----------------------------------------------------------------------------------|
| miR | character. miRNA symbol. |
| method | character. Choices are "Pearson", "Distance", "Both" and "BothIntersected" |
| Platform | character. Choices are "Affy1", "Affy2". |
| outpath | character. The path where the data is stored if TEXT=TRUE. Default is tempdir(). |
| Text | logical . To choose between storing the data as text file. Default is FALSE. |

Value

Outputs the target information, Target Prediction Score, miRNA target function and Target Database that predicts the interaction in a dataframe. Depending upon the output choice data is stored in the path specified. Default option prints output to the console.

Examples

```
miRNA="dme-miR-12"
miRTargets_Stat (miRNA,method=c ("Pearson"),Platform=c ("Affy1"),Text=FALSE)
```

| | |
|---------------|---------------------------------------------------------------------------|
| Visualisation | <i>Visualises the targetGene:miRNA network using Cytoscape and igraph</i> |
|---------------|---------------------------------------------------------------------------|

Description

Visualises the targetGene:miRNA network using Cytoscape and igraph .

Usage

```
Visualisation(
  miRNA,
  mRNA_type = c("GeneSymbol", "FBID", "CGID"),
  method = c("Pearson", "Distance", "Both"),
  platform = c("Affy1", "Affy2"),
  thresh = 50,
  visualisation = c("igraph", "Cytoscape", "Text", "console"),
  path = tempdir(),
  layout = c("kamadakawai", "reingold.tilford", "fruchterman.reingold", "interactive")
)
```

Arguments

| | |
|-----------|---------------------------------------------------------------------------|
| miRNA | character. miRNA Identifier. |
| mRNA_type | character. mRNA id type. The choices are 'GeneSymbol', 'FBID' and 'CGID'. |
| method | character. Statistical Methods. Choices are 'Pearson', 'Distance', 'Both' |

| | |
|---------------|--------------------------------------------------------------------------------------------------------------------|
| platform | character. Affymetrix Platforms. Choices are 'Affy1','Affy2'. |
| thresh | integer. Threshold depicting number of rows to show. |
| visualisation | character. Visualisation type. Choices are 'igraph','Cytoscape','text' and 'console'. |
| path | character. Path where data.frame is saved when visualisation is text. Default is tempdir(). |
| layout | character. Network choices. Choices are 'kamadakawai','reingold.tilford','fruchterman.reingold' and 'interactive'. |

Value

Depending upon the output choice network image or dataframe containing miRNAs that target the query gene are output.

Examples

```
miRNA='dme-miR-12'  
Visualisation(miRNA,mRNA_type=c('GeneSymbol'),method=c('Pearson'),  
platform=c('Affy1'),visualisation=c('igraph'),layout=c('kamadakawai'),  
path=tempdir())
```

Index

* datasets

- Affy1_Distance_Final, [2](#)
- Affy1_Pearson_Final, [3](#)
- Affy2_Distance_Final, [3](#)
- Affy2_Pearson_Final, [4](#)
- miRNA_ID_to_Function, [9](#)
- miRNA_summary_DB, [10](#)

- Affy1_Distance_Final, [2](#)
- Affy1_Pearson_Final, [3](#)
- Affy2_Distance_Final, [3](#)
- Affy2_Pearson_Final, [4](#)

- extract_HostGene, [5](#)
- extract_intragenic_miR, [5](#)

- Gene_Visualisation, [6](#)
- genes_Stat, [7](#)
- GetGOS_ALL, [8](#)

- IntramiRExploreR, [9](#)

- miRNA_ID_to_Function, [9](#)
- miRNA_summary_DB, [10](#)
- miRTargets_Stat, [10](#)

- Visualisation, [11](#)