

# Package: MSstatsLiP (via r-universe)

May 28, 2026

**Type** Package

**Title** LiP Significance Analysis in shotgun mass spectrometry-based proteomic experiments

**Version** 1.18.0

**Date** 2024-3-19

**Description** Tools for LiP peptide and protein significance analysis. Provides functions for summarization, estimation of LiP peptide abundance, and detection of changes across conditions. Utilizes functionality across the MSstats family of packages.

**License** Artistic-2.0

**Depends** R (>= 4.1)

**Imports** dplyr, gridExtra, stringr, ggplot2, grDevices, MSstats, MSstatsConvert, data.table, Biostrings, MSstatsPTM (>= 2.12.0), Rcpp, checkmate, factoextra, ggpubr, purrr, tibble, tidyr, tidyverse, scales, stats, plotly, htmltools

**Suggests** BiocStyle, knitr, rmarkdown, covr, tinytest, gghighlight

**LinkingTo** Rcpp

**VignetteBuilder** knitr

**biocViews** ImmunoOncology, MassSpectrometry, Proteomics, Software, DifferentialExpression, OneChannel, TwoChannel, Normalization, QualityControl

**BugReports** <https://github.com/Vitek-Lab/MSstatsLiP/issues>

**Encoding** UTF-8

**LazyData** TRUE

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.2

**Config/pak/sysreqs**

cmake libfontconfig1-dev libfreetype6-dev libfribidi-dev make libharfbuzz-dev libicu-dev libjpeg-dev libpng-dev libtiff-dev libuv1-dev libwebp-dev libxml2-dev libssl-dev libx11-dev zlib1g-dev

**Repository** <https://bioc-release.r-universe.dev>

**Date/Publication** 2026-04-28 12:57:16 UTC

**RemoteUrl** <https://github.com/bioc/MSstatsLiP>

**RemoteRef** RELEASE\_3\_23

**RemoteSha** 9647f5aa2b607b15cd139c7c9dd5ce67711a04f2

## Contents

annotSite . . . . .	2
calculateProteolyticResistance . . . . .	3
calculateTrypticity . . . . .	4
correlationPlotLiP . . . . .	5
dataProcessPlotsLiP . . . . .	6
dataSummarizationLiP . . . . .	8
DIANNtoMSstatsLiPFormat . . . . .	11
groupComparisonLiP . . . . .	12
groupComparisonPlotsLiP . . . . .	14
LiPRawData . . . . .	16
locateMod . . . . .	18
locatePTM . . . . .	18
MSstatsLiP_data . . . . .	19
MSstatsLiP_model . . . . .	20
MSstatsLiP_Summarized . . . . .	21
PCAPlotLiP . . . . .	22
raw_lip . . . . .	24
raw_prot . . . . .	25
ResistanceBarcodePlotLiP . . . . .	27
SkylineTest . . . . .	28
SkylinetoMSstatsLiPFormat . . . . .	29
SpectronauttoMSstatsLiPFormat . . . . .	31
StructuralBarcodePlotLiP . . . . .	33
tidyFasta . . . . .	34
TrPRawData . . . . .	35
trypticHistogramLiP . . . . .	36
<b>Index</b>	<b>38</b>

---

annotSite	<i>Annotate modification site</i>
-----------	-----------------------------------

---

### Description

annotSite annotates modified sites as their residues and locations.

### Usage

```
annotSite(aaIndex, residue, lenIndex = NULL)
```

**Arguments**

aaIndex	An integer vector. Location of the sites.
residue	A string vector. Amino acid residue.
lenIndex	An integer. Default is NULL

**Value**

A string.

**Examples**

```
annotSite(10, "K")
annotSite(10, "K", 3L)
```

---

**calculateProteolyticResistance**

*Calculates proteolytic resistance for provided data. Requires input from dataSummarizationLiP function. Can optionally calculate differential analysis using proteolytic resistance. In order for this function to work, Conditions and run numbers must match between the LiP and TrP data.*

---

**Description**

Calculates proteolytic resistance for provided data. Requires input from dataSummarizationLiP function. Can optionally calculate differential analysis using proteolytic resistance. In order for this function to work, Conditions and run numbers must match between the LiP and TrP data.

**Usage**

```
calculateProteolyticResistance(
  LiP_data,
  fasta_file,
  differential_analysis = FALSE,
  contrast.matrix = "pairwise"
)
```

**Arguments**

LiP_data	name of variable containing LiP data. Must be output of dataSummarizationLiP function.
fasta_file	name of variable containing FASTA data. If FASTA file has not been processed please run the tidyFasta() function on it before inputting into this function. Protein names in file must match those in LiP_data.

`differential_analysis`  
 logical indicating whether to run differential analysis. Default is FALSE. Conditions and run numbers must match between the LiP and TrP data.

`contrast.matrix`  
 either a string of "pairwise" or a matrix including what comparisons to make in the differential analysis. Only required if `differential_analysis=TRUE`. Default is "pairwise".

**Value**

a `data.frame` including either the summarized Proteolytic data or differential analysis depending on parameter selection.

**Examples**

```
fasta <- tidyFasta(system.file("extdata", "ExampleFastaFile.fasta", package="MSstatsLiP"))
#calculateProteolyticResistance(MSstatsLiP_data, fasta)
```

---

`calculateTrypticity`     *Calculates level of trypticity for a list of LiP Peptides.*

---

**Description**

Takes as an input LiP data and a fasta file. These can be the outputs of MSstatsLiP functions.

**Usage**

```
calculateTrypticity(LiP_data, fasta_file)
```

**Arguments**

`LiP_data`            name of variable containing LiP data. Must contain at least two columns named 'PeptideSequence' and 'ProteinName'. The values in these columns must match with what is in the corresponding FASTA file.

`fasta_file`           name of variable containing FASTA data. If FASTA file has not been processed please run the `tidyFasta()` function on it before inputting into this function.

**Value**

a `data.frame` including protein, peptide, and trypticity metrics.

**Examples**

```
fasta <- tidyFasta(system.file("extdata", "ExampleFastaFile.fasta", package="MSstatsLiP"))
calculateTrypticity(MSstatsLiP_data$LiP, fasta)
```

---

correlationPlotLiP      *Plot run correlation for provided LiP and TrP experiment.*

---

### Description

Plot run correlation for provided LiP and TrP experiment.

### Usage

```
correlationPlotLiP(
  data,
  method = "pearson",
  value_columns = "INTENSITY",
  x.axis.size = 10,
  y.axis.size = 10,
  legend.size = 10,
  width = 10,
  height = 10,
  address = ""
)
```

### Arguments

data	output of MSstatsLiP converter function. Must include at least ProteinName, Run, and Intensity columns
method	one of "pearson", "kendall", "spearman". Default is pearson.
value_columns	one of "INTENSITY" or "ABUNDANCE". INTENSITY is the raw data, whereas ABUNDANCE is the log transformed INTENSITY column. INTENSITY is default.
x.axis.size	size of axes labels, e.g. name of the comparisons in heatmap, and in comparison plot. Default is 10.
y.axis.size	size of axes labels, e.g. name of targeted proteins in heatmap. Default is 10.
legend.size	size of legend for color at the bottom of volcano plot. Default is 10.
width	width of the saved file. Default is 10.
height	height of the saved file. Default is 10.
address	the name of folder that will store the results. Default folder is the current working directory. The other assigned folder has to be existed under the current working directory. An output pdf file is automatically created with the default name of "VolcanoPlot.pdf" or "Heatmap.pdf". The command address can help to specify where to store the file as well as how to modify the beginning of the file name. If address=FALSE, plot will be not saved as pdf file but showed in window

### Value

plot or pdf

## Examples

```
## Use output of dataSummarizationLiP function
correlationPlotLiP(MSstatsLiP_Summarized, address = FALSE)
```

---

dataProcessPlotsLiP     *Visualization for explanatory data analysis*

---

## Description

To illustrate the quantitative data and quality control of MS runs, dataProcessPlotsLiP takes the quantitative data from MSstatsLiP converter functions as input and generate two types of figures in pdf files as output : (1) profile plot (specify "ProfilePlot" in option type), to identify the potential sources of variation for each protein; (2) quality control plot (specify "QCPlot" in option type), to evaluate the systematic bias between MS runs.

## Usage

```
dataProcessPlotsLiP(
  data,
  type = "PROFILEPLOT",
  ylimUp = FALSE,
  ylimDown = FALSE,
  x.axis.size = 10,
  y.axis.size = 10,
  text.size = 4,
  text.angle = 90,
  legend.size = 7,
  dot.size.profile = 2,
  ncol.guide = 5,
  width = 10,
  height = 12,
  lip.title = "All Peptides",
  protein.title = "All Proteins",
  which.Peptide = "all",
  which.Protein = NULL,
  originalPlot = TRUE,
  summaryPlot = TRUE,
  address = "",
  isPlotly = FALSE
)
```

## Arguments

**data**                    name of the list with LiP and (optionally) Protein data, which can be the output of the MSstatsLiP. [dataSummarizationLiP](#) function.

type	choice of visualization. "ProfilePlot" represents profile plot of log intensities across MS runs. "QCPlot" represents box plots of log intensities across channels and MS runs.
ylimUp	upper limit for y-axis in the log scale. FALSE(Default) for Profile Plot and QC Plot uses the upper limit as rounded off maximum of $\log_2(\text{intensities})$ after normalization + 3..
ylimDown	lower limit for y-axis in the log scale. FALSE(Default) for Profile Plot and QC Plot uses 0..
x.axis.size	size of x-axis labeling for "Run" and "channel in Profile Plot and QC Plot.
y.axis.size	size of y-axis labels. Default is 10.
text.size	size of labels represented each condition at the top of Profile plot and QC plot. Default is 4.
text.angle	angle of labels represented each condition at the top of Profile plot and QC plot. Default is 0.
legend.size	size of legend above Profile plot. Default is 7.
dot.size.profile	size of dots in Profile plot. Default is 2.
ncol.guide	number of columns for legends at the top of plot. Default is 5.
width	width of the saved pdf file. Default is 10.
height	height of the saved pdf file. Default is 10.
lip.title	title of all LiP QC plot
protein.title	title of all Protein QC plot
which.Peptide	LiP peptide list to draw plots. List can be names of LiP peptides or order numbers of LiPs. Default is "all", which generates all plots for each protein. For QC plot, "allonly" will generate one QC plot with all proteins.
which.Protein	String of protein's to plot if the user would like to plot all Peptides associated with a given Protein. Default is NULL. Please do not include "all" or "allonly" here.
originalPlot	TRUE(default) draws original profile plots, without normalization.
summaryPlot	TRUE(default) draws profile plots with protein summarization for each channel and MS run.
address	the name of folder that will store the results. Default folder is the current working directory. The other assigned folder has to be existed under the current working directory. An output pdf file is automatically created with the default name of "ProfilePlot.pdf" or "QCplot.pdf". The command address can help to specify where to store the file as well as how to modify the beginning of the file name. If address=FALSE, plot will be not saved as pdf file but showed in window.
isPlotly	Parameter to use Plotly or ggplot2. If set to TRUE, MSstats will save Plotly plots as HTML files. If set to FALSE MSstats will save ggplot2 plots as PDF files

**Value**

plot or pdf

**Examples**

```
# Use the output of the MSstatsLiP_Summarized function
# Profile Plot
dataProcessPlotsLiP(MSstatsLiP_Summarized, type = "ProfilePlot")

# QCPlot Plot
dataProcessPlotsLiP(MSstatsLiP_Summarized, type = "QCPlot")
```

---

`dataSummarizationLiP` *Summarizes LiP and TrP datasets seperately using methods from MSstats.*

---

**Description**

Utilizes functionality from MSstats and MSstatsPTM to clean, summarize, and normalize LiP peptide and TrP global protein data. Imputes missing values, protein and LiP peptide level summarization from peptide level quantification. Applies global median normalization on peptide level data and normalizes between runs. Returns list of two summarized datasets.

**Usage**

```
dataSummarizationLiP(
  data,
  logTrans = 2,
  normalization = "equalizeMedians",
  normalization.LiP = "equalizeMedians",
  nameStandards = NULL,
  nameStandards.LiP = NULL,
  featureSubset = "all",
  featureSubset.LiP = "all",
  remove_uninformative_feature_outlier = FALSE,
  remove_uninformative_feature_outlier.LiP = FALSE,
  min_feature_count = 2,
  min_feature_count.LiP = 1,
  n_top_feature = 3,
  n_top_feature.LiP = 3,
  summaryMethod = "TMP",
  equalFeatureVar = TRUE,
  censoredInt = "NA",
  MBimpute = TRUE,
  MBimpute.LiP = FALSE,
  remove50missing = FALSE,
```

```

    fix_missing = NULL,
    maxQuantileforCensored = 0.999,
    use_log_file = FALSE,
    append = FALSE,
    verbose = TRUE,
    log_file_path = NULL,
    base = "MSstatsLiP_log_"
)

```

## Arguments

<code>data</code>	name of the list with LiP and TrP data.tables, which can be the output of the MSstatsPTM converter functions
<code>logTrans</code>	logarithm transformation with base 2(default) or 10
<code>normalization</code>	normalization for the protein level dataset, to remove systematic bias between MS runs. There are three different normalizations supported. 'equalizeMedians'(default) represents constant normalization (equalizing the medians) based on reference signals is performed. 'quantile' represents quantile normalization based on reference signals is performed. 'globalStandards' represents normalization with global standards proteins. FALSE represents no normalization is performed
<code>normalization.LiP</code>	normalization for LiP level dataset. Default is 'equalizeMedians'. Can be adjusted to any of the options described above.
<code>nameStandards</code>	vector of global standard peptide names for protein dataset. only for normalization with global standard peptides.
<code>nameStandards.LiP</code>	Same as above for LiP dataset.
<code>featureSubset</code>	For protein dataset only. "all"(default) uses all features that the data set has. "top3" uses top 3 features which have highest average of log2(intensity) across runs. "topN" uses top N features which has highest average of log2(intensity) across runs. It needs the input for n_top_feature option. "highQuality" flags uninformative feature and outliers
<code>featureSubset.LiP</code>	For LiP dataset only. Options same as above.
<code>remove_uninformative_feature_outlier</code>	For protein dataset only. It only works after users used featureSubset="highQuality" in dataProcess. TRUE allows to remove 1) the features are flagged in the column, feature_quality="Uninformative" which are features with bad quality, 2) outliers that are flagged in the column, is_outlier=TRUE, for run-level summarization. FALSE (default) uses all features and intensities for run-level summarization.
<code>remove_uninformative_feature_outlier.LiP</code>	For LiP dataset only. Options same as above.
<code>min_feature_count</code>	optional. Only required if featureSubset = "highQuality". Defines a minimum number of informative features a protein needs to be considered in the feature selection algorithm.

<code>min_feature_count.LiP</code>	For LiP dataset only. Options the same as above.
<code>n_top_feature</code>	For protein dataset only. The number of top features for <code>featureSubset='topN'</code> . Default is 3, which means to use top 3 features.
<code>n_top_feature.LiP</code>	For LiP dataset only. Options same as above.
<code>summaryMethod</code>	"TMP"(default) means Tukey's median polish, which is robust estimation method. "linear" uses linear mixed model.
<code>equalFeatureVar</code>	only for <code>summaryMethod="linear"</code> . default is TRUE. Logical variable for whether the model should account for heterogeneous variation among intensities from different features. Default is TRUE, which assume equal variance among intensities from features. FALSE means that we cannot assume equal variance among intensities from features, then we will account for heterogeneous variation from different features.
<code>censoredInt</code>	Missing values are censored or at random. 'NA' (default) assumes that all 'NA's in 'Intensity' column are censored. '0' uses zero intensities as censored intensity. In this case, NA intensities are missing at random. The output from Skyline should use '0'. Null assumes that all NA intensities are randomly missing.
<code>MBimpute</code>	For protein dataset only. only for <code>summaryMethod="TMP"</code> and <code>censoredInt='NA'</code> or '0'. TRUE (default) imputes 'NA' or '0' (depending on <code>censoredInt</code> option) by Accelerated failure model. FALSE uses the values assigned by <code>cutoffCensored</code> .
<code>MBimpute.LiP</code>	For LiP dataset only. Options same as above. Default is FALSE.
<code>remove50missing</code>	only for <code>summaryMethod="TMP"</code> . TRUE removes the runs which have more than 50% missing values. FALSE is default.
<code>fix_missing</code>	Default is Null. Optional, same as the 'fix_missing' parameter in <code>MSstatsConvert::MSstatsBalancedDesign</code> function
<code>maxQuantileforCensored</code>	Maximum quantile for deciding censored missing values. default is 0.999
<code>use_log_file</code>	logical. If TRUE, information about data processing will be saved to a file.
<code>append</code>	logical. If TRUE, information about data processing will be added to an existing log file.
<code>verbose</code>	logical. If TRUE, information about data processing will be printed to the console.
<code>log_file_path</code>	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If <code>append = TRUE</code> , has to be a valid path to a file.
<code>base</code>	start of the file name.

**Value**

list of summarized LiP and TrP results. These results contain the reformatted input to the summarization function, as well as run-level summarization results.

**Examples**

```
# Use output of converter
head(MSstatsLiP_data[["LiP"]])
head(MSstatsLiP_data[["TrP"]])

# Run summarization
MSstatsLiP_model <- dataSummarizationLiP(MSstatsLiP_data)
```

---

DIANNtoMSstatsLiPFormat

*Converts raw LiP MS data from DIA-NN into the format needed for MSstatsLiP.*

---

**Description**

Takes as an input both raw LiP and Trp outputs from DIA-NN

**Usage**

```
DIANNtoMSstatsLiPFormat(
  lip_data,
  trp_data = NULL,
  annotation = NULL,
  global_qvalue_cutoff = 0.01,
  qvalue_cutoff = 0.01,
  pg_qvalue_cutoff = 0.01,
  useUniquePeptide = TRUE,
  removeFewMeasurements = TRUE,
  removeOxidationMpeptides = FALSE,
  removeProtein_with1Feature = FALSE,
  use_log_file = FALSE,
  append = FALSE,
  verbose = TRUE,
  log_file_path = NULL
)
```

**Arguments**

lip_data	name of LiP Skyline output, which is long-format.
trp_data	name of TrP Skyline output, which is long-format.
annotation	name of 'annotation.txt' data which includes Condition, BioReplicate, Run. If annotation is already complete in Skyline, use annotation=NULL (default). It will use the annotation information from input.
global_qvalue_cutoff	The global qvalue cutoff. Default is 0.01.

**qvalue\_cutoff** Cutoff for DetectionQValue. Default is 0.01.  
**pg\_qvalue\_cutoff** local qvalue cutoff for protein groups Run should be the same as filename. Default is .01.  
**useUniquePeptide** TRUE (default) removes peptides that are assigned for more than one proteins. We assume to use unique peptide for each protein.  
**removeFewMeasurements** TRUE (default) will remove the features that have 1 or 2 measurements across runs.  
**removeOxidationMpeptides** TRUE will remove the peptides including 'oxidation (M)' in modification. FALSE is default.  
**removeProtein\_with1Feature** TRUE will remove the proteins which have only 1 feature, which is the combination of peptide, precursor charge, fragment and charge. FALSE is default.  
**use\_log\_file** logical. If TRUE, information about data processing will be saved to a file.  
**append** logical. If TRUE, information about data processing will be saved to a file.  
**verbose** logical. If TRUE, information about data processing will be printed to the console.  
**log\_file\_path** character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If 'append = TRUE', has to be a valid path to a file.

**Value**

a list of two data.frames in MSstatsLiP format

**Examples**

```
## Output will be in format
head(MSstatsLiP_data[["LiP"]])
head(MSstatsLiP_data[["TrP"]])
```

---

groupComparisonLiP     *Model LiP and TrP data and make adjustments if needed Returns list of three modeled datasets*

---

**Description**

Takes summarized LiP peptide and TrP protein data from dataSummarizationLiP If global protein data is unavailable, LiP data only can be passed into the function. Including protein data allows for adjusting LiP Fold Change by the change in global protein abundance..



```
# Returns list of three models
names(MSstatsLiP_model)
head(MSstatsLiP_model$LiP.Model)
head(MSstatsLiP_model$TrP.Model)
head(MSstatsLiP_model$Adjusted.LiP.Model)
```

---

```
groupComparisonPlotsLiP
```

*Visualization for model-based analysis and summarization*

---

## Description

To analyze the results of modeling changes in abundance of LiP peptides and overall protein, groupComparisonPlotsLiP takes as input the results of the groupComparisonLiP function. It assesses the results of three models: unadjusted LiP, adjusted LiP, and overall protein. To assess the results of the model, the following visualizations can be created: (1) VolcanoPlot (specify "VolcanoPlot" in option type), to plot peptides or proteins and their significance for each model. (2) Heatmap (specify "Heatmap" in option type), to evaluate the fold change between conditions and peptides/proteins

## Usage

```
groupComparisonPlotsLiP(
  data = data,
  type = type,
  sig = 0.05,
  FCcutoff = 1,
  logBase.pvalue = 10,
  ylimUp = FALSE,
  ylimDown = FALSE,
  xlimUp = FALSE,
  x.axis.size = 10,
  y.axis.size = 10,
  dot.size = 3,
  text.size = 4,
  text.angle = 0,
  legend.size = 13,
  ProteinName = TRUE,
  colorkey = TRUE,
  numProtein = 100,
  width = 10,
  height = 10,
  which.Comparison = "all",
  which.Peptide = "all",
  which.Protein = NULL,
  address = "",
  isPlotly = FALSE
)
```

**Arguments**

data	name of the list with models, which can be the output of the MSstatsLiP <code>groupComparisonLiP</code> function
type	choice of visualization, one of VolcanoPlot or Heatmap
sig	FDR cutoff for the adjusted p-values in heatmap and volcano plot. level of significance for comparison plot. 100(1-sig)% confidence interval will be drawn. sig=0.05 is default.
FCcutoff	or volcano plot or heatmap, whether involve fold change cutoff or not. FALSE (default) means no fold change cutoff is applied for significance analysis. FC-cutoff = specific value means specific fold change cutoff is applied.
logBase.pvalue	for volcano plot or heatmap, (-) logarithm transformation of adjusted p-value with base 2 or 10(default).
ylimUp	for all three plots, upper limit for y-axis. FALSE (default) for volcano plot/heatmap use maximum of -log2 (adjusted p-value) or -log10 (adjusted p-value). FALSE (default) for comparison plot uses maximum of log-fold change + CI.
ylimDown	for all three plots, lower limit for y-axis. FALSE (default) for volcano plot/heatmap use minimum of -log2 (adjusted p-value) or -log10 (adjusted p-value). FALSE (default) for comparison plot uses minimum of log-fold change - CI.
xlimUp	for Volcano plot, the limit for x-axis. FALSE (default) for use maximum for absolute value of log-fold change or 3 as default if maximum for absolute value of log-fold change is less than 3.
x.axis.size	size of axes labels, e.g. name of the comparisons in heatmap, and in comparison plot. Default is 10.
y.axis.size	size of axes labels, e.g. name of targeted proteins in heatmap. Default is 10.
dot.size	size of dots in volcano plot and comparison plot. Default is 3.
text.size	size of ProteinName label in the graph for Volcano Plot. Default is 4.
text.angle	angle of x-axis labels represented each comparison at the bottom of graph in comparison plot. Default is 0.
legend.size	size of legend for color at the bottom of volcano plot. Default is 7.
ProteinName	for volcano plot only, whether display protein/peptide names or not. TRUE (default) means protein names, which are significant, are displayed next to the points. FALSE means no protein names are displayed.
colorkey	TRUE(default) shows colorkey.
numProtein	The number of proteins which will be presented in each heatmap. Default is 50.
width	width of the saved file. Default is 10.
height	height of the saved file. Default is 10.
which.Comparison	list of comparisons to draw plots. List can be labels of comparisons or order numbers of comparisons from levels(data\$Label), such as levels(testResultMultiComparisons\$Comparison). Default is "all", which generates all plots for each protein.
which.Peptide	Peptide list to draw comparison plots. List can be names of Peptides or order numbers of Peptides from levels. Default is "all", which generates all comparison plots for each protein.

which.Protein	Protein list to draw comparison plots. Will draw all peptide plots for listed Proteins. List must be names of Proteins. Default is "all", which generates all comparison plots for each protein.
address	the name of folder that will store the results. Default folder is the current working directory. The other assigned folder has to be existed under the current working directory. An output pdf file is automatically created with the default name of "VolcanoPlot.pdf" or "Heatmap.pdf". The command address can help to specify where to store the file as well as how to modify the beginning of the file name. If address=FALSE, plot will be not saved as pdf file but showed in window
isPlotly	Parameter to use Plotly or ggplot2. If set to TRUE, MSstats will save Plotly plots as HTML files. If set to FALSE MSstats will save ggplot2 plots as PDF files

**Value**

plot or pdf

**Examples**

```
## Use output of the groupComparisonLiP function

# Volcano Plot
groupComparisonPlotsLiP(MSstatsLiP_model, type = "VOLCANO PLOT")

# Heatmap Plot
groupComparisonPlotsLiP(MSstatsLiP_model, type = "HEATMAP")
```

---

LiPRawData

*LiPRawData*

---

**Description**

Example of input LiP dataset.

**Usage**

LiPRawData

**Format**

A data.table consisting of 546 rows and 29 columns. Raw LiP data for use in testing and examples.

**Details**

Input to MSstatsLiP converter SpectronauttoMSstatsLiPFormat. Contains the following columns:

- R.Condition : Label of conditions (EG Disease/Control)
- R.FileName : Name of spectral processing run
- R.Replicate : Name of biological replicate
- PG.ProteinAccessions : Protein name
- PG.ProteinGroups : Protein name, can be multiple
- PG.Quantity : Protein Quantity
- PEP.GroupingKey : Peptide grouping
- PEP.StrippedSequence : Peptide sequence
- PEP.Quantity : Peptide quantity
- EG.iRTPredicted : Predicted value
- EG.Library : Name of library
- EG.ModifiedSequence : Peptide sequence including any post-translational modifications
- EG.PrecursorId : Peptide sequence with modifications including charge
- EG.Qvalue : Qvalue
- FG.Charge : Identified Ion charge
- FG.Id : Peptide sequence with charge
- FG.PrecMz : Prec Mz reading
- FG.Quantity : Initial quantity reading
- F.Charge : F.Charge
- F.FrgIon : Fragment ion
- F.FrgLossType : Label for loss type
- F.FrgMz : Mz reading
- F.FrgNum : numeric Frg
- F.FrgType : character label for Frg
- F.ExcludedFromQuantification : True/False boolean for if to exclude
- F.NormalizedPeakArea : Normalized peak intensity
- F.NormalizedPeakHeight : Normalized peak height
- F.PeakArea : Unnormalized peak area
- F.PeakHeight : Unnormalized peak height

**Examples**

```
head(LiPRawData)
```

---

locateMod	<i>Locate modified sites with a peptide</i>
-----------	---

---

**Description**

locateMod locates modified sites with a peptide.

**Usage**

```
locateMod(peptide, aaStart, residueSymbol)
```

**Arguments**

peptide	A string. Peptide sequence.
aaStart	An integer. Starting index of the peptide.
residueSymbol	A string. Modification residue and denoted symbol.

**Value**

A string.

**Examples**

```
locateMod("P*EP*TIDE", 3, "\\*")
```

---

locatePTM	<i>Annotate modified sites with associated peptides</i>
-----------	---

---

**Description**

PTMlocate annotates modified sites with associated peptides.

**Usage**

```
locatePTM(peptide, uniprot, fasta, modResidue, modSymbol, rmConfound = FALSE)
```

**Arguments**

peptide	A string vector of peptide sequences. The peptide sequence does not include its preceding and following AAs.
uniprot	A string vector of Uniprot identifiers of the peptides' originating proteins. UniProtKB entry isoform sequence is used.
fasta	A tibble with FASTA information. Output of tidyFasta.
modResidue	A string. Modifiable amino acid residues.

modSymbol	A string. Symbol of a modified site.
rmConfound	A logical. TRUE removes confounded unmodified sites, FALSE otherwise. Default is FALSE.

**Value**

A data frame with three columns: uniprot\_iso, peptide, site.

**Examples**

```
fasta <- tidyFasta(system.file("extdata", "013297.fasta", package="MSstatsLiP"))
locatePTM("DRVSYIHNDSC*TR", "013297", fasta, "C", "\\*")
```

---

MSstatsLiP_data	<i>MSstatsLiP_data</i>
-----------------	------------------------

---

**Description**

Example output of MSstatsLiP converter functions.

**Usage**

```
MSstatsLiP_data
```

**Format**

A data.table consisting of 546 rows and 29 columns. Raw TrP data for use in testing and examples.

**Details**

Example output of MSstatsLiP converter functions. (Eg. SpectronautoMSstatsLiPFormat). A list containing two data.tables named LiP and TrP corresponding to the processed LiP and TrP data now in MSstatsLiP format. The data.tables contain the following columns:

- ProteinName : Character column of protein names
- PeptideSequence : Character column of peptide sequence name
- PrecursorCharge : Numeric charge feature
- FragmentIon : Character fragment ion feature
- ProductCharge : Numeric charge of product
- IsotopeLabelType : Character label type
- Condition : Character label for condition (Eg. Disease/Control)
- BioReplicate : Name of biological replicate
- Run : Name of run
- Fraction : Fraction number if fractionation is present
- Intensity : Unnormalized feature intensity
- FULL\_PEPTIDE(LiP data only) : Combined protein name and peptide sequence. Used for LiP data only because LiP is summarized to peptide level (not protein)

## Examples

```
head(MSstatsLiP_data$LiP)
head(MSstatsLiP_data$TrP)
```

---

MSstatsLiP_model	<i>MSstatsLiP_model</i>
------------------	-------------------------

---

## Description

Example output of groupComparisonLiP converter functions.

## Usage

```
MSstatsLiP_model
```

## Format

A data.table consisting of 546 rows and 29 columns. Raw TrP data for use in testing and examples.

## Details

Example output of MSstatsLiP groupComparisonLiP function. A list containing three data.tables corresponding to unadjusted LiP, TrP, and adjusted LiP models. The data.tables contain the following columns:

- ProteinName : Character column of protein names
- PeptideSequence : Character column of peptide sequence name
- Label : Condition comparison (Eg. Disease vs Control)
- log2FC : Fold Change output results of model
- SE : Standard error output of model
- Tvalue : Tvalue output of model
- DF : Degrees of Freedom output of model
- pvalue : Pvalue result of model (unadjusted)
- adj.pvalue : Adjusted Pvalue, generally BH adjustment is used
- issue : Issue in model if any is reported
- MissingPercentage : Percent of missing values in specific model
- ImputationPercentage : Percent of values that needed to be imputed
- fully\_TRI: Boolean indicating if Peptide is fully tryptic
- NSEMI\_TRI: Boolean indicating if Peptide is NSEMI tryptic
- CSEMI\_TRI: Boolean indicating if Peptide is CSEMI tryptic
- CTERMINUS: Boolean indicating if Peptide is CTERMINUS tryptic

- NTERMINUS: Boolean indicating if Peptide is NTERMINUS tryptic
- StartPos: Start position of peptide sequence
- EndPos: End position of peptide sequence
- FULL\_PEPTIDE(LiP data only) : Combined protein name and peptide sequence. Used for LiP data only because LiP is summarized to peptide level (not protein)

### Examples

```
head(MSstatsLiP_model$LiP.Model)
head(MSstatsLiP_model$TrP.Model)
head(MSstatsLiP_model$Adjusted.LiP.Model)
```

---

MSstatsLiP\_Summarized *MSstatsLiP\_Summarized*

---

### Description

Example output of MSstatsLiP summarization function dataSummarizationLiP.

### Usage

```
MSstatsLiP_Summarized
```

### Format

A list containing two lists of summarization information for LiP and TrP data.

### Details

Example output of MSstatsLiP summarization function dataSummarizationLiP. A list containing two lists named LiP and TrP containing summarization information for LiP and TrP data. Each of LiP and TrP contain data named: FeatureLevelData, ProteinLevelData, SummaryMethod, ModelQC, PredictBySurvival. The two main data.tables (FeatureLevelData and ProteinLevelData are shown below):

- FeatureLevelData :
  - PROTEIN : Protein ID with modification site mapped in. Ex. Protein\_1002\_S836
  - FULL\_PEPTIDE (LiP Only) : Combined name of protein and peptide sequence
  - PEPTIDE : Full peptide with charge
  - TRANSITION: Charge
  - FEATURE : Combination of Protein, Peptide, and Transition Columns
  - LABEL :
  - GROUP : Condition (ex. Healthy, Cancer, Time0)
  - RUN : Unique ID for technical replicate of one TMT mixture.
  - SUBJECT : Unique ID for biological subject.

- FRACTION : Unique Fraction ID
- originalRUN : Run name
- censored :
- INTENSITY : Original intensity value
- ABUNDANCE : Log adjusted intensity value
- newABUNDANCE : Normalized abundance column
- ProteinLevelData :
  - RUN : MS run ID
  - FULL\_PEPTIDE (LiP Only) : Combined name of protein and peptide sequence
  - Protein : Protein ID with modification site mapped in. Ex. Protein\_1002\_S836
  - LogIntensities: Protein-level summarized abundance
  - originalRUN : Labeling information (126, ... 131)
  - GROUP : Condition (ex. Healthy, Cancer, Time0)
  - SUBJECT : Unique ID for biological subject.
  - TotalGroupMeasurements : Unique ID for technical replicate of one TMT mixture.
  - NumMeasuredFeature : Unique ID for TMT mixture.
  - MissingPercentage : Unique ID for TMT mixture.
  - more50missing : Unique ID for TMT mixture.
  - NumImputedFeature : Unique ID for TMT mixture.

## Examples

```
head(MSstatsLiP_Summarized$LiP$FeatureLevelData)
head(MSstatsLiP_Summarized$LiP$ProteinLevelData)

head(MSstatsLiP_Summarized$TrP$FeatureLevelData)
head(MSstatsLiP_Summarized$TrP$ProteinLevelData)
```

---

PCAPlotLiP

*Visualize PCA analysis for LiP and TrP datasets.*

---

## Description

Takes as input LiP and TrP data from summarization function `dataSummarizationLiP`. Runs PCA on the summarized data. Can visualize the PCA analysis in three different plots: (1) BarPlot (specify "bar.plot=TRUE" in option `bar.plot`), to plot a bar plot showing the explained variance per PCA component (2) Peptide/Protein PCA (specify "protein.pca = TRUE" in option `protein.pca`), to create a dot plot with PCA component 1 and 2 on the axis, for different peptides and proteins. (3) Comparison PCA (specify "comparison.pca = TRUE" in option `comparison.pca`), to create a arrow plot with PCA component 1 and 2 on the axis, for different comparisons

**Usage**

```
PCAPlotLiP(
  data,
  center.pca = TRUE,
  scale.pca = TRUE,
  n.components = 10,
  bar.plot = TRUE,
  protein.pca = TRUE,
  comparison.pca = FALSE,
  which.pep = "all",
  which.comparison = "all",
  width = 10,
  height = 10,
  address = "",
  isPlotly = FALSE
)
```

**Arguments**

<code>data</code>	data name of the list with LiP and (optionally) Protein data, which can be the output of the <code>MSstatsLiP</code> <a href="#">dataSummarizationLiP</a> function.
<code>center.pca</code>	a logical value indicating whether the variables should be shifted to be zero centered. Alternately, a vector of length equal the number of columns of <code>x</code> can be supplied. The value is passed to <code>scale</code>
<code>scale.pca</code>	a logical value indicating whether the variables should be scaled to have unit variance before the analysis takes place. The default is <code>FALSE</code> for consistency with <code>S</code> , but in general scaling is advisable. Alternatively, a vector of length equal the number of columns of <code>x</code> can be supplied. The value is passed to <code>scale</code> .
<code>n.components</code>	an integer of PCA components to be returned. Default is 10.
<code>bar.plot</code>	a logical value indicating if to visualize PCA bar plot
<code>protein.pca</code>	a logical value indicating if to visualize PCA peptide plot
<code>comparison.pca</code>	a logical value indicating if to visualize PCA comparison plot
<code>which.pep</code>	a list of peptides to be visualized. Default is "all". If too many peptides are plotted the names can overlap.
<code>which.comparison</code>	a list of comparisons to be visualized. Default is "all".
<code>width</code>	width of the saved file. Default is 10.
<code>height</code>	height of the saved file. Default is 10.
<code>address</code>	the name of folder that will store the results. Default folder is the current working directory. The other assigned folder has to be existed under the current working directory. An output pdf file is automatically created with the default name of "VolcanoPlot.pdf" or "Heatmap.pdf". The command <code>address</code> can help to specify where to store the file as well as how to modify the beginning of the file name. If <code>address=FALSE</code> , plot will be not saved as pdf file but showed in window

`isPlotly`      Parameter to use Plotly or ggplot2. If set to TRUE, MSstats will save Plotly plots as HTML files. If set to FALSE MSstats will save ggplot2 plots as PDF files

**Value**

plot or pdf

**Examples**

```
# Use output of dataSummarizationLiP function

# BarPlot
PCAPlotLiP(MSstatsLiP_Summarized, bar.plot = TRUE, protein.pca = FALSE)

# Protein/Peptide PCA Plot
PCAPlotLiP(MSstatsLiP_Summarized, bar.plot = FALSE, protein.pca = TRUE)

# Condition PCA Plot
PCAPlotLiP(MSstatsLiP_Summarized, bar.plot = FALSE, protein.pca = FALSE,
           comparison.pca = TRUE)
```

---

raw\_lip

*raw\_lip*

---

**Description**

A different example of input LiP dataset.

**Usage**

```
raw_lip
```

**Format**

A data.table consisting of 6,944 rows and 29 columns. Raw LiP data for use in testing and examples.

**Details**

Input to MSstatsLiP converter SpectronautoMSstatsLiPFormat. Contains the following columns:

- R.Condition : Label of conditions (EG Disease/Control)
- R.FileName : Name of spectral processing run
- R.Replicate : Name of biological replicate
- PG.ProteinAccessions : Protein name
- PG.ProteinGroups : Protein name, can be multiple

- PG.Quantity : Protein Quantity
- PEP.GroupingKey : Peptide grouping
- PEP.StrippedSequence : Peptide sequence
- PEP.Quantity : Peptide quantity
- EG.iRTPredicted : Predicted value
- EG.Library : Name of library
- EG.ModifiedSequence : Peptide sequence including any post-translational modifications
- EG.PrecursorId : Peptide sequence with modifications including charge
- EG.Qvalue : Qvalue
- FG.Charge : Identified Ion charge
- FG.Id : Peptide sequence with charge
- FG.PrecMz : Prec Mz reading
- FG.Quantity : Initial quantity reading
- F.Charge : F.Charge
- F.FrgIon : Fragment ion
- F.FrgLossType : Label for loss type
- F.FrgMz : Mz reading
- F.FrgNum : numeric Frg
- F.FrgType : character label for Frg
- F.ExcludedFromQuantification : True/False boolean for if to exclude
- F.NormalizedPeakArea : Normalized peak intensity
- F.NormalizedPeakHeight : Normalized peak height
- F.PeakArea : Unnormalized peak area
- F.PeakHeight : Unnormalized peak height

### Examples

```
head(raw_lip)
```

---

raw\_prot

*raw\_prot*

---

### Description

Example of input TrP dataset.

### Usage

```
raw_prot
```

**Format**

A data.table consisting of 9,120 rows and 29 columns. Raw TrP data for use in testing and examples.

**Details**

Input to MSstatsLiP converter SpectronautoMSstatsLiPFormat. Contains the following columns:

- R.Condition : Label of conditions (EG Disease/Control)
- R.FileName : Name of spectral processing run
- R.Replicate : Name of biological replicate
- PG.ProteinAccessions : Protein name
- PG.ProteinGroups : Protein name, can be multiple
- PG.Quantity : Protein Quantity
- PEP.GroupingKey : Peptide grouping
- PEP.StrippedSequence : Peptide sequence
- PEP.Quantity : Peptide quantity
- EG.iRTPredicted : Predicted value
- EG.Library : Name of library
- EG.ModifiedSequence : Peptide sequence including any post-translational modifications
- EG.PrecursorId : Peptide sequence with modifications including charge
- EG.Qvalue : Qvalue
- FG.Charge : Identified Ion charge
- FG.Id : Peptide sequence with charge
- FG.PrecMz : Prec Mz reading
- FG.Quantity : Initial quantity reading
- F.Charge : F.Charge
- F.FrgIon : Fragment ion
- F.FrgLossType : Label for loss type
- F.FrgMz : Mz reading
- F.FrgNum : numeric Frg
- F.FrgType : character label for Frg
- F.ExcludedFromQuantification : True/False boolean for if to exclude
- F.NormalizedPeakArea : Normalized peak intensity
- F.NormalizedPeakHeight : Normalized peak height
- F.PeakArea : Unnormalized peak area
- F.PeakHeight : Unnormalized peak height

**Examples**

```
head(raw_prot)
```

---

ResistanceBarcodePlotLiP

*Proteolytic Resistance Barcode plot. Shows accessibility score of different fully tryptic peptides in a protein.*

---

## Description

Proteolytic Resistance Barcode plot. Shows accessibility score of different fully tryptic peptides in a protein.

## Usage

```
ResistanceBarcodePlotLiP(
  data,
  fasta_file,
  which.prot = "all",
  which.condition = "all",
  differential_analysis = FALSE,
  which.comp = "all",
  adj.pvalue.cutoff = 0.05,
  FC.cutoff = 0,
  width = 12,
  height = 4,
  address = "",
  isPlotly = FALSE
)
```

## Arguments

data	list of data.tables containing LiP and TrP data in MSstatsLiP format. Should be output of summarization function as <a href="#">dataSummarizationLiP</a> .
fasta_file	A string of path to a FASTA file
which.prot	a list of peptides to be visualized. Default is "all" which will plot a separate barcode plot for each protein.
which.condition	a list of conditions to be visualized. Default is "all" which will plot all conditions for a single protein in the same barcode plot.
differential_analysis	a boolean indicating if a barcode plot showing the differential analysis should be plotted. If this is selected you must have performed differential analysis on the proteolytic data in the calculateProteolyticResistance function. Default is FALSE.
which.comp	a list of comparisons to be visualized, if differential analysis is passed to plot_differential variable. Default is "all" which will plot a separate barcode plot for each comparison and protein.

<code>adj.pvalue.cutoff</code>	Default is .05. Alpha value for testing significance of model output.
<code>FC.cutoff</code>	Default is 0. Minimum absolute FC before a comparison will be considered significant.
<code>width</code>	width of the saved file. Default is 10.
<code>height</code>	height of the saved file. Default is 10.
<code>address</code>	the name of folder that will store the results. Default folder is the current working directory. The other assigned folder has to be existed under the current working directory. An output pdf file is automatically created with the default name of "VolcanoPlot.pdf" or "Heatmap.pdf". The command address can help to specify where to store the file as well as how to modify the beginning of the file name. If <code>address=FALSE</code> , plot will be not saved as pdf file but showed in window
<code>isPlotly</code>	Parameter to use Plotly or ggplot2. If set to TRUE, MSstats will save Plotly plots as HTML files. If set to FALSE MSstats will save ggplot2 plots as PDF files

**Value**

plot or pdf

**Examples**

```
# Specify Fasta path
fasta_path = system.file("extdata", "ExampleFastaFile.fasta", package="MSstatsLiP")

# Use model data to create Barcode Plot
#ResistanceBarcodePlotLiP(MSstatsLiP_model, fasta_path)
```

---

SkylineTest

*SkylineTest*

---

**Description**

Example of input data from Skylinet.

**Usage**

```
SkylineTest
```

**Format**

A data.table consisting of 2115 rows and 13 columns. Raw data for use in testing and examples.

## Details

Input to MSstatsLiP converter SkylinetoMSstatsLiPFormat Contains the following columns:

- Protein.Name : Name of Proteins identified by Skyline
- Peptide.Modified.Sequence : Peptide sequence
- Precursor.Charge : Charge of ion
- Fragment.Ion : Fragment ion
- Product.Charge : Identified Ion charge
- Isotope.Label.Type : Label Type
- Condition : Name of condition
- BioReplicate : name of bioreplicate annotated to data
- File.Name : Name of spectral processing run
- Area : Abundance area
- Standard.Type : Type name for row
- Truncated : Boolean if row was truncated

## Examples

```
head(SkylineTest)
```

---

SkylinetoMSstatsLiPFormat

*Converts raw LiP MS data from Skyline into the format needed for MSstatsLiP.*

---

## Description

Takes as as input both raw LiP and Trp outputs from Skyline.

## Usage

```
SkylinetoMSstatsLiPFormat(  
  LiP.data,  
  TrP.data = NULL,  
  annotation = NULL,  
  msstats_format = FALSE,  
  removeiRT = TRUE,  
  filter_with_Qvalue = TRUE,  
  qvalue_cutoff = 0.01,  
  useUniquePeptide = TRUE,  
  removeFewMeasurements = TRUE,  
  removeOxidationMpeptides = FALSE,  
  removeProtein_with1Feature = FALSE,
```

```

    use_log_file = FALSE,
    append = FALSE,
    verbose = TRUE,
    log_file_path = NULL
  )

```

### Arguments

LiP.data	name of LiP Skyline output, which is long-format.
TrP.data	name of TrP Skyline output, which is long-format.
annotation	name of 'annotation.txt' data which includes Condition, BioReplicate, Run. If annotation is already complete in Skyline, use annotation=NULL (default). It will use the annotation information from input.
msstats_format	logical indicating how the data was output from Skyline. FALSE (default) indicates that standard Skyline output was selected. TRUE should be selected if the Skyline data was output using the MSstats format option in Skyline.
removeiRT	TRUE (default) will remove the proteins or peptides which are labeled 'iRT' in 'StandardType' column. FALSE will keep them.
filter_with_Qvalue	TRUE (default) will filter out the intensities that have greater than qvalue_cutoff in DetectionQValue column. Those intensities will be replaced with zero and will be considered as censored missing values for imputation purpose.
qvalue_cutoff	Cutoff for DetectionQValue. default is 0.01.
useUniquePeptide	TRUE (default) removes peptides that are assigned for more than one proteins. We assume to use unique peptide for each protein.
removeFewMeasurements	TRUE (default) will remove the features that have 1 or 2 measurements across runs.
removeOxidationMpeptides	TRUE will remove the peptides including 'oxidation (M)' in modification. FALSE is default.
removeProtein_with1Feature	TRUE will remove the proteins which have only 1 feature, which is the combination of peptide, precursor charge, fragment and charge. FALSE is default.
use_log_file	logical. If TRUE, information about data processing will be saved to a file.
append	logical. If TRUE, information about data processing will be saved to a file.
verbose	logical. If TRUE, information about data processing will be printed to the console.
log_file_path	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If 'append = TRUE', has to be a valid path to a file.

### Value

a list of two data.frames in MSstatsLiP format

**Examples**

```
## Output will be in format
head(MSstatsLiP_data[["LiP"]])
head(MSstatsLiP_data[["TrP"]])
```

---

```
SpectronauttoMSstatsLiPFormat
```

*Converts raw LiP MS data from Spectronaut into the format needed for MSstatsLiP.*

---

**Description**

Takes as as input both raw LiP and Trp outputs from Spectronaut.

**Usage**

```
SpectronauttoMSstatsLiPFormat(
  LiP.data,
  fasta,
  Trp.data = NULL,
  annotation = NULL,
  intensity = "PeakArea",
  filter_with_Qvalue = TRUE,
  qvalue_cutoff = 0.01,
  useUniquePeptide = TRUE,
  removeFewMeasurements = TRUE,
  removeProtein_with1Feature = FALSE,
  removeNonUniqueProteins = TRUE,
  removeModifications = TRUE,
  removeiRT = TRUE,
  summaryforMultipleRows = max,
  which.Conditions = "all",
  use_log_file = FALSE,
  append = FALSE,
  verbose = TRUE,
  log_file_path = NULL,
  base = "MSstatsLiP_log_"
)
```

**Arguments**

LiP.data	name of LiP Spectronaut output, which is long-format.
fasta	A string of path to a FASTA file, used to match LiP peptides.
Trp.data	name of TrP Spectronaut output, which is long-format.
annotation	name of 'annotation.txt' data which includes Condition, BioReplicate, Run. If annotation is already complete in Spectronaut, use annotation=NULL (default). It will use the annotation information from input.

intensity	'PeakArea'(default) uses not normalized peak area. 'NormalizedPeakArea' uses peak area normalized by Spectronaut
filter_with_Qvalue	TRUE(default) will filter out the intensities that have greater than qvalue_cutoff in EG.Qvalue column. Those intensities will be replaced with zero and will be considered as censored missing values for imputation purpose.
qvalue_cutoff	Cutoff for EG.Qvalue. default is 0.01.
useUniquePeptide	TRUE(default) removes peptides that are assigned for more than one proteins. We assume to use unique peptide for each protein.
removeFewMeasurements	TRUE (default) will remove the features that have 1 or 2 measurements across runs.
removeProtein_with1Feature	TRUE will remove the proteins which have only 1 feature, which is the combination of peptide, precursor charge, fragment and charge. FALSE is default.
removeNonUniqueProteins	TRUE will remove proteins that were not uniquely identified. IE if the protein column contains multiple proteins seperated by ";". TRUE is default
removeModifications	TRUE will remove peptide that contain a modification. Modification must be indicated by "[". TRUE is default
removeiRT	TRUE will remove proteins that contain iRT. True is default
summaryforMultipleRows	max(default) or sum - when there are multiple measurements for certain feature and certain run, use highest or sum of multiple intensities.
which.Conditions	list of conditions to format into MSstatsLiP format. If "all" all conditions will be used. Default is "all".
use_log_file	logical. If TRUE, information about data processing will be saved to a file.
append	logical. If TRUE, information about data processing will be added to an existing log file.
verbose	logical. If TRUE, information about data processing will be printed to the console.
log_file_path	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If append = TRUE, has to be a valid path to a file.
base	start of the file name.

**Value**

a list of two data. frames in MSstatsLiP format

**Examples**

```
# Output datasets of Spectronaut
head(LiPRawData)
head(TrPRawData)

fasta_path <- system.file("extdata", "ExampleFastaFile.fasta", package="MSstatsLiP")

MSstatsLiP_data <- SpectronauttoMSstatsLiPFormat(LiPRawData,
                                                fasta_path,
                                                TrPRawData)

head(MSstatsLiP_data[["LiP"]])
head(MSstatsLiP_data[["TrP"]])
```

---

StructuralBarcodePlotLiP

*Barcode plot. Shows protein coverage of LiP modified peptides.*

---

**Description**

Barcode plot. Shows protein coverage of LiP modified peptides.

**Usage**

```
StructuralBarcodePlotLiP(
  data,
  fasta,
  model_type = "Adjusted",
  which.prot = "all",
  which.comp = "all",
  adj.pvalue.cutoff = 0.05,
  FC.cutoff = 0,
  FT.only = FALSE,
  width = 12,
  height = 4,
  address = "",
  isPlotly = FALSE
)
```

**Arguments**

<code>data</code>	list of data.tables containing LiP and TrP data in MSstatsLiP format. Should be output of modeling function such as <a href="#">groupComparisonLiP</a> .
<code>fasta</code>	A string of path to a FASTA file
<code>model_type</code>	A string of either "Adjusted" or "Unadjusted", indicating whether to plot the adjusted or unadjusted models. Default is "Adjusted".
<code>which.prot</code>	a list of peptides to be visualized. Default is "all" which will plot a separate barcode plot for each protein.

which.comp	a list of comparisons to be visualized. Default is "all" which will plot a separate barcode plot for each comparison and protein.
adj.pvalue.cutoff	Default is .05. Alpha value for testing significance of model output.
FC.cutoff	Default is 0. Minimum absolute FC before a comparison will be considered significant.
FT.only	FALSE plots all FT and HT peptides, TRUE plots FT peptides only. Default is FALSE.
width	width of the saved file. Default is 10.
height	height of the saved file. Default is 10.
address	the name of folder that will store the results. Default folder is the current working directory. The other assigned folder has to be existed under the current working directory. An output pdf file is automatically created with the default name of "VolcanoPlot.pdf" or "Heatmap.pdf". The command address can help to specify where to store the file as well as how to modify the beginning of the file name. If address=FALSE, plot will be not saved as pdf file but showed in window
isPlotly	Parameter to use Plotly or ggplot2. If set to TRUE, MSstats will save Plotly plots as HTML files. If set to FALSE MSstats will save ggplot2 plots as PDF files

**Value**

plot or pdf

**Examples**

```
# Specify Fasta path
fasta_path <- system.file("extdata", "ExampleFastaFile.fasta", package="MSstatsLiP")

# Use model data to create Barcode Plot
StructuralBarcodePlotLiP(MSstatsLiP_model, fasta_path,
  model_type = "Adjusted",
  address=FALSE)
```

---

tidyFasta

*Read and tidy a FASTA file*


---

**Description**

reads and tidys FASTA file.

**Usage**

```
tidyFasta(path)
```

**Arguments**

path                    a string of path pointing towards a fasta file

**Value**

a tibble of formatted FASTA information

**Examples**

```
tidyFasta(system.file("extdata", "013297.fasta", package="MSstatsLiP"))
```

---

TrPRawData

*TrPRawData*

---

**Description**

Example of input TrP dataset.

**Usage**

```
TrPRawData
```

**Format**

A data.table consisting of 4692 rows and 29 columns. Raw TrP data for use in testing and examples.

**Details**

Input to MSstatsLiP converter SpectronautoMSstatsLiPFormat. Contains the following columns:

- R.Condition : Label of conditions (EG Disease/Control)
- R.FileName : Name of spectral processing run
- R.Replicate : Name of biological replicate
- PG.ProteinAccessions : Protein name
- PG.ProteinGroups : Protein name, can be multiple
- PG.Quantity : Protein Quantity
- PEP.GroupingKey : Peptide grouping
- PEP.StrippedSequence : Peptide sequence
- PEP.Quantity : Peptide quantity
- EG.iRTPredicted : Predicted value
- EG.Library : Name of library
- EG.ModifiedSequence : Peptide sequence including any post-translational modifications
- EG.PrecursorId : Peptide sequence with modifications including charge
- EG.Qvalue : Qvalue

- FG.Charge : Identified Ion charge
- FG.Id : Peptide sequence with charge
- FG.PrecMz : Prec Mz reading
- FG.Quantity : Initial quantity reading
- F.Charge : F.Charge
- F.FrgIon : Fragment ion
- F.FrgLossType : Label for loss type
- F.FrgMz : Mz reading
- F.FrgNum : numeric Frg
- F.FrgType : character label for Frg
- F.ExcludedFromQuantification : True/False boolean for if to exclude
- F.NormalizedPeakArea : Normalized peak intensity
- F.NormalizedPeakHeight : Normalized peak height
- F.PeakArea : Unnormalized peak area
- F.PeakHeight : Unnormalized peak height

### Examples

```
head(TrPRawData)
```

---

```
trypticHistogramLiP Histogram of Half vs Fully tryptic peptides. Calculates proteotypicity,
and then uses calcuations in histogram.
```

---

### Description

Histogram of Half vs Fully tryptic peptides. Calculates proteotypicity, and then uses calcuations in histogram.

### Usage

```
trypticHistogramLiP(
  data,
  fasta,
  x.axis.size = 10,
  y.axis.size = 10,
  legend.size = 10,
  width = 12,
  height = 4,
  color_scale = "bright",
  address = "",
  isPlotly = FALSE
)
```

**Arguments**

<code>data</code>	output of MSstatsLiP converter function. Must include at least ProteinName, PeptideSequence, BioReplicate, and Condition columns
<code>fasta</code>	A string of path to a FASTA file, used to match LiP peptides.
<code>x.axis.size</code>	size of x-axis labeling for plot. Default is 10.
<code>y.axis.size</code>	size of y-axis labeling for plot. Default is 10.
<code>legend.size</code>	size of feature legend for half vs fully tryptic peptides below graph. Default is 7.
<code>width</code>	Width of final pdf to be plotted
<code>height</code>	Height of final pdf to be plotted
<code>color_scale</code>	colors of bar chart. Must be one of "bright" or "grey". Default is "bright".
<code>address</code>	the name of folder that will store the results. Default folder is the current working directory. The other assigned folder has to be existed under the current working directory. An output pdf file is automatically created with the default name of "TyrpticPlot.pdf". If address=FALSE, plot will be not saved as pdf file but shown in window..
<code>isPlotly</code>	Parameter to use Plotly or ggplot2. If set to TRUE, MSstats will save Plotly plots as HTML files. If set to FALSE MSstats will save ggplot2 plots as PDF files

**Value**

plot or pdf

**Examples**

```
# Use output of summarization function
trypticHistogramLiP(MSstatsLiP_Summarized,
  system.file("extdata", "ExampleFastaFile.fasta", package="MSstatsLiP"),
  color_scale = "bright", address = FALSE)
```

# Index

## \* datasets

- LiPRawData, [16](#)
- MSstatsLiP\_data, [19](#)
- MSstatsLiP\_model, [20](#)
- MSstatsLiP\_Summarized, [21](#)
- raw\_lip, [24](#)
- raw\_prot, [25](#)
- SkylineTest, [28](#)
- TrPRawData, [35](#)

- tidyFasta, [34](#)
- TrPRawData, [35](#)
- trypticHistogramLiP, [36](#)

annotSite, [2](#)

calculateProteolyticResistance, [3](#)  
calculateTrypticity, [4](#)  
correlationPlotLiP, [5](#)

dataProcessPlotsLiP, [6](#)  
dataSummarizationLiP, [6](#), [8](#), [13](#), [23](#), [27](#)  
DIANNtoMSstatsLiPFormat, [11](#)

groupComparisonLiP, [12](#), [15](#), [33](#)  
groupComparisonPlotsLiP, [14](#)

LiPRawData, [16](#)  
locateMod, [18](#)  
locatePTM, [18](#)

MSstatsLiP\_data, [19](#)  
MSstatsLiP\_model, [20](#)  
MSstatsLiP\_Summarized, [21](#)

PCAPlotLiP, [22](#)

raw\_lip, [24](#)  
raw\_prot, [25](#)  
ResistanceBarcodePlotLiP, [27](#)

SkylineTest, [28](#)  
SkylinetoMSstatsLiPFormat, [29](#)  
SpectronauttoMSstatsLiPFormat, [31](#)  
StructuralBarcodePlotLiP, [33](#)