Package: MSstatsQC (via r-universe)

November 25, 2026

Version 2.32.0

Type Package

Title Longitudinal system suitability monitoring and quality control for proteomic experiments

Description MSstatsQC is an R package which provides longitudinal system suitability monitoring and quality control tools for proteomic experiments.

License Artistic License 2.0

URL http://msstats.org/msstatsqc

LazyData True

BugReports https://groups.google.com/forum/#!forum/msstatsqc

RoxygenNote 7.3.3

Imports dplyr,plyr, plotly, ggplot2, ggExtra, stats, grid, MSnbase, qcmetrics, h2o, FrF2, car, reshape2, jsonlite

Suggests knitr, rmarkdown, testthat, RforProteomics

VignetteBuilder knitr

biocViews Software, QualityControl, Proteomics, MassSpectrometry, Normalization

Encoding UTF-8

Config/pak/sysreqs cmake libglpk-dev libgmp3-dev make default-jdk libicu-dev libuv1-dev libxml2-dev libnetcdf-dev libssl-dev zlib1g-dev

Repository Bioconductor 3.24

Date/Publication 2026-11-23 22:39:43 UTC

RemoteUrl https://github.com/bioc/MSstatsQC

RemoteRef RELEASE_3_24

RemoteSha bf2310bc55d502c3c9d0f1781803cdbf1867f9f4

Contents

ChangePointEstimator . . . 2
CUSUMChart . . . 4
DataProcess . . . 5
DecisionMap . . . 6
MissingDataMap . . . 7
MSnbaseToMSstatsQC . . . 8
MSstatsQC.ML.deployR . . . 8
MSstatsQC.ML.sim.size.detectR . . . 9
MSstatsQC.ML.trainR . . . 10
mzQCToMSstatsQC . . . 11
QCloudDDA . . . 12
QCloudSRM . . . 13
QuiCDIA . . . 13
RadarPlot . . . 14
RemoveMissing . . . 15
RiverPlot . . . 16
S9Site54 . . . 17
XmRChart . . . 18

Index **20**

`ChangePointEstimator` *A function to identify the time of a change in the mean or variability of a metric*

Description

A function to identify the time of a change in the mean or variability of a metric

Usage

```
ChangePointEstimator(
  data = NULL,
  peptide,
  L = 1,
  U = 5,
  metric,
  normalization = TRUE,
  ytitle = "Change Point Plot - mean",
  type = "mean",
  selectMean = NULL,
  selectSD = NULL
)
```

Arguments

data	comma-separated (.csv), metric file. It should contain a "Precursor" column and the metrics columns. It should also include "Annotations" for each observation.
peptide	the name of precursor of interest.
L	Lower bound of the guide set.
U	Upper bound of the guide set.
metric	the name of metric of interest.
normalization	TRUE metric is standardized and FALSE if not standardized.
ytitle	the y-axis title of the plot. Defaults to "Change Point Plot - mean". The x-axis title is by default "QCno-name of peptide"
type	the type of the control chart. Two values can be assigned, "mean" or "variability". Default is "mean".
selectMean	the mean of a metric. It is used when mean is known. It is NULL when mean is not known. The default is NULL.
selectSD	the standard deviation of a metric. It is used when standard deviation is known. It is NULL when mean is not known. The default is NULL.

Value

A plot of likelihood statistics versus time per peptide and metric generated from `CP.data.prepare` data frame.

Examples

```
# First process the data to make sure it's ready to use
sampleData <- DataProcess(S9Site54)
head(sampleData)
# Find the name of the peptides
levels(sampleData$Precursor)
# Calculate change point statistics
ChangePointEstimator(data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime")
ChangePointEstimator(
    data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime",
    ytitle = "Change Point Plot - variability", type = "variability"
)
ChangePointEstimator(
    data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime",
    selectMean = 27.78, selectSD = 8.19
)
ChangePointEstimator(data = sampleData, peptide = "DDGSWEVIEGYR", metric = "TotalArea")
ChangePointEstimator(
    data = sampleData, peptide = "DDGSWEVIEGYR", metric = "TotalArea",
    selectMean = 35097129, selectSD = 34132861
)
ChangePointEstimator(data = sampleData, peptide = "TAAYVNAIEK", metric = "MaxFWHM")
```

CUSUMChart *A function to create cumulative sum charts for mean (CUSUMm) and cumulative sum charts for variability (CUSUMv) control charts*

Description

A function to create cumulative sum charts for mean (CUSUMm) and cumulative sum charts for variability (CUSUMv) control charts

Usage

```
CUSUMChart(
  data = NULL,
  peptide,
  L = 1,
  U = 5,
  metric,
  normalization = TRUE,
  ytitle = "CUSUMm",
  type = "mean",
  selectMean = NULL,
  selectSD = NULL,
  referenceValue = 0.5,
  decisionInterval = 5
)
```

Arguments

data	comma-separated (.csv), metric file. It should contain a "Precursor" column and the metrics columns. It should also include "Annotations" for each observation.
peptide	the name of precursor of interest.
L	Lower bound of the guide set.
U	Upper bound of the guide set.
metric	the name of metric of interest.
normalization	TRUE if metric is standardized and FALSE if not standardized.
ytitle	the y-axis title of the plot. Defaults to "CUSUMm". The x-axis title is by default "Time : name of peptide"
type	the type of the control chart. Two values can be assigned, "mean" or "variability". Default is "mean"
selectMean	the mean of a metric. It is used when mean is known. It is NULL when mean is not known. The default is NULL.
selectSD	the standard deviation of a metric. It is used when standard deviation is known. It is NULL when mean is not known. The default is NULL.
referenceValue	the value that is used to tune the control chart for a proper shift size
decisionInterval	the threshold to detect an out-of-control observation

Value

A plot of pozitive and negative CUSUM statistics versus time per peptide and metric generated from `CUSUM.data.prepare` data frame.

Examples

```
# First process the data to make sure it's ready to use
sampleData <- DataProcess(S9Site54)
head(sampleData)
# Find the name of the peptides
levels(sampleData$Precursor)
# Calculate CUSUM statistics
CUSUMChart(data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime")
CUSUMChart(
    data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime",
    ytitle = "CUSUMv", type = "variability"
)
CUSUMChart(
    data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime",
    selectMean = 27.78, selectSD = 8.19
)
CUSUMChart(data = sampleData, peptide = "DDGSWEVIEGYR", metric = "TotalArea")
CUSUMChart(
    data = sampleData, peptide = "DDGSWEVIEGYR", metric = "TotalArea",
    selectMean = 35097129, selectSD = 34132861
)
CUSUMChart(data = sampleData, peptide = "TAAYVNAIEK", metric = "MaxFWHM")
```

`DataProcess` *A data processing function*

Description

A data processing function

Usage

```
DataProcess(data = NULL)
```

Arguments

`data`	Comma-separated (*.csv), QC file format. It should contain a Precursor column and the metrics columns.

Value

A data frame that processes using `input.sanity.check` function.

Examples

```
# The data is "S9Site54" which is defined in the package.
data <- DataProcess(S9Site54)
```

`DecisionMap` *A function to create heatmaps to compare performance with user defined performance criteria*

Description

A function to create heatmaps to compare performance with user defined performance criteria

Usage

```
DecisionMap(
  data = NULL,
  method = "XmR",
  peptideThresholdRed = 0.7,
  peptideThresholdYellow = 0.5,
  L = 1,
  U = 5,
  type = "mean",
  title = "heatmap plot",
  listMean = NULL,
  listSD = NULL
)
```

Arguments

`data`	Comma-separated (*.csv), QC file format. It should contain a Precursor column and the metrics columns.
`method`	It is either "CUSUM" or "XmR"
`peptideThresholdRed`	Is a threshold that marks percentage of peptides above it red on the heatmap. Defaults to 0.7
`peptideThresholdYellow`	Is a threshold that marks percentage of peptides above it and below the peptideThresholdRed, yellow on the heatmap. Defaults to 0.5
`L`	Lower bound of the giude set. Defaults to 1
`U`	Upper bound of the guide set. Defaults to 5
`type`	can take two values, "mean" or "dispersion". Defaults to "mean"
`title`	the title of the plot. Defaults to "heatmap plot"
`listMean`	List of the means for the metrics. If you don't know the means leave it as NULL and they will be calculated automatically by using L and U. The default is NULL.

listSD — List of the standard deviations for the metrics. If you don't know the standard deviations leave it as NULL and they will be calculated automatically by using L and U. The default is NULL.

Value

A heatmap to aggregate results per metric generated from heatmap.DataFrame data frame.

Examples

```
# First process the data to make sure it's ready to use
sampleData <- DataProcess(S9Site54)
head(sampleData)
# Draw Decision maker plot
DecisionMap(data = sampleData, method = "CUSUM")
DecisionMap(data = sampleData, method = "CUSUM", type = "variability")
DecisionMap(data = sampleData, method = "XmR")
DecisionMap(data = sampleData, method = "XmR", type = "variability")
```

MissingDataMap *A function to summarize missing values*

Description

A function to summarize missing values

Usage

```
MissingDataMap(data)
```

Arguments

data — Processed data

Value

A plot of missing values.

Examples

```
# The data is "S9Site54" which is defined in the package.
data <- DataProcess(S9Site54)
MissingDataMap(data)
```

MSnbaseToMSstatsQC *A function to convert MSnbase files to MSstatsQC format*

Description

A function to convert MSnbase files to MSstatsQC format

Usage

```
MSnbaseToMSstatsQC(msfile)
```

Arguments

msfile	data file to be converted

Value

A data frame that can be used with MSstatsQC

A csv file that is converted from raw files

Examples

```
library(RforProteomics)

msfile <- getPXD000001mzXML()

MSnbaseToMSstatsQC(msfile)
```

MSstatsQC.ML.deployR *A function to test random forest classifiers for QC data*

Description

A function to test random forest classifiers for QC data

Usage

```
MSstatsQC.ML.deployR(Test.set, guide.set, rf_model)
```

Arguments

Test.set	comma-separated (.csv), metric file. It should contain a "Precursor" column and the metrics columns. It should also include "Annotations" for each run.
guide.set	comma-separated (.csv), metric file. It should contain a "Precursor" column and the metrics columns. It should also include "Annotations" for each run.
rf_model	the model that was trained previosly by MSstatsQC-ML training process

Value

Probability of failure predictions based on a trained model

Examples

```
S9Site54.dataML <- DataProcess(MSstatsQC::S9Site54[, ])
colnames(S9Site54.dataML)[1] <- c("idfile")
colnames(S9Site54.dataML)[2] <- c("peptide")
S9Site54.dataML$peptide <- as.factor(S9Site54.dataML$peptide)
S9Site54.dataML$idfile <- as.numeric(S9Site54.dataML$idfile)
S9Site54.dataML <- within(S9Site54.dataML, rm(Annotations, missing))
guide.set <- dplyr::filter(S9Site54.dataML, idfile <= 20)

rf_model <- MSstatsQC.ML.trainR(guide.set, sim.size = 10)

Test.set <- dplyr::filter(S9Site54.dataML, idfile > 20)

MSstatsQC.ML.deployR(Test.set, guide.set, rf_model = rf_model)

Test.set <- S9Site54.dataML

MSstatsQC.ML.deployR(Test.set, guide.set, rf_model = rf_model)
```

MSstatsQC.ML.sim.size.detectR

A function to train random forest classifiers for QC data

Description

A function to train random forest classifiers for QC data

Usage

```
MSstatsQC.ML.sim.size.detectR(guide.set, sim.start, sim.end)
```

Arguments

guide.set	comma-separated (.csv), metric file. It should contain a "Precursor" column and the metrics columns. It should also include "Annotations" for each run.
sim.start	enter min simulation size.
sim.end	enter max simulation size.

Value

a plot for sim.size vs performance

Examples

```
# First process the data to make sure it's ready to use
S9Site54.dataML <- DataProcess(MSstatsQC::S9Site54[, ])
colnames(S9Site54.dataML)[1] <- c("idfile")
colnames(S9Site54.dataML)[2] <- c("peptide")
S9Site54.dataML$peptide <- as.factor(S9Site54.dataML$peptide)
S9Site54.dataML$idfile <- as.numeric(S9Site54.dataML$idfile)
S9Site54.dataML <- within(S9Site54.dataML, rm(Annotations, missing))
guide.set <- dplyr::filter(S9Site54.dataML, idfile <= 20)

MSstatsQC.ML.sim.size.detectR(guide.set, sim.start = 10, sim.end = 2500)
```

MSstatsQC.ML.trainR *A function to train random forest classifiers for QC data*

Description

A function to train random forest classifiers for QC data

Usage

```
MSstatsQC.ML.trainR(
  guide.set,
  sim.size,
  guide.set.annotations = NULL,
  nfolds = NULL,
  a = 1.5,
  b = 2
)
```

Arguments

guide.set	comma-separated (.csv), metric file. It should contain a "Precursor" column and the metrics columns. It should also include "Annotations" for each run.
sim.size	enter simulation size.
guide.set.annotations	comma-separated (.csv), metric file with annotations such as pass and fail.
nfolds	fold for cross validation
a	lower threshold to define shift size
b	upper threshold to define shift size

Value

A trained model and performance indicators from train/validation/test splits

Examples

```
S9Site54.dataML <- DataProcess(MSstatsQC::S9Site54[, ])
colnames(S9Site54.dataML)[1] <- c("idfile")
colnames(S9Site54.dataML)[2] <- c("peptide")
S9Site54.dataML$peptide <- as.factor(S9Site54.dataML$peptide)
S9Site54.dataML$idfile <- as.numeric(S9Site54.dataML$idfile)
S9Site54.dataML <- within(S9Site54.dataML, rm(Annotations, missing))
guide.set <- dplyr::filter(S9Site54.dataML, idfile <= 20)

MSstatsQC.ML.trainR(guide.set, sim.size = 10)
```

---

mzQCToMSstatsQC *A function to convert mzQC files to MSstatsQC format*

Description

A function to convert mzQC files to MSstatsQC format

Usage

```
mzQCToMSstatsQC(mzQCfile)
```

Arguments

mzQCfile	data file to be converted

Value

A data frame that can be used with MSstatsQC

A csv file that is converted from raw files

Examples

```
library(RforProteomics)

msfile <- getPXD000001mzXML()

mzQCToMSstatsQC(msfile)
```

QCloudDDA *DDA QC data from QCloud System*

Description

QC results generated from QCloud system

Usage

```
data(QCloudDDA)
```

Format

csv

Details

DDA QC data from QCloud System

Value

An example dataset generated from QCloud system

Examples

```
head(QCloudDDA)
```

QCloudSRM *SRM QC data from QCloud System*

Description

QC results generated from QCloud system

Usage

```
data(QCloudSRM)
```

Format

csv

Details

SRM QC data from QCloud System

Value

An example dataset generated from QCloud system

Examples

```
head(QCloudSRM)
```

QuiCDIA *DIA iRT data from QuiC System*

Description

QC results generated from QuiC system

Usage

```
data(QuiCDIA)
```

Format

csv

Details

DIA iRT data from QuiC System

Value

An example dataset generated from QuiC system

Examples

```
head(QuiCDIA)
```

`RadarPlot` *A function to create radar plot to aggregate results from X and mR charts or CUSUMm and CUSUMv charts.*

Description

A function to create radar plot to aggregate results from X and mR charts or CUSUMm and CUSUMv charts.

Usage

```
RadarPlot(
  data = NULL,
  L = 1,
  U = 5,
  method = "XmR",
  listMean = NULL,
  listSD = NULL
)
```

Arguments

`data`	omma-separated (.csv), metric file. It should contain a "Precursor" column and the metrics columns. It should also include "Annotations" for each observation.
`L`	lower bound of the guide set.
`U`	upper bound of the guide set.
`method`	defines the method selected to construct control charts.
`listMean`	list of the means for each metric. It is used when mean is known. It is NULL when mean is not known. The default is NULL.
`listSD`	list of the standard deviations for each metric. It is used when standard deviation is known. It is NULL when mean is not known. The default is NULL. automatically by using L and U. The default is NULL.

Value

A radar plot to aggregate results per metric generated from `XmR.Radar.Plot.DataFrame` data frame or `CUSUM.Radar.Plot.DataFrame` data frame.

Examples

```
# First process the data to make sure it's ready to use
sampleData <- DataProcess(S9Site54)
head(sampleData)
# Draw XmR radar plot
RadarPlot(data = sampleData)
RadarPlot(data = sampleData, method = "CUSUM")
RadarPlot(
    data = sampleData,
    listMean = list(
        "BestRetentionTime" = 27.78,
        "TotalArea" = 35097129,
        "MaxFWHM" = 0.28,
        "MinStartTime" = 24
    ),
    listSD = list(
        "BestRetentionTime" = 8.19,
        "TotalArea" = 34132861,
        "MaxFWHM" = 0.054,
        "MinStartTime" = 24
    )
)
```

RemoveMissing *A data processing function for removing missing values*

Description

A data processing function for removing missing values

Usage

```
RemoveMissing(data = NULL)
```

Arguments

data	Comma-separated (*.csv), QC file format. It should contain a Precursor column and the metrics columns.

Value

A data frame that processes using `input.sanity.check` function.

Examples

```
# The data is "S9Site54" which is defined in the package.
data <- RemoveMissing(S9Site54)
```

`RiverPlot` *A function to create river plot to aggregate results from X and mR charts or CUSUMm and CUSUMv charts.*

Description

A function to create river plot to aggregate results from X and mR charts or CUSUMm and CUSUMv charts.

Usage

```
RiverPlot(
  data = NULL,
  L = 1,
  U = 5,
  method = "XmR",
  listMean = NULL,
  listSD = NULL
)
```

Arguments

`data`	omma-separated (.csv), metric file. It should contain a "Precursor" column and the metrics columns. It should also include "Annotations" for each observation.
`L`	lower bound of the guide set.
`U`	upper bound of the guide set.
`method`	defines the method selected to construct control charts.
`listMean`	list of the means for each metric. It is used when mean is known. It is NULL when mean is not known. The default is NULL.
`listSD`	list of the standard deviations for each metric. It is used when standard deviation is known. It is NULL when mean is not known. The default is NULL.

Value

A river plot to aggregate results per metric generated from `XmR.Summary.DataFrame` data frame or `CUSUM.Summary.DataFrame` data frame.

Examples

```
# First process the data to make sure it's ready to use
sampleData <- DataProcess(S9Site54)
head(sampleData)
# Draw XmR summary plot
RiverPlot(data = sampleData)
RiverPlot(
    data = sampleData, L = 1, U = 20, method = "XmR",
    listMean = list(
```

```
        "BestRetentionTime" = 27.78,
        "TotalArea" = 35097129,
        "MaxFWHM" = 0.28,
        "MinStartTime" = 24
    ),
    listSD = list(
        "BestRetentionTime" = 8.19,
        "TotalArea" = 34132861,
        "MaxFWHM" = 0.054,
        "MinStartTime" = 24
    )
)
```

S9Site54 *CPTAC study 9.1 site 54 dataset*

Description

system suitabilty testing results generated during CPTAC Study 9.1 for Site 54

Usage

```
data(S9Site54)
```

Format

csv

Details

CPTAC system suitability testing data for Site 54 from Study 9.1

Value

An example dataset generated from CPTAC study 9.1

References

http://www.mcponline.org/content/early/2015/02/18/mcp.M114.047050

Examples

```
head(S9Site54)
```

XmRChart *A function to construct individual (X) and moving range (mR) control charts*

Description

A function to construct individual (X) and moving range (mR) control charts

Usage

```
XmRChart(
  data = NULL,
  peptide,
  L = 1,
  U = 5,
  metric,
  normalization = FALSE,
  ytitle = "Individual observations",
  type = "mean",
  selectMean = NULL,
  selectSD = NULL
)
```

Arguments

data	comma-separated (.csv), metric file. It should contain a "Precursor" column and the metrics columns. It should also include "Annotations" for each observation.
peptide	the name of precursor of interest.
L	Lower bound of the guide set.
U	Upper bound of the guide set.
metric	the name of metric of interest.
normalization	TRUE if metric is standardized and FALSE if not standardized.
ytitle	the y-axis title of the plot. Defaults to "Individual observations". The x-axis title is by default "Time : name of peptide"
type	the type of the control chart. Two values can be assigned, "mean" or "variability". Default is "mean".
selectMean	the mean of a metric. It is used when mean is known. It is NULL when mean is not known. The default is NULL.
selectSD	the standard deviation of a metric. It is used when standard deviation is known. It is NULL when mean is not known. The default is NULL.

Value

A plot of individual values or moving ranges versus time per peptide and metric generated from `XmR.data.prepare` data frame.

Examples

```
# First process the data to make sure it's ready to use
sampleData <- DataProcess(S9Site54)
head(sampleData)
# Find the name of the peptides
levels(sampleData$Precursor)
# Calculate X and mR statistics
XmRChart(data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime")
XmRChart(
    data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime",
    ytitle = "moving ranges", type = "variability"
)
XmRChart(
    data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime",
    selectMean = 27.78, selectSD = 8.19
)
XmRChart(data = sampleData, peptide = "DDGSWEVIEGYR", metric = "TotalArea")
XmRChart(
    data = sampleData, peptide = "DDGSWEVIEGYR", metric = "TotalArea",
    selectMean = 35097129, selectSD = 34132861
)
XmRChart(data = sampleData, peptide = "TAAYVNAIEK", metric = "MaxFWHM")
XmRChart(data = sampleData, peptide = "LVNELTEFAK", metric = "MinStartTime")
```

Index

∗ **MSnbase,**
MSnbaseToMSstatsQC, 8
∗ **Sum,**
CUSUMChart, 4
∗ **XmR,**
XmRChart, 18
∗ **XmR**
RadarPlot, 14
RiverPlot, 16
∗ **change**
ChangePointEstimator, 2
∗ **chart**
ChangePointEstimator, 2
CUSUMChart, 4
XmRChart, 18
∗ **control**
ChangePointEstimator, 2
CUSUMChart, 4
XmRChart, 18
∗ **cumulative**
CUSUMChart, 4
∗ **datasets**
QCloudDDA, 12
QCloudSRM, 13
QuiCDIA, 13
S9Site54, 17
∗ **deployment**
MSstatsQC.ML.deployR, 8
∗ **engineering**
MSstatsQC.ML.trainR, 10
∗ **feature**
MSstatsQC.ML.trainR, 10
∗ **heatmap**
DecisionMap, 6
∗ **input**
MSnbaseToMSstatsQC, 8
mzQCToMSstatsQC, 11
∗ **learning,**
MSstatsQC.ML.deployR, 8
MSstatsQC.ML.sim.size.detectR, 9
MSstatsQC.ML.trainR, 10
∗ **machine**
MSstatsQC.ML.deployR, 8
MSstatsQC.ML.sim.size.detectR, 9
MSstatsQC.ML.trainR, 10
∗ **mzqc,**
mzQCToMSstatsQC, 11
∗ **point,**
ChangePointEstimator, 2
∗ **qcmetrics,**
MSnbaseToMSstatsQC, 8
mzQCToMSstatsQC, 11
∗ **simulation**
MSstatsQC.ML.sim.size.detectR, 9
∗ **size**
MSstatsQC.ML.sim.size.detectR, 9
∗ **training,**
MSstatsQC.ML.trainR, 10

ChangePointEstimator, 2
CUSUMChart, 4

DataProcess, 5
DecisionMap, 6

MissingDataMap, 7
MSnbaseToMSstatsQC, 8
MSstatsQC.ML.deployR, 8
MSstatsQC.ML.sim.size.detectR, 9
MSstatsQC.ML.trainR, 10
mzQCToMSstatsQC, 11

QCloudDDA, 12
QCloudSRM, 13
QuiCDIA, 13

RadarPlot, 14
RemoveMissing, 15
RiverPlot, 16

S9Site54, 17

XmRChart, 18