Package: OPWeight (via r-universe)

November 25, 2026

Type Package

Title Optimal p-value weighting with independent information

Version 1.36.0

Date 2017-02-26

Description This package perform weighted-pvalue based multiple hypothesis test and provides corresponding information such as ranking probability, weight, significant tests, etc . To conduct this testing procedure, the testing method apply a probabilistic relationship between the test rank and the corresponding test effect size.

Depends R (>= 3.4.0),

License Artistic-2.0

LazyData true

Imports graphics, qvalue, MASS, tibble, stats,

Suggests airway, BiocStyle, cowplot, DESeq2, devtools, ggplot2, gridExtra, knitr, Matrix, rmarkdown, scales, testthat

VignetteBuilder knitr

biocViews ImmunoOncology, BiomedicalInformatics, MultipleComparison, Regression, RNASeq, SNP

RoxygenNote 6.0.1

URL https://github.com/mshasan/OPWeight

Bugreports https://github.com/mshasan/OPWeight/issues

Config/pak/sysreqs libicu-dev

Repository Bioconductor 3.24

Date/Publication 2026-11-23 22:39:15 UTC

RemoteUrl https://github.com/bioc/OPWeight

RemoteRef RELEASE_3_24

RemoteSha 6091eb3d6a6d89061bf65f4fd2e547575404b5da

Contents

opw 2
prob_rank_givenEffect 5
prob_rank_givenEffect_approx 6
prob_rank_givenEffect_exact 8
prob_rank_givenEffect_simu 9
weight_binary 11
weight_by_delta 12
weight_continuous 13

Index **15**

---

opw *Perform Optimal Pvalue Weighting*

Description

A function to perform weighted pvalue multiple hypothesis test. This function compute the probabilities of the ranks of the filter statistics given the effect sizes, and consequently the weights if neighter the weights nor the probabilities are given. Then provides the number of rejected null hypothesis and the list of the rejected pvalues as well as the corresponing filter statistics.

Usage

```
opw(pvalue, filter, weight = NULL, ranksProb = NULL,
  mean_filterEffect = NULL, mean_testEffect = NULL,
  effectType = c("continuous", "binary"), alpha = 0.05, nrep = 10000,
  tail = 1L, delInterval = 0.001, method = c("BH", "BON"), ...)
```

Arguments

`pvalue`	Numeric vector of pvalues of the test statistics
`filter`	Numeric vector of filter statistics
`weight`	An optional numeric weight vector not required
`ranksProb`	An optional numeric vector of the ranks probability of the filters given the mean effect
`mean_filterEffect`	Numeric, value of the mean filter effect of the true alternatives
`mean_testEffect`	Numeric, value of the mean test effect of the true alterantives
`effectType`	Character ("continuous" or "binary"), type of effect sizes
`alpha`	Numeric, significance level of the hypothesis test
`nrep`	Integer, number of replications for importance sampling, default value is 10,000, can be increased to obtain smoother probability curves

`tail`	Integer (1 or 2), right-tailed or two-tailed hypothesis test. default is right-tailed test.
`delInterval`	Numeric, interval between the `delta` values of a sequence. Note that, `delta` is a LaGrange multiplier, necessary to normalize the weight
`method`	Character ("BH" or "BON"), type of methods is used to obtain the results; Benjemini-Hochberg or Bonferroni
`...`	Arguments passed to internal functions

Details

If one wants to test

$$H_0 : epsilon_i = 0 vs. H_a : epsilon_i > 0,$$

then the `mean_testEffect` and `mean_filterEffect` should be mean of the test and filter effect sizes, respectively. This is called hypothesis testing for the continuous effect sizes.

If one wants to test

$$H_0 : epsilon_i = 0 vs. H_a : epsilon_i = epsilon,$$

then `mean_testEffect` and `mean_filterEffect` should be median or any discrete value of the test and filter effect sizes. This is called hypothesis testing for the Binary effect sizes, where `epsilon` refers to a fixed value.

The main goal of the function is to compute the probabilities of the ranks from the pvalues and the filter statistics, consequently the weights. Although `weights` `ranksProb` are optional, `opw` has the options so that one can compute the probabilities and the weights externally if necessary (see examples).

Internally, `opw` function compute the `ranksProb` and consequently the weights, then uses the pvalues to make conclusions about hypotheses. Therefore, if `ranksProb` is given then `mean_filterEffect` and are redundant, and should not be provided to the funciton. Although `ranksProb` is not required to the function, One can compute `ranksProb` by using the function `prob_rank_givenEffect`.

The function internally compute `mean_filterEffect` and `mean_testEffect` from a simple linear regression with box-cox transformation between the test and filter statistics, where the filters are regressed on the test statistics. Thus, filters need to be positive to apply `boxcox` from the `R` library `MASS`. Then the estimated `mean_filterEffect` and `mean_testEffect` are used to obtian the `ranksProb` and the weights. Thus, in order to apply the function properly, it is crucial to understand the uses `mean_filterEffect` and `mean_testEffect`. If `mean_filterEffect` and `mean_testEffect` are not provided then the test statistics computed from the pvalues will be used to compute the relationship between the filter statistics and the test statistics.

If one of the mean effects `mean_filterEffect` and `mean_testEffect` are not provided then the missing mean effect will be computed internally.

Value

`totalTests` Integer, total number of hypothesis tests evaluated

`nullProp` Numeric, estimated propotion of the true null hypothesis

`ranksProb` Numeric vector of ranks probability given the mean filter effect, p(rank | ey = mean_filterEffect)

`weight` Numeric vector of normalized weight

`rejections` Integer, total number of rejections

`rejections_list` data frame, list of rejected p-values and the corresponding filter statistics and the adjusted p-values if method = "BH" used.

Author(s)

Mohamad S. Hasan, shakilmohamad7@gmail.com

See Also

`prob_rank_givenEffect` `weight_binary` `weight_continuous` `qvalue` `dnorm`

Examples

```
# generate pvalues and filter statistics
m = 1000
set.seed(3)
filters = runif(m, min = 0, max = 2.5)          # filter statistics
H = rbinom(m, size = 1, prob = 0.1)             # hypothesis true or false
tests = rnorm(m, mean = H * filters)            # Z-score
pvals = 1 - pnorm(tests)                        # pvalue

# general use
results <- opw(pvalue = pvals, filter = filters, effectType = "continuous",
                                                method = "BH")

# supply the mean effects for both the filters and the tests externally
mod <- lm(log(filters) ~ tests)
et = mean(tests)
ey = mod$coef[[1]] + mod$coef[[2]]*et
results2 <- opw(pvalue = pvals, filter = filters,
               mean_filterEffect = ey, mean_testEffect = et, tail = 2,
               effectType = "continuous", method = "BH")

# supply the rank probabilities externally
library(qvalue)
ranks <- 1:m
nullProp = qvalue(p = pvals, pi0.method = "bootstrap")$pi0
m0 = ceiling(nullProp*m)
m1 = m - m0
probs <- sapply(ranks, prob_rank_givenEffect, et = ey, ey = ey,
                                        nrep = 10000, m0 = m0, m1 = m1)
results3 <- opw(pvalue = pvals, filter = filters, ranksProb = probs,
                 effectType = "continuous", tail = 2, method = "BH")
```

```
# supply weight externally
wgt <- weight_continuous(alpha = .05, et = et, m = m, ranksProb = probs)
results4 <- opw(pvalue = pvals, filter = filters, weight = wgt,
                        effectType = "continuous", alpha = .05, method = "BH")
```

`prob_rank_givenEffect` *Probability of rank of test given effect size*

Description

Comnpute the probability of rank of a test being higher than any other tests given the effect size from external information.

Usage

```
prob_rank_givenEffect(k, et, ey, nrep = 10000, m0, m1)
```

Arguments

`k`	Integer, rank of a test
`et`	Numeric, effect of the targeted test for importance sampling
`ey`	Numeric, mean filter efffect from the external information
`nrep`	Integer, number of replications for importance sampling
`m0`	Integer, number of true null hypothesis
`m1`	Integer, number of true alternative hypothesis

Details

If one wants to test

$$H_0 : epsilon_i = 0 vs. H_a : epsilon_i > 0,$$

then `ey` should be mean of the filter effect sizes, This is called hypothesis testing for the continuous effect sizes.

If one wants to test

$$H_0 : epsilon_i = 0 vs. H_a : epsilon_i = epsilon,$$

then `ey` should be median or any discrete value of the filter effect sizes. This is called hypothesis testing for the Binary effect sizes.

If `monitor = TRUE` then a window will open to see the progress of the computation. It is useful for a large number of tests

`m1` and `m0` can be estimated using `qvalue` from a bioconductor package `qvalue`.

Value

prob Numeric, probability of the rank of a test

Author(s)

Mohamad S. Hasan, shakilmohamad7@gmail.com

See Also

dnorm pnorm rnorm qvalue

Examples

```
# compute the probability of the rank of a test being third if all tests are
# from the true null
prob <- prob_rank_givenEffect(k = 3, et = 0, ey = 0, nrep = 10000,
                                      m0 = 50, m1 = 50)

# compute the probabilities of the ranks of a test being rank 1 to 100 if the
# targeted test effect is 2 and the overall mean filter effect is 1.
ranks <- 1:100
prob <- sapply(ranks, prob_rank_givenEffect, et = 2, ey = 1, nrep = 10000,
                                m0 = 50, m1 = 50)

# plot
plot(ranks,prob)
```

---

prob_rank_givenEffect_approx

Probability of rank of test given effect size by normal approximation

---

Description

A normal approximation to comnpute the probability of rank of a test being higher than any other test given the effect size from external information.

Usage

```
prob_rank_givenEffect_approx(k, et, ey, nrep = 10000, m0, m1,
  effectType = c("binary", "continuous"))
```

Arguments

k	Integer, rank of a test
et	Numeric, effect of the targeted test for importance sampling
ey	Numeric, mean/median filter efffect from external information

nrep	Integer, number of replications for importance sampling
m0	Integer, number of true null hypothesis
m1	Integer, number of true alternative hypothesis
effectType	Character ("continuous" or "binary"), type of effect sizes

Details

If one wants to test

$$H_0 : epsilon_i = 0 vs. H_a : epsilon_i > 0,$$

then ey should be mean of the filter effect sizes, This is called hypothesis testing for the continuous effect sizes.

If one wants to test

$$H_0 : epsilon_i = 0 vs. H_a : epsilon_i = epsilon,$$

then ey should be median or any discrete value of the filter effect sizes. This is called hypothesis testing for the Binary effect sizes.

m1 and m0 can be estimated using qvalue from a bioconductor package qvalue.

Value

prob Numeric, probability of the rank of a test

Author(s)

Mohamad S. Hasan, shakilmohamad7@gmail.com

See Also

dnorm pnorm rnorm qvalue

Examples

```
# compute the probability of the rank of a test being third if all tests are
# from the true null
prob <- prob_rank_givenEffect(k = 3, et = 0, ey = 0, nrep = 10000,
                                      m0 = 50, m1 = 50)

# compute the probabilities of the ranks of a test being rank 1 to 100 if the
# targeted test effect is 2 and the overall mean filter effect is 1.
ranks <- 1:100
prob <- sapply(ranks, prob_rank_givenEffect, et = 2, ey = 1, nrep = 10000,
                                m0 = 50, m1 = 50)

# plot
plot(ranks,prob)
```

`prob_rank_givenEffect_exact` *Probability of rank of test given effect size by exact method*

Description

An exact method to comnpute the probability of rank of a test being higher than any other test given the effect size from external information.

Usage

```
prob_rank_givenEffect_exact(k, et, ey, nrep = 10000, m0, m1,
  effectType = c("binary", "continuous"))
```

Arguments

`k`	Integer, rank of a test
`et`	Numeric, effect of the targeted test for importance sampling
`ey`	Numeric, mean/median filter efffect from external information
`nrep`	Integer, number of replications for importance sampling
`m0`	Integer, number of true null hypothesis
`m1`	Integer, number of true alternative hypothesis
`effectType`	Character ("continuous" or "binary"), type of effect sizes

Details

If one wants to test

$$H_0 : epsilon_i = 0 vs. H_a : epsilon_i > 0,$$

then `ey` should be mean of the filter effect sizes, This is called hypothesis testing for the continuous effect sizes.

If one wants to test

$$H_0 : epsilon_i = 0 vs. H_a : epsilon_i = epsilon,$$

then `ey` should be median or any discrete value of the filter effect sizes. This is called hypothesis testing for the Binary effect sizes.

`m1` and `m0` can be estimated using `qvalue` from a bioconductor package `qvalue`.

Value

`prob` Numeric, probability of the rank of a test

Author(s)

Mohamad S. Hasan, shakilmohamad7@gmail.com

See Also

dnorm pnorm rnorm qvalue

Examples

```
# compute the probability of the rank of a test being third if all tests are
# from the true null
prob <- prob_rank_givenEffect_exact(k=3, et=0, ey=0, nrep=10000, m0=50, m1=50,
                                effectType= "continuous")

# compute the probabilities of the ranks of a test being rank 1 to 100 if the
# targeted test effect is 2 and the overall mean filter effect is 1.
ranks <- 1:100
prob <- sapply(ranks, prob_rank_givenEffect, et = 2, ey = 1, nrep = 10000,
                               m0 = 50, m1 = 50)

# plot
plot(ranks, prob)
```

---

prob_rank_givenEffect_simu

Probability of rank of test given effect size by simulations

Description

A simulation approach to comnpute the probability of rank of a test being higher than any other test given the effect size from the external information.

Usage

```
prob_rank_givenEffect_simu(s, ey, e.one, m0, m1, effectType = c("binary",
  "continuous"))
```

Arguments

s	number of samples of test statistics composed of null and alternative tests
ey	Numeric, filter test efffect from the external information
e.one	Numeric, one test effect that will vary across all tests
m0	Integer, number of true null hypothesis
m1	Integer, number of true alternative hypothesis
effectType	Character ("continuous" or "binary"), type of effect sizes

Details

If one wants to test

$$H_0 : epsilon_i = 0 vs. H_a : epsilon_i > 0,$$

then ey should be mean of the filter effect sizes, This is called hypothesis testing for the continuous effect sizes.

If one wants to test

$$H_0 : epsilon_i = 0 vs. H_a : epsilon_i = epsilon,$$

then ey should be median or any discrete value of the filter effect sizes. This is called hypothesis testing for the Binary effect sizes.

This is a simulation approach to compute the probability of the rank, P(rank | effect = ey) to verify the actual P(rank | effect = ey). Suppose, we have a vector of m = m1+m0 observations, where the first m1 observations are from the true alternative and second m0 are from the true null models. If we pick two tests one from the first position and the other from the (m0+1)-th position, then we would expect that the first observation's rank is greater than m0, and (m1+1)-th observation's rank is less than or equal to m1. However, this is not always true, especially when the effect size of the test statistics is low, but the above scenerio become obvious as the the effect size increases. `m1` and `m0` can be estimated using `qvalue` from a bioconductor package `qvalue`.

Value

`r0` Integer, rank of the null test statistic
`r1` Integer, rank of the alternative test statistic

Author(s)

Mohamad S. Hasan, shakilmohamad7@gmail.com

See Also

`runif` `rnorm` `qvalue`

Examples

```
# total number of sample generated (use sample size at least 1,000,000)
sampleSize = 10000
m0 = 50
m1 = 50
m = m0 +m1

# compute rank of the tests
rank <- sapply(1:sampleSize, prob_rank_givenEffect_simu, ey = 1, e.one = 1,
                          m0 = m0, m1 = m1, effectType = "continuous")

# rank may generate missing valuse because of the large effcet size,
# therefore, to make a matplot one needs vector of equal size. This procedure
# will replace the missing value to make the equal sized vectors
```

```
# probability of the rank of a null test
prob0 <- rep(NA, m)
prob0_x <- tapply(rank[1,], rank[1,], length)/sampleSize
prob0[as.numeric(names(prob0_x))] <- as.vector(prob0_x)

# probability of the rank of an alternative test
prob1 <- rep(NA, m)
prob1_x <- tapply(rank[2,], rank[2,], length)/sampleSize
prob1[as.numeric(names(prob1_x))] <- as.vector(prob1_x)

# plot
matplot(1:m, cbind(prob0, prob1), type = "l")
```

`weight_binary` *Weight for the Binary effect sizes*

Description

Compute weight from the probability of the rank given the effect size for the binary effect size

Usage

```
weight_binary(alpha, et, m, m1, tail = 1L, delInterval = 0.001, ranksProb)
```

Arguments

`alpha`	Numeric, significance level of the hypothesis test
`et`	Numeric, mean effect size of the test statistics
`m`	Integer, totoal number of hypothesis test
`m1`	Integer, number of true alternative hypothesis
`tail`	Integer (1 or 2), right-tailed or two-tailed hypothesis test. default is right-tailed test.
`delInterval`	Numeric, interval between the `delta` values of a sequence. Note that, `delta` is a LaGrange multiplier, necessary to normalize the weight
`ranksProb`	Numeric vector of the ranks probability of the tests given the effect size

Details

If one wants to test

$$H_0 : epsilon_i = 0 vs. H_a : epsilon_i = epsilon,$$

then `et` and `ey` should be median or any discrete value of the test and filter effect sizes, respectively. This is called hypothesis testing for the Binary effect sizes. `m1` can be estimated using `qvalue` from a bioconductor package `qvalue`.

Value

`weight` Numeric vector of normalized weight of the tests for the binary case

Author(s)

Mohamad S. Hasan, shakilmohamad7@gmail.com

See Also

`prob_rank_givenEffect` `weight_continuous` `qvalue`

Examples

```
# compute the probabilities of the ranks of a test being rank 1 to 100 if the
# targeted test effect is 2 and the overall mean filter effect is 1.
ranks <- 1:100
prob2 <- sapply(ranks, prob_rank_givenEffect, et = 2, ey = 1, nrep = 10000,
                              m0 = 50, m1 = 50)
# plot the prooabbility
plot(ranks, prob2)

# compute weight for the binary case
weight_bin <- weight_binary(alpha = .05, et = 1, m = 100, m1 = 50, tail=1,
                            delInterval = .0001, ranksProb = prob2)

# plot the weight
plot(ranks, weight_bin)
```

---

weight_by_delta *Find sum of weights for the LaGrange multiplier*

Description

Compute sum of weights for a given value of the LaGrange multiplier

Usage

```
weight_by_delta(delta, alpha = 0.05, et, m, m1, tail = 1L, ranksProb,
  effectType = c("continuous", "binary"))
```

Arguments

`delta`	Numeric value of the LagRange multiplier
`alpha`	Numeric, significance level of the hypothesis test
`et`	Numeric, mean effect size of the test statistics
`m`	Integer, totoal number of hypothesis test

m1	Integer, number of true alternative tests
tail	Integer (1 or 2), right-tailed or two-tailed hypothesis test. default is right-tailed test.
ranksProb	Numeric vector of the ranks probability of the filter statistics given the effect size
effectType	Character ("continuous" or "binary"), type of effect sizes

Details

To obtain the normalized weight, and to make sure that the sum of the weights is equal to the number of tests and the weights are positive, an optimal value of the LaGrange multiplier delta needed. This function will compute the weights for a given value of the LaGrange multiplier and provide the sum of the weights in return.

Value

sumWeight_per_delta sum of weights per delta value

Author(s)

Mohamad S. Hasan, shakilmohamad7@gmail.com

Examples

```
# generate a sequence of delta
delta <- seq(0, 1, .0001)

# compute probability fiven effect
filters = runif(100, min = 0, max = 2.5)
probs <- dnorm(filters, mean = 0, sd = 1)

# compute the sum of weights for each delta
weightSum_by_delta <- sapply(delta, weight_by_delta, m = 100, m1 = 50, et = 2,
                             ranksProb = probs, effectType = "continuous")
```

---

weight_continuous *Weight for the continuous effect sizes*

Description

Compute weight from the probability of the rank given the effect size for the continuous effect size

Usage

```
weight_continuous(alpha, et, m, tail = 1L, delInterval = 0.001, ranksProb)
```

Arguments

alpha	Numeric, significance level of the hypothesis test
et	Numeric, mean effect size of the test statistics
m	Integer, totoal number of hypothesis test
tail	Integer (1 or 2), right-tailed or two-tailed hypothesis test. default is right-tailed test.
delInterval	Numeric, interval between the delta values of a sequence. Note that, delta is a LaGrange multiplier, necessary to normalize the weight
ranksProb	Numeric vector of ranks probability of the tests given the effect size

Details

If one wants to test

$$H_0 : epsilon_i = 0 vs. H_a : \epsilon_i > 0,$$

then et and ey should be mean value of the test and filter effect sizes, respectively. This is called hypothesis testing for the continuous effect sizes.

Value

weight Numeric vector of normalized weight of the tests for the continuous case

Author(s)

Mohamad S. Hasan, shakilmohamad7@gmail.com

See Also

prob_rank_givenEffect weight_binary

Examples

```
# compute the probabilities of the ranks of a test being rank 1 to 100 if the
# targeted test effect is 2 and the overall mean filter effect is 1.
ranks <- 1:100
prob2 <- sapply(ranks, prob_rank_givenEffect, et = 2, ey = 1, nrep = 10000,
                              m0 = 50, m1 = 50)

# plot the prooabbility
plot(ranks, prob2)

# compute weight for the continuous case
weight_cont <- weight_continuous(alpha = .05, et = 1, m = 100, tail = 1,
                                    delInterval = .0001, ranksProb = prob2)

# plot the weight
plot(ranks, weight_cont)
```

Index

dnorm, *4*, *6, 7*, *9*

opw, 2

pnorm, *6, 7*, *9*
prob_rank_givenEffect, *3, 4*, 5, *12*, *14*
prob_rank_givenEffect_approx, 6
prob_rank_givenEffect_exact, 8
prob_rank_givenEffect_simu, 9

qvalue, *4*, *6, 7*, *9, 10*, *12*

rnorm, *6, 7*, *9, 10*
runif, *10*

weight_binary, *4*, 11, *14*
weight_by_delta, 12
weight_continuous, *4*, *12*, 13