Package: RTCA (via r-universe)

November 25, 2026

Type Package

Title Open-source toolkit to analyse data from xCELLigence System (RTCA)

Version 1.66.0

Date 2012-01-11

Author Jitao David Zhang

Maintainer Jitao David Zhang <davidvonpku@gmail.com>

Description Import, analyze and visualize data from Roche(R) xCELLigence RTCA systems. The package imports real-time cell electrical impedance data into R. As an alternative to commercial software shipped along the system, the Bioconductor package RTCA provides several unique transformation (normalization) strategies and various visualization tools.

License LGPL-3

LazyLoad yes

Depends methods,stats,graphics,Biobase,RColorBrewer, gtools

Suggests xtable

Collate AllClasses.R AllGenerics.R AllMethods.R algorithms.R visualization.R RTCAfunctions.R spectramaxImport.R

URL http://code.google.com/p/xcelligence/,http://www.xcelligence.roche.com/,http://www.nextbiomotif.com/Home/scientific-programming

biocViews ImmunoOncology, CellBasedAssays, Infrastructure, Visualization, TimeCourse

Repository Bioconductor 3.24

Date/Publication 2026-11-23 22:29:57 UTC

RemoteUrl https://github.com/bioc/RTCA

RemoteRef RELEASE_3_24

RemoteSha cd1828e771011a93e87ba6529900536d5c90f9ef

Contents

alphaNames . . . 2
combineRTCA . . . 3
controlView . . . 4
derivativeTransform . . . 6
factor2numeric . . . 7
interpolationTransform . . . 8
nearestTimeIndex . . . 9
parseRTCA . . . 10
plateView . . . 12
plotGridEffect . . . 13
ratioTransform . . . 14
rgrTransform . . . 15
RTCA-class . . . 16
RTCAtimeline-class . . . 18
sliceRTCA . . . 19
smoothTransform . . . 20
spectramaxImport . . . 21

Index **23**

`alphaNames` *Auxilliary functions for experiments with microtitre plates*

Description

Functions to manipulate indices or names of microtitre plates

Usage

```
alphaNames(row = 8, column = 12, order=c("column","row"))
repairAlphaName(x)
alphaNames2Pos(x)
rowcol2pos(row = 1, column=1, plateFormat=c("96","384"))
```

Arguments

`row`	integer, row index, 1,. . . ,8 for 96-well plates
`column`	integer, column index, 1,. . . ,12 for 96-well plates
`x`	character, Well alpha name, in the form of [A-Z][0-9][0-9], like 'A01'
`order`	character, should the alpha names returned in a row-first or column-first order?
`plateFormat`	integer, the microtitre format, either 96 or 384

Details

alphaNames returns so-called *alpha well names* in the form of [A-H][0-9][0-9] (i.e., A01, C03, D11, H12) for microtitre plates. The order of returned alphaNames is controlled by the option order, which can be set either as col or row

repairAlphaName attempts to fix incomplete alpha well names. Now it is mainly used to fix well names missing the leading 0 of numeric index, like A1.

alphaName2Pos returns the row and column number of the given alpha well name, in the form of two-column data frame with *row* and *col* as colnames.

rowcol2pos returns the row-wise position index of given row and column index.

Value

See details

Author(s)

Jitao David Zhang <jitao_david.zhang@roche.com>

Examples

```
wells <- alphaNames()

repairAlphaName("A1")

alphaNames2Pos(c("A01","B02","C03","H12"))

rowcol2pos(3,1)
```

---

combineRTCA *Combine a list of RTCA objects*

Description

Combine a list of RTCA objects

Usage

```
combineRTCA(list)
```

Arguments

list	A list of RTCA objects

Details

The current implementation requires all the objects have exactly the same time-points recorded (or at least of same length).

The combined RTCA object has an obligatory column in the phenoData 'Plate' (upper-case!), which matches the names of the RTCA list. When the list has no names, the 'Plate' field is filled with integer index starting from 1.

Value

A new RTCA object

Note

Special attention should be given to the cases where the list parameter partially has names. In this case all items without name will be assigned to a 'Plate' field of empty string (""). Therefore it is advised either to assign names to all items of the list, or leave them all off.

Author(s)

Jitao David Zhang <jitao_david.zhang@roche.com>

Examples

```
## An artificial example
require(RTCA)

ofile <- system.file("/extdata/testOutput.csv", package="RTCA")
x <- parseRTCA(ofile)

xSub1 <- x[,1:3]
xSub2 <- x[,4:ncol(x)]
xComb <- combineRTCA(list(sub1=xSub1, sub2=xSub2))
identical(exprs(x), exprs(xComb))
pData(xComb)$Plate

## in case of nameless list
pData(combineRTCA(list(xSub1, xSub2)))$Plate

## partial names
pData(combineRTCA(list(a=xSub1, xSub2)))$Plate
```

---

controlView *PLOT CONTROL WELLS IN RTCA DATA*

Description

A convenience function to plot sample wells with control wells on an *E-plate* in RTCA system. To use the function the phenoData field of the RTCA object must contain a field named "GeneSymbol".

Usage

```
controlView(rtca, genesymbol = c("Allstar", "COPB2", "GFP", "mock", "PLK1", "WEE1"), cols, ylim, smooth
```

Arguments

rtca	An object of RTCA.To use the function, the phenoData must contain a column which name is specified by the pData.column parameter.
genesymbol	character, gene symbols to be plotted.
cols	character, colors used by the provided gene symbols
ylim	y-axis lim
smooth	logical, whether the RTCA object should be smoothed before plotting
group	logical. If 'group' is set to TRUE, wells with the same *GeneSymbol* will be summarized and plotted. For instance, these could be biological replicates. Otherwise each well is plotted separatedly
ylab	y axis label
xlab	x axis label
drawsd	logical, should the error bar be drawn to represent standard deviation?
normline	logical, should the base-time indicated by a line? See ratioTransform for the concept of the *base-time*
ncol	integer, legend column number
legendpos	character, legend position
pData.column	The column which the genesymbol parameter will be matched with
...	other parameters passed to the plot function

Details

The function is often called to draw sample and control in one plot.

Value

NULL, the function is called for its side effect

Author(s)

Jitao David Zhang <jitao_david.zhang@roche.com>

See Also

RTCA

Examples

```
require(RTCA)

ofile <- system.file("extdata/testOutput.csv", package="RTCA")
pfile <- system.file("extdata/testOutputPhenoData.csv", package="RTCA")

pData <- read.csv(pfile, sep="\t", row.names="Well")
metaData <- data.frame(labelDescription=c(
"Rack number",
"siRNA catalogue number",
"siRNA gene symbol",
"siRNA EntrezGene ID",
"siRNA targeting accession"
))

phData <- new("AnnotatedDataFrame", data=pData, varMetadata=metaData)
x <- parseRTCA(ofile, phenoData=phData)

controlView(x, genesymbol=c("mock","COPB2","PLK1"),ylim=c(0,2))
```

---

derivativeTransform *DERIVATIVE TRANSFORM OF RTCA OBJECT*

Description

Derivative transform of RTCA object, returning the change rate of cell impedance

Usage

```
derivativeTransform(object)
```

Arguments

object	An object of RTCA

Details

The first derivative of the cell impedance curve measured by RTCA. The derivative of the last time point is estimated by that of the next to last point.

Value

An RTCA object populated with derivative values

Author(s)

Jitao David Zhang <jitao_david.zhang@roche.com>

See Also

smoothTransform and interpolationTransform for smoothing and interpolating the RTCA data. rgrTransform calculates relative growth rate, which calls derivativeTransform.

Examples

```
require(RTCA)

ofile <- system.file("/extdata/testOutput.csv", package="RTCA")
x <- parseRTCA(ofile)

xDeriv <- derivativeTransform(x)
```

---

factor2numeric *FACTOR UNITILITIES*

Description

The functions implement easy interface to certain tasks of factor. See datails for explaination

Usage

```
factor2numeric(x)
relevels(x, refs)
```

Arguments

x	A vector of factor
refs	A vector of character, reference vector to give the orderof levels

Details

relevels re-arrange the order of levels by the given character refs. Alternatively user could use factor(...,levels=refs) to achieve a similar effect, however the relevels enables also partial list. The missing levels in refs will be ordered to the last.

factor2numeric converts factor of numerics into their numeric form.

Value

A vector of factor

Author(s)

Jitao David Zhang <jitao_david.zhang@roche.com>

Examples

```
## factor2numeric
numFac <- factor(c(3.5, 2.5, 2.5,3.5, 1))
numFac
levels(numFac)

factor2numeric(numFac)
class(factor2numeric(numFac))

## relevels
relevels(numFac, c("3.5", "1", "2.5"))
relevels(numFac, c("3.5", "2.5"))
```

`interpolationTransform` *TRANSFORM RTCA DATA WITH INTERPOLATION*

Description

Interpolate RTCA data

Usage

```
interpolationTransform(object, interval=0.01, method=c("linear","constant","fmm","periodic","natural
```

Arguments

`object`	An `RTCA` object
`...`	other parameters, `interval` and `method` are implemented, see below
`interval`	numeric, the interval between interpolated points, set to 0.01 by default
`method`	character, specifying the method for interpolation, "linear" by default (for linear interpolation). Allowed options are: "linear" and "constant" for `approx` interpolation, and "fmm", "periodic", "natural" and "monoH.FC" for cubic spline interpolation

Details

Since most RTCA experiements record the experiments in the irregular time-series, sometimes however it is desired to have regular intervals. `interpolationTransform` interpolate between data points to estimate results of regular intervals.

Two classes of interpolations are supported by now: linear (using `approx`) and cubic spline (`spline`) interpolation. By default linear interpolation is used.

Value

An interpolated object of `RTCA`.

Author(s)

Jitao David Zhang <jitao_david.zhang@roche.com>

See Also

rgrTransform stands for *relative growth rate transformation*, ratioTransform for ratio normalization adopted by Roche commercial software. smoothTransform to smooth the RTCA readout.

Examples

```
require(RTCA)

ofile <- system.file("/extdata/testOutput.csv", package="RTCA")
x <- parseRTCA(ofile)

xInter <- interpolationTransform(x)
```

---

nearestTimeIndex *GET INDEX FOR NEAREST TIME*

Description

Get index for the nearest time point to the given one. Called internally in many time-point related functions.

Usage

```
nearestTimeIndex(rtca, time)
```

Arguments

rtca	An object of RTCA
time	numeric, a time point

Details

The function finds the time point with minimum absolute difference to the given time and returns its index.

Value

An integer, the index of the nearest time point

Author(s)

Jitao David Zhang <jitao_david.zhang@roche.com>

See Also

timepoints to return all time points of an RTCA object.

Examples

```
require(RTCA)

ofile <- system.file("/extdata/testOutput.csv", package="RTCA")
x <- parseRTCA(ofile)

x
xIndex <- nearestTimeIndex(x, 25)
timepoints(x)[xIndex]
```

---

parseRTCA *PARSE RTCA OUTPUT FILE*

Description

The function parses RTCA output file into RTCA object

Usage

```
parseRTCA(file, dec = ".", phenoData, maskWell, ...)
```

Arguments

file	character, name of the RTCA output file
dec	decimal sign of the file
phenoData	phenoData
maskWell	character, either names or regular expression pattern(s) for well(s) to mask
...	other parameters passed to read.table

Details

A csv-like format file can be exported from the RTCA device, which can be fed into this function to set up an instance of RTCA object.

In the */extdata/* directory of the package, such a file is provided as an example. The first line contains the experiment ID, which is followed by a matrix of recorded data in the tabular form. The first and second column records the time-interval in the unit of hour and hour-minute-second format respectively. The rest columns then record the read-out ('Cell-Index', or 'CI') of the device, with each well a role.

phenoData allows user to annotate the wells.Its usage mimicks the ExpressionSet object in the Biobase package.

maskWell allows to mask wells in case, for example, they are known to be contaminated. The values can be either a vector of well names, or a regular expression pattern for wells to be masked. To learn regular expression patterns see grep.

Value

An object of RTCA-class

Author(s)

Jitao David Zhang <jitao_david.zhang@roche.com>

References

http://www.roche-applied-science.com/proddata/gpip/3_8_9_1_1_1.html

Examples

```
require(RTCA)

ofile <- system.file("extdata/testOutput.csv", package="RTCA")
pfile <- system.file("extdata/testOutputPhenoData.csv", package="RTCA")

pData <- read.csv(pfile, sep="\t", row.names="Well")
metaData <- data.frame(labelDescription=c(
"Rack number",
"siRNA catalogue number",
"siRNA gene symbol",
"siRNA EntrezGene ID",
"siRNA targeting accession"
))

phData <- new("AnnotatedDataFrame", data=pData, varMetadata=metaData)
x <- parseRTCA(ofile, phenoData=phData)

print(x)

## mask wells, e.g. due to unusual values
x.skip <- parseRTCA(ofile, phenoData=phData, maskWell=c("D09"))
x.skip.multiWells <- parseRTCA(ofile, phenoData=phData, maskWell=c("A01", "B01",
"C02"))
## skip the last row
x.skip.pattern <- parseRTCA(ofile, phenoData=phData,
maskWell=c("H[0-9]{2}"))

## check the number of masked wells
noMasked <- function(x) sum(apply(x, 2, function(x) all(is.na(x))))
noMasked(exprs(x))
noMasked(exprs(x.skip))
noMasked(exprs(x.skip.multiWells))
noMasked(exprs(x.skip.pattern))
```

plateView *PLATE VIEW OF RTCA DATA*

Description

Plots a *E-plate* in RTCA assays in one plot to convey an overview of the plate

Usage

```
plateView(rtca, ylim, titles,...)
```

Arguments

rtca	An object of RTCA
ylim	ylab lim
titles	Titles of sub-figures representing each well. If missing, the function seeks whether a *Well* column is available in the pData of the RTCA object, and if so, its value will be used. If not, the sample names (by sampleNames function) will be used as titles.
...	Other parameters passed to the plot function. Currently options col, lty and lwd are supported. See details below.

Details

For now the function only supports the visualization of a 96-well *E-plate*.

The plate view plot draws lines indicating cell index (or its transformations) in a birdview. When ... are not specified, default color, line style and width are used. col,lty and lwd can be a vector, and if needed they will be expanded to have the same length as wells.

Value

NULL, the function is called for the side effect

Author(s)

Jitao David Zhang <jitao_david.zhang@roche.com>

See Also

RTCA for data structure, plot for the basic plot function.

Examples

```
require(RTCA)

ofile <- system.file("extdata/testOutput.csv", package="RTCA")
rtca <- parseRTCA(ofile)

## Not run automatically, because of 'margin too large'
## plateView(rtca)
## plateView(rtca, lty=2)
## plateView(rtca, col=rep(1:8, each=12))

rtca.skip <- parseRTCA(ofile, maskWell="H[0-9]{2}")
## plateView(rtca.skip)
```

`plotGridEffect` *PLOT GRID EFFECT OF RTCA*

Description

Plot the mean and deviation of rows/columns of a RTCA *E-plate*, to provide hints of potential row/column effect of the plate

Usage

```
plotGridEffect(rtca, mode = c("column", "row"), xlab = "time point",
ylab = "readout", legend = TRUE, col, ...)
```

Arguments

`rtca`	An object of `RTCA`
`mode`	character, either "column" or "row", to choose which effect to depict
`xlab`	x-axis label
`ylab`	y-axis label
`legend`	logical, whether the legend should be added
`col`	Color of the curves
`...`	Further parameters passed to `plot` function

Details

The error bars depicts the standard deviations

Value

`NULL`, the funciton is called for its side effect

Author(s)

Jitao David Zhang

Examples

```
require(RTCA)

ofile <- system.file("extdata/testOutput.csv", package="RTCA")
x <- parseRTCA(ofile)
plotGridEffect(x)
```

`ratioTransform` *RATIO TRANSFORMATION OF RTCA DATA*

Description

Performs ratio transformation (normalisation) of RTCA data, as recommended by the producer Roche.

Usage

```
ratioTransform(object, time)
```

Arguments

`object`	An object of `RTCA`
`time`	numeric, the time point used to normalize the whole series of data

Details

The *xCelligence* software provided by Roche performs ratio transform implicitly by dividing the time-series impedance measurement by the value of a selected time point (so-called 'base-time'), for instance 5 hours after compound transfection, in each cell. The aim of this transformation was to scale (normalize) the data of different wells, since the normalized values of all wells are uniformly 1 at the base-time.

However, this method is vulnerable to arbitrary selection of the time point chosen to normalize. It may be helpful to try several base-time values before comparing normalized results.

See `derivativeTransform` and `rgrTransform` for other normalization (scaling) possibilities.

Value

An object of `RTCA`, populated with normalized value. The normalized values of all wells are uniformly 1 at the base-time.

Author(s)

Jitao David Zhang <jitao_david.zhang@roche.com>

See Also

smoothTransform and interpolationTransform for smoothing and interpolating the RTCA data. rgrTransform calculates relative growth rate, derivativeTransform calculates derivatitve. The later two methods are not sensative to the selection of base-time point.

Examples

```
require(RTCA)

ofile <- system.file("/extdata/testOutput.csv", package="RTCA")
x <- parseRTCA(ofile)

xNorm <- ratioTransform(x, 35)
```

---

rgrTransform *TRANSFORM RTCA DATA INTO RELATIVE GROWTH RATE*

Description

Transform RTCA data into relative growth rate

Usage

```
rgrTransform(object, smooth)
```

Arguments

object	An object of RTCA
smooth	logical, should the object be smooth transformed after the rgrTransform? Set to TRUE by default

Details

TODO: relative growth rate

Value

An object of RTCA populated with relative growth rate instead of input data

Author(s)

Jitao David Zhang <jitao_david.zhang@roche.com>

References

TODO: reference

See Also

derivativeTransform for first derivative. ratioTransform for ratio normalization adopted by Roche commercial software. smoothTransform and interpolationTransform for other transformation possibilities.

Examples

```
require(RTCA)

ofile <- system.file("/extdata/testOutput.csv", package="RTCA")
x <- parseRTCA(ofile)

xRgr <- rgrTransform(x)
```

RTCA-class *Class "RTCA"*

Description

RTCA object

Objects from the Class

Objects can be created by calls of the form `new("RTCA", assayData, phenoData, featureData, experimentData, annotation, exprs, ...)`. However, it is more common to be constructed by parseRTCA function by reading in RTCA output data directly.

Slots

expID: Object of class `"character"`, experiment ID

timeline: Object of class `"RTCAtimeline"`, recording action track along the time line

assayData: Object of class `"AssayData"`, assay data inherited from `ExpressionSet-class`

phenoData: Object of class `"AnnotatedDataFrame"`, pheno data of the assay, annotating the wells

featureData: Object of class `"AnnotatedDataFrame"`, feature data of the assay, preserved for time-line recording by the package

experimentData: Object of class `"MIAME"`, idle

annotation: Object of class `"character"`, idle

.__classVersion__: Object of class `"Versions"`,idle

Extends

Class ExpressionSet-class, directly. Class eSet-class, by class "ExpressionSet", distance 2. Class VersionedBiobase-class, by class "ExpressionSet", distance 3. Class Versioned-class, by class "ExpressionSet", distance 4.

Methods

addAction `signature(object = "RTCA", time = "numeric",action = "character")`: add action at the specified time, passed to the `RTCAtimeline` slot

getAction `signature(object = "RTCA", time = "numeric")`: get action at the specified time, passed to the `RTCAtimeline` slot

plotRTCA `signature(x = "RTCA")`: plot RTCA

rmAction `signature(object = "RTCA", time = "numeric")`: remove action at the specified time, passed to the `RTCAtimeline` slot

show `signature(object = "RTCA")`: print method

expID codesignature(object = "RTCA"): get Experiment ID

expID<- codesignature(object = "RTCA", value = "ANY"): set Experiment ID

time `signature(x = "RTCA")`: deprecated

timeline `signature(object = "RTCA")`: get the `RTCAtimeline` slot

timeline<- `signature(object = "RTCA")`: assign the `RTCAtimeline` slot

timepoints `signature(object = "RTCA")`: get the recording time points in a vector

timepoints<- `signature(object = "RTCA")`: assign the recording time points

updateAction `signature(object = "RTCA", time = "numeric", action = "character")`: update the action at the specified time, passed to the `RTCAtimeline` slot

plot `signature(x = "RTCA", y)`: plot the RTCA running plot with `matplot`. `y` is interpretated as the indices of the columns to be plotted, and will be expanded to all the columns in case it is missing.

Author(s)

Jitao David Zhang <jitao_david.zhang@roche.com>

References

1 https://www.roche-applied-science.com/sis/xcelligence/index.jsp?id=xcect_000000 introduces *xCelligence* system.

2 http://www.roche-applied-science.com/proddata/gpip/3_8_9_1_1_1.html for brief introduction into RTCA

Examples

```
new("RTCA", expID="testExp01")
```

`RTCAtimeline-class` *Class "RTCAtimeline"*

Description

Time line of actions performed by the xCelligence device, supporting CRUD manipulations (create, read, update and delete).

Objects from the Class

Objects can be created by calls of the form `new("RTCAtimeline")`. However, it is more common to be called implicitly by creating an instance of `RTCA` object.

Slots

`actionTrack`**:** Object of class `"data.frame"`, records action track in the form of two-column `data.frame`. The two columns must have the names 'time' and 'action'.

`timeUnit`**:** Object of class `"character"`, recording the unit of time points stored in the `actionTrack` slot.

`startTime`**:** Object of class `"POSIXct"`, the absolute time when the measurement started (at the time point '0')

Methods

addAction `signature(object = "RTCAtimeline", time = "numeric", action = "character")`: add action at the specified time

actionTrack `signature(object = "RTCAtimeline")`: get the action track in the form of `data.frame`

actionTrack<- `signature(object = "RTCAtimeline", value = "data.frame")`: assign the action track

getAction `signature(object = "RTCAtimeline", time = "numeric")`: get action at the specified time

orderAction `signature(object = "RTCAtimeline")`: order the action track by the time

reset `signature(object = "RTCAtimeline")`: undo all editing of the object and reset it to the initial state

rmAction `signature(object = "RTCAtimeline", time = "numeric")`: remove the action at the specified time

timeUnit `signature(object = "RTCAtimeline")`: return the time unit used by the actiont track

timeUnit<- `signature(object = "RTCAtimeline", value = "character")`: assign the time unit used by the actiont track

start `signature(object = "RTCAtimeline")`: return the starting POSIXct time of the experiment

timeUnit<- `signature(object = "RTCAtimeline", value = "character")`: assign the starting POSIXct time of the experiment

Author(s)

Jitao David Zhang <jitao_david.zhang@roche.com>

References

1 http://www.xcelligence.roche.com/ introduces *xCelligence* system.

2 http://www.roche-applied-science.com/proddata/gpip/3_8_9_1_1_1.html for brief introduction into RTCA

See Also

RTCA

Examples

```
tl <- new("RTCAtimeline")
show(tl)
```

---

sliceRTCA *SLICE RTCA OBJECT WITH TIME*

Description

Subset (slice) RTCA object with starting- and ending-time

Usage

```
sliceRTCA(x, start, end)
```

Arguments

x	An object of RTCA
start	numeric, start time
end	numeric, end time

Details

In case the exact starting- or ending-time is not matched, the nearest time point will be used to subset.

Value

An object of RTCA

Author(s)

Jitao David Zhang <jitao_david.zhang@roche.com>

Examples

```
require(RTCA)

ofile <- system.file("/extdata/testOutput.csv", package="RTCA")
x <- parseRTCA(ofile)

subx <- sliceRTCA(x, 20, 50)
```

`smoothTransform` *SMOOTH TRANSFORM OF RTCA OBJECT*

Description

Smoothing the RTCA cell impedance measurement

Usage

```
smoothTransform(object, ...)
```

Arguments

`object`	An object of `RTCA`
`...`	Parameters passed to `smooth.spline`

Details

`smoothTransform` smooths the RTCA cell impedance measurement by calling the function `smooth.spline`. This feature can be useful for visualiation purposes and in conjuction with other transformations.

Value

An `RTCA` object populated with smoothed values

Note

`ratioTransform` performs ratio transformation recommended by the machine provider. `interpolationTransform` for interpolating the RTCA data. `derivativeTransform` returns cell impedance change rates and `rgrTransform` calculates relative growth rate.

Author(s)

Jitao David Zhang <jitao_david.zhang@roche.com>

Examples

```
require(RTCA)

ofile <- system.file("/extdata/testOutput.csv", package="RTCA")
x <- parseRTCA(ofile)

xSmooth <- smoothTransform(x)
```

`spectramaxImport` *Import output files from Spectramax spectrophotometer*

Description

Import output files from Spectramax spectrophotometer (plate reader) into the list format compatible with the cellHTS2 package.

Usage

```
spectramaxImport(file, encoding="latin1")
```

Arguments

`file`	A Spectramax file
`encoding`	File character encoding, by default "latin1"

Details

The function imports output files from Spectramax plate reader, with which single-channel cell-based assays could be performed. Such assay includes WST-1 viability assay, which can be used to validate RTCA assay results.

Value

A list of two items: one data frame (no name) and one character vector (*txt*). The data frame contains following columns:

`well`	Well indices ([A-Z][0-9][0-9] format) on the microtitre plate
`val`	Value of each well

The character vector *txt* contains a copy of the file contents.

Author(s)

Jitao David Zhang <jitao_david.zhang@roche.com>

See Also

cellHTS2 package documentation.

Examples

```
wstFiles <- dir(system.file("extdata", package="RTCA"),
pattern="^WST.*csv$", full.names=TRUE)
spectramaxImport(wstFiles[1])

## NOT RUN
## spectramaxImport also supports multiple files, in which case the
## result is a list of individual lists
spectramaxImport(wstFiles)
## END NOT RUN
```

Index

∗ **IO**
parseRTCA, 10
∗ **classes**
RTCA-class, 16
RTCAtimeline-class, 18
∗ **file**
parseRTCA, 10
∗ **hplot**
controlView, 4
plateView, 12
plotGridEffect, 13
∗ **misc**
factor2numeric, 7
∗ **models**
rgrTransform, 15
∗ **ts**
interpolationTransform, 8

actionTrack *(*RTCAtimeline-class*)*, 18
actionTrack,RTCAtimeline-method *(*RTCAtimeline-class*)*, 18
actionTrack<- *(*RTCAtimeline-class*)*, 18
actionTrack<-,RTCAtimeline,data.frame-method *(*RTCAtimeline-class*)*, 18
addAction *(*RTCAtimeline-class*)*, 18
addAction,RTCA,numeric,character-method *(*RTCA-class*)*, 16
addAction,RTCAtimeline,numeric,character-method *(*RTCAtimeline-class*)*, 18
alphaNames, 2
alphaNames2Pos *(*alphaNames*)*, 2
approx, *8*

combineRTCA, 3
controlView, 4

derivativeTransform, 6, *14*, *16*, *20*
derivativeTransform,RTCA-method *(*RTCA-class*)*, 16

expID *(*RTCA-class*)*, 16
expID,RTCA-method *(*RTCA-class*)*, 16
expID<- *(*RTCA-class*)*, 16
expID<-,RTCA-method *(*RTCA-class*)*, 16

factor2numeric, 7, *7*

getAction *(*RTCAtimeline-class*)*, 18
getAction,RTCA,numeric-method *(*RTCA-class*)*, 16
getAction,RTCAtimeline,numeric-method *(*RTCAtimeline-class*)*, 18
grep, *10*

interpolationTransform, *7*, 8, *15*, *16*, *20*
interpolationTransform,RTCA-method *(*RTCA-class*)*, 16

matplot, *17*

nearestTimeIndex, 9

orderAction *(*RTCAtimeline-class*)*, 18
orderAction,RTCAtimeline-method *(*RTCAtimeline-class*)*, 18

parseRTCA, 10, *16*
plateView, 12
plot, *5*, *12*, *13*
plot,RTCA-method *(*RTCA-class*)*, 16
plotGridEffect, 13
plotRTCA,RTCA-method *(*RTCA-class*)*, 16

ratioTransform, *5*, *9*, 14, *16*, *20*
ratioTransform,RTCA-method *(*RTCA-class*)*, 16
read.table, *10*
relevels, *7*
relevels *(*factor2numeric*)*, 7
repairAlphaName *(*alphaNames*)*, 2
reset *(*RTCAtimeline-class*)*, 18

reset,RTCAtimeline-method
(RTCAtimeline-class), 18
rgrTransform, *7*, *9*, *14*, 15, *15*, *20*
rgrTransform,RTCA-method (RTCA-class),
16
rmAction (RTCAtimeline-class), 18
rmAction,RTCA,numeric-method
(RTCA-class), 16
rmAction,RTCAtimeline,numeric-method
(RTCAtimeline-class), 18
rowcol2pos (alphaNames), 2
RTCA, *5*, *6*, *8–10*, *12–15*, *18–20*
RTCA-class, 16
RTCAtimeline,RTCA-method (RTCA-class),
16
RTCAtimeline-class, 18
RTCAtimeline<-,RTCA-method
(RTCA-class), 16

show,RTCA-method (RTCA-class), 16
sliceRTCA, 19
smooth.spline, *20*
smoothTransform, *7*, *9*, *15*, *16*, 20
smoothTransform,RTCA,ANY-method
(RTCA-class), 16
smoothTransform,RTCA,missing-method
(RTCA-class), 16
spectramaxImport, 21
spline, *8*
startTime (RTCAtimeline-class), 18
startTime,RTCAtimeline-method
(RTCAtimeline-class), 18
startTime<- (RTCAtimeline-class), 18
startTime<-,RTCAtimeline,POSIXct-method
(RTCAtimeline-class), 18

time,RTCA-method (RTCA-class), 16
timeline (RTCA-class), 16
timeline,RTCA-method (RTCA-class), 16
timeline<- (RTCA-class), 16
timeline<-,RTCA-method (RTCA-class), 16
timepoints, *10*
timepoints (RTCA-class), 16
timepoints,RTCA-method (RTCA-class), 16
timepoints<- (RTCA-class), 16
timepoints<-,RTCA-method (RTCA-class),
16
timeUnit (RTCAtimeline-class), 18
timeUnit,RTCAtimeline-method
(RTCAtimeline-class), 18
timeUnit<- (RTCAtimeline-class), 18
timeUnit<-,RTCAtimeline,character-method
(RTCAtimeline-class), 18

updateAction (RTCAtimeline-class), 18
updateAction,RTCA,numeric,character-method
(RTCA-class), 16
updateAction,RTCAtimeline,numeric,character-method
(RTCAtimeline-class), 18