

Package: ReactomePA (via r-universe)

June 2, 2026

Type Package

Title Reactome Pathway Analysis

Version 1.56.0

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Description This package provides functions for pathway analysis based on REACTOME pathway database. It implements enrichment analysis, gene set enrichment analysis and several functions for visualization. This package is not affiliated with the Reactome team.

Depends R (>= 3.4.0)

Imports AnnotationDbi, enrichplot, enrichit, ggplot2 (>= 3.3.5),
ggraph, reactome.db, igraph, graphite, gson, yulab.utils (>= 0.1.5)

Suggests clusterProfiler, knitr, rmarkdown, org.Hs.eg.db, prettydoc,
testthat

VignetteBuilder knitr

ByteCompile true

License GPL-2

URL <https://yulab-smu.top/contribution-knowledge-mining/>

BugReports <https://github.com/GuangchuangYu/ReactomePA/issues>

biocViews Pathways, Visualization, Annotation, MultipleComparison,
GeneSetEnrichment, Reactome

RoxygenNote 7.3.3

Encoding UTF-8

Config/pak/sysreqs libcairo2-dev cmake libfontconfig1-dev libfreetype6-dev libglpk-dev make libicu-dev libpng-dev libuv1-dev libxml2-dev libssl-dev zlib1g-dev

Repository <https://bioc-release.r-universe.dev>

Date/Publication 2026-04-28 12:36:22 UTC

RemoteUrl <https://github.com/bioc/ReactomePA>

RemoteRef RELEASE_3_23

RemoteSha 16d7fcb44c80e1d09e2c33327a40bc8efa78fff9

Contents

DataSet	2
enrichPathway	2
getALLEG	3
getDb	4
gsePathway	5
gson_Reactome	6
viewPathway	6
Index	8

DataSet	<i>Datasets sample contains a sample of gene IDs.</i>
---------	---

Description

Datasets sample contains a sample of gene IDs.

enrichPathway	<i>Pathway Enrichment Analysis of a gene set. Given a vector of genes, this function will return the enriched pathways with FDR control.</i>
---------------	--

Description

Pathway Enrichment Analysis of a gene set. Given a vector of genes, this function will return the enriched pathways with FDR control.

Usage

```
enrichPathway(
  gene,
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  universe = NULL,
  minGSSize = 10,
  maxGSSize = 500,
  qvalueCutoff = 0.2,
  organism = "human",
  readable = FALSE
)
```

Arguments

gene	a vector of entrez gene id.
pvalueCutoff	Cutoff value of pvalue.
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes
minGSSize	minimal size of genes annotated by Ontology term for testing.
maxGSSize	maximal size of each geneSet for analyzing
qvalueCutoff	Cutoff value of qvalue
organism	one of "human", "rat", "mouse", "celegans", "yeast", "zebrafish", "fly".
readable	whether mapping gene ID to gene Name

Value

A `enrichResult` instance.

Author(s)

Guangchuang Yu <http://ygc.name>

See Also

[enrichResult-class](#)

Examples

```
gene <- c("11171", "8243", "112464", "2194",
          "9318", "79026", "1654", "65003",
          "6240", "3476", "6238", "3836",
          "4176", "1017", "249")
yy = enrichPathway(gene, pvalueCutoff=0.05)
head(summary(yy))
#plot(yy)
```

getALLEG

getALLEG

Description

get all entrezgene ID of a specific organism

Usage

```
getALLEG(organism)
```

Arguments

organism species

Value

entrez gene ID vector

Author(s)

Yu Guangchuang

getDb

getDb

Description

mapping organism name to annotationDb package name

Usage

```
getDb(organism)
```

Arguments

organism one of supported organism

Value

annotationDb name

Author(s)

Yu Guangchuang

gsePathway

gsePathway

Description

Gene Set Enrichment Analysis of Reactome Pathway

Usage

```
gsePathway(
  geneList,
  organism = "human",
  exponent = 1,
  minGSSize = 10,
  maxGSSize = 500,
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  verbose = TRUE,
  nPerm = 1000,
  method = "multilevel",
  adaptive = FALSE,
  minPerm = 101,
  maxPerm = 1e+05,
  pvalThreshold = 0.1
)
```

Arguments

geneList	order ranked geneList
organism	organism
exponent	weight of each step
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of each geneSet for analyzing
pvalueCutoff	pvalue Cutoff
pAdjustMethod	pvalue adjustment method
verbose	print message or not
nPerm	The number of permutations for the "permute" method
method	one of "sample", "permute", "multilevel"
adaptive	logical
minPerm	minimal number of permutations for the "multilevel" method
maxPerm	maximal number of permutations for the "multilevel" method
pvalThreshold	The p-value threshold for the "multilevel" method

Value

gseaResult object

Author(s)

Yu Guangchuang

gson_Reactome *gson_Reactome*

Description

download the latest version of Reactome and stored in a 'GSON' object

Usage

```
gson_Reactome(organism = "human")
```

Arguments

organism one of "human", "rat", "mouse", "celegans", "yeast", "zebrafish", "fly".

Value

a 'GSON' object

Examples

```
## Not run:  
rec_gson <- gson_Reactome("human")  
  
## End(Not run)
```

viewPathway *viewPathway*

Description

view reactome pathway

Usage

```
viewPathway(  
  pathName,  
  organism = "human",  
  readable = TRUE,  
  foldChange = NULL,  
  keyType = "ENTREZID",  
  layout = "kk"  
)
```

Arguments

pathName	pathway Name
organism	supported organism
readable	logical
foldChange	fold change
keyType	keyType of gene ID (i.e. names of foldChange, if available)
layout	graph layout

Details

plotting reactome pathway

Value

plot

Author(s)

Yu Guangchuang

Index

* **datasets**

DataSet, [2](#)

* **manip**

enrichPathway, [2](#)

DataSet, [2](#)

enrichPathway, [2](#)

getALLEG, [3](#)

getDb, [4](#)

gsePathway, [5](#)

gson_Reactome, [6](#)

viewPathway, [6](#)