

Package: Rmmquant (via r-universe)

June 18, 2026

Type Package

Title RNA-Seq multi-mapping Reads Quantification Tool

Version 1.30.0

Date 2023-04-05

Description RNA-Seq is currently used routinely, and it provides accurate information on gene transcription. However, the method cannot accurately estimate duplicated genes expression. Several strategies have been previously used, but all of them provide biased results. With Rmmquant, if a read maps at different positions, the tool detects that the corresponding genes are duplicated; it merges the genes and creates a merged gene. The counts of ambiguous reads is then based on the input genes and the merged genes. Rmmquant is a drop-in replacement of the widely used tools findOverlaps and featureCounts that handles multi-mapping reads in an unbiased way.

License GPL-3

Encoding UTF-8

LazyData true

SystemRequirements C++11

Depends R (>= 3.6)

Imports Rcpp (>= 0.12.8), methods, S4Vectors, GenomicRanges, SummarizedExperiment, devtools, TBX20BamSubset, TxDb.Mmusculus.UCSC.mm9.knownGene, org.Mm.db, DESeq2, apeglm, BiocStyle

LinkingTo Rcpp

RoxygenNote 7.0.2

biocViews GeneExpression, Transcription

Suggests knitr, rmarkdown, testthat

VignetteBuilder knitr

Config/pak/sysreqs cmake libfontconfig1-dev libfreetype6-dev libfribidi-dev git make libharfbuzz-dev libbz2-dev libgit2-dev libicu-dev libjpeg-dev liblzma-dev libpng-dev libtiff-dev libuv1-dev libwebp-dev libxml2-dev libssl-dev libx11-dev xz-utils zlib1g-dev

Repository <https://bioc-release.r-universe.dev>

Date/Publication 2026-04-28 12:48:09 UTC

RemoteUrl <https://github.com/bioc/Rmmquant>

RemoteRef RELEASE_3_23

RemoteSha f1e09814d7845a97c1eef8e8006a7ca9468466ec

Contents

| | |
|-------------------------------------|----------|
| counts | 2 |
| Rmmquant | 3 |
| RmmquantClass-class | 3 |
| RmmquantClassExample | 4 |
| RmmquantExample | 4 |
| RmmquantRun | 5 |
| show,RmmquantClass-method | 6 |
| validateRmmquant | 7 |
| Index | 8 |

| | |
|--------|---|
| counts | <i>Get the counts table of an RmmquantClass object.</i> |
|--------|---|

Description

Get the counts table of an RmmquantClass object.

Usage

```
counts(object)
```

```
## S4 method for signature 'RmmquantClass'
counts(object)
```

Arguments

object An RmmquantClass object.

Value

The count matrix, in a SummarizedExperiment

Examples

```
example <- RmmquantClassExample()
counts(example)
```

Rmmquant

Rmmquant: RNA-Seq multi-mapping Reads Quantification Tool

Description

Counts the number of reads per gene.

Author(s)

Matthias Zytnicki, <matthias.zytnicki@inra.fr>

RmmquantClass-class

An S4 class for Rmmquant.

Description

An S4 class for Rmmquant.

Slots

annotationFile The annotation file

readsFiles The reads files

genomicRanges The annotation, in a GenomicRanges format.

genomicRangesList The annotation, in a GenomicRangesList format.

sampleNames The name of the samples

overlap The minimum number of overlapping base pairs to declare a match.

strands Whether annotation of the same strand should be considered.

sorts Whether the files are sorted.

countThreshold The reads files

mergeThreshold The reads files

printGeneName Whether the (vernacular) gene name is reported.

quiet Shut Rmmquant up.

progress Print the progress of the tool.

nThreads The number of threads.

formats The format of the reads files (SAM or BAM).

nOverlapDiff Difference of overlap between a primary map and a secondary map.

pcOverlapDiff Ratio of overlap between a primary map and a secondary map.

counts A SummarizedExperiment storing the counts.

RmmquantClassExample *Example of Rmmquant constructor.*

Description

Example of Rmmquant constructor.

Usage

```
RmmquantClassExample()
```

Value

An RmmquantClass.

Examples

```
example <- RmmquantExample()
```

RmmquantExample *Example of Rmmquant use*

Description

Example of Rmmquant use

Usage

```
RmmquantExample()
```

Value

An SummarizedExperiemnt.

Examples

```
example <- RmmquantExample()
```

RmmquantRun

Main Rmmquant function.

Description

Main Rmmquant function.

Usage

```
RmmquantRun(
  annotationFile = "",
  readsFiles = character(),
  genomicRanges = GRanges(),
  genomicRangesList = GRangesList(),
  sampleNames = character(),
  overlap = NA_integer_,
  strands = character(),
  sorts = logical(),
  countThreshold = NA_integer_,
  mergeThreshold = NA_real_,
  printGeneName = FALSE,
  quiet = TRUE,
  progress = FALSE,
  nThreads = 1,
  formats = character(),
  nOverlapDiff = NA_integer_,
  pcOverlapDiff = NA_real_,
  lazyload = FALSE
)
```

Arguments

| | |
|-------------------|--|
| annotationFile | The annotation file |
| readsFiles | The reads files |
| genomicRanges | The annotation, in a GenomicRanges format. |
| genomicRangesList | The annotation, in a GenomicRangesList format. |
| sampleNames | The name of the samples |
| overlap | The minimum number of overlapping base pairs to declare a match. |
| strands | Whether annotation of the same strand should be considered. |
| sorts | Whether the files are sorted. |
| countThreshold | The reads files |
| mergeThreshold | The reads files |
| printGeneName | Whether the (vernacular) gene name is reported. |

| | |
|---------------|--|
| quiet | Shut Rmmquant up. |
| progress | Print the progress of the tool. |
| nThreads | The number of threads. |
| formats | The format of the reads files (SAM or BAM). |
| nOverlapDiff | Difference of overlap between a primary map and a secondary map. |
| pcOverlapDiff | Ratio of overlap between a primary map and a secondary map. |
| lazyload | Usual for S4 functions. |

Value

A SummerizedExperiment.

Examples

```
dir <- system.file("extdata", package="Rmmquant", mustWork = TRUE)
gtfFile <- file.path(dir, "test.gtf")
samFile <- file.path(dir, "test.sam")
table <- RmmquantRun(gtfFile, samFile)
```

show,RmmquantClass-method

Show the content of an RmmquantClass object.

Description

Show the content of an RmmquantClass object.

Usage

```
## S4 method for signature 'RmmquantClass'
show(object)
```

Arguments

object An RmmquantClass object.

Value

A description of the object.

Examples

```
example <- RmmquantClassExample()
example
```

validateRmmquant *Rmmquant object validation function.*

Description

Rmmquant object validation function.

Usage

```
validateRmmquant(object)
```

Arguments

object A RmmquantClass object.

Value

TRUE, if succeed, otherwise a character.

Index

[counts](#), [2](#)
[counts](#), [RmmquantClass-method \(counts\)](#), [2](#)

[Rmmquant](#), [3](#)
[RmmquantClass-class](#), [3](#)
[RmmquantClassExample](#), [4](#)
[RmmquantExample](#), [4](#)
[RmmquantRun](#), [5](#)

[show](#), [RmmquantClass-method](#), [6](#)

[validateRmmquant](#), [7](#)