Package: TreeSummarizedExperiment (via r-universe)

November 1, 2026

Type Package

Title TreeSummarizedExperiment: a S4 Class for Data with Tree Structures

Version 2.20.0

Date 2025-03-10

Description TreeSummarizedExperiment has extended SingleCellExperiment to include hierarchical information on the rows or columns of the rectangular data.

Depends R(>= 3.6.0), SingleCellExperiment, S4Vectors (>= 0.23.18), Biostrings

License GPL (>=2)

Encoding UTF-8

LazyData true

biocViews DataRepresentation, Infrastructure

Imports methods, BiocGenerics, utils, ape, rlang, dplyr, SummarizedExperiment, BiocParallel, IRanges, treeio

VignetteBuilder knitr

Suggests ggtree, ggplot2, BiocStyle, knitr, rmarkdown, testthat

RoxygenNote 7.1.1

Collate 'TreeSummarizedExperiment.R' 'aboutLoop.R' 'allClass.R' 'aggTSE.R' 'allGenerics.R' 'changeTree.R' 'classAccessor.R' 'classValid.R' 'coercion.R' 'combine.R' 'data.R' 'deprecate_Fun.R' 'internal_utils.R' 'makeTSE.R' 'tree_addLabel.R' 'tree_asLeaf.R' 'tree_asPhylo.R' 'tree_convertNode.R' 'tree_countLeaf.R' 'tree_countNode.R' 'tree_distNode.R' 'tree_findAncestor.R' 'tree_findChild.R' 'tree_findDescendant.R' 'tree_findSibling.R' 'tree_isLeaf.R' 'tree_joinNode.R' 'tree_matTree.R' 'tree_printNode.R' 'tree_shareNode.R' 'tree_showNode.R' 'tree_toTree.R' 'tree_trackNode.R' 'tree_unionLeaf.R' 'updateObject.R'

Config/pak/sysreqs cmake make libicu-dev libuv1-dev zlib1g-dev

Repository Bioconductor 3.23

Date/Publication 2026-04-28 12:50:19 UTC

RemoteUrl https://github.com/bioc/TreeSummarizedExperiment

RemoteRef RELEASE_3_23

RemoteSha b51d2a5c824510fe16fd7d51d9c93b08e6ec58cd

Contents

TreeeSummarizedExperiment-package . . . 3
addLabel . . . 3
aggTSE . . . 4
aggValue . . . 6
asLeaf . . . 8
asPhylo . . . 9
changeTree . . . 10
countLeaf . . . 12
countNode . . . 13
detectLoop . . . 14
distNode . . . 15
findAncestor . . . 16
findChild . . . 17
findOS . . . 18
findSibling . . . 19
isLeaf . . . 20
LinkDataFrame-class . . . 21
LinkDataFrame-constructor . . . 21
makeTSE . . . 22
matTree . . . 23
printNode . . . 24
rbind,TreeSummarizedExperiment-method . . . 25
resolveLoop . . . 26
rowLinks . . . 27
shareNode . . . 32
showNode . . . 33
signalNode . . . 34
tinyTree . . . 35
toTree . . . 36
trackNode . . . 37
transNode . . . 38
TreeSummarizedExperiment-class . . . 39
TreeSummarizedExperiment-constructor . . . 40
unionLeaf . . . 42
updateObject,TreeSummarizedExperiment-method . . . 43

Index **44**

TreeeSummarizedExperiment-package

The TreeSummarizedExperiment *package*

Description

TreeSummarizedExperiment implement a class of the same name, which extends SingleCellExperiment to include hierarchical information on the rows or columns of the rectangular data.

Details

It also includes an additional slot for storing reference sequences per feature.

See Also

TreeSummarizedExperiment class

addLabel *add labels to nodes of a tree*

Description

addLabel label nodes of a tree (phylo object)

Usage

```
addLabel(tree, label = NULL, on = c("all", "leaf", "internal"))
```

Arguments

tree	A phylo object
label	A character vector to provide node labels. The label is passed to nodes that are sorted by their node number in ascending order. The default is NULL, nodes are labeled by adding a prefix Node_ to their node number.
on	Chosen from "all", "leaf", "internal". If "all", all nodes are labeled; if "leaf", leaves are labeled; if "internal", internal nodes are labeled.

Value

a phylo object

Author(s)

Ruizhu Huang

Examples

```
data(tinyTree)
library(ggtree)

# PLOT tree
# The node labels are in orange texts and the node numbers are in blue
ggtree(tinyTree, branch.length = 'none')+
    geom_text2(aes(label = label), color = "darkorange",
           hjust = -0.1, vjust = -0.7) +
    geom_text2(aes(label = node), color = "darkblue",
               hjust = -0.5, vjust = 0.7)

# change labels
nodes <- showNode(tree = tinyTree, only.leaf = FALSE)
tt <- addLabel(tree = tinyTree, label = LETTERS[nodes],
               on = "all")

ggtree(tt, branch.length = 'none')+
    geom_text2(aes(label = label), color = "darkorange",
           hjust = -0.1, vjust = -0.7) +
    geom_text2(aes(label = node), color = "darkblue",
               hjust = -0.5, vjust = 0.7)
```

---

aggTSE *Perform data aggregations based on the available tree structures*

Description

aggTSE aggregates values on the leaf nodes of a tree to a specific arbitrary level of the tree. The level is specified via the nodes of the tree. Users could decide on which dimension (row or column) and how should the aggregation be performed.

Usage

```
aggTSE(
  x,
  rowLevel = NULL,
  rowBlock = NULL,
  colLevel = NULL,
  colBlock = NULL,
  rowFun = sum,
  colFun = sum,
  whichRowTree = 1,
  whichColTree = 1,
  whichAssay = NULL,
  message = FALSE,
  rowDataCols,
```

```
  colDataCols,
  rowFirst = TRUE,
  BPPARAM = NULL
)
```

Arguments

x	A TreeSummarizedExperiment object.
rowLevel	A numeric (node numbers) or character (node labels) vector. It provides the level on the tree that data is aggregated to. The aggregation is on the row dimension. The default is rowLevel = NULL, and no aggregation is performed.
rowBlock	A column name in the rowData to separate the aggregation.
colLevel	A numeric (node numbers) or character (node labels) vector. It provides the level on the tree that data is aggregated to. The aggregation is on the column dimension. The default is colLevel = NULL, and no aggregation is performed.
colBlock	A column name in the colData to separate the aggregation.
rowFun	A function to be applied on the row aggregation. It's similar to the FUN in apply.
colFun	A function to be applied on the col aggregation. It's similar to the FUN in apply.
whichRowTree	A integer scalar or string indicating which row tree is used in the aggregation. The first row tree is used as default.
whichColTree	A integer scalar or string indicating which row tree is used in the aggregation. The first row tree is used as default.
whichAssay	A integer scalar or string indicating which assay of x to use in the aggregation. If NULL, all assay tables are used in aggregation.
message	A logical value. The default is TRUE. If TRUE, it will print out the running process.
rowDataCols	The rowData columns to include.
colDataCols	The colData columns to include.
rowFirst	TRUE or FALSE. If the aggregation is in both dims., it is performed firstly on the row dim for rowFirst = TRUE or on the column dim for rowFirst = FALSE.
BPPARAM	Default is NULL and the computation isn't run in parallel. To run computation parallelly, an optional BiocParallelParam instance determining the parallel back-end to be used during evaluation, or a list of BiocParallelParam instances, to be applied in sequence for nested calls to **BiocParallel** functions.

Value

A TreeSummarizedExperiment object

Author(s)

Ruizhu HUANG

Examples

```
# assays data
set.seed(1)
toyTable <- matrix(rnbinom(20, size = 1, mu = 10), nrow = 5)
colnames(toyTable) <- paste(rep(LETTERS[1:2], each = 2),
                            rep(1:2, 2), sep = "_")
rownames(toyTable) <- paste("entity", seq_len(5), sep = "")

toyTable

# the column data
colInf <- DataFrame(gg = c(1, 2, 3, 3),
                    group = rep(LETTERS[1:2], each = 2),
                    row.names = colnames(toyTable))
colInf

# the toy tree
library(ape)
set.seed(4)
treeC <- rtree(4)
treeC$node.label <- c("All", "GroupA", "GroupB")

library(ggtree)
ggtree(treeC, size = 2) +
   geom_text2(aes(label = node), color = "darkblue",
           hjust = -0.5, vjust = 0.7, size = 6) +
    geom_text2(aes(label = label), color = "darkorange",
               hjust = -0.1, vjust = -0.7, size = 6)


tse <- TreeSummarizedExperiment(assays = list(toyTable),
                                colData = colInf,
                                colTree = treeC,
                                colNodeLab = treeC$tip.label,
                                metadata = list(test = 1:4))

aggCol <- aggTSE(x = tse, colLevel = c("GroupA", "GroupB"),
                 colFun = sum)

assays(aggCol)[[1]]
```

---

aggValue *Perform data aggregations based on the available tree structures*

Description

aggValue aggregates values on the leaf nodes of a tree to a specific arbitrary level of the tree. The level is specified via the nodes of the tree. Users could decide on which dimension (row or column) and how should the aggregation be performed.

Usage

```
aggValue(
  x,
  rowLevel = NULL,
  rowBlock = NULL,
  colLevel = NULL,
  colBlock = NULL,
  FUN = sum,
  assay = NULL,
  message = FALSE
)
```

Arguments

x	A TreeSummarizedExperiment object.
rowLevel	A numeric (node numbers) or character (node labels) vector. It provides the level on the tree that data is aggregated to. The aggregation is on the row dimension. The default is rowLevel = NULL, and no aggregation is performed.
rowBlock	A column name in the rowData to separate the aggregation.
colLevel	A numeric (node numbers) or character (node labels) vector. It provides the level on the tree that data is aggregated to. The aggregation is on the column dimension. The default is colLevel = NULL, and no aggregation is performed.
colBlock	A column name in the colData to separate the aggregation.
FUN	A function to be applied on the aggregation. It's similar to the FUN in apply.
assay	A integer scalar or string indicating which assay of x to use in the aggregation. If NULL, all assay tables are used in aggregation.
message	A logical value. The default is TRUE. If TRUE, it will print out the running process.

Value

A TreeSummarizedExperiment object or a matrix. The output has the same class of the input x.

Author(s)

Ruizhu HUANG

See Also

aggTSE

asLeaf *change internal nodes to leaf nodes*

Description

asLeaf updates a phylo tree by changing the specified internal nodes to leaf nodes. In other words, the descendant nodes of the specified internal nodes are removed.

Usage

```
asLeaf(tree, node)
```

Arguments

tree	A phylo object.
node	A numeric or character vector. It specifies internal nodes that are changed to leaves via their node labels or numbers.

Value

A phylo object.

Examples

```
library(ggtree)
data(tinyTree)
ggtree(tinyTree, ladderize = FALSE) +
    geom_text2(aes(label = label), color = "darkorange",
           hjust = -0.1, vjust = -0.7) +
    geom_text2(aes(label = node), color = "darkblue",
               hjust = -0.5, vjust = 0.7) +
    geom_hilight(node = 16) +
    geom_point2()

# remove the blue branch
NT1 <- asLeaf(tree = tinyTree, node = 16)

ggtree(NT1, ladderize = FALSE) +
    geom_text2(aes(label = label), color = "darkorange",
               hjust = -0.1, vjust = -0.7) +
    geom_point2()

# if mergeSingle = TRUE, the node (Node_17) is removed.
NT2 <- asLeaf(tree = tinyTree, node = c(15, 13))


ggtree(NT2, ladderize = FALSE) +
    geom_text2(aes(label = label), color = "darkorange",
               hjust = -0.1, vjust = -0.7) +
```

```
geom_point2()
```

---

asPhylo *Convert a data frame to a phylo object*

Description

asPhylo converts a data frame to a phylo object. Compared to toTree, asPhylo allows the output tree to have different number of nodes in paths connecting leaves to the root.

Usage

```
asPhylo(data, column_order = NULL, asNA = NULL)
```

Arguments

data	A data frame or matrix.
column_order	A vector that includes the column names of data to reorder columns of data. Default is NULL, the original order of data is kept.
asNA	This specifies strings that are considered as NA

Details

The last column is used as the leaf nodes

Value

a phylo object

Author(s)

Ruizhu Huang

Examples

```
library(ggtree)

# Example 0:
taxTab <- data.frame(R1 = rep("A", 5),
                     R2 = c("B1", rep("B2", 4)),
                     R3 = paste0("C", 1:5))
# Internal nodes: their labels are prefixed with colnames of taxTab
#  e.g., R2:B2
taxTree <- asPhylo(data = taxTab)
ggtree(taxTree) +
 geom_text2(aes(label = label), color = "red", vjust = 1) +
 geom_nodepoint()
```

```
 # (Below gives the same output as toTree)
 taxTab$R1 <- paste0("R1:", taxTab$R1)
 taxTab$R2 <- paste0("R2:", taxTab$R2)
 taxTree <- asPhylo(data = taxTab)
# viz the tree
 ggtree(taxTree) +
 geom_text2(aes(label = label), color = "red", vjust = 1) +
 geom_nodepoint()

# Example 1
df1 <- rbind.data.frame(c("root", "A1", "A2", NA),
                        c("root", "B1", NA, NA))
colnames(df1) <- paste0("L", 1:4)
tree1 <- asPhylo(df1)

ggtree(tree1, color = "grey") +
geom_nodepoint() +
   geom_text2(aes(label = label), angle = 90,
              color = "red", vjust = 2,
              size = 4)

# Example 2
df2 <- data.frame(Group_1 = rep("Root", 11),
                  Group_2 = rep(c(13, 21), c(9, 2)),
                  Group_3 = rep(c(14, 18, "unknown"), c(5, 4, 2)),
                  Group_4 = rep(c(15, "unknown", 19, "unknown"), c(4, 1, 3, 3)),
                  Group_5 = rep(c(16, "unknown", 20, "unknown"), c(3, 2, 2, 4)),
                  Group_6 = rep(c(17, "unknown"), c(2, 9)),
                  LEAF = 1:11)

tree2 <- asPhylo(df2, asNA = "unknown")

ggtree(tree2, color = "grey") +
geom_nodepoint() +
   geom_text2(aes(label = label), angle = 90,
              color = "red", vjust = 2,
              size = 4)

# Example 3
df3 <- df2
df3[10:11, 3] <- ""

tree3 <- asPhylo(df3, asNA = c("unknown", ""))

ggtree(tree3, color = "grey") +
geom_nodepoint() +
   geom_text2(aes(label = label), angle = 90,
              color = "red", vjust = 2,
              size = 4)
```

---

changeTree *Change the row or column tree*

Description

changeTree changes a row or column tree in a TreeSummarizedExperiment object.

Usage

```
changeTree(
  x,
  rowTree = NULL,
  rowNodeLab = NULL,
  colTree = NULL,
  colNodeLab = NULL,
  whichRowTree = 1,
  whichColTree = 1
)
```

Arguments

x	A TreeSummarizedExperiment object
rowTree	A phylo object. A new row tree.
rowNodeLab	A character string. It provides the labels of nodes that the rows of assays tables corresponding to. If NULL (default), the row names of the assays tables are used.
colTree	A phylo object. A new column tree.
colNodeLab	A character string. It provides the labels of nodes that the columns of assays tables corresponding to. If NULL (default), the column names of the assays tables are used.
whichRowTree	Which row tree to be replaced? Default is 1 (the first tree in the rowTree slot).
whichColTree	Which column tree to be replaced? Default is 1 (the first tree in the colTree slot).

Value

A TreeSummarizedExperiment object

Author(s)

Ruizhu Huang

Examples

```
library(ape)
set.seed(1)
treeR <- ape::rtree(10)

# the count table
count <- matrix(rpois(160, 50), nrow = 20)
rownames(count) <- paste0("entity", 1:20)
colnames(count) <- paste("sample", 1:8, sep = "_")
```

```
# The sample information
sampC <- data.frame(condition = rep(c("control", "trt"),
                                    each = 4),
                    gender = sample(x = 1:2, size = 8,
                                    replace = TRUE))
rownames(sampC) <- colnames(count)
# build a TreeSummarizedExperiment object
tse <- TreeSummarizedExperiment(assays = list(count),
                                colData = sampC,
                                rowTree = treeR,
                                rowNodeLab = rep(treeR$tip.label, each =2))

treeR2 <- drop.tip(phy = treeR, tip = c("t10", "t9", "t8"))

# if rownames are not used in node labels of the tree, provide rowNodeLab
use <- changeTree(x = tse, rowTree = treeR2,
                  rowNodeLab = rep(treeR$tip.label, each =2))
use

# if rownames are used in node labels of tree, rowNodeLab is not required.

rownames(tse) <- rep(treeR$tip.label, each =2)
cse <- changeTree(x = tse, rowTree = treeR2)
cse
```

`countLeaf` *count the number of leaf nodes*

Description

`countLeaf` calculates the number of leaves on a `phylo` tree.

Usage

```
countLeaf(tree)
```

Arguments

`tree`	A phylo object

Value

a numeric value

Author(s)

Ruizhu Huang

Examples

```
library(ggtree)

data(tinyTree)

ggtree(tinyTree, branch.length = 'none') +
geom_text2(aes(label = label), hjust = -0.3) +
geom_text2(aes(label = node), vjust = -0.8,
hjust = -0.3, color = 'blue')


(n <- countLeaf(tinyTree))
```

---

countNode *count the number of nodes*

Description

countNode calculates the number of nodes on a phylo tree.

Usage

```
countNode(tree)
```

Arguments

tree	A phylo object

Value

a numeric value

Author(s)

Ruizhu Huang

Examples

```
library(ggtree)

data(tinyTree)

ggtree(tinyTree, branch.length = 'none') +
       geom_text2(aes(label = label), hjust = -0.3) +
       geom_text2(aes(label = node), vjust = -0.8,
       hjust = -0.3, color = 'blue')
```

```
(n <- countNode(tinyTree))
```

`detectLoop` *Detect loops* `detectLoop` *detects loops*

Description

Detect loops `detectLoop` detects loops

Usage

```
detectLoop(tax_tab)
```

Arguments

`tax_tab`	a data frame where columns store hierarchical levels. The columns from the left to the right correspond nodes from the root to the leaf.

Value

a data frame

Author(s)

Ruizhu Huang

Examples

```
df <- data.frame(A = rep("a", 8),
                 B = rep (c("b1", "b2", "b3", "b4"), each = 2),
                 C = paste0("c", c(1, 2, 2, 3:7)),
                 D = paste0("d", 1:8))

# The result means that a loop is caused by 'b1' and 'b2' in column 'B' and
# 'c2' in column 'C' (a-b1-c2; a-b2-c2)
detectLoop(tax_tab = df)

df <- data.frame(R1 = rep("A", 6),
                     R2 = c("B1", rep("B2", 4), "B3"),
                     R3 = c("C1", "C2", "C3", NA, NA, NA),
                     R4 = c("D1", "D2", "D3", NA, NA, NA),
                     R5 = paste0("E", 1:6))
detectLoop(tax_tab = df)

df <- data.frame(R1 = rep("A", 7),
                     R2 = c("B1", rep("B2", 4), "B3", "B3"),
                     R3 = c("C1", "C2", "C3", "", "", "", ""),
                     R4 = c("D1", "D2", "D3", "", "", "", ""),
                     R5 = paste0("E", 1:7))
```

```
detectLoop(tax_tab = df)

df <- data.frame(R1 = rep("A", 7),
                     R2 = c("B1", rep("B2", 4), "B3", "B3"),
                     R3 = c("C1", "C2", "C3", NA, NA, NA, NA),
                     R4 = c("D1", "D2", "D3", NA, NA, NA, NA),
                     R5 = paste0("E", 1:7))
detectLoop(tax_tab = df)
```

---

distNode *Calculate the distance between any two nodes on the tree*

Description

distNode is to calculate the distance between any two nodes on a phylo tree

Usage

```
distNode(tree, node)
```

Arguments

tree	A phylo object.
node	A numeric or character vector of length two.

Value

A numeric value.

Examples

```
library(ggtree)
data(tinyTree)
ggtree(tinyTree) +
    geom_text2(aes(label = node), color = "darkorange",
           hjust = -0.1, vjust = -0.7) +
    geom_text2(aes(label = branch.length), color = "darkblue",
               vjust = 0.7)


distNode(tree = tinyTree, node = c(10, 11))
distNode(tree = tinyTree, node = c(12, 13))
distNode(tree = tinyTree, node = c(13, 15))
distNode(tree = tinyTree, node = c(12, 14))
```

findAncestor *Find the ancestors of specified nodes*

Description

findAncestor finds the ancestor in the nth generation above specified nodes.

Usage

```
findAncestor(tree, node, level, use.alias = FALSE)
```

Arguments

tree	A phylo object
node	A vector of node numbers or node labels
level	A vector of numbers to define nth generation before the specified nodes
use.alias	A logical value, TRUE or FALSE. The default is FALSE, and the node label would be used to name the output; otherwise, the alias of node label would be used to name the output. The alias of node label is created by adding a prefix "alias_" to the node number.

Value

A vector of nodes. The numeric value is the node number, and the vector name is the corresponding node label. If a node has no label, it would have NA as name when use.alias = FALSE, and have the alias of node label as name when use.alias = TRUE.

Author(s)

Ruizhu Huang

Examples

```
library(ggtree)
data(tinyTree)
ggtree(tinyTree, branch.length = 'none') +
 geom_text2(aes(label = label), color = "darkorange",
           hjust = -0.1, vjust = -0.7) +
 geom_text2(aes(label = node), color = "darkblue",
               hjust = -0.5, vjust = 0.7)

 findAncestor(tree = tinyTree, node = c(18, 13), level = 1)
```

findChild *Find the children*

Description

findChild finds children of an internal node.

Usage

```
findChild(tree, node = 11, use.alias = FALSE)
```

Arguments

tree	A phylo object.
node	An internal node. It could be the node number or the node label.
use.alias	A logical value, TRUE or FALSE. The default is FALSE, and the node label would be used to name the output; otherwise, the alias of node label would be used to name the output. The alias of node label is created by adding a prefix "alias_" to the node number.

Value

A vector of nodes. The numeric value is the node number, and the vector name is the corresponding node label. If a node has no label, it would have NA as name when use.alias = FALSE, and have the alias of node label as name when use.alias = TRUE.

Author(s)

Ruizhu Huang

Examples

```
data(tinyTree)

library(ggtree)
ggtree(tinyTree) +
geom_text2(aes(label = node), color = "darkblue",
               hjust = -0.5, vjust = 0.7) +
geom_hilight(node = 17, fill = 'steelblue', alpha = 0.5) +
geom_text2(aes(label = label), color = "darkorange",
           hjust = -0.1, vjust = -0.7)

(tips <- findChild(tree = tinyTree, node = 17))
```

findOS *Find descendants (or offsprings)*

Description

findDescendant finds descendants of a node.

Usage

```
findOS(tree, node, only.leaf = TRUE, self.include = FALSE, use.alias = FALSE)

findDescendant(
  tree,
  node,
  only.leaf = TRUE,
  self.include = FALSE,
  use.alias = FALSE
)
```

Arguments

tree	A phylo object.
node	An internal node. It could be the node number or the node label.
only.leaf	A logical value, TRUE or FALSE. The default is TRUE. If default, only the leaf nodes in the descendant nodes would be returned.
self.include	A logical value, TRUE or FALSE. The default is FALSE. If TRUE, the node specified in **node** is included and the leaf node itself is returned as its descendant.
use.alias	A logical value, TRUE or FALSE. The default is FALSE, and the node label would be used to name the output; otherwise, the alias of node label would be used to name the output. The alias of node label is created by adding a prefix "alias_" to the node number.

Value

A vector of nodes. The numeric value is the node number, and the vector name is the corresponding node label. If a node has no label, it would have NA as name when use.alias = FALSE, and have the alias of node label as name when use.alias = TRUE.

Author(s)

Ruizhu Huang

Examples

```
data(tinyTree)

library(ggtree)
ggtree(tinyTree) +
geom_text2(aes(label = node), color = "darkblue",
               hjust = -0.5, vjust = 0.7) +
geom_hilight(node = 17, fill = 'steelblue', alpha = 0.5) +
geom_text2(aes(label = label), color = "darkorange",
           hjust = -0.1, vjust = -0.7)

(tips <- findDescendant(tree = tinyTree, node = c(17), only.leaf = TRUE))
```

`findSibling` *find the sibling node*

Description

`findSibling` is to find the sibling node of an `node` node.

Usage

```
findSibling(tree, node, use.alias = FALSE)
```

Arguments

`tree`	A phylo object.
`node`	A numeric or character vector. Node labels or node numbers.
`use.alias`	A logical value, TRUE or FALSE. The default is FALSE, and the original node label would be used to name the output; otherwise, the alias of node label would be used to name the output. The alias of node label is created by adding a prefix `"alias_"` to the node number.

Value

A vector of nodes. The numeric value is the node number, and the vector name is the corresponding node label. If a node has no label, it would have NA as name when `use.alias = FALSE`, and have the alias of node label as name when `use.alias = TRUE`.

Examples

```
library(ggtree)
data(tinyTree)
ggtree(tinyTree, branch.length = 'none') +
    geom_text2(aes(label = label), color = "darkorange",
           hjust = -0.1, vjust = -0.7) +
    geom_text2(aes(label = node), color = "darkblue",
               hjust = -0.5, vjust = 0.7)
```

```
findSibling(tree = tinyTree, node = 17)
findSibling(tree = tinyTree, node = c(13, 17))
```

`isLeaf` *To test whether the specified nodes are leaf nodes*

Description

`isLeaf` is to test wheter some specified nodes are leaf nodes of a tree.

Usage

```
isLeaf(tree, node)
```

Arguments

`tree`	A phylo object.
`node`	A numeric or character vector. Node labels or node numbers.

Value

a logical vector with the same length as the input `node`.

Author(s)

Ruizhu HUANG

Examples

```
data(tinyTree)
library(ggtree)

# PLOT tree
# The node labels are in orange texts and the node numbers are in blue
ggtree(tinyTree,branch.length = 'none')+
    geom_text2(aes(label = label), color = "darkorange",
           hjust = -0.1, vjust = -0.7) +
    geom_text2(aes(label = node), color = "darkblue",
               hjust = -0.5, vjust = 0.7)

isLeaf(tree = tinyTree, node = c(5, 4, 18))
isLeaf(tree = tinyTree, node = c("t4", "t9", "Node_18" ))
```

`LinkDataFrame-class` *LinkDataFrame: A S4 class extended from DataFrame An S4 class LinkDataFrame*

Description

The **LinkDataFrame** is extended from the class **DataFrame** to include at least four columns `nodeLab`, `nodeLab_alias`, `nodeNum`, and `isLeaf`.

Constructor

See `LinkDataFrame-constructor` for constructor functions.

`LinkDataFrame-constructor` *Construct a LinkDataFrame Construct a LinkDataFrame object*

Description

Construct a LinkDataFrame Construct a LinkDataFrame object

Usage

```
LinkDataFrame(nodeLab, nodeLab_alias, nodeNum, isLeaf, whichTree, ...)
```

Arguments

`nodeLab`	A character vector
`nodeLab_alias`	A character vector
`nodeNum`	A numeric vector
`isLeaf`	A logical vector
`whichTree`	A character vector
`...`	All arguments accepted by `DataFrame-class`.

Value

A LinkDataFrame object

See Also

`LinkDataFrame` `DataFrame`

Examples

```
(ld <- LinkDataFrame(nodeLab = letters[1:5],
                     nodeLab_alias = LETTERS[1:5],
                     nodeNum = 1:5,
                     isLeaf = TRUE,
                     whichTree = LETTERS[1:5],
                     right = 1:5))
```

---

makeTSE *A toy TreeSummarizedExperiment object*

Description

makeTSE creates a toy TreeSummarizedExperiment object.

Usage

```
makeTSE(nrow = 10, ncol = 4, include.rowTree = TRUE, include.colTree = TRUE)
```

Arguments

nrow	a numeric value to specify the number of rows of TreeSummarizedExperiment
ncol	a numeric value to specify the number of columns of TreeSummarizedExperiment
include.rowTree	TRUE or FALSE. Default is TRUE, so the output TreeSummarizedExperiment has a phylo object in rowTree.
include.colTree	TRUE or FALSE. Default is TRUE, so the output TreeSummarizedExperiment has a phylo object in colTree.

Details

The assays contains a matrix with values from 1:(nrow*ncol). The rowData has two columns, var1 and var2. var1 is created with rep_len(letters, nrow). var2 is created with rep_len(c(TRUE, FALSE), nrow). The colData has two columns, ID and group. ID is created with seq_len(ncol). group is created with rep_len(LETTERS[1:2], ncol). The row/col tree is generated with ape::rtree(). So, to generate reproducible trees, set.seed() is required.

Value

A TreeSummarizedExperiment object

Author(s)

Ruizhu Huang

Examples

```
set.seed(1)
makeTSE()
```

`matTree` *Transform a phylo object into a matrix.*

Description

`matTree` transforms a phylo tree into a matrix. The entry of the matrix is node number. Each row represents a path connecting a leaf node and the root. The columns are arranged in the order as the path passing the nodes to reach the root.

Usage

```
matTree(tree)
```

Arguments

`tree`	A phylo object

Value

A matrix

Author(s)

Ruizhu Huang

Examples

```
library(ggtree)

data(tinyTree)
ggtree(tinyTree, branch.length = 'none') +
 geom_text2(aes(label = node))


# each row of the matrix representing a path.
# the first column is leaf nodes; the last non-NA value in a row is the root
mat <- matTree(tree = tinyTree)
```

printNode *To print out the node labels*

Description

nodeLabel is to print out the node labels of a phylo tree.

Usage

```
printNode(tree, type = c("leaf", "internal", "all"))
```

Arguments

tree	A phylo object.
type	A character value choose from leaf, all, and internal. If leaf, the output is a data frame including only leaf nodes; if internal, the output is a data frame including only internal nodes; if all, the output is a data frame including all nodes.

Value

a data frame

Author(s)

Ruizhu HUANG

Examples

```
data(tinyTree)
library(ggtree)

# PLOT tree
# The node labels are in orange texts and the node numbers are in blue
ggtree(tinyTree,branch.length = 'none')+
    geom_text2(aes(label = label), color = "darkorange",
           hjust = -0.1, vjust = -0.7) +
    geom_text2(aes(label = node), color = "darkblue",
               hjust = -0.5, vjust = 0.7)

(pn1 <- printNode(tinyTree, type = "leaf"))
(pn2 <- printNode(tinyTree, type = "internal"))
(pn3 <- printNode(tinyTree, type = "all"))
```

rbind,TreeSummarizedExperiment-method
Combine TSEs by rows or columns

Description

rbind and cbind take one or more TreeSummarizedExperiment objects and combine them by columns or rows, respectively.

Usage

```
## S4 method for signature 'TreeSummarizedExperiment'
rbind(..., deparse.level = 1)

## S4 method for signature 'TreeSummarizedExperiment'
cbind(..., deparse.level = 1)
```

Arguments

...	One or more TreeSummarizedExperiment objects.
deparse.level	See cbind

Value

A TreeSummarizedExperiment object

Author(s)

Ruizhu Huang

Examples

```
# rbind works :
# a) TSE without rowTree and without colTree
# b) TSE with rowTree but without colTree
# c) TSE without rowTree but with colTree
# d) TSE with rowTree & colTree

set.seed(1)
# a)
(tse_a <- makeTSE(include.colTree = FALSE))
(tse_b <- makeTSE(include.colTree = FALSE))

# b)
(tse_c <- makeTSE(include.rowTree = FALSE))
(tse_d <- makeTSE(include.rowTree = FALSE))

rbind(tse_a, tse_b)
cbind(tse_c, tse_d)
```

`resolveLoop` *Resolve loops* `resolveLoop` *resolve loops by adding suffix to the child node. The suffix is "_i" where 'i' is a number. Please see examples.*

Description

Resolve loops `resolveLoop` resolve loops by adding suffix to the child node. The suffix is "_i" where 'i' is a number. Please see examples.

Usage

```
resolveLoop(tax_tab)
```

Arguments

`tax_tab`	a data frame where columns store hierarchical levels. The columns from the left to the right correspond nodes from the root to the leaf.

Value

a data frame

Author(s)

Ruizhu Huang

Examples

```
# example 1
df <- data.frame(A = rep("a", 8),
                 B = rep (c("b1", "b2", "b3", "b4"), each = 2),
                 C = paste0("c", c(1, 2, 2, 3:7)),
                 D = paste0("d", 1:8))

# The result means that a loop is caused by 'b1' and 'b2' in column 'B' and
# 'c2' in column 'C' (a-b1-c2; a-b2-c2)
resolveLoop(tax_tab = df)

# example 2
taxTab <- data.frame(R1 = rep("A", 5),
                     R2 = c("B1", rep("B2", 3), ""),
                     R3 = c("C1", "C2", "C3", "", ""),
                     R4 = c("D1", "D2", "D3", "", ""),
                     R5 = paste0("E", 1:5))

resolveLoop(tax_tab = taxTab)
# example 3
taxTab <- data.frame(R1 = rep("A", 6),
                     R2 = c("B1", rep("B2", 4), ""),
```

```
                      R3 = c("C1", "C2", "C3", "", "", ""),
                      R4 = c("D1", "D2", "D3", "", "", ""),
                      R5 = paste0("E", 1:6))

resolveLoop(tax_tab = taxTab)

 # example 3
taxTab <- data.frame(
            R1 = rep("A", 5),
            R2 = c("B1", rep("B2", 3), "B3"),
            R3 = c("C1", "C2", "C3", NA, NA),
            R4 = c("D1", "D2", "D3", NA, NA),
            R5 = paste0("E", 1:5))
resolveLoop(tax_tab = taxTab)
```

---

rowLinks *TreeSummarizedExperiment-accessors*

Description

All accessor functions that work on SingleCellExperiment should work on **TreeSummarized-Experiment**. Additionally, new accessors rowLinks colLinks, rowTree and colTree accessor function are available for **TreeSummarizedExperiment**.

Usage

```
rowLinks(x)

## S4 method for signature 'TreeSummarizedExperiment'
rowLinks(x)

colLinks(x)

## S4 method for signature 'TreeSummarizedExperiment'
colLinks(x)

rowTree(x, whichTree = 1, value)

## S4 method for signature 'TreeSummarizedExperiment'
rowTree(x, whichTree = 1, value)

rowTree(x, whichTree = 1) <- value

## S4 replacement method for signature 'TreeSummarizedExperiment'
rowTree(x, whichTree = 1) <- value
```

```
colTree(x, whichTree = 1)

## S4 method for signature 'TreeSummarizedExperiment'
colTree(x, whichTree = 1)

colTree(x, whichTree = 1) <- value

## S4 replacement method for signature 'TreeSummarizedExperiment'
colTree(x, whichTree = 1) <- value

rowTreeNames(x, value)

## S4 method for signature 'TreeSummarizedExperiment'
rowTreeNames(x, value)

rowTreeNames(x) <- value

## S4 replacement method for signature 'TreeSummarizedExperiment'
rowTreeNames(x) <- value

colTreeNames(x, value)

## S4 method for signature 'TreeSummarizedExperiment'
colTreeNames(x, value)

colTreeNames(x) <- value

## S4 replacement method for signature 'TreeSummarizedExperiment'
colTreeNames(x) <- value

referenceSeq(x)

## S4 method for signature 'TreeSummarizedExperiment'
referenceSeq(x)

referenceSeq(x) <- value

## S4 replacement method for signature 'TreeSummarizedExperiment'
referenceSeq(x) <- value

## S4 method for signature 'TreeSummarizedExperiment,ANY,ANY,ANY'
x[i, j, ..., drop = TRUE]

## S4 replacement method for signature
## 'TreeSummarizedExperiment,ANY,ANY,TreeSummarizedExperiment'
x[i, j, ...] <- value

## S4 replacement method for signature 'TreeSummarizedExperiment'
```

```
rownames(x) <- value

## S4 replacement method for signature 'TreeSummarizedExperiment'
colnames(x) <- value

subsetByLeaf(
  x,
  rowLeaf,
  colLeaf,
  whichRowTree,
  whichColTree,
  updateTree = TRUE
)

## S4 method for signature 'TreeSummarizedExperiment'
subsetByLeaf(
  x,
  rowLeaf,
  colLeaf,
  whichRowTree,
  whichColTree,
  updateTree = TRUE
)

subsetByNode(x, rowNode, colNode, whichRowTree, whichColTree)

## S4 method for signature 'TreeSummarizedExperiment'
subsetByNode(x, rowNode, colNode, whichRowTree, whichColTree)
```

Arguments

x	A TreeSummarizedExperiment object
whichTree	A numeric indicator or name character to specify which tree in the rowTree or colTree to be extracted. The default is to extract the first tree. If whichTree = NULL, a list of all trees is extracted.
value	• the new rownames or colnames as a character value. See BiocGenerics. • A DNAStringSet object or an object coercible to one
i, j	The row, column index to subset x. The arguments of the subset function []
...	The argument from the subset function []
drop	A logical value, TRUE or FALSE. The argument from the subset function []
rowLeaf	A vector of leaves that are used to subset rows. One could use the leaf number, or the leaf label to specify nodes, but not a mixture of them.
colLeaf	A vector of leaves that are used to subset columns. One could use the leaf number, or the leaf label to specify nodes, but not a mixture of them.
whichRowTree	A numeric indicator or name character to specify which tree in the rowTree.
whichColTree	A numeric indicator or name character to specify which tree in the colTree.

updateTree	TRUE or FALSE. Default is TRUE, which updates tree structures after subsetting.
rowNode	A vector of nodes that are used to subset rows. One could use the node number, the node label or the node alias to specify nodes, but not a mixture of them.
colNode	A vector of nodes that are used to subset columns. One could use the node number, the node label or the node alias to specify nodes, but not a mixture of them.

Value

Elements from TreeSummarizedExperiment.

Author(s)

Ruizhu HUANG

See Also

TreeSummarizedExperiment SingleCellExperiment

Examples

```
# the assay table
set.seed(1)
y <- matrix(rnbinom(300,size=1,mu=10),nrow=10)
colnames(y) <- paste(rep(LETTERS[1:3], each = 10), rep(1:10,3), sep = "_")
rownames(y) <- tinyTree$tip.label

# the row data
rowInf <- DataFrame(var1 = sample(letters[1:3], 10, replace = TRUE),
                    var2 = sample(c(TRUE, FALSE), 10, replace = TRUE))
# the column data
colInf <- DataFrame(gg = factor(sample(1:3, 30, replace = TRUE)),
                    group = rep(LETTERS[1:3], each = 10))

# the tree structure on the rows of assay tables
data("tinyTree")

# the tree structure on the columns of assay tables
sampTree <- ape::rtree(30)
sampTree$tip.label <- colnames(y)

# create the TreeSummarizedExperiment object
toy_tse <- TreeSummarizedExperiment(assays = list(y),
                                    rowData = rowInf,
                                    colData = colInf,
                                    rowTree = tinyTree,
                                    colTree = sampTree)

## extract the rowData
(rowD <- rowData(x = toy_tse))
```

```
## extract the colData
(colD <- colData(x = toy_tse))

## extract the linkData
# on rows
(rowL <- rowLinks(x = toy_tse))
# on columns
(colL <- colLinks(x = toy_tse))

 ## extract the treeData
# on rows
(rowT <- rowTree(x = toy_tse))
# on columns
(colT <- colTree(x = toy_tse))

# the referenceSeq data
refSeq <- DNAStringSetList(one = DNAStringSet(rep("A",nrow(toy_tse))),
                           two = DNAStringSet(rep("B",nrow(toy_tse))))
referenceSeq(toy_tse) <- refSeq
toy_tse

# subset treeSE by leaves
library(ape)
set.seed(1)
z <- makeTSE(nrow = 5, ncol = 4, include.rowTree = TRUE, include.colTree = FALSE)
y <- makeTSE(nrow = 4, ncol = 4, include.rowTree = TRUE, include.colTree = FALSE)
tr <- ape::rtree(4)
zy <- rbind(z, y)
x <- changeTree(x = zy, rowTree = tr, whichRowTree = 2, rowNodeLab = tr$tip.label)
rowLinks(zy)
rowLinks(x)
## 1) rowLeaf exist only in one of trees
rf <- c("t1", "t3")
sx <- subsetByLeaf(x = x, rowLeaf = rf)
rowLinks(sx)

sx <- subsetByLeaf(x = x, rowLeaf = rf, updateTree = FALSE)
rowLinks(sx)

## 2) rowLeaf exist in all trees
rf <- 1:3
sxx <- subsetByLeaf(x = x, rowLeaf = rf)
rowLinks(sxx)



## 3) rowLeaf exist in all trees, but subset and update only the specified
trees
rf <- c(3:4)
sxx <- subsetByLeaf(x = x, rowLeaf = rf, whichRowTree = "phylo")
rowLinks(sxx)
```

shareNode *Find the share node*

Description

shareNode is to find the node where the specified nodes first meet.

Usage

```
shareNode(tree, node, use.alias = FALSE)
```

Arguments

tree	A phylo object.
node	A vector of node numbers or node labels.
use.alias	A logical value, TRUE or FALSE. The default is FALSE, and the node label would be used to name the output; otherwise, the alias of node label would be used to name the output. The alias of node label is created by adding a prefix "alias_" to the node number.

Value

A vector of nodes. The numeric value is the node number, and the vector name is the corresponding node label. If a node has no label, it would have NA as name when use.alias = FALSE, and have the alias of node label as name when use.alias = TRUE.

Author(s)

Ruizhu Huang

Examples

```
library(ggtree)
data(tinyTree)

# PLOT tree
ggtree(tinyTree, branch.length = 'none') +
    geom_text2(aes(label = label), color = "darkorange",
           hjust = -0.1, vjust = -0.7) +
    geom_text2(aes(label = node), color = "darkblue",
               hjust = -0.5, vjust = 0.7)


## find the node shared by provided node labels
shareNode(node = c('t4','t9'), tree = tinyTree,
          use.alias = FALSE)

shareNode(node = c('t10','Node_17'), tree = tinyTree,
```

```
          use.alias = FALSE)

## find the node shared by provided node numbers
shareNode(node = c(2, 3), tree = tinyTree)
```

---

showNode *Find nodes on the tree*

Description

showNode is to get nodes from the tree.

Usage

```
showNode(tree, only.leaf = FALSE, use.alias = FALSE)
```

Arguments

tree	A phylo object.
only.leaf	A logical value, TRUE or FALSE. The default is FALSE, all nodes are output; otherwise, leaves are output
use.alias	A logical value, TRUE or FALSE. The default is FALSE, and the node label would be used to name the output; otherwise, the alias of node label would be used to name the output. The alias of node label is created by adding a prefix "alias_" to the node number.

Value

A vector of nodes. The numeric value is the node number, and the vector name is the corresponding node label. If a node has no label, it would have NA as name when use.alias = FALSE, and have the alias of node label as name when use.alias = TRUE.

Author(s)

Ruizhu Huang

Examples

```
library(ggtree)
data(tinyTree)

# PLOT tree
ggtree(tinyTree, branch.length = 'none') +
    geom_text2(aes(label = label), color = "darkorange",
           hjust = -0.1, vjust = -0.7) +
    geom_text2(aes(label = node), color = "darkblue",
               hjust = -0.5, vjust = 0.7)
```

```
## find the node shared by provided node labels
showNode(tree = tinyTree, only.leaf = TRUE,
          use.alias = FALSE)

showNode(tree = tinyTree, only.leaf = FALSE,
          use.alias = FALSE)
```

---

signalNode *Join nodes*

Description

joinNode is to use as few as possible nodes to represent the provided nodes so that descendant leaves covered by the input nodes and output nodes are exactly the same.

Usage

```
signalNode(tree, node, use.alias = FALSE)

joinNode(tree, node, use.alias = FALSE)
```

Arguments

tree	A tree (phylo object)
node	A vector of node numbers or node labels
use.alias	A logical value, TRUE or FALSE. The default is FALSE, and the node label would be used to name the output; otherwise, the alias of node label would be used to name the output. The alias of node label is created by adding a prefix "alias_" to the node number.

Value

A vector of nodes. The numeric value is the node number, and the vector name is the corresponding node label. If a node has no label, it would have NA as name when use.alias = FALSE, and have the alias of node label as name when use.alias = TRUE.

Author(s)

Ruizhu Huang

Examples

```
data(tinyTree)
library(ggtree)

# PLOT tree
# The node labels are in orange texts and the node numbers are in blue
```

```
ggtree(tinyTree,branch.length = 'none')+
    geom_text2(aes(label = label), color = "darkorange",
           hjust = -0.1, vjust = -0.7) +
    geom_text2(aes(label = node), color = "darkblue",
               hjust = -0.5, vjust = 0.7)

## find the node shared by provided node labels
joinNode(node = c('t4','t9'), tree = tinyTree)
joinNode(node = c('t4','t9'), tree = tinyTree)
joinNode(node = c('t10','Node_18', 't8'),
         tree = tinyTree,
         use.alias = FALSE)
joinNode(node = c('t10','Node_18', 't8'),
         tree = tinyTree,
         use.alias = TRUE)

## find the node shared by provided node numbers
joinNode(node = c(2, 3), tree = tinyTree)
joinNode(node = c(2, 3, 16), tree = tinyTree)
```

`tinyTree` *A simulated phylogenetic tree with 10 tips and 9 internal nodes*

Description

A random phylo object created using the function `rtree`

Usage

```
tinyTree
```

Format

A phylo object with 10 tips and 9 internal nodes:

Tip labels t1, t2, ..., t10.

Node labels Node_11, Node_12, ..., Node_19

toTree *Translate a data frame to a phylo object*

Description

toTree translates a data frame to a phylo object

Usage

```
toTree(data, column_order = NULL)
```

Arguments

data	A data frame or matrix.
column_order	A vector that includes the column names of data to reorder columns of data. Default is NULL, the original order of data is kept.

Details

The last column is used as the leaf nodes

Value

a phylo object

Author(s)

Ruizhu HUANG

Examples

```
library(ggtree)
# Example 1:
taxTab <- data.frame(R1 = rep("A", 5),
                     R2 = c("B1", rep("B2", 4)),
                     R3 = paste0("C", 1:5))
# Internal nodes: their labels are prefixed with colnames of taxTab
#  e.g., R2:B2
tree <- toTree(data = taxTab)
# viz the tree
 ggtree(tree) +
 geom_text2(aes(label = label), color = "red", vjust = 1) +
 geom_nodepoint()

# Example 2: duplicated rows in the 3rd and 4th rows
taxTab <- data.frame(R1 = rep("A", 5),
                     R2 = c("B1", rep("B2", 4)),
                     R3 = c("C1", "C2", "C3", "C3", "C4"))
# duplicated rows are removed with warnings
```

```
tree <- toTree(data = taxTab)

# Example 3: NA values in R2 column
# results: the internal node with the label 'R2:'
taxTab <- data.frame(R1 = rep("A", 5),
                     R2 = c("B1", rep("B2", 2), NA, "B2"),
                     R3 = c("C1", "C2", "C3", NA, "C4"))
tree <- toTree(data = taxTab)
# viz the tree
 ggtree(tree) +
 geom_text2(aes(label = label), color = "red", vjust = 1) +
 geom_nodepoint()

# Example 4: duplicated values in the leaf column (R4)
# Not allowed and give errors
# taxTab <- data.frame(R1 = rep("A", 5),
#                      R2 = c("B1", rep("B2", 3), "B3"),
#                      R3 = c("C1", "C2", "C3", "C3",NA),
#                      R4 = c("D1", "D2", "D3", NA, NA))

# Example 5: loops caused by missing values in B2-C4, B3-C4
taxTab <- data.frame(R1 = rep("A", 6),
                     R2 = c("B1", rep("B2", 4), "B3"),
                     R3 = c("C1", "C2", "C3", "C3", "C4", "C4"),
                     R4 = c("D1", "D2", "D3", "D3", "D4" , "D4"),
                     R5 = paste0("E", 1:6))
 # resolove loops before run to Tree
 # Suffix are adding to C4
 taxNew <- resolveLoop(taxTab)
 tree <- toTree(data = taxNew)

 # viz the tree
 ggtree(tree) +
 geom_text2(aes(label = label), color = "red", vjust = 1) +
 geom_nodepoint()
```

---

trackNode *track the nodes of a phylo tree*

Description

trackNode track nodes of a phylo tree by adding the alias labels to them

Usage

```
trackNode(tree)
```

Arguments

tree	A phylo object

Value

a phylo object

Author(s)

Ruizhu Huang

Examples

```
library(ggtree)

data(tinyTree)

ggtree(tinyTree, branch.length = 'none') +
    geom_text2(aes(label = label), hjust = -0.3) +
    geom_text2(aes(label = node), vjust = -0.8,
               hjust = -0.3, color = 'blue')

#check whether the node number and node label are matched
trackTree <- trackNode(tinyTree)
ggtree(trackTree, branch.length = 'none') +
    geom_text2(aes(label = label), hjust = -0.3) +
    geom_text2(aes(label = node), vjust = -0.8,
               hjust = -0.3, color = 'blue')
```

---

transNode *Transfer between node number and node label*

Description

convertNode does the transformation between the number and the label of a node on a tree

Usage

```
transNode(tree, node, use.alias = FALSE, message = FALSE)

convertNode(tree, node, use.alias = FALSE, message = FALSE)
```

Arguments

tree	A phylo object
node	A character or numeric vector representing tree node label(s) or tree node number(s)
use.alias	A logical value, TRUE or FALSE. This is an optional argument that only requried when the input node is a numeric vector. The default is FALSE, and the node label would be returned; otherwise, the alias of node label would be output. The alias of node label is created by adding a prefix "alias_" to the node number.

message A logical value, TRUE or FALSE. The default is FALSE. If TRUE, message will show when a tree have duplicated labels for some internal nodes.

Value

a vector

Author(s)

Ruizhu Huang

Examples

```
library(ggtree)

data(tinyTree)

ggtree(tinyTree, branch.length = 'none') +
geom_text2(aes(label = label), hjust = -0.3) +
geom_text2(aes(label = node), vjust = -0.8,
hjust = -0.3, color = 'blue')

#check whether the node number and node label are matched
convertNode(tinyTree, node = c(11, 2, 4, 15))

convertNode(tree = tinyTree, node = c("Node_16", "Node_11"))
convertNode(tree = tinyTree, node = c("alias_16", "alias_11"))
```

TreeSummarizedExperiment-class

An S4 class TreeSummarizedExperiment

Description

The class **TreeSummarizedExperiment** is an extension class of standard SingleCellExperiment class. It has four more slots that are not in SingleCellExperiment class: rowTree, rowLinks colTree and colLinks. The hierarchical information of rows (columns) is stored in rowTree (colTree) and the link between the rows (columns) of assays tables and nodes of the tree is given in rowLinks (colLinks).

Details

The class **TreeSummarizedExperiment** is designed to store rectangular data for entities (e.g., microbes or cell types) (assays), information about the hiearchical structure (rowTree on rows; colTree on columns), and the mapping information between the tree nodes and the rows or the columns of the rectangular data. Users could provide the hiearchical structure of the rows, columns or both) of the assays tables, and the link data will be automatically generated in rowLinks, colData or both, respectively. It's required that the object in rowLinks or colLinks has the LinkDataFrame class. Please see the page LinkDataFrame for more details.

Slots

`rowTree` A phylo object or NULL. It gives information about the hiearchical structure of rows of `assays` tables.

`colTree` A phylo object or NULL. It gives information about the hiearchical structure of columns of `assays` tables.

`rowLinks` A LinkDataFrame. It gives information about the link between the nodes of the `rowTree` and the rows of `assays` tables.

`colLinks` A LinkDataFrame. It gives information about the link between the nodes of the `colTree` and the columns of `assays` tables.

`referenceSeq` A `DNAStringSet`/`DNAStringSetList` object or some object coercible to a `DNAStringSet`/`DNAStringSetLis` object. See `DNAStringSet` for more details.

`...` Other slots from `SingleCellExperiment`

Constructor

See `TreeSummarizedExperiment-constructor` for constructor functions.

Accessor

See `TreeSummarizedExperiment-accessor` for accessor functions.

See Also

`TreeSummarizedExperiment` `TreeSummarizedExperiment-accessor` `SingleCellExperiment`

`TreeSummarizedExperiment-constructor`

Construct a TreeSummarizedExperiment object

Description

`TreeSummarizedExperiment` constructs a TreeSummarizedExperiment object.

Usage

```
TreeSummarizedExperiment(
  ...,
  rowTree = NULL,
  colTree = NULL,
  rowNodeLab = NULL,
  colNodeLab = NULL,
  referenceSeq = NULL
)
```

Arguments

...	Arguments passed to the SummarizedExperiment constructor to fill the slots of the base class.
rowTree	A phylo object that provides hiearchical information of rows of assay tables.
colTree	A phylo object that provides hiearchical information of columns of assay tables.
rowNodeLab	A character string. It provides the labels of nodes that the rows of assays tables corresponding to. If NULL (default), the row names of the assays tables are used.
colNodeLab	A character string. It provides the labels of nodes that the columns of assays tables corresponding to. If NULL (default), the column names of the assays tables are used.
referenceSeq	A DNAStringSet/DNAStringSetList object or some object coercible to a DNAStringSet/DNAStringSetL object. See DNAStringSet for more details.

Details

The output TreeSummarizedExperiment object has very similar structure as the SingleCellExperiment. The differences are summarized be as below.

- **rowTree** A slot exists in TreeSummarizedExperiment but not in SingleCellExperiment. It stores the tree structure(s) that provide(s) hierarchical information of assays rows or columns or both.
- **rowData** If a phylo object is available in the slot treeData to provide the hiearchical information about the rows of the assays table, the rowData would be a LinkDataFrame-class instead of DataFrame. The data on the right side of the vertical line provides the link information between the assays rows and the tree phylo object, and could be accessed via linkData; The data on the left side is the original rowData like SingleCellExperiment object.
- **colData** Similar to the explanaition for **rowData** as above.

More details about the LinkDataFrame in the rowData or colData.

- nodeLab The labels of nodes on the tree.
- nodeLab_alias The alias of node labels on the tree.
- nodeNum The numbers of nodes on the tree.
- isLeaf It indicates whether the node is a leaf node or internal node.

Value

a TreeSummarizedExperiment object

Author(s)

Ruizhu HUANG

See Also

TreeSummarizedExperiment TreeSummarizedExperiment-accessor SingleCellExperiment

Examples

```
data("tinyTree")

# the count table
count <- matrix(rpois(100, 50), nrow = 10)
rownames(count) <- c(tinyTree$tip.label)
colnames(count) <- paste("C_", 1:10, sep = "_")

# The sample information
sampC <- data.frame(condition = rep(c("control", "trt"), each = 5),
                    gender = sample(x = 1:2, size = 10, replace = TRUE))
rownames(sampC) <- colnames(count)

# build a TreeSummarizedExperiment object
tse <- TreeSummarizedExperiment(assays = list(count),
                                colData = sampC,
                                rowTree = tinyTree)
```

`unionLeaf` *list leaf nodes that are the descendants of at least one specified node*

Description

`unionLeaf` list the leaf nodes that are the desendants of (at least one) specified nodes.

Usage

```
unionLeaf(tree, node)
```

Arguments

`tree`	A phylo object.
`node`	A numeric or character vector. It specifies internal nodes that are changed to leaves via their node labels or numbers.

Value

A phylo object.

Examples

```
library(ggtree)
data(tinyTree)
ggtree(tinyTree, ladderize = FALSE) +
    geom_text2(aes(label = label), color = "darkorange",
           hjust = -0.1, vjust = -0.7) +
    geom_text2(aes(label = node), color = "darkblue",
               hjust = -0.5, vjust = 0.7) +
```

```
    geom_hilight(node = 18) +
    geom_point2()

u1 <- unionLeaf(tree = tinyTree, node = c(19, 17))
u2 <- unionLeaf(tree = tinyTree, node = c(19, 17, 7))
(u3 <- unionLeaf(tree = tinyTree, node = c(11, 17, 7)))
```

`updateObject,TreeSummarizedExperiment-method`
Update a `TreeSummarizedExperiment` *object*

Description

Update `TreeSummarizedExperiment` objects to the latest version of the class structure. This is usually called by methods in the `TreeSummarizedExperiment` package rather than by users or downstream packages.

Usage

```
## S4 method for signature 'TreeSummarizedExperiment'
updateObject(object, ..., verbose = FALSE)
```

Arguments

`object`	A `TreeSummarizedExperiment` object
`...`	additional arguments, for use in specific `updateObject` methods.
`verbose`	`TRUE` or `FALSE`, indicating whether information about the update should be reported.

Value

An updated `TreeSummarizedExperiment` object

Index

∗ **datasets**
    tinyTree, 35
[,TreeSummarizedExperiment,ANY,ANY,ANY-method
        *(*rowLinks*)*, 27
[<-,TreeSummarizedExperiment,ANY,ANY,TreeSummarizedExperiment-method
        *(*rowLinks*)*, 27

addLabel, 3
aggTSE, 4, *7*
aggValue, 6
apply, *5*, *7*
asLeaf, 8
asPhylo, 9

BiocGenerics, *29*
BiocParallelParam, *5*

cbind, *25*
cbind,TreeSummarizedExperiment-method
        *(*rbind,TreeSummarizedExperiment-method*)*, 25
changeTree, 10
colLinks *(*rowLinks*)*, 27
colLinks,TreeSummarizedExperiment-method
        *(*rowLinks*)*, 27
colnames<-,TreeSummarizedExperiment-method
        *(*rowLinks*)*, 27
colTree *(*rowLinks*)*, 27
colTree,TreeSummarizedExperiment-method
        *(*rowLinks*)*, 27
colTree<- *(*rowLinks*)*, 27
colTree<-,TreeSummarizedExperiment-method
        *(*rowLinks*)*, 27
colTreeNames *(*rowLinks*)*, 27
colTreeNames,TreeSummarizedExperiment-method
        *(*rowLinks*)*, 27
colTreeNames<- *(*rowLinks*)*, 27
colTreeNames<-,TreeSummarizedExperiment-method
        *(*rowLinks*)*, 27
convertNode *(*transNode*)*, 38
countLeaf, 12
countNode, 13

DataFrame, *21*, *41*
detectLoop, 14
distNode, 15
DNAStringSet, *29*, *40*, *41*

findAncestor, 16
findChild, 17
findDescendant *(*findOS*)*, 18
findOS, 18
findSibling, 19

isLeaf, 20

joinNode *(*signalNode*)*, 34

LinkDataFrame, *21*, *39*
LinkDataFrame
        *(*LinkDataFrame-constructor*)*, 21
LinkDataFrame-class, 21
LinkDataFrame-constructor, 21

makeTSE, 22
matTree, 23

printNode, 24

rbind,TreeSummarizedExperiment-method, 25
referenceSeq *(*rowLinks*)*, 27
referenceSeq,TreeSummarizedExperiment-method
        *(*rowLinks*)*, 27
referenceSeq<- *(*rowLinks*)*, 27
referenceSeq<-,TreeSummarizedExperiment-method
        *(*rowLinks*)*, 27
resolveLoop, 26
rowLinks, 27
rowLinks,TreeSummarizedExperiment-method
        *(*rowLinks*)*, 27

rownames<-,TreeSummarizedExperiment-method
(rowLinks), 27
rowTree (rowLinks), 27
rowTree,TreeSummarizedExperiment-method
(rowLinks), 27
rowTree<- (rowLinks), 27
rowTree<-,TreeSummarizedExperiment-method
(rowLinks), 27
rowTreeNames (rowLinks), 27
rowTreeNames,TreeSummarizedExperiment-method
(rowLinks), 27
rowTreeNames<- (rowLinks), 27
rowTreeNames<-,TreeSummarizedExperiment-method
(rowLinks), 27
rtree, *35*

shareNode, 32
showNode, 33
signalNode, 34
SingleCellExperiment, *27*, *30*, *39–41*
subsetByLeaf (rowLinks), 27
subsetByLeaf,TreeSummarizedExperiment-method
(rowLinks), 27
subsetByNode (rowLinks), 27
subsetByNode,TreeSummarizedExperiment-method
(rowLinks), 27
SummarizedExperiment, *41*

tinyTree, 35
toTree, 36
trackNode, 37
transNode, 38
TreeeSummarizedExperiment-package, 3
TreeSummarizedExperiment, *3*, *5*, *30*, *40, 41*
TreeSummarizedExperiment
(TreeSummarizedExperiment-constructor),
40
TreeSummarizedExperiment-accessor
(rowLinks), 27
TreeSummarizedExperiment-class, 39
TreeSummarizedExperiment-combine
(rbind,TreeSummarizedExperiment-method),
25
TreeSummarizedExperiment-constructor,
40

unionLeaf, 42
updateObject,TreeSummarizedExperiment-method,
43