

Package: VAExprs (via r-universe)

May 30, 2026

Type Package

Title Generating Samples of Gene Expression Data with Variational Autoencoders

Description A fundamental problem in biomedical research is the low number of observations, mostly due to a lack of available biosamples, prohibitive costs, or ethical reasons. By augmenting a few real observations with artificially generated samples, their analysis could lead to more robust and higher reproducible. One possible solution to the problem is the use of generative models, which are statistical models of data that attempt to capture the entire probability distribution from the observations. Using the variational autoencoder (VAE), a well-known deep generative model, this package is aimed to generate samples with gene expression data, especially for single-cell RNA-seq data. Furthermore, the VAE can use conditioning to produce specific cell types or subpopulations. The conditional VAE (CVAE) allows us to create targeted samples rather than completely random ones.

Version 1.18.0

Date 2022-05-16

LazyData TRUE

Depends keras, mclust

Imports SingleCellExperiment, SummarizedExperiment, tensorflow, scater, CatEncoders, DeepPINCS, purrr, DiagrammeR, stats

Suggests SC3, knitr, testthat, reticulate, rmarkdown

License Artistic-2.0

biocViews Software, GeneExpression, SingleCell

NeedsCompilation no

VignetteBuilder knitr

Config/pak/sysreqs libcairo2-dev cmake libfontconfig1-dev libfreetype6-dev libfribidi-dev libglpk-dev make libharfbuzz-dev default-jdk libicu-dev libjpeg-dev libpng-dev libtiff-dev libuv1-dev libwebp-dev libxml2-dev libssl-dev python3 libx11-dev zlib1g-dev

Repository <https://bioc-release.r-universe.dev>

Date/Publication 2026-04-28 12:56:36 UTC

RemoteUrl <https://github.com/bioc/VAExprs>

RemoteRef RELEASE_3_23

RemoteSha 225150fc2060966171795cd9b6c742c7b94723a3

Contents

fit_vae	2
gen_exprs	5
plot_aug	7
plot_vae	9

Index	12
--------------	-----------

fit_vae	<i>Variational autoencoder model fitting</i>
---------	--

Description

A fundamental problem in biomedical research is the low number of observations available. Augmenting a few real observations with generated in silico samples could lead to more robust analysis. Here, the variational autoencoder (VAE) is used for the realistic generation of single-cell RNA-seq data. Also, the conditional variational autoencoder (CVAE) can be used if labels of samples are available. This function allows us to fit variational autoencoders with the standard Gaussian prior to expression data. It is assumed that there will likely be no clusters in the latent space representation of variational autoencoders.

Usage

```
fit_vae(object = NULL,
        x_train = NULL,
        x_val = NULL,
        y_train = NULL,
        y_val = NULL,
        encoder_layers,
        decoder_layers,
        latent_dim = 2,
        regularization = 1,
        epochs,
        batch_size,
        preprocessing = list(
          x_train = NULL,
          x_val = NULL,
          y_train = NULL,
          y_val = NULL,
```

```

        minmax = NULL,
        lenc = NULL),
    use_generator = FALSE,
    optimizer = "adam",
    validation_split = 0, ...)

```

Arguments

<code>object</code>	SummarizedExperiment object
<code>x_train</code>	expression data for train, where each row is a cell and each column is a gene
<code>x_val</code>	expression data for validation, where each row is a cell and each column is a gene
<code>y_train</code>	labels for train
<code>y_val</code>	labels for validation
<code>encoder_layers</code>	list of layers for encoder
<code>decoder_layers</code>	list of layers for decoder
<code>latent_dim</code>	dimension of latent vector (default: 2)
<code>regularization</code>	regularization parameter, which is nonnegative (default: 1)
<code>epochs</code>	number of epochs
<code>batch_size</code>	batch size
<code>preprocessing</code>	list of preprocessed results, they are set to NULL as default <ul style="list-style-type: none"> • <code>x_train</code> : expression data for train • <code>x_val</code> : expression data for validation • <code>y_train</code> : labels for train • <code>y_val</code> : labels for validation • <code>minmax</code> : result of min-max normalization • <code>lenc</code> : encoded labels
<code>use_generator</code>	use data generator if TRUE (default: FALSE)
<code>optimizer</code>	name of optimizer (default: adam)
<code>validation_split</code>	proportion of validation data, it is ignored when there is a validation set (default: 0)
<code>...</code>	additional parameters for the "fit" or "fit_generator"

Value

<code>model</code>	trained VAE model
<code>encoder</code>	trained encoder model
<code>decoder</code>	trained decoder model
<code>preprocessing</code>	preprocessed results

Author(s)

Dongmin Jung


```

        layer_dense(units = original_dim,
                    activation = "sigmoid")),
epochs = epochs, batch_size = batch_size,
validation_split = 0.5,
use_generator = FALSE,
callbacks = keras::callback_early_stopping(
  monitor = "val_loss",
  patience = 10,
  restore_best_weights = TRUE))

### from preprocessing
vae_result_preprocessing <- fit_vae(preprocessing = vae_result$preprocessing,
  encoder_layers = list(layer_input(shape = c(original_dim)),
    layer_dense(units = intermediate_dim,
      activation = "relu")),
  decoder_layers = list(layer_dense(units = intermediate_dim,
    activation = "relu"),
    layer_dense(units = original_dim,
      activation = "sigmoid")),
  epochs = epochs, batch_size = batch_size,
  validation_split = 0.5,
  use_generator = FALSE,
  callbacks = keras::callback_early_stopping(
    monitor = "val_loss",
    patience = 10,
    restore_best_weights = TRUE))
}

```

gen_exprs

Generate samples with expression data

Description

This function generate expression data by drawing samples from the latent vectors following the standard multivariate Gaussian distribution (the standard multivariate normal distribution) for convenience. However, this assumption for the prior may not be appropriate because there may be underlying distinctions between groups of samples. Any density function can be modeled by the Gaussian mixture model. Here, by using the library "mclust", the finite Gaussian mixture is applied for such sampling. Note that the Gaussian mixture model is not used for fitting in the function "fit_vae".

Usage

```

gen_exprs(x, num_samples,
  batch_size, use_generator = FALSE)

```

Arguments

x	result of the function "fit_vae"
num_samples	number of samples to be generated
batch_size	batch size
use_generator	use data generator if TRUE (default: FALSE)

Value

x_gen	generated expression data, where each row is a cell and each column is a gene
y_gen	generated labels
x_train	real expression data, where each row is a cell and each column is a gene
y_train	real labels
latent_vector	latent vector from real expression data

Author(s)

Dongmin Jung

See Also

mclust::mclustBIC, mclust::mclustModel, mclust::sim, DeepPINCS::multiple_sampling_generator, CatEncoders::inverse.transform

Examples

```
if (keras::is_keras_available() & reticulate::py_available()) {
  ### simulate differentially expressed genes
  set.seed(1)
  g <- 3
  n <- 100
  m <- 1000
  mu <- 5
  sigma <- 5
  mat <- matrix(rnorm(n*m*g, mu, sigma), m, n*g)
  rownames(mat) <- paste0("gene", seq_len(m))
  colnames(mat) <- paste0("cell", seq_len(n*g))
  group <- factor(sapply(seq_len(g), function(x) {
    rep(paste0("group", x), n)
  })))
  names(group) <- colnames(mat)
  mu_upreg <- 6
  sigma_upreg <- 10
  deg <- 100
  for (i in seq_len(g)) {
    mat[(deg*(i-1) + 1):(deg*i), group == paste0("group", i)] <-
      mat[1:deg, group==paste0("group", i)] + rnorm(deg, mu_upreg, sigma_upreg)
  }
  # positive expression only
  mat[mat < 0] <- 0
}
```

```

x_train <- as.matrix(t(mat))

### model
batch_size <- 32
original_dim <- 1000
intermediate_dim <- 512
epochs <- 2
# VAE
vae_result <- fit_vae(x_train = x_train,
                     encoder_layers = list(layer_input(shape = c(original_dim)),
                                           layer_dense(units = intermediate_dim,
                                                         activation = "relu")),
                     decoder_layers = list(layer_dense(units = intermediate_dim,
                                                         activation = "relu"),
                                           layer_dense(units = original_dim,
                                                         activation = "sigmoid")),
                     epochs = epochs, batch_size = batch_size,
                     validation_split = 0.5,
                     use_generator = FALSE,
                     callbacks = keras::callback_early_stopping(
                       monitor = "val_loss",
                       patience = 10,
                       restore_best_weights = TRUE))

# plot
plot_vae(vae_result$model)

### generate samples
set.seed(1)
gen_sample_result <- gen_exprs(vae_result, num_samples = 100)
}

```

plot_aug

Visualization for augmented data

Description

For augmented data, we can create plots for specific types of dimension reduction.

Usage

```
plot_aug(x, plot_fun, ...)
```

Arguments

x	result of the function "gen_exprs"
plot_fun	"PCA", "MDS", "TSNE", "UMAP", "NMF", or "DiffusionMap"
...	additional parameters for the reduced dimension plots such as "scater::runPCA"


```

decoder_layers = list(layer_dense(units = intermediate_dim,
                                activation = "relu"),
                      layer_dense(units = original_dim,
                                activation = "sigmoid")),
epochs = epochs, batch_size = batch_size,
validation_split = 0.5,
use_generator = FALSE,
callbacks = keras::callback_early_stopping(
  monitor = "val_loss",
  patience = 10,
  restore_best_weights = TRUE))

# plot
plot_vae(vae_result$model)

### generate samples
set.seed(1)
gen_sample_result <- gen_exprs(vae_result, num_samples = 100)
# plot
plot_aug(gen_sample_result, "PCA")
}

```

plot_vae

Visualization for the variational autoencoder

Description

You can create a plot of the VAE model. This plot can help you check that the model is connected the way you intended. The node colors indicate the components of the VAE.

Usage

```

plot_vae(x, node_color = list(encoder_col = "tomato",
                              mean_vector_col = "orange",
                              stddev_vector_col = "lavender",
                              latent_vector_col = "lightblue",
                              decoder_col = "palegreen",
                              condition_col = "gray"))

```

Arguments

x	VAE model
node_color	node colors for encoder(default: tomato), mean vector(default: orange), standard deviation vector(default: lavender), latent_vector(default: lightblue), decoder(default: palegreen), and condition(default: gray)

Value

plot for the model architecture

Author(s)

Dongmin Jung

See Also

purrr::map, purrr::map_chr, purrr::pluck, purrr::imap_dfr, DiagrammeR::grViz

Examples

```

if (keras::is_keras_available() & reticulate::py_available()) {
  ### simulate differentially expressed genes
  set.seed(1)
  g <- 3
  n <- 100
  m <- 1000
  mu <- 5
  sigma <- 5
  mat <- matrix(rnorm(n*m*g, mu, sigma), m, n*g)
  rownames(mat) <- paste0("gene", seq_len(m))
  colnames(mat) <- paste0("cell", seq_len(n*g))
  group <- factor(sapply(seq_len(g), function(x) {
    rep(paste0("group", x), n)
  })))
  names(group) <- colnames(mat)
  mu_upreg <- 6
  sigma_upreg <- 10
  deg <- 100
  for (i in seq_len(g)) {
    mat[(deg*(i-1) + 1):(deg*i), group == paste0("group", i)] <-
      mat[1:deg, group==paste0("group", i)] + rnorm(deg, mu_upreg, sigma_upreg)
  }
  # positive expression only
  mat[mat < 0] <- 0
  x_train <- as.matrix(t(mat))

  ### model
  batch_size <- 32
  original_dim <- 1000
  intermediate_dim <- 512
  epochs <- 2
  # VAE
  vae_result <- fit_vae(x_train = x_train,
                       encoder_layers = list(layer_input(shape = c(original_dim)),
                                             layer_dense(units = intermediate_dim,
                                                         activation = "relu")),
                       decoder_layers = list(layer_dense(units = intermediate_dim,
                                                         activation = "relu"),
                                             layer_dense(units = original_dim,
                                                         activation = "sigmoid")),
                       epochs = epochs, batch_size = batch_size,
                       validation_split = 0.5,

```

```
        use_generator = FALSE,  
        callbacks = keras::callback_early_stopping(  
            monitor = "val_loss",  
            patience = 10,  
            restore_best_weights = TRUE))  
    # plot  
    plot_vae(vae_result$model)  
}
```

Index

`fit_vae`, 2

`gen_exprs`, 5

`plot_aug`, 7

`plot_vae`, 9