

Package: anansi (via r-universe)

June 12, 2026

Type Package

Title Annotation-Based Analysis of Specific Interactions

Version 1.2.0

Description Studies including both microbiome and metabolomics data are becoming more common. Often, it would be helpful to integrate both datasets in order to see if they corroborate each others patterns. All vs all association is imprecise and likely to yield spurious associations. This package takes a knowledge-based approach to constrain association search space, only considering metabolite-function pairs that have been recorded in a pathway database. This package also provides a framework to assess differential association.

Depends R (>= 4.5.0)

Imports S7, stats, methods, igraph, Matrix, forcats, S4Vectors, SummarizedExperiment, MultiAssayExperiment, SingleCellExperiment, TreeSummarizedExperiment, rlang, ggplot2, ggforce, patchwork, ggraph, tidygraph

Suggests BiocStyle, dplyr, tidyr, graph, mia, KEGGREST, testthat (>= 3.0.0), knitr, rmarkdown

License GPL-3

Encoding UTF-8

LazyData false

RoxygenNote 7.3.3

Config/testthat/edition 3

biocViews Microbiome, Metabolomics, Regression, Pathways, KEGG

URL <https://github.com/thomazbastiaanssen/anansi>,
<https://thomazbastiaanssen.github.io/anansi>

BugReports <https://github.com/thomazbastiaanssen/anansi/issues>

VignetteBuilder knitr

Roxygen list(markdown = TRUE)

Config/pak/sysreqs cmake libfontconfig1-dev libfreetype6-dev libglpk-dev make libicu-dev libuv1-dev libxml2-dev zlib1g-dev

Repository <https://bioc-release.r-universe.dev>

Date/Publication 2026-04-28 13:05:41 UTC

RemoteUrl <https://github.com/bioc/anansi>

RemoteRef RELEASE_3_23

RemoteSha 732d604b97020d038ccb53fe52aa3fa1c13934f5

Contents

anansi-coercion	3
AnansiTale	4
AnansiWeb	5
AnansiWeb-methods	7
AnansiWeb-pairwise	8
dictionary	9
ec2ko	9
FMT_KOs	10
FMT_metab	11
FMT_metadata	12
getEdgeList	12
getFeaturePairs	13
getGraph	13
krebs	14
linkBiobakeryMap	14
metadata	15
metadata<-	16
MultiFactor	16
MultiFactor-methods	18
pairwiseApply	19
plotAnansi	20
randomAnansi	22
tableX	23
tableY	24
weaveWeb	24
weaveWeb-methods	25

Index

28

anansi-coercion *Coercion functions for anansi*

Description

Coercion functions for anansi

Usage

```
## S3 method for class '`anansi::AnansiWeb`'  
as.list(x, ...)  
  
## S3 method for class '`anansi::MultiFactor`'  
as.list(x, ..., use.names = TRUE)  
  
## S3 method for class '`anansi::AnansiWeb`'  
as.data.frame(x, row.names, optional, ...)  
  
asMAE(x)  
  
asTSE(x)
```

Arguments

x	input object
...	additional arguments (currently not used).
use.names	Logical scalar, whether output list should contain character (Default) or integer data frame. If FALSE, returns unfactor(x).
row.names, optional	Not used. See ?base::data.frame

Value

An object of the desired class.

See Also

[unfactor\(\)](#)

Examples

```
# AnansiWeb  
x <- randomWeb(  
  n_samples = 5,  
  n_features_x = 4,  
  n_features_y = 6  
)
```

```

as.list(x)
as.data.frame(x)

# AnansiWeb to MultiAssayExperiment
asMAE(x)
asTSE(x)

# MultiFactor
x <- randomMultiFactor(n_types = 3, n_features = 3)
as.list(x, use.names = TRUE)

```

AnansiTale

AnansiTale S7 container class. Not intended for general use.

Description

AnansiTale is the main container that will hold your stats output data coming out of the anansi pipeline.

Usage

```

AnansiTale(
  subject = character(0),
  type = character(0),
  df = integer(0),
  estimates = integer(0),
  f.values = integer(0),
  t.values = integer(0),
  p.values = integer(0)
)

```

Arguments

subject	A character that describes the data that was queried.
type	A character that describes type of parameter contained in the estimates slot. For example r.values for correlations or r.squared for models.
df	a vector of length 2, containing df1 and df2 corresponding to the F-ratio considered.
estimates	A matrix containing the estimates for the parameters named in the type slot.
f.values	A matrix containing the f-values, for least-squares.
t.values	A matrix containing the t-values, for correlations.
p.values	A matrix containing the p.values for the parameters named in the type slot.

Value

an AnansiTale

Slots

`subject` A character that describes the data that was queried.

`type` A character that describes type of parameter contained in the estimates slot. For example `r.values` for correlations or `r.squared` for models.

`df` a vector of length 2, containing `df1` and `df2` corresponding to the F-ratio considered.

`estimates` A matrix containing the estimates for the parameters named in the type slot.

`f.values` A matrix containing the f-values, for least-squares.

`t.values` A matrix containing the t-values, for correlations.

`p.values` A matrix containing the p.values for the parameters named in the type slot.

Examples

```
AnansiTale
```

AnansiWeb

AnansiWeb S7 container class

Description

AnansiWeb is an S7 class containing two feature tables as well as a dictionary to link them. AnansiWeb is the main container that will hold your input data throughout the `anansi` pipeline.

Typical use of the `anansi` package will involve generating an AnansiWeb object using the `weaveWeb()` function.

The function `AnansiWeb()` constructs an AnansiWeb object from two feature tables and an adjacency matrix.

Usage

```
## Constructor for `AnansiWeb` objects
AnansiWeb(tableX, tableY, dictionary, metadata = data.frame())
```

Arguments

`tableY`, `tableX` A table containing features of interest. Rows should be samples and columns should be features. Y and X refer to the position of the features in a formula: `Y ~ X`.

`dictionary` A binary adjacency matrix of class `Matrix`, or coercible to `Matrix`

`metadata` list of metadata. Optional.

Value

an AnansiWeb object, with sparse binary biadjacency matrix with features from *y* as rows and features from *x* as columns in dictionary slot.

Slots

tableY, *tableX* Two matrix objects of measurements, data. Rows are samples and columns are features. Access with `@tableY` and `@tableX`.

dictionary Matrix, binary adjacency matrix. Optionally sparse. Typically generated using the `weaveWeb()` function. Access with `@dictionary`.

metadata Optional data.frame of sample metadata. Access with `@metadata`.

See Also

- [AnansiWeb-methods](#)
- `randomAnansi`: For generation of random AnansiWeb objects.
- `kegg_link()`: For examples of input for link argument.

Examples

```
# Use AnansiWeb() to construct an AnansiWeb object from components:
tX <- `dimnames<-`(replicate(5, (rnorm(36))),
  value = list(
    as.character(seq_len(36)),
    letters[1:5]
  )
)
tY <- `dimnames<-`(replicate(3, (rnorm(36))),
  value = list(
    as.character(seq_len(36)),
    LETTERS[1:3]
  )
)
d <- matrix(TRUE,
  nrow = NCOL(tY), ncol = NCOL(tX),

  # Note: Dictionary should have named dimensions
  dimnames = list(
    y_names = colnames(tY),
    x_names = colnames(tX)
  )
)
web <- AnansiWeb(tableX = tX, tableY = tY, dictionary = d)
```

Description

Methods for AnansiWeb S7 container class

Arguments

x input, AnansiWeb object

Value

The desired information from an AnansiWeb object

See Also

- [weaveWeb\(\)](#): for general use.
- [AnansiWeb-pairwise](#): for methods for pairwise operations

Examples

```
# Setup
web <- randomWeb(n_samp = 36)

# Accessors
dimnames(web)
dim(web)
names(web)

# Getters and setters:

tableX(web)[1:5, 1:5]
tableY(web)[1:5, 1:5]
dictionary(web)
head(metadata(web))

# Assign some random metadata
metadata(web) <- data.frame(
  id = row.names(tableY(web)),
  a = rnorm(36),
  b = sample(c("a", "b"), 36, TRUE),
  row.names = "id"
)

# Coerce to list
weblist <- as.list(web)

# Coerce to Data.frame
```

```
webdf <- as.data.frame(web)

# Coerce to MultiAssayExperiment
mae <- asMAE(web)

# Coerce to TreeSummarizedExperiment
tse <- asTSE(web)
```

AnansiWeb-pairwise *Methods for pairwise operations on AnansiWeb objects*

Description

Methods to run pairwise analysis on multi-modal data.

Arguments

<code>X, x</code>	input, AnansiWeb object
<code>...</code>	additional arguments
<code>FUN</code>	a function with at least two arguments. The variables <code>x</code> and <code>y</code> , in order, refer to the corresponding values of feature pairs in <code>tableX</code> and <code>tableY</code> .
<code>MoreArgs, SIMPLIFY, USE.NAMES</code>	see <code>?base::mapply</code>
<code>which</code>	integer matrix, indicating pair positions in <code>x@tableY</code> and <code>x@tableX</code> , respectively. If <code>NULL</code> (default): <code>Matrix::which(x@dictionary, TRUE)</code> .
<code>with.metadata</code>	Logical scalar whether to append metadata to output

Value

`pairs`: A two-column array index, corresponding to `i,j` coordinates in matrix notation.
`getFeaturePairs`: A list of data.frames with the paired data

Examples

```
web <- randomWeb()
# Extract data.frames in pairs (only show first)
getFeaturePairs(web)[1L]

pairs(x = web)

getFeaturePairs(x = web, which = NULL, with.metadata = FALSE)

pairwiseApply(
  X = web,
  FUN = function(x, y) cor(x, y),
  MoreArgs = NULL, SIMPLIFY = TRUE, USE.NAMES = TRUE
)
```

dictionary	<i>Get dictionary</i>
------------	-----------------------

Description

Get dictionary

Usage

```
dictionary(x, ...)
```

Arguments

x	input object
...	additional arguments

Value

dictionary slot of x

Examples

```
x <- randomWeb(10)
dictionary(x)
```

ec2ko	<i>Use linking data from the KEGG database.</i>
-------	---

Description

kegg_link() is a convenience function to return a list containing two data.frames; ec2cpd and ec2ko. This will be their most likely use. ec2cpd and ec2ko are two data.frames, used to link ko, ecs and cpd identifiers in the KEGG database.

Usage

```
data("ec2ko", package = "anansi")

data("ec2cpd", package = "anansi")

kegg_link()
```

Format

ec2ko: a data.frame of two columns, named "ec" and "ko". The IDs refer to KEGG orthologues. Enzyme commission numbers, ecs, typically describe reactions captured by them.

ec2cpd: a data.frame of two columns, named "ec" and "cpd". The IDs refer to compounds in the KEGG database. Enzyme commission numbers, ecs, typically describe reactions either producing or requiring them.

Value

kegg_link() returns a list containing the two aforementioned data.frames, ec2cpd and ec2ko.

Source

ec2ko: Adapted from <https://www.genome.jp/kegg/>, using KEGGREST. Script to generate available in example.

ec2cpd: Adapted from <https://www.genome.jp/kegg/> using KEGGREST. Script to generate available in example.

Examples

```
kegg_link()

# Generate ec2ko and ec2cpd:
# Don't download during tests. set to `TRUE` to download.
dry_run <- TRUE

if (!dry_run) {
  ec2ko <- KEGGREST::keggLink("ec", "ko")
  ec2ko <- data.frame(
    ec = gsub("ec:", "", x = ec2ko, fixed = TRUE),
    ko = gsub("ko:", "", x = names(ec2ko), fixed = TRUE),
    row.names = NULL
  )

  ec2cpd <- KEGGREST::keggLink("ec", "cpd")
  ec2cpd <- data.frame(
    ec = gsub("ec:", "", x = ec2cpd, fixed = TRUE),
    cpd = gsub("cpd:", "", x = names(ec2cpd), fixed = TRUE),
    row.names = NULL
  )
}
```

Description

Piphillin was used to infer functions from the 16S sequencing data in terms of KOs. Unfortunately, the Piphillin algorithm is proprietary and has since been taken down.

Usage

```
data("FMT_data", package = "anansi")
```

Format

A matrix object with 6468 rows, KOs, and 36 columns, samples.

Source

[doi:10.1038/s43587021000939](https://doi.org/10.1038/s43587021000939)

FMT_metab

Snippet of the CLR-transformed hippocampal metabolomics data from the FMT Aging study.

Description

Snippet of the CLR-transformed hippocampal metabolomics data from the FMT Aging study.

Usage

```
data("FMT_data", package = "anansi")
```

Format

A matrix object with three rows, compounds, and 36 columns, samples.

Source

[doi:10.1038/s43587021000939](https://doi.org/10.1038/s43587021000939)

`FMT_metadata`*Snippet of the metadata from the FMT Aging study.*

Description

There were three treatment groups in the study that all received faecal microbiota transplantation (FMT). Young mice that received FMT from young mice (Young yFMT), aged mice that received FMT from aged mice (Aged oFMT) and aged mice that received FMT from young mice (Aged yFMT).

Usage

```
data("FMT_data", package = "anansi")
```

Format

A data.frame object with 36 rows, samples, and two columns, denoting sample ID and treatment group, respectively.

Source

[doi:10.1038/s43587021000939](https://doi.org/10.1038/s43587021000939)

`getEdgeList`*Get a list of edges*

Description

Get a list of edges

Usage

```
getEdgeList(x, ...)
```

Arguments

<code>x</code>	input object
<code>...</code>	additional arguments

Value

a two-column data.frame that lists the content of each entry in the input MultiFactor

Examples

```
x <- randomMultiFactor(n_features = 10)
getEdgeList(x)
```

getFeaturePairs	<i>Get a list of all pairs of features</i>
-----------------	--

Description

Get a list of all pairs of features

Usage

```
getFeaturePairs(x, ...)
```

Arguments

x	input object
...	additional arguments for specific methods

Value

an list of two-column data.frames that represent all feature pairs.

Examples

```
x <- randomWeb(10)
head(getFeaturePairs(x), 3)
```

getGraph	<i>Get a graph object.</i>
----------	----------------------------

Description

Get a graph object.

Usage

```
getGraph(x, ...)
```

Arguments

x	input
...	additional arguments (currently not used).

Value

a specified graph object.

See Also[MultiFactor-methods](#)**Examples**

```
# Show methods
getGraph
```

```
krebs          Simplified snippet of the Krebs cycle
```

Description

Enzymes and metabolites that make up the Krebs cycle. Features share a row when they play a role in the same reaction. Used in vignettes, exported to facilitate user exploration.

Usage

```
data("krebs", package = "anansi")
```

Format

A data.frame of two factors, named "Enzyme" and "Metabolite", which contain these respective components of the krebs cycle.

Source

Generated by hand based on the krebs cycle.

See Also[krebsDemoWeb\(\)](#)

```
linkBiobakeryMap  make a link data.frame for biobakery mapping files input
```

Description

make a link data.frame for biobakery mapping files input

Usage

```
linkBiobakeryMap(map)
```

Arguments

map Character, result from readLines() on uncompressed humann mapping files.

Value

a two-column data.frame that can be converted into an adjacency matrix used as input for `weaveWeb()`.

See Also

[weaveWeb\(\)](#)

Examples

```
# some dummy input, as a character vector of IDs separated by tabs.  
x <- c("x_1\ty_1\ty_2\ty_4", "x_2\ty_1\ty_3", "x_3\ty_2\ty_y")  
linkBiobakeryMap(x)
```

metadata

Get metadata.

Description

Get metadata.

Arguments

x	input object
...	additional arguments

Details

Compatible with `S4Vectors` generic.

Value

metadata slot of x

Examples

```
x <- randomWeb(10)  
metadata(x)
```

```
metadata<-          Set metadata.
```

Description

Set metadata.

Arguments

x input object
 ... additional arguments
 value replacement value, coerced to data.frame

Details

Compatible with S4Vectors generic.

Value

x with modified metadata slot.

Examples

```
x <- randomWeb(10)
metadata(x) <- cbind(
  metadata(x),
  new_groups = c("A", "B")
)
```

```
MultiFactor            MultiFactor S7 container class
```

Description

MultiFactor is an S7 class to organize and manage multiple sets of factors, for instance when tracing or converting feature IDs across databases. Methods for MultiFactor aim to follow factor behaviour.

Usage

```
MultiFactor(x, levels = NULL, drop.unmatched = FALSE)
```

```
## Constructor for `MultiFactor` objects
MultiFactor(x, levels = NULL, drop.unmatched = FALSE)
```

Arguments

x	MultiFactor
levels	an optional named list of vectors of the unique values (as character strings) that x might have taken. The default is the unique set of values taken by <code>lapply(x, as.character)</code> , sorted into increasing order of x.
drop.unmatched	Logical scalar If TRUE (Default), for feature types that are seen at least twice, exclude features that only present in one of their respective link data frames.

Details

The most straightforward way to construct a MultiFactor object is as a named list of named data.frames. The columns of the data.frames indicate the category of factor in that column.

A MultiFactor object presents itself similar to a data.frame, in the sense that level types can be called as columns and individual data.frame components can be called as rows.

Value

a MultiFactor object.

Slots

`index` Named list of named integer data frames of at least two columns each. The column names correspond to names in the `levels` slot. Similar to factors, the integers in those columns correspond to the characters in that level. Accessed through regular list methods (e.g., `[`, `[[`).

`levels` Named list of character vectors. Accessed through `levels(x)`

`map` (sparse) Matrix specifying which elements contain which levels. Accessed through `x@dictionary`.

See Also

[MultiFactor-methods\(\)](#)

- [kegg_link\(\)](#): for an example of valid input.

Examples

```
# Generate some random linkage input
x <- data.frame(
  a = sample(letters[seq(3)], 10, replace = TRUE),
  A = sample(LETTERS[seq(3)], 10, replace = TRUE)
)
MultiFactor(x)
```

MultiFactor-methods *Methods for MultiFactor S7 container class*

Description

`droplevels()` `droplevels(MultiFactor)` returns a `MultiFactor` with unused levels removed, Analogous to the `factor` method.

Arguments

<code>...</code>	<code>i, j</code> indices specifying elements to extract or replace. Indices are numeric or character vectors or empty (missing) or <code>NULL</code> . Numeric values are coerced to integer or whole numbers as by <code>as.integer</code> or for large values by <code>trunc</code> (and hence truncated towards zero). Character vectors will be matched to the names of the object.
<code>value</code>	Replacement value, typically of same type as that which is to be replaced.
<code>exclude</code>	<code>NULL</code> or Named character list of similar structure as <code>levels(MultiFactor)</code> . Which levels to drop from output.
<code>select</code>	<code>NULL</code> or Named character list of similar structure as <code>levels(MultiFactor)</code> . Which levels to keep in output.
<code>use.names, ignore.mcols</code>	For compatibility, not used.
<code>x</code>	<code>MultiFactor</code>
<code>format</code>	Character scalar, controls output format by package name. "igraph" and "graph" are supported.

Details

Only one of `select` and `exclude` should be provided, as they are each others complement.

Value

A `MultiFactor`
a specified graph object.

See Also

`igraph::graph_from_data_frame()` and `igraph::as_graphnel()`, which are used under the hood, from `igraph::igraph()` package.

Examples

```
# Setup
x <- MultiFactor(kegg_link())
x
```

```
# Basic properties
dim(x)
dimnames(x)

# Factor-like properties
head(levels(x)$ko)
droplevels(x)
head(unfactor(x)$ec2ko)

# Extract common output formats
getEdgeList(x)

droplevels(x, exclude = list(ko = "K00001"))
droplevels(x, select = list(ko = "K00001"))
# Generate an igraph object
g <- getGraph(x = kegg_link(), format = "igraph")
plot(g)
```

pairwiseApply	<i>Apply a function on each pair of features</i>
---------------	--

Description

Apply a function on each pair of features

Usage

```
pairwiseApply(X, ...)
```

Arguments

X	input object
...	additional arguments

Value

a list containing the output of applying the function to each feature pair. See `?base::mapply()`

Examples

```
web <- randomWeb(10)

# For each feature pair, was the value for x higher than the value for y?
pairwise_gt <- pairwiseApply(
  X = web,
  FUN = function(x, y) x > y,
  MoreArgs = NULL, SIMPLIFY = FALSE, USE.NAMES = TRUE
)
```

```

head(pairwise_gt)

# Run cor.test() on each pair of features
pairwise_cor <- pairwiseApply(
  X = web,
  FUN = function(x, y) cor.test(x, y),
  MoreArgs = NULL, SIMPLIFY = FALSE, USE.NAMES = TRUE
)

pairwise_cor[1]

```

plotAnansi

Dissociation plot

Description

plotAnansi generates an association plot from the output of `anansi()` in the table format. It provides a convenient way to visually assess relevant results from the anansi analysis, either in the form of a dotplot or a graph.

Arguments

<code>x</code>	a data.frame object output of <code>anansi()</code> in the table format.
<code>...</code>	additional parameters
<code>layout</code>	Character scalar. Specifies the plot layout to generate. It must be one of <code>c("dotplot", "graph")</code> . (Default: dotplot)
<code>association.type</code>	Character scalar. Specifies the type of association to show in the plot. One of <code>"disjointed", "emergent" and "full"</code> . (Default: NULL)
<code>model.var</code>	Character scalar. Specifies the name of a variable in the anansi model. It is relevant only when <code>association.type</code> is <code>"disjointed"</code> or <code>"emergent"</code> . (Default: NULL)
<code>group</code>	Character scalar. Selects one of the groups included in the anansi model. It is relevant only when <code>layout</code> is <code>graph</code> . (Default: All)
<code>signif.threshold</code>	Numeric scalar. Specifies the threshold to mark the significance of <code>association.type</code> . (Default: NULL)
<code>colour_by</code>	Character scalar. Specifies one of the groups terms used in the original anansi call, <code>x</code> by which points should be coloured. (Default: NULL)
<code>color_by</code>	Character scalar. Alias to <code>colour_by</code> .
<code>fill_by</code>	Character scalar. Specifies one of the groups terms used in the original anansi call, <code>x</code> by which points should be filled (Default: "group")
<code>size_by</code>	Character scalar. Specifies one of the groups terms used in the original anansi call, <code>x</code> by which points should be sized. (Default: NULL)

shape_by	Character scalar. Specifies one of the groups terms used in the original anansi call, x by which points should be shaped. (Default: NULL)
x_lab	Character scalar. Specifies the label of the x axis. (Default: "cor")
y_lab	Character scalar. Specifies the label of the y axis. (Default: "")
y_position	Character scalar. Specifies the position of the y labels. It should be either "left" or "right". (Default: "right")
show.cor	Logical scalar. Whether correlation edges should be labelled with correlation coefficients when layout is graph. (Default: FALSE)

Details

plotAnansi provides a standardised method to visualise the results of anansi by means of a differential association plot. The input for this function should be generated from [anansi\(\)](#) or [anansi\(\)](#), with `return.format = "table"`

Value

a figure that can be further modified using the ggplot2 suite

A ggplot2 object.

See Also

[anansi\(\)](#)

Examples

```
# Import libraries
library(mia)
library(TreeSummarizedExperiment)
library(MultiAssayExperiment)
library(ggraph)

web <- randomWeb(n_samples = 100)
mae <- asMAE(web)

# Perform anansi analysis
out <- weaveWeb(mae,
  tableY = "y", tableX = "x"
) |> anansi(formula = ~group_ab)

# Select significant interactions
out <- out[out$full_p.values < 0.05, ]

# Visualise disjointed associations filled by group
plotAnansi(out,
  association.type = "disjointed",
  model.var = "group_ab",
  signif.threshold = 0.05,
  fill_by = "group"
)
```

```
# Visualise full associations filled by group
plotAnansi(out,
  association.type = "full",
  signif.threshold = 0.05,
  fill_by = "group"
)

# Visualise full associations as graph
plotAnansi(out,
  layout = "graph",
  association.type = "full",
  signif.threshold = 0.05,
  show.cor = TRUE
)

# Visualise disjointed associations as graph
plotAnansi(out,
  layout = "graph",
  association.type = "disjointed",
  model.var = "group_ab",
  signif.threshold = 0.05
)
```

randomAnansi

Generate a random AnansiWeb or MultiFactor

Description

Randomly generate a valid AnansiWeb or MultiFactor object.

Usage

```
randomWeb(
  n_samples = 10,
  n_reps = 1L,
  n_features_x = 8,
  n_features_y = 12,
  sparseness = 0.5,
  tableY = NULL,
  tableX = NULL,
  dictionary = NULL
)

randomMultiFactor(n_types = 6, n_features = 100, sparseness = 0.5)

krebsDemoWeb(n_samples = 100, n_reps = 4L)
```

Arguments

n_samples, n_reps	Numeric scalar Number of samples and repeated measures of those samples to be generated. Ignored if tableY and tableX are provided. (defaults: 10 samples without repeats)
n_features_y, n_features_x	Numeric scalar Number of features to be generated. Ignored if tableY and tableX are provided.
sparseness	Numeric scalar, proportion: How rare are connections
tableY, tableX	A table containing features of interest. Rows should be samples and columns should be features. Y and X refer to the position of the features in a formula: Y ~ X.
dictionary	A binary adjacency matrix of class Matrix, or coercible to Matrix.
n_types	Numeric scalar, number of types of features to generate
n_features	Numeric scalar, number of features per type

Value

a randomly generated object of the specified class.

See Also

[AnansiWeb\(\)](#), [MultiFactor\(\)](#)

Examples

```
# Make a random AnansiWeb object
randomWeb()
krebsDemoWeb()
randomMultiFactor()
```

tableX	<i>Get tableX</i>
--------	-------------------

Description

Get tableX

Usage

```
tableX(x, ...)
```

Arguments

x	input object
...	additional arguments

Value

tableX slot of x

Examples

```
x <- randomWeb(10)
tableX(x)
```

tableY

Get tableY

Description

Get tableY

Usage

```
tableY(x, ...)
```

Arguments

x	input object
...	additional arguments

Value

tableY slot of x

Examples

```
x <- randomWeb(10)
tableY(x)
```

weaveWeb

Weave an AnansiWeb object

Description

Weave an AnansiWeb object

Usage

```
weaveWeb(x, ...)
```

```
weaveKEGG(x, ...)
```

Arguments

x input object
... additional arguments

Value

an AnansiWeb object, with sparse binary biadjacency matrix with features from y as rows and features from x as columns in dictionary slot.

See Also

[weaveWeb-methods\(\)](#)

Examples

```
# Setup demo tables
ec2ko <- kegg_link()[["ec2ko"]]
ec2cpd <- kegg_link()[["ec2cpd"]]

# Basic usage
weaveWeb(cpd ~ ko, link = kegg_link())
weaveWeb(x = "ko", y = "ec", link = ec2ko)
weaveWeb(ec ~ cpd, link = ec2cpd)

# A wrapper is available for kegg ko, ec and cpd data
generic <- weaveWeb(cpd ~ ko, link = kegg_link())
kegg_wrapper <- weaveKEGG(cpd ~ ko)

identical(generic, kegg_wrapper)

# The following are equivalent to transposition:
a <- weaveWeb(ko ~ cpd, link = kegg_link()) |> dictionary()
b <- weaveWeb(cpd ~ ko, link = kegg_link()) |> dictionary()

identical(a, Matrix::t(b))
```

weaveWeb-methods

Weave an AnansiWeb

Description

Generate a biadjacency matrix, linking the features between two tables. Return an AnansiWeb object which contains all three.

weaveWeb() is for general use and has flexible default settings.

weaveKEGG() is a wrapper that sets link to kegg_link(). All variants are special cases of weaveWeb().

Arguments

<code>x, y</code>	Character scalar, names of feature types that should be linked. Should be found in the column names of <code>link</code> .
<code>link</code>	One of the following: <ul style="list-style-type: none"> • Character scalar with value "none". • <code>data.frame</code> with two columns • list with two such <code>data.frames</code>.
<code>tableY, tableX</code>	A table containing features of interest. Rows should be samples and columns should be features. Y and X refer to the position of the features in a formula: $Y \sim X$. < For Bioconductor S4 objects > Character scalar or numeric scalar. Selects experiment corresponding to <code>tableY</code> and <code>tableX</code> from <code>experiments(x)</code> of <code>MultiAssayExperiment</code> object by name or index, name is recommended. (Default slots: Y = 1L, X = 2L).
<code>metadata</code>	Optional <code>data.frame</code> of sample metadata, to be included with output. Can be accessed from <code>AnansiWeb</code> generated by <code>weaveWeb()</code> with <code>output@metadata</code> .
<code>verbose</code>	Logical scalar. Whether to print diagnostic information (Default: TRUE).# @param <code>force_new</code> boolean If x already has a dictionary <code>Matrix</code> in metadata, ignore it and generate a new object anyway? (Default: FALSE).
<code>typeY, typeX</code>	Character scalar or numeric scalar. Selects assay from <code>experiments(x)</code> . (Default: 1L - the first assay in that experiment).
<code>experiment1, experiment2</code>	synonymous args to <code>tableY, tableX</code> for compatibility with <code>mia</code> argument style.
<code>assay.type1, assay.type2</code>	synonymous args to <code>typeY, typeX</code> for compatibility with <code>mi</code> argument style.

Details

If the `link` argument is "none", all features will be considered linked. If one or more `data.frames`, `colnames` should be as specified in `x` and `y`.

Value

an `AnansiWeb` object, with sparse binary biadjacency matrix with features from `y` as rows and features from `x` as columns in dictionary slot.

See Also

- [AnansiWeb](#): For general constructor and methods.
- [kegg_link\(\)](#): For examples of input for `link` argument.

Examples

```
# Setup demo tables, see first vignette.
data(FMT_data)
```

```
t1 <- t(FMT_metab)
t2 <- t(FMT_K0s)

# Input objects and syntax:
## define `x` and `y` as characters
web <- weaveWeb(
  x = "ko", y = "cpd", link = kegg_link(),
  tableX = t2, tableY = t1,
  metadata = NULL, verbose = TRUE
)

## define `x` and `y` with a formula
web2 <- weaveWeb(
  x = cpd ~ ko, link = kegg_link(),
  tableX = t2, tableY = t1,
  metadata = NULL, verbose = TRUE
)

identical(web, web2)

# Method for MultiAssayExperiment S4 object
mae <- asMAE(web)
weaveWeb(
  x = mae, link = kegg_link(),
  tableY = "cpd", tableX = "ko",
  force_new = FALSE
)

# Method for TreeSummarizedExperiment S4 object
tse <- asTSE(web)
weaveWeb(
  x = tse, link = kegg_link(),
  tableY = "cpd", tableX = "ko",
  force_new = FALSE
)
```

Index

* datasets

- ec2ko, 9
 - FMT_KOs, 10
 - FMT_metab, 11
 - FMT_metadata, 12
 - krebs, 14
- anansi(), 20, 21
- anansi-coercion, 3
- AnansiTale, 4
- AnansiTale-class (AnansiTale), 4
- AnansiWeb, 5, 26
- AnansiWeb(), 23
- AnansiWeb-methods, 6, 7
- AnansiWeb-pairwise, 7, 8
- as.data.frame.anansi::AnansiWeb
(anansi-coercion), 3
- as.list.anansi::AnansiWeb
(anansi-coercion), 3
- as.list.anansi::MultiFactor
(anansi-coercion), 3
- as.MAE (anansi-coercion), 3
- as.MultiAssayExperiment
(anansi-coercion), 3
- as.TreeSummarizedExperiment
(anansi-coercion), 3
- as.TSE (anansi-coercion), 3
- asMAE (anansi-coercion), 3
- asMultiAssayExperiment
(anansi-coercion), 3
- asMultiFactor (MultiFactor), 16
- asTreeSummarizedExperiment
(anansi-coercion), 3
- asTSE (anansi-coercion), 3
- dictionary, 9
- dictionary-generic (dictionary), 9
- dim.anansi::AnansiWeb
(AnansiWeb-methods), 7
- dimnames.anansi::AnansiWeb
(AnansiWeb-methods), 7
- ec2cpd (ec2ko), 9
- ec2ko, 9
- FMT_KOs, 10
- FMT_metab, 11
- FMT_metadata, 12
- getEdgeList, 12
- getFeaturePairs, 13
- getGraph, 13
- getGraph.anansi::MultiFactor
(MultiFactor-methods), 18
- igraph::as_graphnel(), 18
- igraph::graph_from_data_frame(), 18
- igraph::igraph(), 18
- kegg_link (ec2ko), 9
- kegg_link(), 6, 17, 26
- krebs, 14
- krebsDemoWeb (randomAnansi), 22
- krebsDemoWeb(), 14
- levels.anansi::MultiFactor
(MultiFactor-methods), 18
- linkBiobakeryMap, 14
- metadata, 15
- metadata, anansi::AnansiWeb-method
(metadata), 15
- metadata.set (metadata<-), 16
- metadata<-, 16
- metadata<-, anansi::AnansiWeb-method
(metadata<-), 16
- MultiFactor, 16
- MultiFactor(), 23
- MultiFactor-methods, 18

names.anansi::AnansiWeb
 (AnansiWeb-methods), 7

pairs.anansi::AnansiWeb
 (AnansiWeb-pairwise), 8

pairs.AnansiWeb (AnansiWeb-pairwise), 8

pairwiseApply, 19

pairwiseApply-generic (pairwiseApply),
 19

pairwiseApply.anansi::AnansiWeb
 (AnansiWeb-pairwise), 8

pairwiseApply.AnansiWeb
 (AnansiWeb-pairwise), 8

plotAnansi, 20

plotAnansi-generic (plotAnansi), 20

plotAnansi-methods (plotAnansi), 20

randomAnansi, 6, 22

randomMultiFactor (randomAnansi), 22

randomWeb (randomAnansi), 22

show.anansi::AnansiWeb
 (AnansiWeb-methods), 7

tableX, 23

tableX-generic (tableX), 23

tableY, 24

tableY-generic (tableY), 24

unfactor (MultiFactor-methods), 18

unfactor(), 3

unfactor, anansi::MultiFactor-method
 (MultiFactor-methods), 18

weaveKEGG (weaveWeb), 24

weaveWeb, 24

weaveWeb(), 7, 15

weaveWeb-methods, 25

weaveWeb.character (weaveWeb-methods),
 25

weaveWeb.formula (weaveWeb-methods), 25

weaveWeb.MultiAssayExperiment
 (weaveWeb-methods), 25

weaveWeb.SingleCellExperiment
 (weaveWeb-methods), 25

weaveWeb.TreeSumarizedExperiment
 (weaveWeb-methods), 25