

Package: bedbaser (via r-universe)

June 2, 2026

Title A BEDbase client

Version 1.4.0

Description A client for BEDbase. bedbaser provides access to the API at api.bedbase.org. It also includes convenience functions to import BED files into GRanges objects and BEDsets into GRangesLists.

URL <https://github.com/waldronlab/bedbaser>

BugReports <https://github.com/waldronlab/bedbaser/issues>

biocViews Software, DataImport, ThirdPartyClient

License Artistic License 2.0

Depends R (>= 4.5.0)

Imports AnVIL (>= 1.16.0), BiocFileCache, curl, dplyr, GenomeInfoDb, GenomicRanges, httr, methods, purrr, rtracklayer, rlang, R.utils, stats, stringr, tibble, tidyr, tools, utils

Suggests BiocStyle, knitr, liftOver, testthat (>= 3.0.0), withr

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

VignetteBuilder knitr

Config/testthat/edition 3

Config/pak/sysreqs cmake make libbz2-dev libicu-dev liblzma-dev libsecret-1-dev libuv1-dev libxml2-dev libssl-dev xz-utils zlib1g-dev

Repository <https://bioc-release.r-universe.dev>

Date/Publication 2026-04-28 13:04:27 UTC

RemoteUrl <https://github.com/bioc/bedbaser>

RemoteRef RELEASE_3_23

RemoteSha f503a0e6721667fd129212a62f51b0bac2b11d01

Contents

bb_bed_text_search	2
bb_beds_in_bedset	3
bb_example	4
bb_list_beds	4
bb_list_bedsets	5
bb_metadata	6
bb_save	6
bb_stats	7
bb_to_granges	8
bb_to_grangeslist	8
BEDbase	9
BEDbase-class	10
getCache,BEDbase-method	11
operations,BEDbase-method	11
schemas,BEDbase-method	12
setCache,BEDbase-method	13
tags,BEDbase-method	13
Index	15

bb_bed_text_search *Search BED files by text*

Description

Return all available BED files ranked by relevance to the keywords. Uses the [bedhost API](#) default of 10 records and an initial offset of 0.

Usage

```
bb_bed_text_search(
  bedbase,
  query,
  genome = NULL,
  assay = NULL,
  limit = 10,
  offset = 0
)
```

Arguments

bedbase	BEDbase() object
query	character() keywords to search
genome	character() (default NULL) genome to search
assay	character() (default NULL) assay to search

limit integer(1) (default 10) maximum number of results
offset integer(1) (default 0) page offset of results

Value

tibble of results

Examples

```
bedbase <- BEDbase()  
bb_bed_text_search(bedbase, "hg38")
```

bb_beds_in_bedset *Get BEDs associated with BEDset*

Description

Return a tibble of BED files in BEDset given its id.

Usage

```
bb_beds_in_bedset(bedbase, bedset_id)
```

Arguments

bedbase BEDbase() object
bedset_id integer(1) BEDset record identifier

Value

tibble of BED files in BEDset

Examples

```
bedbase <- BEDbase()  
ex_bedset <- bb_example(bedbase, "bedset")  
bb_beds_in_bedset(bedbase, ex_bedset$id)
```

 bb_example

Get the example BED file or BEDset with metadata

Description

Get the example BED file or BEDset available through [bedhost](#). Useful for an initial exploration of bedbaser with an example BED file and BEDset in BEDbase.

Usage

```
bb_example(bedbase, rec_type = c("bed", "bedset"))
```

Arguments

bedbase	BEDbase() object
rec_type	character(1) bed or bedset

Value

list() bed files or bedsets

Examples

```
bedbase <- BEDbase()
ex_bed <- bb_example(bedbase, "bed")
str(ex_bed)
ex_bedset <- bb_example(bedbase, "bedset")
str(ex_bedset)
```

 bb_list_beds

List BEDs

Description

List BED files available through [bedhost](#). By default uses the bedhost default of 1000 records and an initial offset of 0.

Usage

```
bb_list_beds(
  bedbase,
  genome = NULL,
  bed_compliance = NULL,
  limit = 1000,
  offset = 0
)
```

Arguments

bedbase	BEDbase() object
genome	character(1) (default NULL) genome keyword
bed_compliance	character(1) (default NULL) bed compliance, e.g., 'bed6+4'
limit	integer(1) (default 1000) maximum records
offset	integer(1) (default 0) page token of records

Value

[tibble](#) of BED records

Examples

```
bedbase <- BEDbase()
bb_list_beds(bedbase)
```

bb_list_bedsets	<i>List BEDsets</i>
-----------------	---------------------

Description

List BEDsets available through [bedhost](#). By default uses the bedhost default of 1000 records and an initial offset of 0.

Usage

```
bb_list_bedsets(bedbase, query = "", limit = 1000, offset = 0)
```

Arguments

bedbase	BEDbase() object
query	character() (default "") keyword
limit	integer(1) (default 1000) maximum records
offset	integer(1) (default 0) page token of records

Value

[tibble](#) of BEDset records

Examples

```
bedbase <- BEDbase()
bb_list_bedsets(bedbase)
```

bb_metadata	<i>Get metadata for a BED file or BEDset</i>
-------------	--

Description

Get metadata for a BED file or BEDset given its id. Abort if not found or id is not not 32 characters.

Usage

```
bb_metadata(bedbase, id, full = FALSE)
```

Arguments

bedbase	BEDbase() object
id	integer(1) record or object identifier
full	logical(1) (default FALSE) include full record with stats, files, and metadata

Value

list() metadata

Examples

```
bedbase <- BEDbase()

ex_bed <- bb_example(bedbase, "bed")
bb_metadata(bedbase, ex_bed$id)

ex_bedset <- bb_example(bedbase, "bedset")
bb_metadata(bedbase, ex_bedset$id)
```

bb_save	<i>Save a BED file or BEDset to a path given an id</i>
---------	--

Description

Save a BED file or a BEDset to a local path. If the path does not exist, bb_save() will abort.

Usage

```
bb_save(bedbase, bed_or_bedset_id, path, quietly = TRUE)
```

Arguments

bedbase	BEDbase() object
bed_or_bedset_id	integer(1) BED or BEDset record identifier
path	character(1) directory to save file
quietly	logical(1) (default TRUE) display messages

Value

An invisible NULL

Examples

```
bedbase <- BEDbase()
ex_bed <- bb_example(bedbase, "bed")
bb_save(bedbase, ex_bed$id, tempdir())
```

bb_stats

Get BEDbase statistics

Description

Get statistics on available BED files, BEDsets, and genomes.

Usage

```
bb_stats(bedbase, detailed = FALSE)
```

Arguments

bedbase	BEDbase() object
detailed	logical(1) if TRUE display detailed information

Value

An invisible NULL

Examples

```
bedbase <- BEDbase()
bb_stats(bedbase)
```

bb_to_granges *Create a GRanges object given a BED id*

Description

Create a GRanges object given a BED id. Columns and types are generated for broad and narrow peak files. Known columns and types can be passed as a named vector through `extra_cols`. Otherwise, `bb_to_granges()` attempts to determine the column type and substitute dummy column names.

Usage

```
bb_to_granges(bedbase, bed_id, extra_cols = NULL, quietly = TRUE)
```

Arguments

<code>bedbase</code>	BEDbase() object
<code>bed_id</code>	integer(1) BED record identifier
<code>extra_cols</code>	character() (default NULL) extra column names to construct GRanges objects
<code>quietly</code>	logical(1) (default TRUE) display messages

Value

GRanges

Examples

```
bedbase <- BEDbase()
ex_bed <- bb_example(bedbase, "bed")
bb_to_granges(bedbase, ex_bed$id)
```

bb_to_grangeslist *Create a GRangesList object given a BEDset id*

Description

Create a GRangesList object given a BEDset id

Usage

```
bb_to_grangeslist(bedbase, bedset_id, quietly = TRUE)
```

Arguments

bedbase	BEDbase() object
bedset_id	integer(1) BEDset record identifier
quietly	logical(1) (default TRUE) display messages

Value

[GRangesList](#)

Examples

```
bedbase <- BEDbase()
bedset_id <- "lola_hg38_ucsc_features"
bb_to_grangeslist(bedbase, bedset_id)
```

BEDbase *An R client for BEDbase*

Description

bedbaser exposes the [bedhost API](#) and includes convenience functions for common tasks, such as to import a BED file by id into a GRanges object and a BEDset by its id into a GRangesList.

Usage

```
BEDbase(cache_path, quietly = FALSE)

getCache(x, cache_type = c("bedfiles", "bedsets"))

setCache(x, cache_path, quietly = TRUE)
```

Arguments

cache_path	character(1)
quietly	logical(1) (default TRUE) display messages
x	BEDbase() object
cache_type	character(1) bedfiles or bedsets

Details

BEDbase() creates a cache similar to that of the [Geniml BBClient's cache](#).

The convenience functions are as follows

- `bedbaser::BEDbase()`: API service constructor
- `bedbaser::getCache()`: Retrieve cache

- `bedbaser::setCache()`: Set path to cache
- `bedbaser::bb_stats()`: Retrieve BEDbase statistics
- `bedbaser::bb_example()`: Retrieve an example BED file or BEDset
- `bedbaser::bb_metadata()`: Retrieve metadata for a BED file or BEDset
- `bedbaser::bb_list_beds()`: List all BED files
- `bedbaser::bb_list_bedsets()`: List all BEDsets
- `bedbaser::bb_beds_in_bedset()`: List BED files in BEDset
- `bedbaser::bb_bed_text_search()`: Search BED files by text
- `bedbaser::bb_to_granges()`: Create a GRanges object from a BED id
- `bedbaser::bb_to_grangeslist()`: Create a GRangesList from a BEDset id
- `bedbaser::bb_save()`: Save a BED file to a path.

Value

BEDbase object

Examples

```
bedbase <- BEDbase(cache_path = tempdir())
ex_bed <- bb_example(bedbase, "bed")
bb_metadata(bedbase, ex_bed$id)
```

BEDbase-class

BEDbase class

Description

BEDbase class

Value

BEDbase class instance

```
getCache,BEDbase-method
      Return cache path
```

Description

Return cache path

Usage

```
## S4 method for signature 'BEDbase'
getCache(x, cache_type = c("bedfiles", "bedsets"))
```

Arguments

x	BEDbase() object
cache_type	character(1) bedfiles or bedsets

Value

BiocFileCache() object of BED files

Examples

```
bedbase <- BEDbase(tempdir())
getCache(bedbase, "bedfiles")
```

```
operations,BEDbase-method
      Display API functions
```

Description

Display functions defined through the [bedhost API](#) and their corresponding parameters.

Usage

```
## S4 method for signature 'BEDbase'
operations(x, ..., .deprecated = FALSE)
```

Arguments

x	BEDbase() object
...	other options
.deprecated	(default FALSE) if deprecated

Value

list() API endpoints

Examples

```
bedbase <- BEDbase()  
operations(bedbase)
```

schemas,BEDbase-method

Display bedhost API schemas

Description

Display bedhost API schemas

Usage

```
## S4 method for signature 'BEDbase'  
schemas(x)
```

Arguments

x BEDbase() object

Value

list() API endpoints

Examples

```
bedbase <- BEDbase()  
schemas(bedbase)
```

```
setCache,BEDbase-method
      Set cache along path
```

Description

Create a cache for BED files and BEDsets like [Geniml BBClient's cache](#).

Usage

```
## S4 method for signature 'BEDbase'
setCache(x, cache_path, quietly = TRUE)
```

Arguments

x	BEDbase() object
cache_path	character(1)
quietly	logical(1) (default TRUE) display messages

Value

[BiocFileCache\(\)](#) object of BED files

Examples

```
bedbase <- BEDbase(tempdir())
bedbase <- setCache(bedbase, "/tmp")
```

```
tags,BEDbase-method   Display functions for a tag
```

Description

Display functions available through the API associated with a tag keyword in [bedhost](#).

Usage

```
## S4 method for signature 'BEDbase'
tags(x, .tags, .deprecated = FALSE)
```

Arguments

x	BEDbase() object
.tags	character() tags for filtering operations
.deprecated	(default FALSE) if deprecated

Value

list() API endpoints

Examples

```
bedbase <- BEDbase()
unique(tags(bedbase)$tag)
tags(bedbase, "bedset")
```

Index

[.BEDbase \(BEDbase-class\), 10](#)

[bb_bed_text_search, 2](#)
[bb_beds_in_bedset, 3](#)
[bb_example, 4](#)
[bb_list_beds, 4](#)
[bb_list_bedsets, 5](#)
[bb_metadata, 6](#)
[bb_save, 6](#)
[bb_stats, 7](#)
[bb_to_granges, 8](#)
[bb_to_grangeslist, 8](#)
[BEDbase, 9](#)
[BEDbase-class, 10](#)
[BiocFileCache\(\), 13](#)

[getCache \(BEDbase\), 9](#)
[getCache, BEDbase-method, 11](#)
[GRanges, 8](#)
[GRangesList, 9](#)

[operations, BEDbase-method, 11](#)

[schemas, BEDbase-method, 12](#)
[setCache \(BEDbase\), 9](#)
[setCache, BEDbase-method, 13](#)

[tags, BEDbase-method, 13](#)
[tibble, 3, 5](#)