Package: bugsigdbr (via r-universe)

November 25, 2026

Version 1.20.0

Title R-side access to published microbial signatures from BugSigDB

Description The bugsigdbr package implements convenient access to bugsigdb.org from within R/Bioconductor. The goal of the package is to facilitate import of BugSigDB data into R/Bioconductor, provide utilities for extracting microbe signatures, and enable export of the extracted signatures to plain text files in standard file formats such as GMT.

URL https://github.com/waldronlab/bugsigdbr

BugReports https://github.com/waldronlab/bugsigdbr/issues

Depends R (>= 4.1)

Imports BiocFileCache, methods, vroom, utils

Suggests BiocStyle, knitr, ontologyIndex, rmarkdown, testthat (>= 3.0.0)

License GPL-3

VignetteBuilder knitr

biocViews DataImport, GeneSetEnrichment, Metagenomics, Microbiome

Encoding UTF-8

RoxygenNote 7.3.3

Config/pak/sysreqs libicu-dev libssl-dev

Repository Bioconductor 3.24

Date/Publication 2026-11-23 22:47:50 UTC

RemoteUrl https://github.com/bioc/bugsigdbr

RemoteRef RELEASE_3_24

RemoteSha 62ce79f8c7ad4427458c0a815ecffb2fc12e8e2b

Contents

browseSignature 2
browseTaxon 3
extractTaxLevel 3
getMetaSignatures 4
getOntology 6
getSignatures 7
importBugSigDB 8
restrictTaxLevel 10
subsetByOntology 11
writeGMT 12

Index **13**

`browseSignature` *Displaying BugSigDB signatures pages in a web browser*

Description

Functionality for programmatically displaying microbe signatures on BugSigDB signature pages.

Usage

```
browseSignature(sname)
```

Arguments

`sname`	character. Signature name. Expected to start with a prefix of the form `"bsdb:<X>/<Y>/<Z>_"` encoding the corresponding BugSigDB signature ID.

Value

The URL of the selected BugSigDB signature page. If interactive, opens the URL in the default web browser.

References

BugSigDB: https://bugsigdb.org

Examples

```
sname <- "bsdb:215/1/1_eczema:infant-with-eczema_vs_healthy-control_UP"
browseSignature(sname)
```

browseTaxon *Displaying BugSigDB taxon pages in a web browser*

Description

Functionality for programmatically displaying BugSigDB taxon pages.

Usage

```
browseTaxon(tax.id)
```

Arguments

tax.id	character. NCBI taxonomy ID.

Value

The URL of the selected BugSigDB taxon page. If interactive, opens the URL in the default web browser.

References

BugSigDB: https://bugsigdb.org

Examples

```
# BugSigDB taxon page for Escherichia coli
browseTaxon("562")
```

extractTaxLevel *Extract specific taxonomic levels from a microbe signature*

Description

Functionality for extracting specific taxonomic levels (such as genus and species) from a microbe signature containing taxonomic clades in MetaPhlAn format.

Usage

```
extractTaxLevel(
  sig,
  tax.id.type = c("metaphlan", "taxname"),
  tax.level = "mixed",
  exact.tax.level = TRUE
)
```

Arguments

`sig`	character. Microbe signature containing taxonomic clades in MetaPhlAn format.
`tax.id.type`	Character. Taxonomic ID type of the returned microbe sets. Either `"metaphlan"` (default) or `"taxname"`.
`tax.level`	character. Either `"mixed"` or any subset of `c("kingdom", "phylum", "class", "order", "family", "genus", "species","strain")`. This full vector is equivalent to `"mixed"`.
`exact.tax.level`	logical. Should only the exact taxonomic level specified by `tax.level` be returned? Defaults to `TRUE`. If `FALSE`, a more general `tax.level` is extracted for microbes given at a more specific taxonomic level.

Value

a character vector storing taxonomic clades restricted to chosen taxonomic level(s).

References

BugSigDB: https://bugsigdb.org

Examples

```
ord <- "k__Bacteria|p__Firmicutes|c__Bacilli|o__Lactobacillales"
sig <- c("f__Lactobacillaceae|g__Lactobacillus",
         "f__Aerococcaceae|g__Abiotrophia|s__Abiotrophia defectiva",
         "f__Lactobacillaceae|g__Limosilactobacillus|s__Limosilactobacillus mucosae")
sig <- paste(ord, sig, sep = "|")
sig <- extractTaxLevel(sig, tax.level = "genus")
sig <- extractTaxLevel(sig, tax.level = "genus", exact.tax.level = FALSE)
sig <- extractTaxLevel(sig,
                       tax.id.type = "taxname",
                       tax.level = "genus",
                       exact.tax.level = FALSE)
```

`getMetaSignatures` *Obtain meta-signatures for a column of interest*

Description

Functionality for obtaining meta-signatures for a column of interest

Usage

```
getMetaSignatures(
  df,
  column,
  direction = c("BOTH", "UP", "DOWN"),
  min.studies = 2,
  min.taxa = 5,
  comb.fun = sum,
  ...
)
```

Arguments

df	data.frame storing BugSigDB data. Typically obtained via importBugSigDB.
column	character. Column of interest. Need to be a valid column name of df.
direction	character. Indicates direction of abundance change for signatures to be included in the computation of meta-signatures. Use "UP" to restrict computation to signatures with increased abundance in the exposed group. Use "DOWN" to restrict to signatures with decreased abundance in the exposed group. Defaults to "BOTH" which will not filter signatures by direction of abundance change.
min.studies	integer. Minimum number of studies for a category in column to be included. Defaults to 2, which will then only compute meta-signatures for categories investigated by at least two studies.
min.taxa	integer. Minimum size for meta-signatures. Defaults to 5, which will then only include meta-signatures containing at least 5 taxa.
comb.fun	function. Function for combining sample size of the exposed group and sample size of the unexposed group into an overall study sample size. Defaults to sum which will simply add sample sizes of exposed and unexposed group.
...	additionals argument passed on to getSignatures.

Value

A list of meta-signatures, each meta-signature being a named numeric vector. Names are the taxa of the meta-signature, numeric values correspond to sample size weights associated with each taxon.

See Also

getSignatures

Examples

```
df <- importBugSigDB()

# Body-site specific meta-signatures composed from signatures reported as both
# increased or decreased across all conditions of study:
bs.meta.sigs <- getMetaSignatures(df, column = "Body site")
```

```
# Condition-specific meta-signatures from fecal samples, increased
# in conditions of study. Use taxonomic names instead of the default NCBI IDs:
df.feces <- df[df$`Body site` == "Feces", ]
cond.meta.sigs <- getMetaSignatures(df.feces, column = "Condition",
                                    direction = "UP", tax.id.type = "taxname")

# Inspect the results
names(cond.meta.sigs)
cond.meta.sigs["Bipolar disorder"]
```

`getOntology` *Obtain the EFO and UBERON ontology*

Description

Lightweight wrapper around `ontologyIndex::get_ontology` to parse the Experimental Factor Ontology (EFO) or the Uber-anatomy ontology (UBERON) from OBO format into an R object.

Usage

```
getOntology(onto = c("efo", "uberon"), cache = TRUE)
```

Arguments

`onto`	character. Ontology to obtain. Should be either `"efo"` (default) to obtain the Experimental Factor Ontology (EFO) or `"uberon"` to obtain the Uber-anatomy ontology (UBERON).
`cache`	logical. Should a locally cached version used if available? Defaults to `TRUE`.

Value

An object of class `ontology_index` as defined in the ontologyIndex package.

References

EFO: https://www.ebi.ac.uk/ols/ontologies/efo

UBERON: https://www.ebi.ac.uk/ols/ontologies/uberon

See Also

`get_ontology` from the ontologyIndex package.

Examples

```
uberon <- getOntology("uberon")
```

`getSignatures` *Obtain microbe signatures from BugSigDB*

Description

Functionality for obtaining microbe signatures from BugSigDB

Usage

```
getSignatures(
  df,
  tax.id.type = c("ncbi", "metaphlan", "taxname"),
  tax.level = "mixed",
  exact.tax.level = TRUE,
  min.size = 1
)
```

Arguments

`df`	`data.frame` storing BugSigDB data. Typically obtained via `importBugSigDB`. Rows of experiments without signatures, which have `NA` signature columns, are skipped.
`tax.id.type`	Character. Taxonomic ID type of the returned microbe sets. Either `"ncbi"` (default), `"metaphlan"`, or `"taxname"`.
`tax.level`	character. Either `"mixed"` or any subset of `c("kingdom", "phylum", "class", "order", "family", "genus", "species","strain")`. This full vector is equivalent to `"mixed"`.
`exact.tax.level`	logical. Should only the exact taxonomic level specified by `tax.level` be returned? Defaults to `TRUE`. If `FALSE`, a more general `tax.level` is extracted for microbes given at a more specific taxonomic level.
`min.size`	integer. Minimum signature size. Defaults to 1, which will filter out empty signature. Use `min.size = 0` to keep empty signatures.

Value

a `list` of microbe signatures. Each signature is a character vector of taxonomic IDs depending on the chosen `tax.id.type`.

References

BugSigDB: https://bugsigdb.org

See Also

importBugSigDB

Examples

```
df <- importBugSigDB()
sigs <- getSignatures(df)
```

`importBugSigDB` *Obtain published microbial signatures from bugsigdb.org*

Description

Obtain published microbial signatures from bugsigdb.org

Usage

```
importBugSigDB(version = "10.5281/zenodo.24379934", cache = TRUE)
```

Arguments

`version`	character. A Zenodo DOI, git commit hash, or "devel". Defaults to the most recent stable release on Zenodo, which includes complete and reviewed content from BugSigDB. See details.
`cache`	logical. Should a locally cached version used if available? Defaults to `TRUE`.

Details

There are three different options to obtain data from BugSigDB, as determined by the `version` argument.

- a Zenodo DOI: use this option if you would like to obtain one of the stable release versions of BugSigDB on Zenodo. These stable release versions of BugSigDB have been automatically checked and manually reviewed and provide for the highest data quality. Select this option if you would like to incorporate BugSigDB into analysis and published research. If not specified otherwise, the `importBugSigDB` function will obtain the most recent stable release from Zenodo by default.
- `"devel"`: use this option to obtain the latest version ("bleeding edge") of BugSigDB from the BugSigDBExports GitHub repo (see references). Note that this will also include incomplete and not reviewed content, which should be filtered out prior to an analysis. Select this option if you are a curator that actively contributes to BugSigDB and would like to access data that you and other curators have recently contributed to BugSigDB and that has not been included in a stable release yet.
- a git commit hash: it might be occasionally of interest to obtain a specific snapshot of the BugSigDBExports GitHub repo, e.g. for the sake of debugging and troubleshooting. This can be done by providing the short 7-character git commit hash (SHA) or the full SHA of the export of choice. To provide the full SHA, go to the BugSigDBExports commits page (see references) and use the copy symbol to the left of the 7-character codes to copy the full SHA code of the export version you want to use.

  Note: Zenodo DOIs for versions after 1.2.2, commit hashes after Feb 16, 2025, and `"devel"` will contain records where the PubMed ID is the Study ID if available.

Releases from v1.4.0 on differ from "devel" as follows:

- Releases exclude retracted studies, studies whose review found them incorrect, studies with neither a valid PMID nor a valid DOI, and signatures with no taxa resolved to an NCBI Taxonomy ID. "devel" still includes them: retracted studies are marked "Retracted paper" in the Quality control tag column, and incorrect studies have Review state "Incorrect".
- Releases include experiments without signatures from reviewed studies, which record a negative taxonomic result and alpha diversity. Their rows have NA signature columns, such as Signature page name, and getSignatures skips them.
- DOIs are normalized to the 10.xxxx/... form.

Study columns added in v1.4.0 and in "devel" exports since November 2026:

Curation method "Manual" or "Machine"; empty for most studies curated before it was introduced.

Curation protocol the methods page for machine-curated studies.

submittedBy, submissionDate the user and date of the first revision of the Study page.

Review state the state of the study's review on bugsigdb.org, e.g. "Reviewed" or "Incorrect".

Quality control tag quality control flags set by curators, e.g. "Retracted paper".

Value

a data.frame.

References

BugSigDB: https://bugsigdb.org

Stable release: https://doi.org/10.5281/zenodo.24379934

Latest version (incl. not reviewed content): https://github.com/waldronlab/BugSigDBExports

All releases: https://doi.org/10.5281/zenodo.19740649 (from v1.4.0) and https://doi.org/10.5281/zenodo.5606165 (up to v1.3.1)

Release v1.4.0: https://doi.org/10.5281/zenodo.24379934

Release v1.3.1: https://doi.org/10.5281/zenodo.19740674

Release v1.3.0: https://doi.org/10.5281/zenodo.15272273

Release v1.2.2: https://doi.org/10.5281/zenodo.13997429

Release v1.2.1: https://doi.org/10.5281/zenodo.10627578

Release v1.2.0: https://doi.org/10.5281/zenodo.10407666

Release v1.1.0: https://doi.org/10.5281/zenodo.6468009

Release v1.0.2: https://doi.org/10.5281/zenodo.5904281

Release v1.0.1: https://doi.org/10.5281/zenodo.5819260

Release v1.0.0: https://doi.org/10.5281/zenodo.5606166

BugSigDBExports commits page: https://github.com/waldronlab/BugSigDBExports/commits/devel

Examples

```
df <- importBugSigDB()
```

`restrictTaxLevel` *Restrict microbe signatures to specific taxonomic levels*

Description

Functionality for restricting microbe signatures to specific taxonomic levels such as genus and species.

Usage

```
restrictTaxLevel(df, tax.level = "mixed", exact.tax.level = TRUE, min.size = 1)
```

Arguments

`df`	`data.frame` storing BugSigDB data. Typically obtained via `importBugSigDB`.
`tax.level`	character. Either `"mixed"` or any subset of `c("kingdom", "phylum", "class", "order", "family", "genus", "species","strain")`. This full vector is equivalent to `"mixed"`.
`exact.tax.level`	logical. Should only the exact taxonomic level specified by `tax.level` be returned? Defaults to `TRUE`. If `FALSE`, a more general `tax.level` is extracted for microbes given at a more specific taxonomic level.
`min.size`	integer. Minimum signature size. Defaults to 1, which will filter out empty signatures. Use `min.size = 0` to keep empty signatures.

Value

a `data.frame` with microbe signature columns restricted to chosen taxonomic level(s).

References

BugSigDB: https://bugsigdb.org

See Also

importBugSigDB

Examples

```
df <- importBugSigDB()
df <- restrictTaxLevel(df, tax.level = "genus")
```

subsetByOntology *Ontology-based subsetting of BugSigDB signatures*

Description

This function facilitates ontology-based queries for experimental factors and body sites.

Usage

```
subsetByOntology(df, column = c("Body site", "Condition"), term, ontology)
```

Arguments

df	data.frame storing BugSigDB data. Typically obtained via importBugSigDB.
column	character. Column of df on which subsetting should be performed. Should be either "Body site" (default) or "Condition".
term	character. A valid term of ontology. Subsetting by this term then involves subsetting column to this term and all descendants of that term in the the chosen ontology and that are present in the chosen column of df.
ontology	an object of class ontology_index as defined in the ontologyIndex package. Typically obtained via getOntology.

Value

a data.frame with the chosen column restricted to descendants of the chosen term in the chosen ontology.

References

EFO: https://www.ebi.ac.uk/ols/ontologies/efo

UBERON: https://www.ebi.ac.uk/ols/ontologies/uberon

See Also

importBugSigDB, getOntology

Examples

```
# (1) Obtain BugSigDB data
df <- importBugSigDB()

# (2) Obtain ontology of interest as an R object
uberon <- getOntology("uberon")

# (3) High-level query on body site
sdf <- subsetByOntology(df,
                        column = "Body site",
```

```
                        term = "digestive system element",
                        ontology = uberon)
table(sdf[,"Body site"])
```

---

writeGMT *Write microbe signatures to file in GMT format*

Description

Functionality for writing microbe signatures to file in GMT format.

Usage

```
writeGMT(sigs, gmt.file, ...)
```

Arguments

sigs	A list of microbe signatures (character vectors of taxonomic IDs).
gmt.file	character. Path to output file in GMT format.
...	Arguments passed on to cat()

Value

none, writes to file.

References

GMT file format: http://www.broadinstitute.org/cancer/software/gsea/wiki/index.php/Data_formats

Examples

```
bsdb <- importBugSigDB()
sigs <- getSignatures(bsdb)
writeGMT(sigs, gmt.file = "signatures.gmt")
file.remove("signatures.gmt")
```

Index

browseSignature, 2
browseTaxon, 3

data.frame, *9*

extractTaxLevel, 3

getMetaSignatures, 4
getOntology, 6, *11*
getSignatures, *5*, 7, *9*

importBugSigDB, *5*, *7*, 8, *10, 11*

restrictTaxLevel, 10

subsetByOntology, 11

writeGMT, 12