

# Package: cellity (via r-universe)

May 29, 2026

**Type** Package

**Title** Quality Control for Single-Cell RNA-seq Data

**Version** 1.40.0

**Date** 2016-02-22

**Author** Tomislav Illicic, Davis McCarthy

**Maintainer** Tomislav Ilicic <t.i243@cam.ac.uk>

**Description** A support vector machine approach to identifying and filtering low quality cells from single-cell RNA-seq datasets.

**License** GPL (>= 2)

**Depends** R (>= 3.3)

**Imports** AnnotationDbi, e1071, ggplot2, graphics, grDevices, grid, mvoutlier, org.Hs.eg.db, org.Mm.eg.db, robustbase, stats, topGO, utils

**Suggests** BiocStyle, caret, knitr, testthat, rmarkdown

**VignetteBuilder** knitr

**LazyData** true

**biocViews** ImmunoOncology, RNASeq, QualityControl, Preprocessing, Normalization, Visualization, DimensionReduction, Transcriptomics, GeneExpression, Sequencing, Software, SupportVectorMachine

**RoxygenNote** 5.0.1

**Config/pak/sysreqs** libpng-dev libssl-dev zlib1g-dev

**Repository** <https://bioc-release.r-universe.dev>

**Date/Publication** 2026-04-28 12:42:44 UTC

**RemoteUrl** <https://github.com/bioc/cellity>

**RemoteRef** RELEASE\_3\_23

**RemoteSha** 796669fb4d96314c0ad2439fa87f1dc1bbdf61a4

## Contents

|                         |    |
|-------------------------|----|
| cellity-package         | 2  |
| assess_cell_quality_PCA | 2  |
| assess_cell_quality_SVM | 3  |
| extra_human_genes       | 4  |
| extra_mouse_genes       | 5  |
| extract_features        | 5  |
| feature_generation      | 6  |
| feature_info            | 7  |
| mES1_features           | 7  |
| mES1_labels             | 8  |
| multiplot               | 9  |
| normalise_by_factor     | 9  |
| param_mES_all           | 10 |
| param_mES_common        | 10 |
| plot_pca                | 11 |
| sample_counts           | 12 |
| sample_stats            | 12 |
| simple_cap              | 13 |
| sum_prop                | 13 |
| training_mES_features   | 14 |
| training_mES_labels     | 14 |
| uni.plot                | 15 |

|              |           |
|--------------|-----------|
| <b>Index</b> | <b>16</b> |
|--------------|-----------|

---

|                 |   |
|-----------------|---|
| cellity-package | <i>Quality Control for Single-Cell RNA-seq Data</i> |
|-----------------|---|

---

### Description

**cellity** provides a support vector machine and PCA approaches to identifying and filtering low quality cells from single-cell RNA-seq datasets.

---

|                         |  |
|-------------------------|--|
| assess_cell_quality_PCA | <i>ASSESS CELL QUALITY USING PCA AND OUTLIER DETECTION</i> |
|-------------------------|--|

---

### Description

ASSESS CELL QUALITY USING PCA AND OUTLIER DETECTION

### Usage

```
assess_cell_quality_PCA(features, file = "")
```

### Arguments

features            Input dataset containing features (cell x features)  
 file                Output\_file where plot is saved

### Details

This function applies PCA on features and uses outlier detection to determine which cells are low and which are high quality

### Value

Returns a dataframe indicating which cell is low or high quality (0 or 1 respectively)

### Examples

```
data(training_mES_features)
training_mES_features_all <- training_mES_features[[1]]
training_quality_PCA_allF <- assess_cell_quality_PCA(training_mES_features_all)
```

---

assess\_cell\_quality\_SVM

*Assess quality of a cell - SVM version*

---

### Description

Assess quality of a cell - SVM version

### Usage

```
assess_cell_quality_SVM(training_set_features, training_set_labels,
    ensemble_param, test_set_features)
```

### Arguments

training\_set\_features            A training set containing features (cells x features) for prediction  
 training\_set\_labels            Annotation of each individual cell if high or low quality (1 or 0 respectively)  
 ensemble\_param                Dataframe of parameters for SVM  
 test\_set\_features                Dataset to predict containing features (cells x features)

### Details

This function takes a training set + annotation to predict a test set. It requires that hyper-parameters have been optimised.

**Value**

Returns a dataframe indicating which cell is low or high quality (0 or 1 respectively)  
data.frame with decision on quality of cells

**Examples**

```
data(param_mES_all)
data(training_mES_features)
data(training_mES_labels)
data(mES1_features)
data(mES1_labels)
mES1_features_all <- mES1_features[[1]]
training_mES_features_all <- training_mES_features[[1]]
mES1_quality_SVM <- assess_cell_quality_SVM( training_mES_features_all,
training_mES_labels[,2], param_mES_all, mES1_features_all)
```

---

extra\_human\_genes      *Additional human genes that are used in feature extraction*

---

**Description**

This list contains human genes that are used for feature extraction of biological features

**Usage**

```
extra_human_genes
```

**Format**

a list containing vectors of genes. Name indicates which GO category.

**Value**

NULL, but makes available a list with metadata

**Author(s)**

Tomislav Ilicic & Davis McCarthy, 2015-03-05

**Source**

Wellcome Trust Sanger Institute

---

|                   |   |
|-------------------|---|
| extra_mouse_genes | <i>Additional mouse genes that are used in feature extraction</i> |
|-------------------|---|

---

**Description**

This list contains mouse genes that are used for feature extraction of biological features

**Usage**

```
extra_mouse_genes
```

**Format**

a list containing vectors of genes. Name indicates which GO category.

**Value**

NULL, but makes available a list with metadata

**Author(s)**

Tomislav Ilicic & Davis McCarthy, 2015-03-05

**Source**

Wellcome Trust Sanger Institute

---

|                  |   |
|------------------|---|
| extract_features | <i>Extracts biological and technical features for given dataset</i> |
|------------------|---|

---

**Description**

Extracts biological and technical features for given dataset

**Usage**

```
extract_features(counts_nm, read_metrics, prefix = "", output_dir = "",
  common_features = NULL, GO_terms = NULL, extra_genes = NULL,
  organism = "mouse")
```

**Arguments**

|                 |   |
|-----------------|---|
| counts_nm       | Gene expression counts dataframe (genes x cells). Either normalised by library size or TPM values |
| read_metrics    | Dataframe with mapping statistics produced by python pipeline                                     |
| prefix          | Prefix of outputfiles   |
| output_dir      | Output directory of files   |
| common_features | Subset of features that are applicable within one species, but across cell types                  |
| GO_terms        | DataFrame with gene ontology term IDs, that will be used in feature extraction                    |
| extra_genes     | Additional genes used for feature extraction  |
| organism        | The target organism to generate the features for  |

**Details**

This function takes a combination of gene counts and mapping statistics to extract biological and technical features, which than can be used for quality data analysis

**Value**

a list with two elements, one providing all features, and one providing common features.

**Examples**

```
data(sample_counts)
data(sample_stats)
sample_counts_nm <- normalise_by_factor(sample_counts, colSums(sample_counts))
sample_features <- extract_features(sample_counts_nm, sample_stats)
```

---

feature\_generation      *Helper Function to create all features*

---

**Description**

Helper Function to create all features

**Usage**

```
feature_generation(counts_nm, read_metrics, GO_terms, extra_genes, organism)
```

**Arguments**

|              |   |
|--------------|---|
| counts_nm    | Gene expression counts dataframe (genes x cells). Either normalised by library size or TPM values |
| read_metrics | Dataframe with mapping statistics produced by python pipeline                                     |
| GO_terms     | DataFrame with gene ontology term IDs, that will be used in feature extraction                    |
| extra_genes  | Additional genes used for feature extraction  |
| organism     | The target organism to generate the features for  |

**Value**

Returns the entire set of features in a data.frame

---

|              |  |
|--------------|--|
| feature_info | <i>Information which genes and GO categories should be included as features. Also defines which features are cell-type independent (common features)</i> |
|--------------|--|

---

**Description**

This list contains metadata information that is used to extract features from in the function extract\_features

**Usage**

```
feature_info
```

**Format**

a list with 2 elements (GO\_terms,common\_features).

**Value**

NULL, but makes available a list with metadata

**Author(s)**

Tomislav Ilicic & Davis McCarthy, 2015-03-05

**Source**

Wellcome Trust Sanger Institute

---

|               |   |
|---------------|---|
| mES1_features | <i>Real test dataset containing all and common features from the paper (mESI)</i> |
|---------------|---|

---

**Description**

This list contains 2 dataframes where each contains features per cell (cell X features) that can be used for classification.

**Usage**

```
mES1_features
```

**Format**

a list with 2 elements (all\_features, common\_features).

**Value**

NULL, but makes available a list with 2 dataframes

**Author(s)**

Tomislav Ilicic & Davis McCarthy, 2015-03-05

**Source**

Wellcome Trust Sanger Institute

---

mES1\_labels

*Real test dataset containing annotation of cells*

---

**Description**

This data frame has 2 columns: First showing cell names, the second indicating if cell is of low (0) or high (1) quality

**Usage**

```
mES1_labels
```

**Format**

a dataframe with 2 columns (cell\_names, label).

**Value**

NULL, but makes available a dataframe with cell annotations

**Author(s)**

Tomislav Ilicic & Davis McCarthy, 2015-03-05

**Source**

Wellcome Trust Sanger Institute

---

|           |   |
|-----------|---|
| multiplot | <i>Internal multiplot function to combine plots onto a grid</i> |
|-----------|---|

---

**Description**

Internal multiplot function to combine plots onto a grid

**Usage**

```
multiplot(..., plotlist = NULL, file, cols = 6, layout = NULL)
```

**Arguments**

|          |   |
|----------|---|
| ...      | individual plots to combine into a single plot              |
| plotlist | a vector with names of plots to use in the plot             |
| file     | string giving filename to which pdf of plots is to be saved |
| cols     | integer giving number of columns for the plot               |
| layout   | matrix defining the layout for the plots                    |

**Value**

a plot object

---

|                     |   |
|---------------------|---|
| normalise_by_factor | <i>Internal function to normalize by library size</i> |
|---------------------|---|

---

**Description**

Internal function to normalize by library size

**Usage**

```
normalise_by_factor(counts, norm_factor)
```

**Arguments**

|             |                                 |
|-------------|---------------------------------|
| counts      | matrix of counts                |
| norm_factor | vector of normalisation factors |

**Value**

a matrix with normalized gene counts

**Examples**

```
data(sample_counts)
data(sample_stats)
sample_counts_nm <- normalise_by_factor(sample_counts, colSums(sample_counts))
```

---

param\_mES\_all      *Parameters used for SVM classification*

---

**Description**

This data frame has 3 columns: gamma, cost, class.weights and is optimised for all features and our training data

**Usage**

```
param_mES_all
```

**Format**

a dataframe with 3 columns (gamma, cost, class.weights).

**Value**

NULL, but makes available a dataframe with parameters

**Author(s)**

Tomislav Ilicic & Davis McCarthy, 2015-03-05

**Source**

Wellcome Trust Sanger Institute

---

param\_mES\_common      *Parameters used for SVM classification*

---

**Description**

This data frame has 3 columns: gamma, cost, class.weights and is optimised for common features and our training data

**Usage**

```
param_mES_common
```

**Format**

a dataframe with 3 columns (gamma, cost, class.weights).

**Value**

NULL, but makes available a dataframe with parameters

**Author(s)**

Tomislav Ilicic & Davis McCarthy, 2015-03-05

**Source**

Wellcome Trust Sanger Institute

---

|          |   |
|----------|---|
| plot_pca | <i>Plots PCA of all features. Colors high and low quality cells based on outlier detection.</i> |
|----------|---|

---

**Description**

Plots PCA of all features. Colors high and low quality cells based on outlier detection.

**Usage**

```
plot_pca(features, annot, pca, col, output_file)
```

**Arguments**

|             |  |
|-------------|--|
| features    | Input dataset containing features (cell x features)              |
| annot       | Matrix annotation of each cell                                   |
| pca         | PCA of features  |
| col         | color code indicating what color high and what low quality cells |
| output_file | where plot is stored   |

**Details**

This function plots PCA of all features + most informative features

**Value**

Plots of PCA

---

|               |  |
|---------------|--|
| sample_counts | <i>Sample gene expression data containing 40 cells</i> |
|---------------|--|

---

**Description**

This data frame contains genes (rows) and cells (columns) showing raw read counts

**Usage**

```
sample_counts
```

**Format**

a dataframe with genes x cells

**Value**

NULL, but makes available a dataframe with raw read counts

**Author(s)**

Tomislav Ilicic & Davis McCarthy, 2015-03-05

**Source**

Wellcome Trust Sanger Institute

---

|              |  |
|--------------|--|
| sample_stats | <i>Sample read statistics data containing 40 cells</i> |
|--------------|--|

---

**Description**

This data frame contains read metrics (columns) and cells (rows)

**Usage**

```
sample_stats
```

**Format**

a dataframe with cells x metrics

**Value**

NULL, but makes available a dataframe with read statistics

**Author(s)**

Tomislav Ilicic & Davis McCarthy, 2015-03-05

**Source**

Wellcome Trust Sanger Institute

---

simple\_cap                      *Converts all first letters to capital letters*

---

**Description**

Converts all first letters to capital letters

**Usage**

simple\_cap(x)

**Arguments**

x                      string

**Value**

a character vector in title case

---

sum\_prop                      *Sums up normalised values of genes to groups.*

---

**Description**

Supports TPM and proportion of mapped reads.

**Usage**

sum\_prop(counts, genes\_interest)

**Arguments**

counts                      Normalised gene expression count matrix  
genes\_interest      dataframe of genes of interest to merge

**Value**

a vector of sums per group

---

training\_mES\_features *Original training dataset containing all and common features from the paper (training mES)*

---

**Description**

This list contains 2 dataframes where each contains features per cell (cell X features) that can be used for classification.

**Usage**

```
training_mES_features
```

**Format**

a list with 2 elements (all\_features, common\_features).

**Value**

NULL, but makes available a list with 2 dataframes

**Author(s)**

Tomislav Ilicic & Davis McCarthy, 2015-03-05

**Source**

Wellcome Trust Sanger Institute

---

training\_mES\_labels *Original training dataset containing annotation of cells*

---

**Description**

This data frame has 2 columns: First showing cell names, the second indicating if cell is of low (0) or high (1) quality

**Usage**

```
training_mES_labels
```

**Format**

a dataframe with 2 columns (cell\_names, label).

**Value**

NULL, but makes available a dataframe with cell annotations

**Author(s)**

Tomislav Ilicic & Davis McCarthy, 2015-03-05

**Source**

Wellcome Trust Sanger Institute

---

|          |  |
|----------|--|
| uni.plot | <i>Internal function to detect outliers from the mvoutlier package Modified slightly so that plots are not printed</i> |
|----------|--|

---

**Description**

Internal function to detect outliers from the mvoutlier package Modified slightly so that plots are not printed

**Usage**

```
uni.plot(x, symb = FALSE, quan = 1/2, alpha = 0.025)
```

**Arguments**

|       |                            |
|-------|----------------------------|
| x     | A matrix containing counts |
| symb  | Symbols                    |
| quan  | quan                       |
| alpha | alpha                      |

**Value**

a list of outlier indicators

# Index

`assess_cell_quality_PCA`, 2  
`assess_cell_quality_SVM`, 3

`cellity-package`, 2

`extra_human_genes`, 4  
`extra_mouse_genes`, 5  
`extract_features`, 5

`feature_generation`, 6  
`feature_info`, 7

`mES1_features`, 7  
`mES1_labels`, 8  
`multiplot`, 9

`normalise_by_factor`, 9

`param_mES_all`, 10  
`param_mES_common`, 10  
`plot_pca`, 11

`sample_counts`, 12  
`sample_stats`, 12  
`simple_cap`, 13  
`sum_prop`, 13

`training_mES_features`, 14  
`training_mES_labels`, 14

`uni.plot`, 15