

Package: cleanUpdTSeq (via r-universe)

June 14, 2026

Type Package

Title cleanUpdTSeq cleans up artifacts from polyadenylation sites from oligo(dT)-mediated 3' end RNA sequencing data

Description This package implements a Naive Bayes classifier for accurately differentiating true polyadenylation sites (pA sites) from oligo(dT)-mediated 3' end sequencing such as PAS-Seq, PolyA-Seq and RNA-Seq by filtering out false polyadenylation sites, mainly due to oligo(dT)-mediated internal priming during reverse transcription. The classifier is highly accurate and outperforms other heuristic methods.

Version 1.50.0

Date 2025-07-22

Author Sarah Sheppard, Haibo Liu, Jianhong Ou, Nathan Lawson, Lihua Julie Zhu

Maintainer Jianhong Ou <jou@morgridge.org>; Lihua Julie Zhu <Julie.Zhu@umassmed.edu>

Depends R (>= 3.5.0), BSgenome.Drerio.UCSC.danRer7, methods

Imports BSgenome, GenomicRanges, seqinr, e1071, Biostrings, Seqinfo, IRanges, utils, stringr, stats, S4Vectors

Suggests BiocStyle, rmarkdown, knitr, RUnit, BiocGenerics (>= 0.1.0)

License GPL-2

biocViews Sequencing, 3' end sequencing, polyadenylation site, internal priming

VignetteBuilder knitr

RoxygenNote 7.1.2

LazyData true

Encoding UTF-8

Config/pak/sysreqs

make libbz2-dev libicu-dev liblzma-dev libxml2-dev libssl-dev xz-utils zlib1g-dev

Repository <https://bioc-release.r-universe.dev>

Date/Publication 2026-04-28 12:37:54 UTC

RemoteUrl <https://github.com/bioc/cleanUpdTSeq>

RemoteRef RELEASE_3_23

RemoteSha 549b1e2a5af14deb7d545927030d6eb448d8d92c

Contents

BED6WithSeq2GRangesSeq	2
buildClassifier	3
buildFeatureVector	5
classifier	7
cleanUpdTSeq	7
data.NaiveBayes	8
featureVector-class	9
getContextSequences	9
modelInfo-class	10
naiveBayes-class	10
PASClassifier-class	11
predictTestSet	11
Index	14

BED6WithSeq2GRangesSeq

Covert (extended) BED6 file to a GRanges object

Description

Convert to a GRanges object from a (extended) BED6 file with at least six columns: chrom, chromStart, strEnd, name, score and strand, and optional upstream sequences (including pA sites) and downstream sequences of pA sites

Usage

```
BED6WithSeq2GRangesSeq(
  file,
  skip = 1L,
  withSeq = TRUE,
  upstream.seq.ind = 7L,
  downstream.seq.ind = 8L
)
```

Arguments

file	A character(1) vector, representing a path to a extended BED file containing at least six columns in the order of chrom, chromStart, strEnd, name, score and strand. The strand information must be designated as "+", or "-". Optional fields—upstream sequences (including pA sites) and downstream sequences of pA sites—are allowed. For more details about the BED format, see https://genome.ucsc.edu/FAQ/FAQformat
skip	A integer(1) vector, indicating how many rows (header lines) to skip when the BED file is read into R.
withSeq	A logical(1) vector, indicating that upstream and downstream sequences flanking pA sites are included in the file
upstream.seq.ind	An integer(1),vector delineating the column location of upstream sequences of the putative pA site
downstream.seq.ind	An integer(1),vector delineating the column location of downstream sequences of the putative pA site

Value

An object of GRanges

Author(s)

Haibo Liu, Lihua J. Zhu

Examples

```
testFile <- system.file("extdata", "test.bed",
                        package = "cleanUpdTSeq")
peaks <- BED6WithSeq2GRangesSeq(file = testFile,
                                skip = 1L, withSeq = TRUE)
```

buildClassifier

Build a Naive Bayes Classifier

Description

Computes the conditional a-posterior probabilities of a categorical class variable given independent predictor variables using the Bayes rule.

 buildFeatureVector *build Feature Vector_2*

Description

This function creates a data frame. Fields include peak name, upstream sequence, downstream sequence, and features to be used in classifying the putative polyadenylation site.

Usage

```
buildFeatureVector(
  peaks,
  genome = Drerio,
  upstream = 40L,
  downstream = 30L,
  wordSize = 6L,
  alphabet = "ACGT",
  sampleType = c("TP", "TN", "unknown"),
  replaceNAdistance = 30L,
  method = c("NaiveBayes", "SVM"),
  fetchSeq = FALSE,
  return_sequences = FALSE
)
```

Arguments

peaks	An object of GRanges that may contain the upstream and downstream sequence information. This item is created by the function BED6WithSeq2GRangesSeq .
genome	Name of the genome to get sequences from. To find out a list of available genomes, please type <code>BSgenome::available.genomes()</code> in R.
upstream	An integer(1) vector, length of upstream sequence to retrieve.
downstream	An integer(1) vector, length of downstream sequence to retrieve.
wordSize	An integer(1) vector, size of the kmer feature for the upstream sequence. wordSize = 6 should always be used.
alphabet	A character(1) vector, a string containing DNA bases. By default, "ACTG".
sampleType	A character(1) vector, indicating type of sequences for building feature vectors. Options are TP (true positive) and TN (true negative) for training data, or unknown for test data.
replaceNAdistance	An integer(1) vector, specifying an number for <code>avg.distanceA2PeakEnd</code> , the average distance of As to the putative pA site, when there is no A in the downstream sequence.
method	A character(1) vector, specifying a machine learning method to to use. Currently, only "NaiveBayes" is implemented.

classifier	<i>NaiveBayes classifier</i>
------------	------------------------------

Description

An object of class "naiveBayes" generated from data.NaiveBayes

Usage

```
classifier
```

Format

An object of class "[PASclassifier](#)" including components:

Examples

```
data(classifier)
names(classifier)
```

cleanUpdTSeq	<i>This package classifies putative polyadenylation sites.</i>
--------------	--

Description

3'ends of transcripts have generally been poorly annotated. With the advent of deep sequencing, many methods have been developed to identify 3'ends. The majority of these methods use an oligodT primer which can bind to internal adenine-rich sequences, and lead to artifactual identification of polyadenylation sites. Heuristic filtering methods rely on a certain number of As downstream of a putative polyadenylation site to classify the site as true or oligodT primed. This package provides a robust method to classify putative polyadenylation sites using a Naive Bayes classifier.

Author(s)

Sarah Sheppard, Haibo Liu, Jianhong Ou, Nathan Lawson, Lihua Julie Zhu

data.NaiveBayes *Training Data*

Description

A RData containing negative and positive training data

Usage

```
data.NaiveBayes
```

Format

A list with 2 data frame, "Negative" and "Positive". Negative has 9219 observations on the following 4120 variables. And Positive is a data frame with 22770 observations on the following 4120 variables. The format is:

list("Negative") 'data.frame': 9219 obs. of 4120 variables:

list("Positive") 'data.frame': 22770 obs. of 4120 variables:

Both of them have same structure.

list("y") a numeric vector

list("n.A.Downstream") a numeric vector

list("n.C.Downstream") a numeric vector

list("n.T.Downstream") a numeric vector

list("n.G.Downstream") a numeric vector

list("avg.distanceA2PeakEnd") a numeric vector

list("dimer") a numeric vector

: such as AA, AC, AG, AT, CA, ... etc. a numeric vector

list("heximer") a factor with levels 0 1

: such as AAAAAA, ACGTAC, ... etc. a factor with levels 0 1

list("upstream.seq") a vector of sequence string

list("downstream.seq") a vector of sequence string

Examples

```
library(BSgenome.Drerio.UCSC.danRer7)
data(data.NaiveBayes)
head(str(data.NaiveBayes$Negative))
head(str(data.NaiveBayes$Positive))
```

featureVector-class *Class "featureVector"*

Description

An object of class "featureVector" represents the output of `buildFeatureVector`

Objects from the Class

Objects can be created by calls of the form `new("featureVector", data, info)`.

`getContextSequences` *Retrieve upstream and downstream sequences*

Description

Retrieve upstream and downstream sequences of pA sites from a BSgenome object based on a GRanges object

Usage

```
getContextSequences(peaks, upstream = 40L, downstream = 30L, genome)
```

Arguments

<code>peaks</code>	An object of GRanges representing pA sites
<code>upstream</code>	An integer(1) vector, length of upstream sequence of pA sites, including pA site.
<code>downstream</code>	An integer(1) vector, length of downstream sequences of pA sites
<code>genome</code>	An object of BSgenome.

Value

A data.frame containing sequences upstream and downstream pA sites:

upstream.seq sequence upstream pA site, including pA site

downstream.seq sequence downstream pA site

Author(s)

Haibo Liu

Examples

```

library(BSgenome.Drerio.UCSC.danRer7)
testFile <- system.file("extdata", "test.bed",
                        package = "cleanUpdTSeq")
peaks <- BED6WithSeq2GRangesSeq(file = testFile,
                                skip = 1L, withSeq = FALSE)
peaks_seq <- getContextSequences(peaks,
                                upstream = 40L,
                                downstream = 30L,
                                genome = Drerio)

```

modelInfo-class	Class "modelInfo"
-----------------	-------------------

Description

An object of class "modelInfo" represents the information of sequence to use in the analysis

Objects from the Class

Objects can be created by calls of the form `new("modelInfo", upstream, downstream, wordSize, alphabet)`.

naiveBayes-class	Class "naiveBayes"
------------------	--------------------

Description

An object of class "naiveBayes" represents the conditional a-posterior probabilities of a categorical class variable given independent predictor variables using the Bayes rule.

Objects from the Class

Objects can be created by calls of the form `new("naiveBayes", apriori, tables, levels, call)`.

PASclassifier-class *Class "PASclassifier"*

Description

An object of class "PASclassifier" represents the output of `buildClassifier`

Objects from the Class

Objects can be created by calls of the form `new("PASclassifier", classifier, info)`.

Examples

```
data(classifier)
classifier$info$upstream
classifier$info$wordSize
classifier$info$alphabet
```

`predictTestSet` *predict authenticity of putative pA sites*

Description

classify putative pA sites into true and false bins.

Usage

```
predictTestSet(
  Ndata.NaiveBayes = NULL,
  Pdata.NaiveBayes = NULL,
  testSet.NaiveBayes,
  classifier = NULL,
  outputFile = "test-predNaiveBayes.tsv",
  assignmentCutoff = 0.5,
  return_sequences = FALSE
)
```

Arguments

`Ndata.NaiveBayes`

A data.frame, containing features for the negative training data, which is built using the function `buildFeatureVector`. It is described further in `data.NaiveBayes`.

`Pdata.NaiveBayes`

A data.frame, containing features for the positive training data, which is built using the function `buildFeatureVector`. It is described further in `data.NaiveBayes`.

testSet.NaiveBayes
 An object of `featureVector` for test data built for Naive Bayes analysis using the function `buildFeatureVector`.

classifier
 An object of class `PASClassifier`.

outputFile
 A character(1) vector, file name for outputting prediction results. The prediction output is written to the file, tab separated.

assignmentCutoff
 A numeric(1) vector, specifying the cutoff for classifying a putative pA site into a true or false pA class. It should be any number between 0 and 1. For example, `assignmentCutoff = 0.5` will assign an putative pA site with `prob_true_pA > 0.5` to the True class (1), and any putative pA site with `prob_true_pA <= 0.5` as False (0).

return_sequences
 A logical(1) vector, indicating whether upstream and downstream sequences should be included in the output

Value

A data.frame including all info as described below. The upstream and downstream sequence used in assessing the putative pA site might be included when `return_sequences = TRUE`.

peak_name the name of the putative pA site (originally from the 4th field in the bed file).
 prob_fake_pA the probability that the putative pA site is false
 prob_true_pA the probability that the putative pA site is true
 pred_class the predicted class of the putative pA site, based on the assignment cutoff. 0 = False/oligo(dT) internally primed, 1 = True
 upstream_seq the upstream sequence of the putative pA site used in the analysis
 downstream_seq the downstream sequence of the putative pA site used in the analysis.

Author(s)

Sarah Sheppard, Haibo Liu, Jianhong Ou, Nathan Lawson, Lihua J. Zhu

References

Sheppard S, Lawson ND, Zhu LJ. Accurate identification of polyadenylation sites from 3' end deep sequencing using a naive Bayes classifier. *Bioinformatics*. 2013;29(20):2564-2571.

Examples

```
library(BSgenome.Drerio.UCSC.danRer7)
testFile <- system.file("extdata", "test.bed",
                        package = "cleanUpdTSeq")
## convert the test set to GRanges without upstream and downstream sequence
## information
peaks <- BED6WithSeq2GRangesSeq(file = testFile,
                                skip = 1L, withSeq = TRUE)
## build the feature vector for the test set without sequence information
```

```
testSet.NaiveBayes = buildFeatureVector(peaks,
                                       genome = Drerio,
                                       upstream = 40L,
                                       downstream = 30L,
                                       wordSize = 6L,
                                       alphabet = c("ACGT"),
                                       sampleType = "unknown",
                                       replaceNAdistance = 30,
                                       method = "NaiveBayes",
                                       fetchSeq = TRUE,
                                       return_sequences = TRUE)

data(data.NaiveBayes)
## sample the test data for code testing, DO NOT do this for real data
samp <- c(1:22, sample(23:4118, 50), 4119, 4120)
Ndata.NaiveBayes <- data.NaiveBayes$Negative[, samp]
Pdata.NaiveBayes <- data.NaiveBayes$Positive[, samp]
testSet.NaiveBayes@data <- testSet.NaiveBayes@data[, samp[-1]-1]

test_out <- predictTestSet(Ndata.NaiveBayes,
                           Pdata.NaiveBayes,
                           testSet.NaiveBayes,
                           outputFile = tempfile(),
                           assignmentCutoff = 0.5)
```

Index

- * **classes**
 - featureVector-class, [9](#)
 - modelInfo-class, [10](#)
 - naiveBayes-class, [10](#)
 - PASClassifier-class, [11](#)
- * **datasets**
 - classifier, [7](#)
 - data.NaiveBayes, [8](#)
- \$,PASClassifier-method
 - (PASClassifier-class), [11](#)
- \$,featureVector-method
 - (featureVector-class), [9](#)
- \$,modelInfo-method (modelInfo-class), [10](#)
- \$,naiveBayes-method (naiveBayes-class), [10](#)
- \$<-,PASClassifier-method
 - (PASClassifier-class), [11](#)
- \$<-,featureVector-method
 - (featureVector-class), [9](#)
- \$<-,modelInfo-method (modelInfo-class), [10](#)
- \$<-,naiveBayes-method
 - (naiveBayes-class), [10](#)

- BED6WithSeq2GRangesSeq, [2](#), [5](#)
- buildClassifier, [3](#), [11](#)
- buildFeatureVector, [5](#), [9](#), [11](#), [12](#)

- classifier, [7](#)
- cleanUpdTSeq, [7](#)
- cleanUpdTSeq-package (cleanUpdTSeq), [7](#)

- data.NaiveBayes, [4](#), [8](#), [11](#)

- featureVector, [6](#), [12](#)
- featureVector (featureVector-class), [9](#)
- featureVector-class, [9](#)

- getContextSequences, [9](#)

- modelInfo (modelInfo-class), [10](#)

- modelInfo-class, [10](#)

- naiveBayes, [4](#)
- naiveBayes (naiveBayes-class), [10](#)
- naiveBayes-class, [10](#)

- PASClassifier, [7](#), [12](#)
- PASClassifier (PASClassifier-class), [11](#)
- PASClassifier-class, [11](#)
- predictTestSet, [11](#)