

Package: convert (via r-universe)

June 3, 2026

Version 1.88.0

Title Convert Microarray Data Objects

Author Gordon Smyth <smyth@wehi.edu.au>, James Wettenhall
<wettenhall@wehi.edu.au>, Yee Hwa (Jean Yang)
<jean@biostat.ucsf.edu>, Martin Morgan
<Martin.Morgan@RoswellPark.org>

Maintainer Yee Hwa (Jean) Yang <jean@biostat.ucsf.edu>

Depends R (>= 2.6.0), Biobase (>= 1.15.33), limma (>= 1.7.0), marray,
utils, methods

Description Define coerce methods for microarray data objects.

License LGPL

URL <http://bioinf.wehi.edu.au/limma/convert.html>

biocViews Infrastructure, Microarray, TwoChannel

Repository <https://bioc-release.r-universe.dev>

Date/Publication 2026-04-28 12:30:36 UTC

RemoteUrl <https://github.com/bioc/convert>

RemoteRef RELEASE_3_23

RemoteSha 45d3a7bf886d97e6b313b3c54b2dbb518e6c5413

Contents

coerce	2
Index	4

 coerce

Convert Data Objects

Description

Convert between limma, marray and Biobase data objects.

Details

Objects can be converted (coerced) from one class to another using `as(object, Class)` where `object` is an object to convert and `Class` is the name of the class to convert to. The following conversions are provided:

From:	To:
RGList	marrayRaw
marrayRaw	RGList
MAList	marrayNorm
marrayNorm	MAList
RGList	NChannelSet
marrayRaw	NChannelSet
MAList	ExpressionSet
marrayNorm	ExpressionSet

RGList and marrayRaw are coerced to NChannelSet. Channel values are not transformed.

MAList and marrayNorm are coerced so that the ExpressionSet slot contains log-ratios (M-values) and the ExpressionSet object has the same number of columns as the original object. In this case, information on the A-values is lost.

There is intentionally no conversion from RGList or marrayRaw to ExpressionSet, as ExpressionSet is intended for expression values, not intensities.

Author(s)

Gordon Smyth and others

See Also

[as](#) in the methods package.

Examples

```
##first set up some fake intensity matrices
testRed <- matrix(rnorm(5*2),5,2,
  dimnames=list(paste("gene",1:5, sep=""), c("S1", "S2")))
testGreen <- matrix(rnorm(5*2),5,2,
  dimnames=list(paste("gene",1:5, sep=""), c("S1", "S2")))
```

```
##some sample/target info
testTarget <- data.frame(slide=c("S1", "S2"), Cy3=c("T", "C"),
  Cy5=c("C", "T"), row.names=c("S1", "S2"))

maT <- new("marrayInfo", maLabels=c("S1", "S2"),
  maInfo= testTarget)

##now create instances and convert
x <- new("RGList")
x$R <- testRed
x$G <- testGreen
y <- as(x,"marrayRaw")
z <- as(x, "NChannelSet")

x <- new("marrayRaw")
x@maGf <- testGreen
x@maRf <- testRed
x@maTargets = maT
y <- as(x,"RGList")
z <- as(x, "NChannelSet")

x <- new("MArrayList")
y <- as(x,"marrayNorm")

##we construct a reasonably complete fake, small
##instance of the marrayNorm class
x <- new("marrayNorm")
x@maM <- testRed
x@maA <- testGreen
maTargets(x) = maT
y <- as(x,"MArrayList")
y <- as(x, "ExpressionSet")

x <- new("MArrayList")
x$M <- testRed
x$A <- testGreen
x$targets <- testTarget
y <- as(x,"ExpressionSet")
```

Index

* **classes**

coerce, [2](#)

* **data**

coerce, [2](#)

as, [2](#)

coerce, [2](#)

coerce, MAList, ExpressionSet-method
(coerce), [2](#)

coerce, MAList, marrayNorm-method
(coerce), [2](#)

coerce, marrayNorm, ExpressionSet-method
(coerce), [2](#)

coerce, marrayNorm, MAList-method
(coerce), [2](#)

coerce, marrayRaw, NChannelSet-method
(coerce), [2](#)

coerce, marrayRaw, RGList-method
(coerce), [2](#)

coerce, RGList, marrayRaw-method
(coerce), [2](#)

coerce, RGList, NChannelSet-method
(coerce), [2](#)

convert (coerce), [2](#)