Package: eisaR (via r-universe)

November 25, 2026

Title Exon-Intron Split Analysis (EISA) in R

Version 1.26.0

Description Exon-intron split analysis (EISA) uses ordinary RNA-seq data to measure changes in mature RNA and pre-mRNA reads across different experimental conditions to quantify transcriptional and post-transcriptional regulation of gene expression. For details see Gaidatzis et al., Nat Biotechnol 2015. doi: 10.1038/nbt.3269. eisaR implements the major steps of EISA in R.

Depends R (>= 4.1)

License GPL-3

biocViews Transcription, GeneExpression, GeneRegulation, FunctionalGenomics, Transcriptomics, Regression, RNASeq

Encoding UTF-8

Roxygen list(markdown = TRUE)

Suggests knitr, rmarkdown, testthat, BiocStyle, QuasR, Rbowtie, Rhisat2, Biostrings, BSgenome, BSgenome.Hsapiens.UCSC.hg38, ensembldb, AnnotationDbi, GenomicFeatures, txdbmaker, rtracklayer, withr

VignetteBuilder knitr

Imports stats, GenomicRanges, S4Vectors, IRanges, limma, edgeR (>= 4.0), methods, SummarizedExperiment, BiocGenerics, utils, ggplot2, rlang

URL https://github.com/fmicompbio/eisaR

BugReports https://github.com/fmicompbio/eisaR/issues

Config/roxygen2/version 8.0.0

Config/pak/sysreqs zlib1g-dev

Repository Bioconductor 3.24

Date/Publication 2026-11-23 22:44:11 UTC

RemoteUrl https://github.com/bioc/eisaR

RemoteRef RELEASE_3_24

RemoteSha 110d749fbb3101fa3fe9b88cc7035d4be42b436a

Contents

exportToGtf 2
getFeatureRanges 3
getRegionsFromTxDb 5
getTx2Gene 6
plotEISA 7
runEISA 8

Index **12**

`exportToGtf` *Export GRangesList to GTF*

Description

Export the features in a GRangesList generated by `getFeatureRanges` to a GTF file. The function will represent each row of each of the entries as an "exon", each individual entry as a "transcript", and aggregate all features belonging to the same gene as a "gene" entry in the GTF file.

Usage

```
exportToGtf(grl, filepath)
```

Arguments

`grl`	`GRangesList` object, typically generated by `getFeatureRanges`
`filepath`	Path to output GTF file

Value

Does not return anything, generates a GTF file

Author(s)

Charlotte Soneson

Examples

```
## Get feature ranges
grl <- getFeatureRanges(
  gtf = system.file("extdata/small_example.gtf", package = "eisaR"),
  featureType = c("spliced", "intron"),
  intronType = "separate",
  flankLength = 5L,
  joinOverlappingIntrons = FALSE,
  verbose = TRUE
)

## Export GTF
exportToGtf(grl = grl, filepath = file.path(tempdir(), "exported.gtf"))
```

`getFeatureRanges` *Generate a GRangesList object with feature ranges*

Description

Generate a GRangesList object with genomic ranges for (any combination of) spliced transcripts, unspliced transcripts and introns.

Usage

```
getFeatureRanges(
  gtf,
  featureType = c("spliced", "intron"),
  intronType = "separate",
  flankLength = 90L,
  joinOverlappingIntrons = FALSE,
  collapseIntronsByGene = FALSE,
  keepIntronInFeature = FALSE,
  verbose = TRUE
)
```

Arguments

`gtf`	Path to gtf file.
`featureType`	Character vector indicating the type(s) of features to extract, any subset of `c("spliced", "intron", "unspliced")`.
`intronType`	Character vector indicating how to define the introns (only used if "intron" is part of `featureType`). Has to be either "separate" (introns are defined for each transcript separately) or "collapse" (transcripts of the same gene are first collapsed before introns are defined as any non-exonic part of the gene locus).
`flankLength`	Integer scalar indicating the length of the flanking sequence added to each side of each extracted intron (only used if "intron" is included in `featureType`).

joinOverlappingIntrons
: Logical scalar indicating whether two introns that overlap (after adding the flanking sequences) should be joined into one feature.

collapseIntronsByGene
: Logical scalar indicating whether to collapse overlapping intron ranges by gene after extraction.

keepIntronInFeature
: Logical scalar indicating whether introns (after adding the flank length) should be restricted to stay within the boundaries of the feature they were generated from. For backwards compatibility, the default is FALSE.

verbose
: Logical scalar, whether to print out progress messages.

Value

Returns a GRangesList object where each element represents one extracted feature. The metadata of this object contains two data.frames mapping corresponding identifiers between the different feature types, as well as a list of all features for each type.

Author(s)

Charlotte Soneson

Examples

```
## Get feature ranges
grl <- getFeatureRanges(
  gtf = system.file("extdata/small_example.gtf", package = "eisaR"),
  featureType = c("spliced", "intron"),
  intronType = "separate",
  flankLength = 5L,
  joinOverlappingIntrons = FALSE,
  collapseIntronsByGene = FALSE,
  verbose = TRUE
)

## GRangesList
grl

## Corresponding transcript/gene IDs
S4Vectors::metadata(grl)$corrtx
S4Vectors::metadata(grl)$corrgene

## List of features of different types
S4Vectors::metadata(grl)$featurelist

## Get feature sequences
if (requireNamespace("BSgenome", quietly = TRUE) &&
    requireNamespace("GenomicFeatures", quietly = TRUE)) {
  library(BSgenome)
  genome <- Biostrings::readDNAStringSet(
    system.file("extdata/small_example_genome.fa", package = "eisaR"))
```

```
  seqs <- GenomicFeatures::extractTranscriptSeqs(x = genome,
                                                 transcripts = grl)
  seqs
}
```

`getRegionsFromTxDb` *Get exonic/gene body regions from a transcript database.*

Description

From a transcript database package (TxDb), extract exonic and gene body ranges for use with EISA. These regions can be used to quantify RNA-seq alignments in exons and gene bodies, respectively. Intronic counts can then be obtained from the difference between gene bodies and exonic region counts.

Usage

```
getRegionsFromTxDb(txdb, exonExt = 10L, strandedData = TRUE)
```

Arguments

`txdb`	a `TxDb` or an `EnsDb` object with the transcript annotations.
`exonExt`	`numeric` (default = 10L). Exonic ranges will be extended on either side by this many nucleotides, in order to avoid "bleed-over" of exonic alignments into adjacent intronic regions.
`strandedData`	`logical(1)`. If `TRUE`, the RNA-seq data is assumed to be strand-specific, and therefore only overlapping genes that are on the same strand will be filtered out. If `FALSE`, also genes overlapping on opposite strands will be filtered out.

Details

The exonic regions are generated as follows:

1. extract exons by gene from the `txdb`
2. extend each exon by `exonExt`
3. combine overlapping exons within each gene
4. create gene body ranges from the most extreme exonic coordinates
5. filter out genes that have only a single exon (no intron), have exons on more than a single chromosome or on both strands, or that overlap other genes

Value

a `list` with elements "exons" and "genebodies", containing named `GenomicRanges` objects with ranges for exons and gene bodies, respectively.

Author(s)

Michael Stadler

See Also

TxDb for details on TxDb objects and the txdbmaker package for how to create them, e.g. from .gtf files.

Examples

```
if (requireNamespace("AnnotationDbi", quietly = TRUE)) {
   txdb <- AnnotationDbi::loadDb(system.file("extdata", "hg19sub.sqlite", package = "eisaR"))
    regL <- getRegionsFromTxDb(txdb)
    lengths(regL)
}
```

---

getTx2Gene *Generate a transcript-to-gene mapping from a GRangesList*

Description

Generate a data.frame mapping transcript IDs to gene IDs, based on a GRangesList object generated by getFeatureRanges.

Usage

```
getTx2Gene(grl, filepath = NULL)
```

Arguments

grl	GRangesList object, typically generated by getFeatureRanges
filepath	Either NULL or the path to a file where the transcript-to-gene mapping will be written

Value

Invisibly returns a data.frame with the transcript-to-gene mapping.

Author(s)

Charlotte Soneson

Examples

```
## Get feature ranges
grl <- getFeatureRanges(
  gtf = system.file("extdata/small_example.gtf", package = "eisaR"),
  featureType = c("spliced", "intron"),
  intronType = "separate",
  flankLength = 5L,
  joinOverlappingIntrons = FALSE,
  verbose = TRUE
)

## Get transcript-to-gene mapping
t2g <- getTx2Gene(grl = grl)
t2g
```

---

plotEISA *Visualize the results from an exon-intron split analysis.*

Description

plotEISA takes the return value from runEISA and generates a scatterplot of intronic versus exonic changes.

Usage

```
plotEISA(
  x,
  contrast = c("ExIn", "none"),
  minLfc = NULL,
  maxFDR = 0.05,
  genecolors = c("#E41A1C", "#497AB3", "#222222"),
  ...
)
```

Arguments

x	list with EISA results, typically the return value from runEISA
contrast	one of "ExIn" or "none". If "ExIn" (the default), genes that significantly differ between exonic and intronic changes are highlighted. "none" turns off gene highlighting.
minLfc	NULL or numeric(1) with the minimal absolute log2 fold change to color a gene. If NULL (the default), no fold changes are not used to select genes for highlighting.
maxFDR	numeric(1) with maximal false discovery rate for gene highlighting.
genecolors	Vector of length three specifying the colors to use for genes that are significantly up, down or unchanged.
...	Currently not used, provided for backward compatibility.

Value

A ggplot object.

Author(s)

Michael Stadler, Charlotte Soneson

Examples

```
# see the help for runEISA() for a full example
```

---

runEISA *Run Exon-Intron Split Analysis.*

Description

Starting from count tables with exonic and intronic counts for two conditions, perform all the steps in EISA (normalize, identify quantifyable genes, calculate contrasts and their significance).

Usage

```
runEISA(
  cntEx,
  cntIn,
  cond,
  method = NULL,
  modelSamples = TRUE,
  geneSelection = c("filterByExpr", "none", "Gaidatzis2015"),
  statFramework = c("QLF", "LRT"),
  legacyQLF = FALSE,
  effects = c("predFC", "Gaidatzis2015"),
  pscnt = 2L,
  sizeFactor = c("exon", "intron", "individual"),
  recalcNormFactAfterFilt = TRUE,
  recalcLibSizeAfterFilt = FALSE,
  ...
)
```

Arguments

cntEx	Gene by sample matrix with exonic counts, OR a SummarizedExperiment with two assays named exon and intron, containing exonic and intronic counts, respectively. If cntEx is a SummarizedExperiment, cntIn will be disregarded.
cntIn	Gene by sample matrix with intronic counts. Must have the same structure as cntEx (same number and order of rows and columns) if cntEx is a matrix. Will be disregarded if cntEx is a SummarizedExperiment.

cond
: numeric, character or factor with two levels that groups the samples (columns of cntEx and cntIn) into two conditions. The contrast will be defined as secondLevel - firstLevel.

method
: One of NULL (the default) or "Gaidatzis2015". If "Gaidatzis2015", gene filtering, statistical analysis and calculation of contrasts is performed as described in Gaidatzis et al. 2015, and the statistical analysis is based on glmFit and glmLRT. This is done by setting the arguments modelSamples, geneSelection, effects, pscnt, statFramework, sizeFactor, recalcNormFactAfterFilt and recalcLibSizeAfterFilt to appropriate values (see details), overriding the defaults or any value passed to these arguments. If NULL, the default values of the arguments will be used instead (recommended).

modelSamples
: Whether to include a sample identifier in the design matrix of the statistical model. If TRUE, potential sample effects that affect both exonic and intronic counts of that sample will be taken into account, which could result in higher sensitivity (default: TRUE).

geneSelection
: Controls how to select quantifyable genes. One of the following:

  "filterByExpr": (default) First, counts are normalized using calcNormFactors, treating intronic and exonic counts as individual samples. Then, filterByExpr is used with default parameters to select quantifyable genes.

  "none": This will use all the genes provided in the count tables, assuming that an appropriate selection of quantifyable genes has already been done.

  "Gaidatzis2015": First, intronic and exonic counts are linearly scaled to the mean library size (estimated as the sum of all intronic or exonic counts, respectively). Then, quantifyable genes are selected as the genes with counts x that fulfill log2(x + 8) > 5 in both exons and introns.

statFramework
: Selects the framework within edgeR that is used for the statistical analysis. One of:

  "QLF": (default) Quasi-likelihood F-test using glmQLFit and glmQLFTest. This framework is highly recommended as it gives stricter error rate control by accounting for the uncertainty in dispersion estimation.

  "LRT": Likelihood ratio test using glmFit and glmLRT.

legacyQLF
: Whether to use the 'legacy' version of glmQLFit. See glmQLFit for more details. If FALSE, the new method introduced in edgeR 4.0.0 is used.

effects
: How the effects (contrasts or log2 fold-changes) are calculated. One of:

  "predFC": (default) Fold-changes are calculated using the fitted model with predFC with prior.count = pscnt. Please note that if a sample factor is included in the model (modelSamples=TRUE), effects cannot be obtained from that model. In that case, effects are obtained from a simpler model without sample effects.

  "Gaidatzis2015": Fold-changes are calculated using the formula log2((x + pscnt)/(y + pscnt)). If pscnt is not set to 8, runEISA will warn that this deviates from the method used in Gaidatzis et al., 2015.

pscnt
: numeric(1) with pseudocount to add to read counts (default: 2). For method = "Gaidatzis2015", it is set to 8. It is added to scaled read counts used in geneSelection = "Gaidatzis2015" and effects = "Gaidatzis2015", or else used in cpm(..., prior.count = pscnt) and predFC(..., prior.count = pscnt).

`sizeFactor` How the size factors are calculated in the analysis. If 'exon' (default), the exon-derived size factors are used also for the columns corresponding to intronic counts. If 'intron', the intron-derived size factors are used also for the columns corresponding to exonic counts. If 'individual', column-wise size factors are calculated.

`recalcNormFactAfterFilt` Logical, indicating whether normalization factors should be recalculated after filtering out lowly expressed genes.

`recalcLibSizeAfterFilt` Logical, indicating whether library sizes should be recalculated after filtering out lowly expressed genes.

`...` additional arguments passed to the `DGEList` constructor, such as `lib.size` or `genes`.

Details

Setting `method = "Gaidatzis2015"` has precedence over other argument values and corresponds to setting: `modelSamples = FALSE`, `geneSelection = "Gaidatzis2015"`, `statFramework = "LRT"`, `effects = "Gaidatzis2015"`, `pscnt = 8`, `sizeFactor = "individual"`, `recalcNormFactAfterFilt = TRUE`, `recalcLibSizeAfterFilt = FALSE`.

Value

a `list` with elements

fracIn fraction intronic counts in each sample

contrastName contrast name

contrasts contrast matrix for quantifyable genes, with average log2 fold-changes in exons (`Dex`), in introns (`Din`), and average difference between log2 fold-changes in exons and introns (`Dex.Din`)

DGEList `DGEList` object used in model fitting

tab.ExIn statisical results for differential changes between exonic and intronic contrast, an indication for post-transcriptional regulation.

contr.ExIn contrast vector used for testing the difference between exonic and intronic contrast (results in `tab.ExIn`)

designMatrix design matrix used for testing the difference between exonic and intronic contrast (results in `tab.ExIn`)

params a `list` with parameter values used to run EISA

Author(s)

Michael Stadler

References

Analysis of intronic and exonic reads in RNA-seq data characterizes transcriptional and post-transcriptional regulation. Dimos Gaidatzis, Lukas Burger, Maria Florescu and Michael B. Stadler Nature Biotechnology, 2015 Jul;33(7):722-9. doi: 10.1038/nbt.3269.

See Also

DGEList for DGEList object construction, calcNormFactors for normalization, filterByExpr for gene selection, glmFit and glmQLFit for statistical analysis.

Examples

```
cntEx <- readRDS(system.file("extdata", "Fig3abc_GSE33252_rawcounts_exonic.rds",
                             package = "eisaR"))[,-1]
cntIn <- readRDS(system.file("extdata", "Fig3abc_GSE33252_rawcounts_intronic.rds",
                             package = "eisaR"))[,-1]
cond <- factor(c("ES","ES","TN","TN"))
res <- runEISA(cntEx, cntIn, cond)
plotEISA(res)
```

Index

calcNormFactors, *9*, *11*

DGEList, *10*, *11*

exportToGtf, 2

filterByExpr, *9*, *11*

getFeatureRanges, 3
getRegionsFromTxDb, 5
getTx2Gene, 6
glmFit, *9*, *11*
glmLRT, *9*
glmQLFit, *9*, *11*
glmQLFTest, *9*

plotEISA, 7
predFC, *9*

runEISA, *7*, 8

TxDb, *5*, *6*