Package: geva (via r-universe)

November 1, 2026

Type Package

Title Gene Expression Variation Analysis (GEVA)

Description Statistic methods to evaluate variations of differential expression (DE) between multiple biological conditions. It takes into account the fold-changes and p-values from previous differential expression (DE) results that use large-scale data (*e.g.*, microarray and RNA-seq) and evaluates which genes would react in response to the distinct experiments. This evaluation involves an unique pipeline of statistical methods, including weighted summarization, quantile detection, cluster analysis, and ANOVA tests, in order to classify a subset of relevant genes whose DE is similar or dependent to certain biological factors.

Version 1.20.0

URL https://github.com/sbcblab/geva

BiocType Software

biocViews Classification, DifferentialExpression, GeneExpression, Microarray, MultipleComparison, RNASeq, SystemsBiology, Transcriptomics

License LGPL-3

Encoding UTF-8

Depends R (>= 4.1)

Imports grDevices, graphics, methods, stats, utils, dbscan, fastcluster, matrixStats

Suggests devtools, knitr, rmarkdown, roxygen2, limma, topGO, testthat (>= 3.0.0)

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.1

VignetteBuilder knitr

Collate 'stringhelpers.R' 'callhelpers.R' 'vectorhelpers.R'
'printhelpers.R' 'asserts.R' 'usecasechecks.R' 'plotting.R'
'dochelpers.R' 'generics.R' 'classhelpers.R' 'c_SVTable.R'
'c_GEVAGroupSet.R' 'c_GEVACluster.R' 'funhelpers.R' 'linq.R'
'c_TypedList.R' 'c_SVAttribute.R' 'c_GEVAInput.R'
'c_GEVASummary.R' 'c_GEVAGroupedSummary.R' 'c_GEVAQuantiles.R'
'c_GEVAQuantilesAdjusted.R' 'c_GEVAResults.R' 'summarization.R'
'clusteringbase.R' 'matrixhelpers.R' 'statmath.R'
'dclustering.R' 'quantiles.R' 'factoring.R' 'scoremerge.R'
'finalize.R' 'geva-package.R' 'hclustering.R' 'idealtesting.R'
'input.R'

Config/testthat/edition 3

Repository Bioconductor 3.23

Date/Publication 2026-04-28 12:55:17 UTC

RemoteUrl https://github.com/bioc/geva

RemoteRef RELEASE_3_23

RemoteSha fbfe0b12121d4e7201e95df329fb9a6c0d512c28

Contents

generics . . . 3
geva.cluster . . . 5
geva.dcluster . . . 7
geva.finalize . . . 9
geva.hcluster . . . 11
geva.ideal.example . . . 13
geva.input.correct . . . 14
geva.merge.input . . . 16
geva.quantiles . . . 20
geva.quick . . . 22
geva.summarize . . . 23
GEVACluster-class . . . 25
GEVAGroupedSummary-class . . . 26
GEVAGroupSet-class . . . 27
GEVAInput-class . . . 29
GEVAQuantiles-class . . . 30
GEVAQuantilesAdjusted-class . . . 32
GEVAResults-class . . . 33
GEVASummary-class . . . 34
SVAttribute-class . . . 36
SVTable-class . . . 37
top.genes . . . 39
TypedList-class . . . 40

Index **42**

generics *GEVA Generic Methods*

Description

Exhaustive list of generic methods exported from GEVA. Use `findMethods` to retrieve the specific usages.

Usage

```
inputvalues(object)

inputweights(object, normalized)

inputdata(object)

inputnames(object)

infolist(object, field, ...)

infolist(object) <- value

factors(object)

factors(object) <- value

classification.table(object)

classification.table(object) <- value

analysis.params(gobject)

featureTable(object)

featureTable(object) <- value

sv(object)

svattr(S, V)

elem.class(typedlist)

elem.class(typedlist) <- value

groupsets(object)

groupsets(object) <- value
```

```
groups(object)

scores(object, group)

centroids(object)

offsets(object)

sv.scores(object)

qindexes(object)

qareasizes(object)

qcount(object)

quantiles(object)

quantiles.method(object)

group.rels(object)

cluster.method(object)

results.table(gres)

sv.data(object)

variation(object, ...)

get.summary.method(x)

get.variation.method(x)

get.distance.method(x)

as.SVTable(x, ...)
```

Arguments

object, x, gobject	Primary object. See the documentation from each class for specific usages
normalized	logical, whether to return values in the normalized scale
field	When used with a information list, returns the information entry with the corresponding name
...	Additional parameters. If used with an imported S3 method, passes the arguments to the default vector, matrix or data.frame implementation

value	The value to be assigned
S	Vector to construct the S slot
V	Vector to construct the V slot
typedlist	A TypedList object
group	Character to filter the returned groups. Omit it to return all groups
gres	A GEVAResults objec

Value

See the specific usages for each method.

Examples

```
# Returing analysis parameters from an object
gsummary <- geva.summarize(geva.ideal.example(),
                           summary.method="mean",
                           variation.method="sd")
anpars <- analysis.params(gsummary)
print(anpars)
# $summary.method
# [1] "mean"
# $variation.method
# [1] "sd"
```

---

geva.cluster *GEVA Cluster Analysis*

Description

Performs a cluster analysis from summarized data.

Usage

```
geva.cluster(
  sv,
  cluster.method = options.cluster.method,
  cl.score.method = options.cl.score.method,
  resolution = 0.3,
  distance.method = options.distance,
  ...,
  grouped.return = FALSE
)

options.cluster.method
# c("hierarchical", "density", "quantiles")
```

```
options.cl.score.method
# c("auto", "hclust.height", "density", "centroid")

options.distance
# c("euclidean", "manhattan")
```

Arguments

sv	a numeric SVTable object (usually GEVASummary)
cluster.method	character, one of the main grouping methods (see 'Details')
cl.score.method	character, method used to calculate the cluster scores for each point. Ignored if cluster.method is quantiles
resolution	numeric (0 to 1), used as a "zoom" parameter for cluster detection. A zero value returns the minimum number of clusters that can detected by the cluster.method, while 1 returns the maximum amount of clusters. Ignored if cluster.method is quantiles
distance.method	character, two-point distance calculation method. Options are "eucludian" or "manhattan" distances
...	further arguments passed to geva.dcluster(), geva.hcluster(), or geva.quantiles(). In addition, the following arguments are accepted: • eps : numeric, defines the *epsilon* coefficient for density clustering (see 'Details') • mink.p : numeric, parameter for the Minkowsky metric used in hierarchial clustering. Used as the p argument for fastcluster::hclust.vector() • verbose : logical, whether to print the current progress (default is TRUE)
grouped.return	logical, whether to concatenate the clustered and summarized data into a single object

Details

The cluster.method determines which grouping subroutine is used to classify the summarized data points based on distance and partitioning. Each option has their equivalent functions that can be called directly: "density" uses geva.dcluster(); "hierarchical" uses geva.hcluster(); and "quantiles" calls geva.quantiles(). However, this wrapper function can also be used to join GEVASummary and GEVAGroupSet objects into a single GEVAGroupedSummary object by setting grouped.return to TRUE.

The cl.score.method argument defines how scores are calculated for each SV point (row in sv) that was assigned to a cluster, (*i.e.*, excluding non-clustered points). If specified as "auto", the parameter will be selected based on the cluster.method: "density" (rate of neighbor points) for the density method; and "hclust.height" (local hierarchy height) for the hierarchical method. The "centroid" method calculates the scores based on the proportional distance between each point to its cluster's centroid. Note that the cl.score.method argument is ignored if cluster.method is "quantiles", since quantile scores are always based on their local centroid distances.

The resolution value is a more accessible way to define the cluster separation threshold used in density and hierarchical clustering methods. Density clusters uses an *epsilon* value that represents

the minimum distance of separation, whereas hierarchical clusters are defined by cutting the hierarchy tree wherever there is a minimum distance between two hierarchies. In this sense, `resolution` translates a value between `0` and `1` to propotional value for *epsilon* or hierarchical height (depending on the `cluster.method`) that would result in the least number of possible clusters for `0` and the highest number for `1`. Nevertheless, if *epsilon* is specified as `eps` in the optinal arguments, its value is used and `resolution` is ignored.

Value

This function produces a `GEVAGroupSet`-derived object, particularly a `GEVACluster` for the `"hierarchical"` and `"density"` cluster methods or a `GEVAQuantiles` for the `"quantiles"` method.

However, if `grouped.return` is `TRUE` and `sv` is a `GEVASummary` object, the produced `GEVAGroupSet` data will be concatenated to the input and returned as a `GEVAGroupedSummary`

See Also

Other geva.cluster: `geva.dcluster()`, `geva.hcluster()`, `geva.quantiles()`

Examples

```
## Cluster analysis from a randomly generated input

# Preparing the data
ginput <- geva.ideal.example()      # Generates a random input example
gsummary <- geva.summarize(ginput)  # Summarizes with the default parameters

# Hierarchical clustering
gclust <- geva.cluster(gsummary, cluster.method="hierarchical")
plot(gclust)

# Density clustering
gclust <- geva.cluster(gsummary, cluster.method="density")
plot(gclust)

# Density clustering with slightly more resolution
gclust <- geva.cluster(gsummary,
                       cluster.method="density",
                       resolution=0.35)
plot(gclust)
```

`geva.dcluster` *GEVA Density Clustering*

Description

Performs a density cluster analysis from summarized data.

Usage

```
geva.dcluster(
  sv,
  resolution = 0.3,
  dcluster.method = options.dcluster.method,
  cl.score.method = options.cl.score.method,
  minpts = 2,
  ...,
  eps = NA_real_,
  include.raw.results = FALSE
)

options.dcluster.method
# c("dbscan", "optics")
```

Arguments

sv	a numeric SVTable object (usually GEVASummary)
resolution	numeric (0 to 1), used as a "zoom" parameter for cluster detection. A zero value returns the minimum number of clusters that can detected, while 1 returns the maximum amount of detectable clusters. Ignored if eps is specified
dcluster.method	character, density-based method for cluster separation
cl.score.method	character, method used to calculate the cluster scores for each point. If "auto", the "density" method is selected
minpts	integer, minimum number of points required to form a cluster
...	additional arguments. Accepts verbose (logical, default is TRUE) to enable or disable printing the current progress
eps	numeric, maximum neighborhood distance between points to be clustered
include.raw.results	logical, whether to attach intermediate results to the returned object

Details

This function performs a density cluster analysis with the aid of implemented methods from the dbscan::dbscan package. The available methods for the dcluster.method arguments are "dbscan" and "options", which internally call dbscan::dbscan() and dbscan::optics(), respectively.

The resolution value is an accessible way to define the cluster separation threshold used in density clustering. The *DBSCAN* algorithm uses an *epsilon* value that represents the minimum distance of separation, and resolution translates a value between 0 and 1 to a propotional value within the acceptable range of *epsilon* values. This allows defining the rate of clusters from 0 to 1, which results in the least number of possible clusters for 0 and the highest number for 1. Nevertheless, if *epsilon* is specified as eps in the optinal arguments, its value is used and resolution is ignored.

The cl.score.method argument defines how scores are calculated for each SV point (row in sv) that was assigned to a cluster, (*i.e.*, excluding non-clustered points). If specified as "auto", the parameter will be selected based on the rate of neighbor points ("density").

If include.raw.results is TRUE, some aditional data will be attached to the info slot of the returned GEVACluster objects, including the *kNN* tree generated during the intermediate steps.

Value

A GEVACluster object

Note

In density clustering, only the most dense points are clustered. For the unclustered points, the grouping value is set to NA.

See Also

Other geva.cluster: geva.cluster(), geva.hcluster(), geva.quantiles()

Examples

```
## Density clustering from a randomly generated input

# Preparing the data
ginput <- geva.ideal.example()      # Generates a random input example
gsummary <- geva.summarize(ginput)  # Summarizes with the default parameters

# Density clustering
gclust <- geva.dcluster(gsummary)
plot(gclust)

# Density clustering with slightly more resolution
gclust <- geva.dcluster(gsummary, resolution=0.35)
plot(gclust)
```

---

geva.finalize *Concatenating GEVA calculations into the final results*

Description

Merges the obtained information (Summarization, Clustering, and Quantiles), then applies the final steps to produce the classification results for the SV points (genes).

Usage

```
geva.finalize(
  gsummary,
  ...,
  p.value = 0.05,
  p.val.adjust = options.factoring.p.adjust,
  constraint.factors = TRUE
```

```
)

options.factoring.p.adjust
# c("partial.quantiles", "holm", "hochberg", "hommel",
#   "bonferroni", "BH", "BY", "fdr", "none")
```

Arguments

`gsummary`	a `GEVASummary` object
`...`	Intermediate results produced from the `gsummary` object, such as clusters (`GEVACluster`), quantiles (`GEVAQuantiles`), or any other object inherited from `GEVAGroupSet`
`p.value`	`numeric` (0 to 1), p-value cutoff used in the ANOVA procedures (factor analysis only)
`p.val.adjust`	`character`, p-value correction method (factor analysis only). Possible values are: "partial.quantiles", "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
`constraint.factors`	`logical`. If `TRUE`, the S values are restricted to the range within the quantile centroids (factor analysis only)

Details

In this procedure, the SV points (*i.e.*, each row in the `GEVASummary` object) are classified according to the detected quantiles (see geva.quantiles), whose results can be adjusted using other grouping analysis results such as clusters (see geva.cluster). To achieve the best statistical accuracy, both `GEVAQuantiles` and `GEVACluster` objects must be given in the `...` as optional arguments. If a `GEVAQuantiles` argument is not present, it is automatically calculated using the default parameters.

If multiple factors are present in the `GEVASummary` object (retrieved by `factors(gsummary)`), a factor analysis is also performed, giving two additional possible classifications (*factor-dependent* and *factor-specific*) besides the default ones (*similar*, *basal*, and *sparse*).

In factor analysis, an ANOVA is applied for each gene using Fisher's and Levene's tests to distinguish genes whose *logFC* (differential expression) variation is dependent or specific to the analyzed factors based on the p-value cutoff. The `p.val.adjust` argument defines how these p-values will be adjusted: by quantile separation between each factor (`"partial.quantiles"` method); or by one of the default methods listed in stats::p.adjust.methods.

The `constraint.factors` argument determines if the `S` values (summarized *logFC*) will be limited to the range between the quantile centroids during factor analysis. For example, if the quantile centroids were -0.90, 0.00, and 0.90 in the S axis, values such as -1.53 and 2.96 would be converted to -0.90 and 0.90, respectively. This constraint is particularly applied to avoid significative observations from ANOVA based on multiple degrees of differential expression.
In another example to illustrate the constraint of factors, given two sets of values: A = (-1.00, -1,10, 0.00, 0.20, 1.00, 1.15), and B = (0.00, 0.12, 1.11, 1.00, 1.95, 2.00), with the centroids located in C = (-0.90, 0.00, 0.90), and the factors F = (Cond1, Cond1, Cond2, Cond2, Cond3, Cond3). If `constraint.factors` is `FALSE`, both A and B are considered as significantly separated factors, whereas if `TRUE`, only A will present a significant separation, since in B the values 1.11, 1.00, 1.95, and 2.00 are converted to 0.90. In qualitative terms, if `constraint.factors` is `TRUE`, all values above 0.90 are considered the same over-expressed values, ensuring that they will fit in the same

degree of differential expression. Hence, in this example using the constrained values, B would not represent a significant separation between the factors Cond1, Cond2, and Cond3.

Value

A GEVAResults object, containing the entire set of results. The relevant genes can be retrieved using top.genes()

Note

To perform factor analysis, the following observations must be considered:

- The factors must be defined in the provided data. They can be retrieved using the factors accessor. If factors are not present or are entirelly composed by NA, they can be assigned through factors<- by providing a factor or character vector of the same length of the input columns;
- Each factor must include two or more values, since the factor analysis is based on ANOVA and at least two values are needed to variance calculation;
- Columns whose factor value is NA are not considered.

See Also

p.adjust.methods

Examples

```
## Finalizing example using a random generated input
ginput <- geva.ideal.example()      # Generates a random input (for testing purposes only)
gsummary <- geva.summarize(ginput)   # Summarizes the input
gquant <- geva.quantiles(gsummary)   # Calculates the quantiles
gclust <- geva.cluster(gsummary)     # Calculates the clusters
gresults <- geva.finalize(gsummary, gquant, gclust)  # Finishes the results

head(top.genes(gresults))            # Prints the final results
plot(gresults)                       # Plots the final SV-plot
```

---

geva.hcluster *GEVA Hierarchical Clustering*

Description

Performs a hierarchical cluster analysis from summarized data.

Usage

```
geva.hcluster(
  sv,
  resolution = 0.3,
  hc.method = options.hc.method,
  hc.metric = options.hc.metric,
  cl.score.method = options.cl.score.method,
  ...,
  include.raw.results = FALSE
)

options.hc.metric
# c("euclidean", "maximum", "manhattan", "canberra",
#   "binary", "minkowski")

options.hc.method
# c("centroid", "median", "ward", "single")
```

Arguments

sv	a numeric SVTable object (usually GEVASummary)
resolution	numeric (0 to 1), used as a "zoom" parameter for cluster detection. A zero value returns the minimum number of clusters that can detected, while 1 returns the maximum amount of detectable clusters
hc.method	character, the agglomeration method to be used. Used as the method argument for fastcluster::hclust.vector()
hc.metric	character, the distance measure to be used. Used as the metric argument for fastcluster::hclust.vector()
cl.score.method	character, method used to calculate the cluster scores for each point. If "auto", the "hclust.height" method is selected
...	additional arguments: • mink.p : numeric, parameter for the Minkowsky metric. Used as the p argument for fastcluster::hclust.vector() • verbose : logical, whether to print the current progress (default is TRUE)
include.raw.results	logical, whether to attach intermediate results to the returned object

Details

This function performs a hierarchical cluster analysis with the aid of implemented methods from the fastcluster::fastcluster package, particularly the fastcluster::hclust.vector() function. The available methods for the hc.method and hc.metric are described in the function's documentation page (see fastcluster::hclust.vector()).

The resolution value is an accessible way to define the cluster separation threshold used in hierarchical clustering. The algorithm produces a dendrogram-like hierarchy in which each level/node

is separated by a distance (sometimes called "height") to the next level/node, and the `resolution` translates a value between `0` and `1` to a propotional value within the total hierarchy height. This allows defining the rate of clusters from `0` to `1`, which results in the least number of possible clusters (usually two) for `0`, and the highest number (approximately one cluster per point) for `1`.

If `include.raw.results` is `TRUE`, some aditional data will be attached to the `info` slot of the returned `GEVACluster` objects, including the *kNN* tree generated during the intermediate steps.

Value

A `GEVACluster` object

Note

In hierarchical clustering, all points are clustered. Therefore, setting `resolution` to `1` will result into one cluster per point, where the cluster analysis may become pointless (no pun intended).

See Also

Other geva.cluster: `geva.cluster()`, `geva.dcluster()`, `geva.quantiles()`

Examples

```
## Hierarchical clustering from a randomly generated input

# Preparing the data
ginput <- geva.ideal.example()      # Generates a random input example
gsummary <- geva.summarize(ginput)  # Summarizes with the default parameters

# Hierarchical clustering
gclust <- geva.hcluster(gsummary)
plot(gclust)

# Hierarchical clustering with slightly more resolution
gclust <- geva.hcluster(gsummary,
                        resolution=0.35)
plot(gclust)
```

---

geva.ideal.example *GEVA "Ideal" Example for Package Testing*

Description

Generates a random example of GEVAInput object that simulates an ideal analysis dataset. Used for testing purposes only.

Usage

```
geva.ideal.example(probecount = 10000, nfactors = 3, colsperfactor = 3)
```

Arguments

probecount	integer, number of probes (*i.e.*, table rows)
nfactors	integer, number of factors (*e.g.*, experimental groups)
colsperfactor	integer, number of columns (*e.g.*, experiments) per factor

Value

A GEVAInput object. The included tables are composed by probecount rows and nfactors * colsperfactor columns

See Also

geva.summarize

Examples

```
## "Ideal" input example
ginput <- geva.ideal.example()     # Generates a random example
gsummary <- geva.summarize(ginput) # Summarizes the generated data
plot(gsummary)                     # Plots the summarized data
```

---

geva.input.correct *GEVA Input Post-processing*

Description

Helper functions used to edit the contents from a GEVAInput.

Usage

```
geva.input.correct(ginput, na.rm = TRUE, inf.rm = TRUE, invalid.col.rm = TRUE)

geva.input.filter(
  ginput,
  p.value.cutoff = 0.05,
  by.any = FALSE,
  na.val = 0,
  ...
)

geva.input.rename.rows(
  ginput,
  attr.column,
  dupl.rm.method = c("least.p.vals", "order")
)
```

Arguments

ginput	A GEVAInput object
na.rm	logical; if TRUE, removes all rows containing NA
inf.rm	logical; if TRUE, removes all rows containing infinite values (Inf or -Inf)
invalid.col.rm	logical; if TRUE, searches for any column that is entirely composed by invalid values (according to the other arguments) and removes it before checking the rows
p.value.cutoff	numeric (0 to 1), the p-value cutoff. Rows containing values above this threshold are removed
by.any	logical, set to TRUE to delete the rows with at least one occurrence above the cutoff; or FALSE to delete only those rows in which all values are above the specified threshold
na.val	numeric, the replacement for NA values
...	optional arguments. Accepts verbose (logical, default is TRUE) to enable or disable printing the progress
attr.column	character, target column with the values that will replace the current row names
dupl.rm.method	character, method to remove duplicate names. The possible options are: • "least.p.vals" : Keeps the duplicate that contains the least sum of p-values • "order" : Keeps the first occurrence of the duplicate in the current row order

Details

geva.input.correct corrects the numeric input data (values and weights), removing rows that include invalid values such as NA or infinite.

geva.input.filter attempts to select the most relevant part of the input data, removing rows containing p.values (1 - weights) above a specific threshold.

geva.input.rename.rows replaces the row names with a column from the feature table (see GEVAInput). The column name specified for attr.column must be included in the names(featureTable(ginput)). Any duplicates are removed according to the dupl.rm.method, and the selected duplicates are stored as a new column named "renamed_id" inside the feature table from the returned object.

Value

A modified GEVAInput object

Examples

```
## geva.input.correct example
colexample1 <- runif(1000, -1, 1)        # Random column 1
colexample2 <- runif(1000, -1, 1)        # Random column 2
colexample3 <- runif(1000, -1, 1)        # Random column 3
colexample3[runif(1000, -1, 1) < 0] = NA # Random NA's
```

```
ginput = geva.merge.input(col1=colexample1,
                          col2=colexample2,
                          col3=colexample3)
# Before the correction:
print(nrow(ginput))    # Returns 1000
# Applies the correction (removes rows with NA's)
ginput <- geva.input.correct(ginput)
# After the correction:
print(nrow(ginput))    # Returns less than 1000

## ---
## geva.input.filter example
ginput <- geva.ideal.example(1000)  # Generates a random input
# Before the filter:
print(nrow(ginput))    # Returns 1000
# Applies the filter
ginput <- geva.input.filter(ginput)
# After the filter:
print(nrow(ginput))    # Returns less than 1000

## ---
## geva.input.rename.rows example
ginput <- geva.ideal.example()  # Generates a random input
# Renames to 'Symbol'
ginput <- geva.input.rename.rows(ginput,
                                 attr.column = "Symbol")
print(head(ginput))             # The row names are set now as the gene symbols
```

`geva.merge.input` *GEVA Input Processing and Merge*

Description

Functions to read, load, and concatenate the experimental comparisons from the data input. This is the initial step to proceed with any GEVA analysis.

Usage

```
geva.merge.input(
  ...,
  col.values = "logFC",
  col.pvals = "adj.P.Val",
  col.other = NULL
)

geva.read.tables(
  filenames = NULL,
  dirname = ".",
```

```
  col.values = "logFC",
  col.pvals = "adj.P.Val",
  col.other = NULL,
  ...,
  files.pattern = "\\.txt$",
  p.value.cutoff = 0.05,
  read.args = list()
)
```

Arguments

`...`	multiple `matrix` or `data.frame` objects. At least two arguments are required for `geva.merge.input`, but it's optional for `geva.read.tables`. The optional arguments in `geva.read.tables` are also passed to its internal call to `geva.merge.input` and `geva.input.filter`. In addition, the following optional arguments are accepted: • `na.val` : (`numeric`) value between `0` and `1` used as replacement when a p-value column is not present (default is `NA`) • `use.regex` : (`logical`) whether to match the column names using regular expressions (default is `FALSE`) • `verbose` : (`logical`) whether to print the current loading and merge progress (default is `TRUE`)
`col.values`	`character` vector, possible name(s) to match the *logFC* column(s) from each table
`col.pvals`	`character` vector, possible name(s) to match the p-value column(s) from each table
`col.other`	`character` vector, name(s) to match additional columns (*e.g.*, gene symbols). Ignored if `NULL`
`filenames`	`character` vector with two or more file paths
`dirname`	single `character`, base directory containing the input files. Ignored if `filenames` is specified
`files.pattern`	single `character`, pattern used to filter the files inside `dirname`. Ignored if `filenames` is specified
`p.value.cutoff`	`numeric` (`0` to `1`), initial p-value threshold. Rows entirely composed by p-values above this cutoff (*i.e.*, no significant *logFC*) are removed after the final merge. Ignored if `NA` or `NULL`
`read.args`	`list` of additional arguments passed to utils::read.table

Details

The `geva.merge.input` function takes multiple tables as arguments (*e.g.*, `matrix` or `data.frame` objects), extracts the *logFC* columns from each table and merges them into a single `GEVAInput` dataset.

The column names are specified in the `col.values` and `col.pvals` arguments (`character`) and must correctly match the column names for *logFC* and p-value columns, respectively, in the inputs

to be extracted. Multiple values for column names can also be specified as valid name possibilities if they differ among the tables.

The function `geva.merge.input` reads multiple tab-delimited text files containing, extracts the *logFC* columns from each table and merges into a single `GEVAInput` dataset.

Value

A `GEVAInput` object

Note

The inclusion of p-value columns is not technically required, but strongly recommended as they improve the statistical accuracy in the summarization steps. If the p-value (or adjusted p-value) columns are present, their values are converted to weights by applying `1 - pvalue` for each `pvalue` element, otherwise an optional `na.val` optional argument can specified as replacement to the absent values (default is `NA`). Weights are used to accomodate the central *logFC* values towards the most significant observations and penalize potential statistical innacuracies.

Examples

```
### EXAMPLE 1
## geva.merge.input example with three randomly generated tables
## (For demonstration purposes only)

# Number of rows
n <- 10000

# Random row (probe) names
probnms <- sprintf("PROBE_%s", 1:n)

# Random gene names (optional)
genenms <- paste0(sprintf("GENE_%s", 1:n), LETTERS[1:n %% (length(LETTERS)+1)])

# Random table 1
dt1 <- data.frame(row.names=probnms,
                  logfc=(rnorm(n, 0, sd=2) * rnorm(n, 0, sd=0.5)),
                  pvalues = runif(n, max=0.08),
                  genesymbol = genenms)
# Random table 2
dt2 <- data.frame(row.names=probnms,
                  logfc=(rnorm(n, 0, sd=2) * rnorm(n, 0, sd=0.5)),
                  pvalues = runif(n, max=0.08),
                  genesymbol = genenms)
# Random table 3
dt3 <- data.frame(row.names=probnms,
                  logfc=(rnorm(n, 0, sd=2) * rnorm(n, 0, sd=0.5)),
                  pvalues = runif(n, max=0.08),
                  genesymbol = genenms)

# Merges the three tables
ginput <- geva.merge.input(exp1=dt1, exp2=dt2, exp3=dt3,
```

```
                            col.values="logfc",
                            col.pvals="pvalues",
                            col.other="genesymbol")

    # Prints the first rows from the merged table
    print(head(ginput))               # values
    print(head(inputweights(ginput))) # weights

    # ---
    ## Not run:

    ### EXAMPLE 2
    ## geva.read.tables example with three tab-delimited files

    # Table file examples. Each one has 3 columns: "logfc", "pvalues", and "genesymbol"
    # Replace it with your tab-delimited files (e.g. exported from limma's topTable)
    fnames <- c("dt1.txt", "dt2.txt", "dt3.txt")

    ginput <- geva.read.tables(fnames,
                            col.values="logfc",
                            col.pvals="pvalues",
                            col.other="genesymbol")

    # Prints the first rows from the merged table
    print(head(ginput))               # values
    print(head(inputweights(ginput))) # weights


    # ---

    ### EXAMPLE 3
    ## geva.read.tables example with tab-delimited files in a directory

    # Directory name (replace it with a directory containing the table files)
    dirnm <- "C:/User/robertplant123/Documents/R/gevaexamples"

    # In this example, table files contain 3 columns: "logfc", "pvalues", and "genesymbol"
    # Reads all txt files in the directory
    ginput <- geva.read.tables(dirname=dirnm,
                            col.values="logfc",
                            col.pvals="pvalues",
                            col.other="genesymbol")

    # (Optional step)
    # Let's assume that all table file names start with "dt" and ends with the ".txt" extension,
    # such as dt1.txt, dt2.txt and so on...
    fname_pattern <- c("^dt.+?\\.txt$")  # Defines a RegEx pattern to find the files
    # Loads only files that match the file name pattern
    ginput <- geva.read.tables(dirname=dirnm,
                            files.pattern=fname_pattern,
                            col.values="logfc",
                            col.pvals="pvalues",
                            col.other="genesymbol")
```

```
# Prints the first rows from the merged table
print(head(ginput))               # values
print(head(inputweights(ginput))) # weights

## End(Not run)
```

`geva.quantiles` *GEVA Quantiles Detection*

Description

Calculates the quantiles of a `SVTable`.

Usage

```
geva.quantiles(
  sv,
  quantile.method = options.quantiles,
  initial.thresholds = c(S = NA_real_, V = NA_real_),
  nq.s = 3L,
  nq.v = 2L,
  comb.score.fn = prod,
  ...
)

options.quantiles
# c("range.slice", "proportional", "density", "k.max.sd",
#   "custom")
```

Arguments

`sv`	a `SVTable` object (usually `GEVASummary`)
`quantile.method`	`character`, method to detect the initial quantile thresholds. Ignored if `initial.thresholds` is specified with no `NA` elements
`initial.thresholds`	named `numeric` vector with the threshold that delimits the initial quantile
`nq.s`	`integer`, number of quantiles in S-axis (experimental, see 'Note')
`nq.v`	`integer`, number of quantiles in V-axis (experimental, see 'Note')
`comb.score.fn`	`function` applied to merge `S` and `V` score columns into a single column. The function must require only one argument of `numeric vector` type and return a single `numeric` value. Examples include `prod` or `mean`
`...`	additional arguments include:

- qslice : numeric (0 to 1), the axis fraction used by "range.slice" and "density" methods (see 'Details'). Default is 0.25
- k : integer, neighbor points used by "density" and "k.max.sd" methods (see 'Details'). Default is 16
- verbose : logical, whether to print the current progress. Default is TRUE

Details

The quantile.method defines how the initial quantile (usually the one at the bottom center) is calculated. Each method has a specific way to estimate the first spatial delimiter, as described below:

"range.slice" **(default)** Separation is set at the nearest point to a fraction of the spatial range. This fraction can be specified by the qslice optional argument (numeric, default is 0.25, or 25%);

"density" Separation is set at the point with the most proportional density by *k* neighbor points to its current spatial fraction. This method uses the optional arguments qslice (numeric, default is 0.25, or 25%) for the desired spatial fraction, and k (numeric, default is 16) for the number of neighbor points;

"k.max.sd" Separation is set at the point with the greatest standard deviation of distance to its *k* neighbor points. The number of neighbor points can be specified by the k optional argument (numeric, default is 16);

"proportional" Separation is set at the exact axis division so that all quantiles have the size;

"custom" Uses the values specified in the initial.thresholds argument.

A custom initial separation point can be specified in the initial.thresholds as a numeric vector of two elements, where the first element refers to S axis and the second, to V axis. If one of the elements is NA, the initial quantile is calculated for that axis only. If both values are not NA, the quantile separation method is ignored and automatically set to "custom".

The nq.s and nq.v arguments determine the number of quantiles for the S and V axes, respectively. These parameters can be used to increase the number of possible partitions in the SV space, but their applicability is currently being tested (see 'Note').

The comb.score.fn is a function applied to the partial scores for each SV point to combine them into a single value. The result value is defined as the "quantile score" for a SV point. The function is applied iteratively to two-element numeric vectors.

Note

Customizing the number of quantiles by nq.s and nq.v is a **experimental feature** and the remaining analysis steps are mostly based on the default parameters for these arguments. Tests are being conducted to determine this feature's applicability for the next releases.

See Also

geva.cluster

Other geva.cluster: geva.cluster(), geva.dcluster(), geva.hcluster()

Examples

```
## Quantile detection from a randomly generated input

# Preparing the data
ginput <- geva.ideal.example()      # Generates a random input example
gsummary <- geva.summarize(ginput)  # Summarizes with the default parameters

# Default usage
gquants <- geva.quantiles(gsummary) # Detects the quantiles
plot(gquants)                       # Plots the quantiles

# Custom initial delimiters
gquants <- geva.quantiles(gsummary,
                          initial.thresholds = c(S=1.00, V=0.5))
plot(gquants)                       # Plots the quantiles

# Quantile detection using densities
gquants <- geva.quantiles(gsummary, quantile.method = 'density')
plot(gquants)                       # Plots the quantiles
```

---

geva.quick *All-In-One Function for GEVA Intermediate Procedures*

Description

Given a GEVAInput object, applies the geva.summarize(), geva.quantiles, geva.cluster, and geva.finalize in a single call. Optional arguments are passed to the internal calls of these functions.

Usage

```
geva.quick(gobject, ...)
```

Arguments

gobject	A GEVAInput, or any object that returns a GEVAInput upon calling inputdata(gobject) (*e.g.*, GEVASummary or GEVAResults).
...	Optional arguments passed to geva.summarize(), geva.quantiles(), geva.cluster(), and geva.finalize()

Details

This function performs the summarization, quantile detecetion, and clustering of an input data, then merges the results together and, if applicable, performs a factor analysis. If the gobject is not a GEVAInput, it must provide a valid GEVAInput object when called by inputdata(gobject). Moreover, all parameters used in previous analysis will be taken into account. For instance, if gobject is a GEVASummary obtained by using variation.method='mad', the internal call to geva.summarize

in this function will use `variation.method='mad'` as well, unless if another parameter for `variation.method` is specified in the `...` arguments.

Therefore, this function can be useful not only as a shortcut to analyze `GEVAInput` but also for parameter testing when applied to a `GEVAResults` object, since the previous parameters are reused, while the specified parameters are overriden.

Value

A `GEVAResults` object

Examples

```
## Basic usage using a random generated input
ginput <- geva.ideal.example()   # Generates a random input example
gresults <- geva.quick(ginput)   # Performs the entire analysis (default parameters)

print(head(top.genes(gresults))) # Prints the results
plot(gresults)                        # Plots the final SV-plot


## Example with non-default parameters
ginput <- geva.ideal.example()   # Generates a random input example
gresults <- geva.quick(ginput,
                       summary.method="median",
                       variation.method="mad",
                       quantiles.method="density",
                       cluster.method="density",
                       resolution=0.32)

print(head(top.genes(gresults))) # Prints the results
plot(gresults)                   # Plots the final SV-plot
```

---

geva.summarize *Summarizes the GEVAInput*

Description

Performs the summarization step by calculating the central points and variation estimates of *logFC* values from the input data.

Usage

```
geva.summarize(
  ginput,
  summary.method = options.summary,
  variation.method = options.variation,
  ...
)
```

```
options.summary
# c("mean", "median")

options.variation
# c("sd", "var", "mad")
```

Arguments

ginput	a GEVAInput object
summary.method	single character, method used to calculate the central (summarized) *logFC* values
variation.method	single character, method used to calculate the distribution degree (variation) of the *logFC* values
...	additional arguments. Accepts verbose (logical, default is TRUE) to enable or disable printing the current progress

Details

The options.summary refer to the available operations to calculate central *logFC* values (mean or median), whereas options.variation presents three functions to calculate *logFC* variation (sd: Standard Deviation; var: Variance; and mad: Median Absolute Deviation). Moreover, all those operations include a weighted counterpart applied using the weights table from the GEVAInput object.

Value

A GEVASummary object

See Also

base::mean(), stats::median()

stats::var(), stats::sd(), stats::mad()

Examples

```
## Summarization of a randomly generated input
ginput <- geva.ideal.example()     # Generates a random input example
gsummary <- geva.summarize(ginput) # Summarizes with the default parameters
plot(gsummary)                     # Plots the summarized data
```

GEVACluster-class *GEVA Clustering Results*

Description

The GEVACluster class represents the classification results from a cluster analysis. For each probe/gene, there is a assigned cluster among the *g* defined clusters.

This class inherits from GEVAGroupSet.

Value

A GEVACluster object

Slots

grouping factor (*m* elements, *g* levels), cluster assignment for each gene/probe
(Inherited from GEVAGroupSet)

scores numeric vector (*m* elements) comprising a score value for each cluster assignment
(Inherited from GEVAGroupSet)

ftable data.frame (*m* lines) with additional cluster assignment features
(Inherited from GEVAGroupSet)

centroids numeric SVTable (*g* lines) with the S and V centroid coordinates for each cluster
(Inherited from GEVAGroupSet)

offsets numeric SVTable (*m* lines) with the S and V coordinate offsets each gene/probe from its cluster centroid
(Inherited from GEVAGroupSet)

info list of supplementary information
(Inherited from GEVAGroupSet)

cluster.method character, method used in the cluster analysis (see geva.cluster)

Methods

(See also the inherited methods from GEVAGroupSet)

Plotting

lines(x, ...) Draws convex hulls around the clustered points

plot(x, y, ...) Draws a SV-plot that highlights the clustered points. Convex hulls are included for visual purposes only and do not avoid enclosing points from other clusters on concave parts.
Can be combined with another SVTable or GEVAGroupSet given as the y argument to include additional graphical elements

GEVAGroupedSummary-class

GEVA Grouped Summary-Variation Table

Description

The GEVAGroupedSummary class inherits the GEVASummary class and includes group analysis data (*e.g.*, clustering and quantile detection).

Value

A GEVAGroupedSummary object

Slots

`sv` `numeric` `matrix` composed by two columns: `S` (summary) and `V` (variation)
(Inherited from SVTable)

`inputdata` GEVAInput-class with the data input
(Inherited from GEVASummary)

`sv.method` Names of the statistical methods used to summarize data
(Inherited from GEVASummary)

`info` list with additional information
(Inherited from GEVASummary)

`groupsetlist` TypedList of GEVAGroupSet objects

Methods

(See also the inherited methods from GEVASummary)

Conversion and coercion

`as.expression(x, ginput, ...)` Converts this object to `expression`

`as.matrix(x, ...)` Converts this object to `matrix`

Plotting

`lines(x, ...)` Draws delimiters within quantiles and convex hulls around the clustered points

`plot(x, y, ...)` Draws a SV-plot. The horizontal axis is for *summary* (S) and the vertical axis is for *variation* (V).
In addition, highlights the included group sets

`points(x, ...)` Generic `points` implementation for `GEVAGroupedSummary`

Properties

`analysis.params(gobject)` Returns a `list` of analysis parameters passed to `geva.cluster` to obtain this object

Sub-slot accessors

`cluster.method(object)` Gets a `character` vector listing the `cluster.method` from each group set

`quantiles(object)` Gets the `GEVAQuantiles`, or `NULL` if not present

`GEVAGroupSet-class` *GEVA Grouping Results*

Description

The `GEVAGroupSet` class represents the classification of summarized values from a `SVTable`, where each gene/probe has one assigned group among g defined groups. This is an abstract class. Inherits the `GEVACluster` and `GEVAQuantiles` classes.

Value

A `GEVAGroupSet` object

Slots

`grouping factor` (*m* elements, *g* levels) used to group the genes/probes

`scores numeric` vector (*m* elements) with the assigned grouping scores for each gene/probe

`ftable data.frame` (*m* lines) with additional grouping features

`centroids numeric SVTable` (*g* lines) with the S and V centroid coordinates for each group

`offsets numeric SVTable` (*m* lines) with the S and V coordinate offsets each gene/probe from its group centroid

`info list` of additional information

Methods

Alternative accessors

`levels(x)` Returns the unique group names included in the group set. Equivalent to `levels(groups(x))`

Conversion and coercion

`as.data.frame(x, row.names = names(x), ...)` Returns a `data.frame` with the `groups` and `scores` slots as columns

`as.expression(x, sv, ...)` Gets the expression that reproduces this `GEVAGroupSet` object, including function parameters used by `geva.cluster`. The `sv` argument is optional but can be specified to replace the source `SVTable`

`as.SVTable(x, which = c("sv", "offsets", "centroids"), ...)` Retrieves a `SVTable` based on the contents indicated by `which`. The accepted arguments are: `sv` for the source data; `offsets` for the `offsets` slots; and `centroids` for the `centroids` slot

Dimension accessors

`length(x)` Returns the number of rows in the `sv` slot

`names(x)` Gets the assigned names by the classification and scores

Plotting

`color.values(x, point.col = NULL, ...)` Gets the colors associated to the grouped data points. If not present, generates random group colors.
If `point.col` is a single `character` or an vector of the same length of data points, adjusts the color values to web RGBA

`plot(x, y, ...)` Draws a SV-plot that highlights the grouped information.
Can be combined with another `SVTable` or `GEVAGroupSet` given as the `y` argument to include additional graphical elements

`points(x, ...)` Draws the grouped points

Properties

`analysis.params(gobject)` Returns a `list` of analysis parameters passed to `geva.cluster` to obtain this object

`cluster.method(object)` Returns the option used as the `cluster.method` argument when calling `geva.cluster`

Sub-slot accessors

`classification.table(object) <- value` Stores the classification `data.frame` on this object

`classification.table(object)` Returns a `data.frame` of predicted classifications, if supported by this object

`sv.data(object)` Returns a `SVTable` with the source SV coordinates

`sv(object)` Returns the `numeric matrix` in the `SVTable` from `sv.data(object)`

GEVAInput-class *GEVA Input Data*

Description

The GEVAInput class contains the initial data for GEVA usage. It stores numeric matrices of *logFC* values from differential expression comparison results. Options for calculations and summarizing are also included.

Value

A GEVAInput object

Slots

values numeric matrix (*m*n*) of log-ratio values, usually *logFC*

weights numeric matrix (*m*n*) of weighted values. If not defined, all weight values are equal to 1

factors factor (*n* elements) representing the grouping of the n columns. If not defined, all factors are equal to NA

ftable data.frame with *m* rows containing attribute columns associated to the features (*e.g.*, probes or genes)

info list of supplementary information related to the input

Methods

Alternative accessors

levels(x) Returns the unique values from the assigned factors; or NA if there are no assigned factors in x

Conversion and coercion

as.array(x, ...) Converts this object to array

Dimension accessors

dim(x) Gets the dimensions defined for both matrices in values and weights slots

dimnames(x) <- value Sets the list with the row and column names.
Individual dimension names can also be set using rownames<- and colnames<-

dimnames(x) Gets a list with the row and column names.
Individual dimension names can also be accessed through rownames and colnames

inputnames(object) Gets the input column names (same as colnames(object))

length(x) Returns the number of rows in the values slot

`names(x)` Same as `inputnames`. For internal use

Plotting

`plot(x, y, ...)` Summarizes the input using the default parameters, then calls the plot on the returned `GEVASummary` object.
Not intended to regular use and will give a warning if called

Properties

`analysis.params(gobject)` Returns a `list` of analysis parameters passed to `geva.merge.input` or `geva.read.tables` to obtain this object

Subsetting

`head(x, n = 6L, ...)` Returns the first parts of the `values` table

`tail(x, n = 6L, ...)` Returns the last parts of the `values` table

GEVAQuantiles-class *GEVA Quantiles Grouping Results*

Description

The `GEVAQuantiles` class represents the results of a quantile detection analysis. For each probe/gene, there is a assigned quantile among the g defined quantiles.

This class inherits from `GEVAGroupSet` and is inherited by `GEVAQuantilesAdjusted`.

Value

A `GEVAQuantiles` object

Slots

`grouping factor` (m elements, g levels), quantile assignment for each gene/probe
(Inherited from `GEVAGroupSet`)

`scores numeric` vector (m elements) with the assigned quantile scores for each gene/probe
(Inherited from `GEVAGroupSet`)

`ftable data.frame` (m lines) with additional quantile assignment features
(Inherited from `GEVAGroupSet`)

`centroids numeric SVTable` (g lines) with the S and V centroid coordinates for each quantile
(Inherited from `GEVAGroupSet`)

`offsets numeric SVTable` (m lines) with the S and V coordinate offsets each gene/probe from its quantile centroid
(Inherited from `GEVAGroupSet`)

`info` `list` of additional information
(Inherited from `GEVAGroupSet`)

`svscores` `numeric` `SVTable` (*m* lines) with individual partial scores for the assigned quantiles

`qareasizes` `numeric` `SVTable` (*g* lines) with the S and V sizes for each quantile

`qindexes` `integer` `SVTable` (*g* lines) representing the position index to each quantile, in terms of summary and variation

`qcount` integer attributes (`SVIntAttribute`) with the defined number of quantiles for the S and V axes

`qcutoff` numeric attributes (`SVNumAttribute`) with the initial quantile cutoff in S and V, starting from the point zero

`qmethod` `character`, method used to calculate the initial quantiles (see `geva.quantiles()`)

Methods

(See also the inherited methods from `GEVAGroupSet`)

Conversion and coercion

`as.expression(x, sv, ...)` Converts this object to `expression`

`as.SVTable( x, which = c("sv", "offsets", "centroids", "qindexes"), ..., row.names = names(x) )`
Converts this object to `SVTable`

Plotting

`lines(x, ...)` Draws the quantile delimiter lines

`plot(x, y, ...)` Draws a SV-plot that highlights the points from each quantile. Dashed lines are included as the quantile delimiters.
Can be combined with another `SVTable` or `GEVAGroupSet` given as the `y` argument to include additional graphical elements

Properties

`cluster.method(object)` Returns the option used as the `cluster.method` argument when calling `geva.cluster`.
Instances of this object always return `'quantiles'`

Sub-slot accessors

`classification.table(object) <- value` Sets the `data.frame` with the qualitative contrasts of classification relevance

`classification.table(object)` Gets a `data.frame` with the qualitative contrasts of classification relevance

`quantiles(object)` Gets the unique quantile names

GEVAQuantilesAdjusted-class
GEVA Adjusted Quantiles Results

Description

The GEVAQuantilesAdjusted class represents the results of a quantile detection analysis with adjusted assignments based on relationships with other GEVAGroupSet objects. For each probe/gene, there is a assigned quantile among the *g* defined quantiles.

This class inherits from GEVAQuantiles.

Value

A GEVAQuantilesAdjusted object

Slots

grouping factor (*m* elements, *g* levels), quantile assignment for each gene/probe
(Inherited from GEVAGroupSet)

scores numeric vector (*m* elements) with the assigned quantile scores for each gene/probe
(Inherited from GEVAGroupSet)

ftable data.frame (*m* lines) with additional quantile assignment data
(Inherited from GEVAGroupSet)

centroids numeric SVTable (*g* lines) with the S and V centroid coordinates for each quantile
(Inherited from GEVAGroupSet)

offsets numeric SVTable (*m* lines) with the S and V coordinate offsets each gene/probe from its quantile centroid
(Inherited from GEVAGroupSet)

info list of additional information
(Inherited from GEVAGroupSet)

svscores numeric SVTable (*m* lines) with individual partial scores for the assigned quantiles
(Inherited from GEVAQuantiles)

qareasizes numeric SVTable (*g* lines) with the S and V sizes for each quantile
(Inherited from GEVAQuantiles)

qindexes integer SVTable (*g* lines) representing the position index to each quantile, in terms of summary and variation
(Inherited from GEVAQuantiles)

qcount integer attributes (SVIntAttribute) with the defined number of quantiles for the S and V axes
(Inherited from GEVAQuantiles)

qcutoff numeric attributes (SVNumAttribute) with the initial quantile cutoff in S and V, starting from the point zero
(Inherited from GEVAQuantiles)

grouprels TypedList of named factor elements representing external group relationships to the current quantiles

Methods

(See also the inherited methods from GEVAQuantiles and GEVAGroupSet)

GEVAResults-class *GEVA Results Table*

Description

The GEVAResults class contains the final results from GEVA analyses. It represents the results of multiple statistical approaches from summary/variation data, clustering, quantile detection, and factor analysis (if applicable).

Value

A GEVAResults object

Slots

`resultstable` `data.frame` (*m* lines) with classification results for the genes/probes

`svdata` GEVASummary used as input

`quantdata` GEVAQuantiles or GEVAQuantilesAdjusted with the final quantile assignments for the summarized data

`factoring` `data.frame` (*m* lines) with detailed results for the factor analyses, such as p-values for each factor. If there was no factor analysis, this slot is NULL or empty

`classiftable` `data.frame` used as reference for the final classification

`info` `list` of supplementary information

Methods

Conversion and coercion

`as.expression(x, gsummary, gquants, ...)` Gets the expression that reproduces this GEVAResults object, including function parameters used by `geva.finalize`. The `gsummary` and `gquants` arguments are optional but can be specified to replace the internal GEVASummary and GEVAQuantiles, respectively

Dimension accessors

`dim(x)` Returns the dimensions from the `resultstable` slot

`dimnames(x)` Returns a `list` with the row and column names from the `results.table` slot. Individual dimension names can also be accessed through `rownames` and `colnames`

`length(x)` Returns the number of rows in the `resultstable` slot

`names(x)` Returns the column names from the `resultstable` slot

Plotting

`plot(x, y, ...)` Draws a SV-plot that highlights the relevant points from adjusted quantiles

`points(x, which, ..., classif)` Draws the results points.
If `which` (`character` vector) is given, plots only the matching genes/probes.
If `classif` (`character` vector) is given, plots only points with the matching classification

Properties

`x$name <- value` Extracts a column from the `resultstable` slot

`x[i, j, ..., drop=TRUE]` Extracts the contents from the `resultstable` slot

`analysis.params(gobject)` Returns a `list` of analysis parameters passed to `geva.finalize` or `geva.quick` to obtain this object

Sub-slot accessors

`featureTable(object)` Returns the features `data.frame` from the internal `GEVAInput`

`head(x, ...)` Returns the first lines of `results.table(x)`

`inputdata(object)` Returns the internal `GEVAInput`

`inputvalues(object)` Returns the values `matrix` from the internal `GEVAInput`

`inputweights(object, normalized)` Returns the weights `matrix` from the internal `GEVAInput`

`levels(x)` Returns the factors used in factor analysis, if present

GEVASummary-class *GEVA Summary-Variation Table*

Description

The `GEVASummary` class represents the calculation results for summary and variation from a `GEVAInput`.

This class inherits from `SVTable`.

Value

A `GEVASummary` object

Slots

`sv numeric matrix` composed by two columns: `S` (summary) and `V` (variation)
(Inherited from `SVTable`)

`inputdata` GEVAInput-class with the data input

`sv.method` Names of the statistical methods used to summarize data

`info` list with additional information

Methods

(See also the inherited methods from SVTable)

Conversion and coercion

`as.expression(x, ginput, ...)` Gets the expression that reproduces this `GEVASummary` object, including function parameters used by `geva.summary`. The `ginput` argument is optional but can be specified to replace the internal `GEVAInput`

`as.matrix(x, ...)` Equivalent to `sv(x)`

Grouping

`groupsets(object) <- value` Converts this instance to `GEVAGroupedSummary` and sets the list of `GEVAGroupSet` objects. Can be used with `$<name>` to specify the object name in the list. If `value` is a `GEVAGroupSet`, inserts the element and sets the name based on the value call

`groupsets(object)` Gets the list of `GEVAGroupSet` objects attached to this instance. Only applicable for `GEVAGroupedSummary` objects

Plotting

`plot(x, y, ...)` Draws a SV-plot. The horizontal axis is for *summary* (S) and the vertical axis is for *variation* (V)

Properties

`analysis.params(gobject)` Returns a `list` of analysis parameters passed to `geva.summarize` to obtain this object

`get.summary.method(x)` Gets a `character` for the summarization method name

`get.variation.method(x)` Gets a `character` for the variation calculation method name

Sub-slot accessors

`factors(object) <- value` Sets the value to the `factor` slot in the internal `GEVAInput`

`factors(object)` Gets the `factor` defined in the `factors` slot in the internal `GEVAInput`

`featureTable(object)` Gets the `data.frame` from the `ftable` slot in the internal `GEVAInput`

`infolist(object, field = NULL, ...)` Gets the `list` from the `info` slot.
If `recursive` is `TRUE`, appends the contents from the `info` slot in the internal `GEVAInput`

`inputvalues(object)` Gets the `matrix` from the `values` slot in the internal `GEVAInput`

`inputweights(object, normalized)` Gets the `matrix` from the `weights` slot in the internal `GEVAInput`

SVAttribute-class *Summary-Variation Attribute Field*

Description

This S4 class stores two character slots representing attribute fields for summary and variation. The SVAttribute class is abstract and must be instantiated as SVChrAttribute (for character), SVNumAttribute (for numeric), or SVIntAttribute (for integer).

Arguments

S	the *summary* value
V	the *variation* value

Value

A SVAttribute object

Slots

S either character or numeric or integer of length one

V either character or numeric or integer of length one

Methods

Alternative accessors

summary(object, ...) Returns the contents from S slot

sv(object) Returns the contents as a named vector

variation(object, ...) Returns the contents from S slot

Constructors

sv.data(object) For internal use. Returns the equivalent object

svattr(S, V) Creates a new SVAttribute

Conversion and coercion

as.character(x, ...) Converts this object to character

as.vector(x, ...) Converts this object to vector

Dimension accessors

dim(x) For internal use, always returns NULL

`names(x)` Returns the slot names (always `c('S', 'V')`)

Properties

`x$name <- value` Queries the vector contents (equivalent to the indexer). Only accepts `$S` and `$V`

`x[i, j, ..., drop=TRUE]` Indexer to access the vector values. Only accepts `'S'` or `'V'` as `i` arguments

Note

The slots `S` and `V` must be of the same class (either `character`, `numeric`, or `integer`).

SVTable-class *Summary-Variation Table*

Description

The `SVTable` class stores a `matrix` composed by two columns: `S` (for *summary*) and `V` (for *variation*).

This class is inherited by `GEVASummary`.

Value

A `SVTable` object

Slots

`sv` `matrix` composed by two columns: `S` (summary) and `V` (variation)

Methods

Alternative accessors

`summary(object, ...)` Returns the `S` column

`sv.data(object)` Equivalent to returning this object itself

`variation(object, ...)` Returns the `V` column

Constructor

`svtable(S, V, row.names = NULL)` Creates a SVTable from the vectors `S` and `V`

Conversion and coercion

`as.data.frame(x, ...)` Converts this object to `data.frame`

`as.matrix(x, ...)` Converts this object to `matrix`

`as.SVTable.data.frame(x, row.names = rownames(x), ...)` Converts a `data.frame` to a `SVTable`

`as.SVTable.matrix(x, row.names = rownames(x), ...)` Converts a `matrix` to a `SVTable`

`as.SVTable(x, ...)` Returns the same object

Dimension accessors

`dimnames(x)` Gets a `list` with the row and column names from the `sv` slot.
Individual dimension names can also be accessed through `rownames` and `colnames`

`dim(x)` Gets the dimensions from the `sv` slot

`length(x)` Returns the number of rows in the `sv` slot

`names(x)` Always returns `c('S', 'V')`

Formatting and evaluation

`format(x, ...)` Generic `format` implementation for `SVTable`

`with(data, expr, ...)` Generic `with` implementation for `SVTable`

Plotting

`plot(x, y, ...)` Draws a SV-plot. The horizontal axis is for *summary* (S) and the vertical axis is for *variation* (V)

`points(x, ...)` Draws the SV points in the plot

Subsetting

`head(x, n = 6L, ...)` Returns the first parts of the matrix contents

`tail(x, n = 6L, ...)` Returns the last parts of the matrix contents

Validation

`is.na(x)` Generic `is.na` implementation for `SVTable`

Note

The matrix from `sv` slot can be `numeric`, `character`, or any other supported type by `matrix`. The same slot from `GEVASummary`, however, is always a numeric `matrix`.

Examples

```
## Creates a SV-table where:
# - S has elements from 1 to 10; and
# - V has elements from 10 to 1
svtab <- svtable(seq.int(1, 10), seq.int(10, 1))
```

top.genes *Top Results from GEVA*

Description

Extracts the genes with a relevant classification according to the GEVA results.

Usage

```
top.genes(
  gevaresults,
  classif = c("similar", "factor-dependent", "factor-specific"),
  which.spec = levels(gevaresults),
  add.cols = NULL,
  ...,
  names.only = FALSE
)
```

Arguments

gevaresults	a GEVAResults object
classif	character vector, filters the returned genes by their final classification. Possible options are "similar", "factor-dependent", "factor-specific", "sparse", and "basal". Multiple options can be combined
which.spec	factor, filters the specific factors to be returned
add.cols	character vector with column names from the feature table (accessed by featureTable(gevaresults)) The matching columns will be added to the returned table
...	optional arguments (not used in this version)
names.only	logical, set to TRUE to return only the table row names

Value

If names.only is FALSE (the default), returns a subset of the resultstable slot (data.frame) from the gevaresults that includes only the filtered genes according to the function parameters.

Otherwise, if names.only is TRUE, returns only the row names (character vector) of this table subset.

Examples

```
## Basic usage with a random generated input
ginput <- geva.ideal.example() # Generates a random input example
gresults <- geva.quick(ginput) # Performs the entire analysis (default parameters)

# Gets a table that includes all the top genes
dtgenes <- top.genes(gresults) # Gets the top genes table
head(dtgenes)                  # Prints the first results
```

```
# Appends the "Symbol" column to the results table
dtgenes <- top.genes(gresults, add.cols="Symbol")
head(dtgenes)                  # Prints the first results

# Appends all feature columns to the results table
dtgenes <- top.genes(gresults, add.cols=names(featureTable(gresults)))
head(dtgenes)                  # Prints the first results

# Gets only the factor-specific genes
dtgenes <- top.genes(gresults, "factor-specific")
head(dtgenes)                  # Prints the first results

# Gets only the factor-specific genes for "Cond_1" factor (if any)
dtgenes <- top.genes(gresults, "factor-specific", "Cond_1")
head(dtgenes)                  # Prints the first results
```

`TypedList-class` *Type-strict List (TypedList-class)*

Description

List containing elements of the same class or inheritance.

Value

A `TypedList` object

Slots

`.Data` `list` of internal contents. Elements must match or inherit a common class (Inherited from `list`)

`elem.class` `character` representing the class related to the elements

Methods

Constructors

`typed.list(..., elem.class = NA_character_)` Creates a TypedList from the elements in `...` derived from the class `elem.class`

Conversion and coercion

`as.list(x, ...)` Converts this object to `list`

`as.typed.list.list(x, elem.class = NA_character_)` Converts a `list` to a `TypedList` if its elements inherit the same type

`as.typed.list(x, elem.class = NA_character_)` Coerces a `TypedList` to support the inherited class indicated by `elem.class`

`as.typed.list.vector(x, elem.class = NA_character_)` Converts a vector to a `TypedList`

Properties

`x[i, j, ...] <- value` Sets a value to this list. The `value` argument must be compatible to the current list type

Examples

```
## Creates a TypeList that stores list-derived objects
tpls = typed.list(A=list(1L:5L),
                  B=data.frame(v1=LETTERS[1L:10L]),
                  elem.class = 'list')

# Note: The 'elem.class' above is optional, since the
# class is automatically detected from the first argument
```

Index

∗ **datasets**
    geva.cluster, 5
    geva.dcluster, 7
    geva.finalize, 9
    geva.hcluster, 11
    geva.quantiles, 20
    geva.summarize, 23
∗ **geva.cluster**
    geva.cluster, 5
    geva.dcluster, 7
    geva.hcluster, 11
    geva.quantiles, 20
[,GEVAInput,ANY,ANY,ANY-method *(GEVAInput-class)*, 29
[,GEVAQuantiles,ANY,ANY,ANY-method *(GEVAQuantiles-class)*, 30
[,GEVAResults,ANY,ANY,ANY-method *(GEVAResults-class)*, 33
[,SVAttribute,ANY,ANY,ANY-method *(SVAttribute-class)*, 36
[,SVTable,ANY,ANY,ANY-method *(SVTable-class)*, 37
[,TypedList,ANY,missing,missing-method *(TypedList-class)*, 40
[<-,TypedList,character,missing-method *(TypedList-class)*, 40
$,GEVAResults-method *(GEVAResults-class)*, 33
$,SVAttribute-method *(SVAttribute-class)*, 36
$,SVTable-method *(SVTable-class)*, 37

analysis.params *(generics)*, 3
analysis.params,GEVAGroupedSummary-method *(GEVAGroupedSummary-class)*, 26
analysis.params,GEVAGroupSet-method *(GEVAGroupSet-class)*, 27
analysis.params,GEVAInput-method *(GEVAInput-class)*, 29
analysis.params,GEVAResults-method *(GEVAResults-class)*, 33
analysis.params,GEVASummary-method *(GEVASummary-class)*, 34
as.array.GEVAInput *(GEVAInput-class)*, 29
as.character.SVAttribute *(SVAttribute-class)*, 36
as.data.frame.GEVAGroupSet *(GEVAGroupSet-class)*, 27
as.data.frame.SVTable *(SVTable-class)*, 37
as.expression.GEVAGroupedSummary *(GEVAGroupedSummary-class)*, 26
as.expression.GEVAGroupSet *(GEVAGroupSet-class)*, 27
as.expression.GEVAQuantiles *(GEVAQuantiles-class)*, 30
as.expression.GEVAResults *(GEVAResults-class)*, 33
as.expression.GEVASummary *(GEVASummary-class)*, 34
as.list.TypedList *(TypedList-class)*, 40
as.matrix.GEVAGroupedSummary *(GEVAGroupedSummary-class)*, 26
as.matrix.GEVASummary *(GEVASummary-class)*, 34
as.matrix.SVTable *(SVTable-class)*, 37
as.SVTable *(generics)*, 3
as.SVTable.data.frame *(SVTable-class)*, 37
as.SVTable.GEVAGroupSet *(GEVAGroupSet-class)*, 27
as.SVTable.GEVAQuantiles *(GEVAQuantiles-class)*, 30
as.SVTable.matrix *(SVTable-class)*, 37
as.SVTable.SVTable *(SVTable-class)*, 37
as.typed.list.list *(TypedList-class)*, 40
as.typed.list.TypedList *(TypedList-class)*, 40

as.typed.list.vector *(TypedList-class)*, 40
as.vector.SVAttribute *(SVAttribute-class)*, 36

base::mean(), *24*

centroids *(generics)*, 3
centroids,GEVAGroupSet-method *(GEVAGroupSet-class)*, 27
classification.table *(generics)*, 3
classification.table,GEVAGroupSet-method *(GEVAGroupSet-class)*, 27
classification.table,GEVAQuantiles-method *(GEVAQuantiles-class)*, 30
classification.table<- *(generics)*, 3
classification.table<-,GEVAGroupSet,data.frame-method *(GEVAGroupSet-class)*, 27
classification.table<-,GEVAQuantiles,data.frame-method *(GEVAQuantiles-class)*, 30
cluster.method *(generics)*, 3
cluster.method,GEVACluster-method *(GEVACluster-class)*, 25
cluster.method,GEVAGroupedSummary-method *(GEVAGroupedSummary-class)*, 26
cluster.method,GEVAGroupSet-method *(GEVAGroupSet-class)*, 27
cluster.method,GEVAQuantiles-method *(GEVAQuantiles-class)*, 30
color.values.GEVAGroupSet *(GEVAGroupSet-class)*, 27

dbscan::dbscan, *8*
dbscan::dbscan(), *8*
dbscan::optics(), *8*
dim,GEVAInput-method *(GEVAInput-class)*, 29
dim,GEVAQuantiles-method *(GEVAQuantiles-class)*, 30
dim,GEVAResults-method *(GEVAResults-class)*, 33
dim,SVAttribute-method *(SVAttribute-class)*, 36
dim,SVTable-method *(SVTable-class)*, 37
dimnames,GEVAInput-method *(GEVAInput-class)*, 29
dimnames,GEVAResults-method *(GEVAResults-class)*, 33
dimnames,SVTable-method *(SVTable-class)*, 37
dimnames<-,GEVAInput,list-method *(GEVAInput-class)*, 29

elem.class *(generics)*, 3
elem.class,TypedList-method *(TypedList-class)*, 40
elem.class<- *(generics)*, 3
elem.class<-,TypedList,character-method *(TypedList-class)*, 40

factors, *11*
factors *(generics)*, 3
factors,GEVAInput-method *(GEVAInput-class)*, 29
factors,GEVASummary-method *(GEVASummary-class)*, 34
factors<- *(generics)*, 3
factors<-,GEVAInput,character-method *(GEVAInput-class)*, 29
factors<-,GEVAInput,factor-method *(GEVAInput-class)*, 29
factors<-,GEVASummary,character-method *(GEVASummary-class)*, 34
factors<-,GEVASummary,factor-method *(GEVASummary-class)*, 34
fastcluster::fastcluster, *12*
fastcluster::hclust.vector(), *6*, *12*
featureTable *(generics)*, 3
featureTable,GEVAGroupSet-method *(GEVAGroupSet-class)*, 27
featureTable,GEVAInput-method *(GEVAInput-class)*, 29
featureTable,GEVAResults-method *(GEVAResults-class)*, 33
featureTable,GEVASummary-method *(GEVASummary-class)*, 34
featureTable<- *(generics)*, 3
featureTable<-,GEVAInput,data.frame-method *(GEVAInput-class)*, 29
format.SVTable *(SVTable-class)*, 37

generics, 3
get.distance.method *(generics)*, 3
get.summary.method *(generics)*, 3
get.summary.method.GEVASummary *(GEVASummary-class)*, 34
get.variation.method *(generics)*, 3

get.variation.method.GEVASummary
(GEVASummary-class), 34
geva.cluster, 5, 9, 10, 13, 21, 22, 25, 27, 28
geva.cluster(), 22
geva.dcluster, 7, 7, 13, 21
geva.dcluster(), 6
geva.finalize, 9, 22, 34
geva.finalize(), 22
geva.hcluster, 7, 9, 11, 21
geva.hcluster(), 6
geva.ideal.example, 13
geva.input.correct, 14
geva.input.filter, 17
geva.input.filter (geva.input.correct), 14
geva.input.rename.rows
(geva.input.correct), 14
geva.merge.input, 16, 30
geva.quantiles, 7, 9, 10, 13, 20, 22
geva.quantiles(), 6, 22, 31
geva.quick, 22, 34
geva.read.tables, 30
geva.read.tables (geva.merge.input), 16
geva.summarize, 14, 23, 35
geva.summarize(), 22
GEVACluster, 7, 9, 10, 13, 25, 27
GEVACluster-class, 25
GEVAGroupedSummary, 7, 26, 35
GEVAGroupedSummary-class, 26
GEVAGroupSet, 7, 10, 25–27, 30–33, 35
GEVAGroupSet-class, 27
GEVAInput, 14, 15, 17, 18, 22, 24, 29, 34, 35
GEVAInput-class, 29
GEVAQuantiles, 7, 10, 27, 30, 32, 33
GEVAQuantiles-class, 30
GEVAQuantilesAdjusted, 30, 32, 33
GEVAQuantilesAdjusted-class, 32
GEVAResults, 5, 11, 22, 23, 33, 39
GEVAResults-class, 33
GEVASummary, 6–8, 10, 12, 20, 22, 24, 26, 33, 34, 37, 38
GEVASummary-class, 34
group.rels (generics), 3
group.rels,GEVAQuantilesAdjusted-method
(GEVAQuantilesAdjusted-class), 32
groups (generics), 3
groups,GEVAGroupSet-method
(GEVAGroupSet-class), 27
groupsets (generics), 3
groupsets,GEVAGroupedSummary-method
(GEVAGroupedSummary-class), 26
groupsets,GEVASummary-method
(GEVASummary-class), 34
groupsets<- (generics), 3
groupsets<-,GEVAGroupedSummary,GEVAGroupSet-method
(GEVAGroupedSummary-class), 26
groupsets<-,GEVASummary,GEVAGroupSet-method
(GEVASummary-class), 34
groupsets<-,GEVASummary,TypedList-method
(GEVASummary-class), 34

head.GEVAInput (GEVAInput-class), 29
head.GEVAResults (GEVAResults-class), 33
head.SVTable (SVTable-class), 37

infolist (generics), 3
infolist,GEVAGroupSet,character-method
(GEVAGroupSet-class), 27
infolist,GEVAGroupSet,missing-method
(GEVAGroupSet-class), 27
infolist,GEVAInput,character-method
(GEVAInput-class), 29
infolist,GEVAInput,missing-method
(GEVAInput-class), 29
infolist,GEVAResults,character-method
(GEVAResults-class), 33
infolist,GEVAResults,missing-method
(GEVAResults-class), 33
infolist,GEVASummary,missing-method
(GEVASummary-class), 34
infolist<- (generics), 3
infolist<-,GEVAGroupSet,list-method
(GEVAGroupSet-class), 27
infolist<-,GEVAInput,list-method
(GEVAInput-class), 29
infolist<-,GEVASummary,list-method
(GEVASummary-class), 34
inputdata (generics), 3
inputdata,GEVAInput-method
(GEVAInput-class), 29
inputdata,GEVAResults-method
(GEVAResults-class), 33
inputdata,GEVASummary-method
(GEVASummary-class), 34
inputnames (generics), 3

inputnames,GEVAInput-method
(GEVAInput-class), 29
inputnames,GEVASummary-method
(GEVASummary-class), 34
inputvalues (generics), 3
inputvalues,GEVAInput-method
(GEVAInput-class), 29
inputvalues,GEVAResults-method
(GEVAResults-class), 33
inputvalues,GEVASummary-method
(GEVASummary-class), 34
inputweights (generics), 3
inputweights,GEVAInput,logical-method
(GEVAInput-class), 29
inputweights,GEVAInput,missing-method
(GEVAInput-class), 29
inputweights,GEVAResults,logical-method
(GEVAResults-class), 33
inputweights,GEVAResults,missing-method
(GEVAResults-class), 33
inputweights,GEVASummary,logical-method
(GEVASummary-class), 34
inputweights,GEVASummary,missing-method
(GEVASummary-class), 34
is.na.SVTable (SVTable-class), 37

length,GEVAGroupSet-method
(GEVAGroupSet-class), 27
length,GEVAInput-method
(GEVAInput-class), 29
length,GEVAResults-method
(GEVAResults-class), 33
length,SVTable-method (SVTable-class),
37
levels.GEVAGroupSet
(GEVAGroupSet-class), 27
levels.GEVAInput (GEVAInput-class), 29
levels.GEVAResults (GEVAResults-class),
33
lines.GEVACluster (GEVACluster-class),
25
lines.GEVAGroupedSummary
(GEVAGroupedSummary-class), 26
lines.GEVAQuantiles
(GEVAQuantiles-class), 30

names,GEVAGroupSet-method
(GEVAGroupSet-class), 27
names,GEVAInput-method
(GEVAInput-class), 29
names,GEVAResults-method
(GEVAResults-class), 33
names,SVAttribute-method
(SVAttribute-class), 36
names,SVTable-method (SVTable-class), 37

offsets (generics), 3
offsets,GEVAGroupSet-method
(GEVAGroupSet-class), 27
options.cl.score.method (geva.cluster),
5
options.cluster.method (geva.cluster), 5
options.dcluster.method
(geva.dcluster), 7
options.distance (geva.cluster), 5
options.factoring.p.adjust
(geva.finalize), 9
options.hc.method (geva.hcluster), 11
options.hc.metric (geva.hcluster), 11
options.quantiles (geva.quantiles), 20
options.summary (geva.summarize), 23
options.variation (geva.summarize), 23

p.adjust.methods, *11*
plot,GEVACluster,SVTable-method
(GEVACluster-class), 25
plot,GEVAGroupedSummary,missing-method
(GEVAGroupedSummary-class), 26
plot,GEVAGroupSet,GEVAGroupSet-method
(GEVAGroupSet-class), 27
plot,GEVAGroupSet,missing-method
(GEVAGroupSet-class), 27
plot,GEVAGroupSet,SVTable-method
(GEVAGroupSet-class), 27
plot,GEVAInput,missing-method
(GEVAInput-class), 29
plot,GEVAQuantiles,SVTable-method
(GEVAQuantiles-class), 30
plot,GEVAResults,missing-method
(GEVAResults-class), 33
plot,GEVASummary,missing-method
(GEVASummary-class), 34
plot,SVTable,GEVAGroupSet-method
(GEVAGroupSet-class), 27
plot,SVTable,missing-method
(SVTable-class), 37

points.GEVAGroupedSummary
(GEVAGroupedSummary-class), 26
points.GEVAGroupSet
(GEVAGroupSet-class), 27
points.GEVAResults (GEVAResults-class),
33
points.SVTable (SVTable-class), 37

qareasizes (generics), 3
qareasizes,GEVAQuantiles-method
(GEVAQuantiles-class), 30
qcount (generics), 3
qcount,GEVAQuantiles-method
(GEVAQuantiles-class), 30
qindexes (generics), 3
qindexes,GEVAQuantiles-method
(GEVAQuantiles-class), 30
quantiles (generics), 3
quantiles,GEVAGroupedSummary-method
(GEVAGroupedSummary-class), 26
quantiles,GEVAQuantiles-method
(GEVAQuantiles-class), 30
quantiles,GEVAResults-method
(GEVAResults-class), 33
quantiles,GEVASummary-method
(GEVASummary-class), 34
quantiles.method,GEVAQuantiles-method
(GEVAQuantiles-class), 30

regular expressions, *17*
results.table (generics), 3
results.table,GEVAResults-method
(GEVAResults-class), 33

scores (generics), 3
scores,GEVAGroupSet,character-method
(GEVAGroupSet-class), 27
scores,GEVAGroupSet,missing-method
(GEVAGroupSet-class), 27
show,GEVACluster-method
(GEVACluster-class), 25
show,GEVAGroupedSummary-method
(GEVAGroupedSummary-class), 26
show,GEVAGroupSet-method
(GEVAGroupSet-class), 27
show,GEVAInput-method
(GEVAInput-class), 29
show,GEVAQuantiles-method
(GEVAQuantiles-class), 30
show,GEVAQuantilesAdjusted-method
(GEVAQuantilesAdjusted-class),
32
show,GEVAResults-method
(GEVAResults-class), 33
show,GEVASummary-method
(GEVASummary-class), 34
show,SVAttribute-method
(SVAttribute-class), 36
show,SVTable-method (SVTable-class), 37
show,TypedList-method
(TypedList-class), 40
stats::mad(), *24*
stats::median(), *24*
stats::p.adjust.methods, *10*
stats::sd(), *24*
stats::var(), *24*
summary.SVAttribute
(SVAttribute-class), 36
summary.SVTable (SVTable-class), 37
sv (generics), 3
sv,GEVAGroupSet-method
(GEVAGroupSet-class), 27
sv,GEVAResults-method
(GEVAResults-class), 33
sv,SVAttribute-method
(SVAttribute-class), 36
sv,SVTable-method (SVTable-class), 37
sv.data,GEVAGroupSet-method
(GEVAGroupSet-class), 27
sv.data,GEVAResults-method
(GEVAResults-class), 33
sv.data,SVAttribute-method
(SVAttribute-class), 36
sv.data,SVTable-method (SVTable-class),
37
sv.scores,GEVAQuantiles-method
(GEVAQuantiles-class), 30
svattr (generics), 3
svattr,character,character-method
(SVAttribute-class), 36
svattr,integer,integer-method
(SVAttribute-class), 36
svattr,numeric,numeric-method
(SVAttribute-class), 36
SVAttribute, *36*
SVAttribute (SVAttribute-class), 36
SVAttribute-class, 36

SVChrAttribute *(SVAttribute-class)*, 36
SVChrAttribute-class
(SVAttribute-class), 36
SVIntAttribute, *31, 32*
SVIntAttribute *(SVAttribute-class)*, 36
SVIntAttribute-class
(SVAttribute-class), 36
SVNumAttribute, *31, 32*
SVNumAttribute *(SVAttribute-class)*, 36
SVNumAttribute-class
(SVAttribute-class), 36
SVTable, *6*, *8*, *12*, *20*, *26, 27*, *31, 32*, *34, 35*, *37*
SVTable *(SVTable-class)*, 37
svtable *(SVTable-class)*, 37
SVTable-class, 37

tail.GEVAInput *(GEVAInput-class)*, 29
tail.SVTable *(SVTable-class)*, 37
top.genes, 39
top.genes(), *11*
typed.list *(TypedList-class)*, 40
TypedList, *5*, *26*, *32*, *40*
TypedList-class, 40

utils::read.table, *17*

variation *(generics)*, 3
variation.SVAttribute
(SVAttribute-class), 36
variation.SVTable *(SVTable-class)*, 37

with.SVTable *(SVTable-class)*, 37