

Package: lionessR (via r-universe)

June 8, 2026

Title Modeling networks for individual samples using LIONESS

Version 1.26.0

Description LIONESS, or Linear Interpolation to Obtain Network Estimates for Single Samples, can be used to reconstruct single-sample networks (<https://arxiv.org/abs/1505.06440>). This code implements the LIONESS equation in the `lioness` function in R to reconstruct single-sample networks. The default network reconstruction method we use is based on Pearson correlation. However, `lionessR` can run on any network reconstruction algorithms that returns a complete, weighted adjacency matrix. `lionessR` works for both unipartite and bipartite networks.

License MIT + file LICENSE

LazyData TRUE

Imports stats, SummarizedExperiment, S4Vectors

Depends R (>= 3.6.0)

Suggests knitr, rmarkdown, igraph, reshape2, limma,

biocViews Network, NetworkInference, GeneExpression

BugReports <https://github.com/mararie/lionessR/issues>

URL <https://github.com/mararie/lionessR>

Encoding UTF-8

RoxygenNote 6.0.1

VignetteBuilder knitr

Config/pak/sysreqs zlib1g-dev

Repository <https://bioc-release.r-universe.dev>

Date/Publication 2026-04-28 12:50:59 UTC

RemoteUrl <https://github.com/bioc/lionessR>

RemoteRef RELEASE_3_23

RemoteSha aa85c615e037f75141c10ad575dfbf3977a0a694

Contents

lioness	2
netFun	3
OSdata	3
Index	4

lioness	<i>LIONESS</i>
---------	----------------

Description

This function uses the LIONESS equation to estimate single-sample networks. The input supports numeric matrix or a SummnerizedExperiment object.

Usage

```
lioness(x, f = netFun)
```

Arguments

x	Numeric matrix with samples in columns or SummnerizedExperiment object
f	Network reconstruction function. Defaults to Pearson correlation.

Value

SummnerizedExperiment object for single-sample association network. The rowData contains the information about the regulators and their targets, while the colData contains the information about the samples. The edge weights of sample specific networks can be accessed through the lioness assay of the object.

Examples

```
exp <- matrix(sample(1000,1000)/1000, 100, 10)
genes <- paste("gene", c(1:nrow(exp)), sep="_")
samples <- paste("sample", c(1:ncol(exp)), sep="_")

rowData <- S4Vectors::DataFrame(row.names = genes, gene = genes)
colData <- S4Vectors::DataFrame(col.names = samples, sample = samples)

se <- SummnerizedExperiment::SummnerizedExperiment(assays = list(counts = exp),
                                                    colData = colData, rowData = rowData)

lionessResults <- lioness(se, netFun)
```

netFun	<i>netFun</i>
--------	---------------

Description

This is the network reconstruction function that will be used to build aggregate networks.

Usage

```
netFun(x)
```

Arguments

x Numeric matrix with samples in columns.

Value

Numeric matrix of association network.

Examples

```
exp <- matrix(sample(1000, 1000)/1000, 100, 10)
netFun(exp)
```

OSdata	<i>OS data</i>
--------	----------------

Description

Pre-processed gene expression data from high-grade osteosarcoma biopsies and sample characteristics were downloaded from GEO (GSE42352). We converted nuIDs to gene symbols using the annotation platform GPL10295. For genes with duplicate gene symbols, we selected the gene with the highest variance. Finally, we subsetted the data to the 53 patients for which 5 year metastasis information was available. Finally, we extracted genes with top 10,000 variance to reduce the size of the dataset.

Usage

```
data(OSdata)
```

Format

Variable "exp": Data frame containing expression data for 10000 genes and 53 samples. Variable "targets": Data frame containing information on whether patients developed metastases within 5 years or not, 53 samples and 2 columns.

Index

* **datasets**

OSdata, 3

* **lioness**

lioness, 2

* **netFun**

netFun, 3

exp (OSdata), 3

lioness, 2

netFun, 3

OSdata, 3

targets (OSdata), 3