

Package: mitology (via r-universe)

May 29, 2026

Type Package

Title Study of mitochondrial activity from RNA-seq data

Version 1.4.0

Description mitology allows to study the mitochondrial activity through high-throughput RNA-seq data. It is based on a collection of genes whose proteins localize in to the mitochondria. From these, mitology provides a reorganization of the pathways related to mitochondria activity from Reactome and Gene Ontology. Further a ready-to-use implementation of MitoCarta3.0 pathways is included.

License AGPL-3

biocViews GeneExpression, RNASeq, Visualization, SingleCell, Spatial, Pathways, Reactome, GO

Imports AnnotationDbi, ape, circlize, clusterProfiler, ComplexHeatmap, ggplot2, ggtree, magrittr, org.Hs.eg.db, ReactomePA, scales

Encoding UTF-8

RoxygenNote 7.3.3

Depends R (>= 4.5.0)

LazyData false

Suggests Biobase, BiocStyle, GSVA, methods, rmarkdown, knitr, SummarizedExperiment, testthat

VignetteBuilder knitr

BugReports <https://github.com/CaluraLab/mitology/issues>

URL <https://github.com/CaluraLab/mitology>

Config/pak/sysreqs libcairo2-dev cmake libfontconfig1-dev libfreetype6-dev libglpk-dev make libicu-dev libpng-dev libuv1-dev libxml2-dev libssl-dev perl zlib1g-dev

Repository <https://bioc-release.r-universe.dev>

Date/Publication 2026-04-28 13:04:59 UTC

RemoteUrl <https://github.com/bioc/mitology>

RemoteRef RELEASE_3_23

RemoteSha a7ed717d4d58a012cb7c9fb2ec3f237503c29d86

Contents

enrichMito	2
getGeneSets	3
gseaMito	3
MitoGenesDB	4
mitoHeatmap	5
mitoTreeHeatmap	6
mitoTreePoint	7
ovse	8
Index	9

enrichMito

Mitochondrial Enrichment Analysis of a gene list.

Description

Given a vector of genes, this function will return the enrichment analysis for the mitochondrial gene sets after FDR control. For the Reactome, GO-CC and GO-BP databases it returns also the enrichment results for the corresponding original pathways.

Usage

```
enrichMito(genes, database)
```

Arguments

genes	a vector of gene ENSEMBL id.
database	character string saying the database to use for the analysis. Either one of "Mito-Carda", "Reactome", "GO-CC" and "GO-BP".

Value

enrichment analysis for the mitochondrial gene sets.

Examples

```
data(ovse)
```

getGeneSets	<i>Get the mitochondrial gene sets</i>
-------------	----------------------------------------

Description

It returns the mitochondrial gene sets (in form of list or data frame) of the four possible databases: "MitoCarta", "Reactome", "GO-CC" and "GO-BP".

Usage

```
getGeneSets(  
  database = "MitoCarta",  
  nametype = "ENSEMBL",  
  objectType = "list",  
  sections = FALSE  
)
```

Arguments

database	character string saying the database to use for the analysis. Either one of "MitoCarta", "Reactome", "GO-CC" and "GO-BP".
nametype	character string saying the type of gene name ID. Either one of "SYMBOL", "ENTREZID" or "ENSEMBL".
objectType	character string saying the type of needed object. Either one of "list" or "dataframe".
sections	logical. Either to keep the aggregated gene set categories or the specific gene sets. Default is FALSE.

Value

the mitochondrial gene sets.

Examples

```
MClust <- getGeneSets()
```

gseaMito	<i>Mitochondrial GSEA of a gene list.</i>
----------	-------------------------------------------

Description

Gene set enrichment analysis for the mitochondrial gene sets. For the Reactome, GO-CC and GO-BP databases it returns also the GSEA results for the corresponding original pathways.

Usage

```
gseaMito(genes, database)
```

Arguments

genes	order ranked gene vector named by ENSEMBL id.
database	character string saying the database to use for the analysis. Either one of "Mito- Carta", "Reactome", "GO-CC" and "GO-BP".

Value

GSEA results for the mitochondrial gene sets.

Examples

```
data(ovse)
```

MitoGenesDB

Mitochondrial genes

Description

Here are listed all the final mitochondrial genes in ENSEMBL id, the corresponding SYMBOL id and the database from where they were collected.

Usage

```
data(MitoGenesDB)
```

Format

An object of class `data.frame` with 2996 rows and 3 columns.

mitoHeatmap	<i>Heatmap of mitochondrial gene sets.</i>
-------------	--------------------------------------------

Description

Given a matrix of scores, it returns a heatmap of the mitochondrial gene sets.

Usage

```
mitoHeatmap(  
  data,  
  database = "MitoCarta",  
  sampleAnnot = NULL,  
  splitSamples = FALSE,  
  splitSections = FALSE,  
  ...  
)
```

Arguments

data	matrix or data.frame with samples in columns and mitochondrial gene sets in rows.
database	character string saying the database used for the analysis. Either one of "MitoCarta", "Reactome", "GO-CC" and "GO-BP".
sampleAnnot	character vector with samples' annotation.
splitSamples	logical. If TRUE it splits samples by annotation. sampleAnnot must be provided.
splitSections	logical. If TRUE it splits gene sets by main section.
...	other parameters specific of the function Heatmap .

Value

A [Heatmap-class](#) object.

Examples

```
MClst <- getGeneSets()  
n <- length(names(MClst)) * 5  
rmatrix <- matrix(rnorm(n, 0), ncol = 5)  
rownames(rmatrix) <- names(MClst)  
colnames(rmatrix) <- paste0("Sample_", seq_len(5))  
mitoHeatmap(data = rmatrix, database = "MitoCarta")
```

mitoTreeHeatmap *Circular heatmap on mitochondrial gene set tree.*

Description

Given a matrix of scores, it returns a circular heatmap of the mitochondrial gene sets (leaf of the database tree) or gene set groups (section of the database tree).

Usage

```
mitoTreeHeatmap(  
  data,  
  database = "MitoCarta",  
  sections = FALSE,  
  samples = NULL,  
  labelNames = "sections",  
  ...  
)
```

Arguments

data	matrix or data.frame with samples in columns and mitochondrial gene sets in rows.
database	character string saying the database used for the analysis. Either one of "MitoCarta", "Reactome", "GO-CC" and "GO-BP".
sections	logical. Either to keep the aggregated gene set categories or the specific gene sets. Default is FALSE.
samples	character vector with the names of samples to be plotted. Otherwise all samples are plotted.
labelNames	character string that says to plot either the names of "sections" or "leaves".
...	other arguments passed on to the gheatmap function.

Value

A [ggplot](#) object.

Examples

```
MClst <- getGeneSets()  
n <- length(names(MClst)) * 5  
rmatrix <- matrix(rnorm(n, 0), ncol = 5)  
rownames(rmatrix) <- names(MClst)  
colnames(rmatrix) <- paste0("Sample_", seq_len(5))  
mitoTreeHeatmap(data = rmatrix, database = "MitoCarta")
```

mitoTreePoint	<i>Circular dotplot on mitochondrial gene set tree.</i>
---------------	---------------------------------------------------------

Description

A circular dotplot of the mitochondrial enrichment results.

Usage

```
mitoTreePoint(  
  data,  
  database = "MitoCarta",  
  pvalCutoff = 0.05,  
  labsize = 3,  
  max_point_size = 4,  
  color = "p.adjust"  
)
```

Arguments

data	named list of the result from <code>enrichMito</code> or <code>gseaMito</code> .
database	character string saying the database to use for the analysis. Either one of "MitoCarta", "Reactome", "GO-CC" and "GO-BP".
pvalCutoff	pvalue cutoff to select enriched gene sets
labsize	label size
max_point_size	max point size
color	variable used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'NES'.

Value

A `ggplot` object.

Examples

```
data(ovse)
```

`ovse`*Example expression data.*

Description

This is an example dataset containing gene expression values (in normalized counts) of 40 ovarian cancer (OVC) patients extracted from the Cancer Genome Atlas (TCGA) database. This dataset should be used only with example purpose. RNA sequencing OVC data were retrieved using [curatedTCGAData](#) package. Data were then normalized with the [betweenLaneNormalization](#) function. To lighten the dataset, the [consensusOVSign](#) function was computed, which return 4 different scores, one for each OVC subtype (Chen et al, 2018, Clinical Cancer Research) and the 10 samples with the highest scores were selected for each subgroup. Further, only the mitochondrial genes included in mitology were kept. Finally, the log fold change of the IMR versus the PRO samples were computed. Further details in [mitology/inst/scripts/howToGenerateOvse.Rmd](#).

Usage

```
data(ovse)
```

Format

An object of class `SummarizedExperiment` with 2388 rows and 40 columns.

Index

* datasets

MitoGenesDB, [4](#)

ovse, [8](#)

betweenLaneNormalization, [8](#)

consensusOVSign, [8](#)

curatedTCGAData, [8](#)

enrichMito, [2](#)

getGeneSets, [3](#)

ggplot, [6](#), [7](#)

gheatmap, [6](#)

gseaMito, [3](#)

Heatmap, [5](#)

MitoGenesDB, [4](#)

mitoHeatmap, [5](#)

mitoTreeHeatmap, [6](#)

mitoTreePoint, [7](#)

ovse, [8](#)