

Package: padma (via r-universe)

May 29, 2026

Type Package

Title Individualized Multi-Omic Pathway Deviation Scores Using Multiple Factor Analysis

Version 1.22.0

Depends R (>= 4.1.0), SummarizedExperiment, S4Vectors

Imports FactoMineR, MultiAssayExperiment, methods, graphics, stats, utils

Suggests testthat, BiocStyle, knitr, rmarkdown, KEGGREST, missMDA, ggplot2, ggrepel, car, cowplot, reshape2

Description Use multiple factor analysis to calculate individualized pathway-centric scores of deviation with respect to the sampled population based on multi-omic assays (e.g., RNA-seq, copy number alterations, methylation, etc). Graphical and numerical outputs are provided to identify highly aberrant individuals for a particular pathway of interest, as well as the gene and omics drivers of aberrant multi-omic profiles.

License GPL (>=3)

URL <https://github.com/andreamrau/padma>

https //github.com/andreamrau/padma/issues

biocViews Software, StatisticalMethod, PrincipalComponent, GeneExpression, Pathways, RNASeq, BioCarta, MethylationSeq

Encoding UTF-8

LazyData TRUE

RoxygenNote 7.3.1

VignetteBuilder knitr

Config/pak/sysreqs cmake make libicu-dev libuv1-dev zlib1g-dev

Repository <https://bioc-release.r-universe.dev>

Date/Publication 2026-04-28 12:53:06 UTC

RemoteUrl <https://github.com/bioc/padma>

RemoteRef RELEASE_3_23

RemoteSha 080ac3bdf2dbc2b4b543c7209eb6f68dca500643

Contents

factorMap	2
LUAD_subset	3
mirtarbase	4
msigdb	5
omicsContrib	6
padma	7
padmaResults-class	9
padmaRun	10
pathway_name	12
summary,padmaResults-method	14

Index	16
--------------	-----------

factorMap	<i>Plot an MFA factor map for individuals or partial factor map based on padma analysis</i>
-----------	---------------------------------------------------------------------------------------------

Description

Produce an MFA factor map for individuals, or MFA partial factor map for a given individual, for a pair of dimensions provided by the user.

Usage

```
factorMap(
  padma_obj,
  partial_id = NULL,
  dim_x = 1,
  dim_y = 2,
  plot_ellipse = TRUE,
  ggplot = TRUE,
  repel_labels = ifelse(ggplot == TRUE, TRUE, FALSE)
)
```

Arguments

padma_obj	Output from running the padma function (with 'full_results = TRUE')
partial_id	Index or sample name to be plotted for a partial factor map.
dim_x	Dimension number of the MFA to be plotted on the x-axis.
dim_y	Dimension number of the MFA to be plotted on the y-axis.
plot_ellipse	If TRUE, superimpose a normal confidence ellipsis on the factor map.
ggplot	If TRUE, use ggplot2 for plotting
repel_labels	If TRUE, use ggrepel to repel sample labels from each other

Value

Plot, or factor map of class ggplot if ggplot2 = TRUE.

Examples

```
LUAD_subset <- padma::LUAD_subset
## Create MultiAssayExperiment object with LUAD data
omics_data <-
  list(rnaseq = as.matrix(LUAD_subset$rnaseq),
       methyl = as.matrix(LUAD_subset$methyl),
       mirna = as.matrix(LUAD_subset$mirna),
       cna = as.matrix(LUAD_subset$cna))
pheno_data <-
  data.frame(LUAD_subset$clinical,
             row.names = LUAD_subset$clinical$bcr_patient_barcode)
mae <-
  suppressMessages(
    MultiAssayExperiment::MultiAssayExperiment(
      experiments = omics_data, colData = pheno_data))

## Run padma
run_padma <-
  padma(mae, gene_map = padma::mirtarbase,
        pathway_name = "c2_cp_BIOCARTA_D4GDI_PATHWAY", verbose = FALSE)

summary(run_padma)

## padma plots
## Not run:
factorMap(run_padma, dim_x = 1, dim_y = 2)
factorMap(run_padma, dim_x = 1, dim_y = 2,
          partial_id = "TCGA-78-7536")
omicsContrib(run_padma, max_dim = 10)

## End(Not run)
```

LUAD_subset

Subset of batch-corrected multi-omic TCGA data in lung adenocarcinoma

Description

List of multi-omic (RNA-seq, copy number alterations, methylation, and miRNA-seq) and phenotypic data in 144 individuals in the TCGA-LUAD data for the 13 genes in the D4-GDI signaling pathway.

Usage

```
data(LUAD_subset)
```

Format

A named list of five objects of class `data.frame` containing a subset of the batch-corrected multi-omic TCGA data from lung adenocarcinoma, corresponding to the 13 genes in the D4 GDI signaling pathway: 'clinical' is of dimension 144 x 55 and contains clinical variables for the 144 individuals. 'rnaseq', 'methyl', 'cna', and 'mirna' are of dimension 13 (genes) or 1 (miRNAs) x 144 (samples), where the row names contain the gene symbol or miRNA name.

Source

TCGA

References

The Cancer Genome Atlas Research Network (2014) Nature 511, 543-550. <https://doi.org/10.1038/nature13385>.

Rau et al. (2019) bioRxiv, <https://doi.org/10.1101/827022>.

Examples

```
data(LUAD_subset)
head(LUAD_subset)
```

mirtarbase

Curated miR-target interaction predictions from miRTarBase

Description

Data.frame of 10,754 predicted miRNA gene targets from miRTarBase (version 7.0), filtered to include only predictions with the 'Functional MTI' support type.

Usage

```
data(mirtarbase)
```

Format

An object of class `data.frame` with two columns: `miRNA`, which provides the miRNA identifier (e.g., 'hsa-miR-20a-5p') and `Target Gene`, which provides the corresponding predicted gene target.

Source

<http://mirtarbase.mbc.nctu.edu.tw/php/index.php>

References

Chou et al. (2018) Nucleic Acids Research 46, D296-D302. <https://doi.org/10.1093/nar/gkx1067>.

Examples

```
data(mirtarbase)
head(mirtarbase)
```

msigdb

MSigDB canonical pathways and corresponding gene lists

Description

Data.frame of 1322 pathways and corresponding gene symbols included in the MSigDB canonical pathways curated gene set catalog, which includes genes whose products are involved in metabolic and signaling pathways reported in curated public databases. This specifically corresponds to the 'C2 curated gene sets' catalog from MSigDB v5.2 available at <http://bioinf.wehi.edu.au/software/MSigDB/> as described in the limma Bioconductor package.

Usage

```
data(msigdb)
```

Format

An object of class `data.frame` with two columns: `geneset`, which provides the 1322 MSigDB curated pathway names (e.g., 'c2_cp_BIOCARTA_41BB_PATHWAY') and `symbol`, which provides the comma-separated corresponding list of gene symbols.

Source

MSigDB Gene sets <http://bioinf.wehi.edu.au/software/MSigDB/>

References

Liberzon et al. (2011) *Bioinformatics* 27:12, 1739-1740. <https://doi.org/10.1093/bioinformatics/btr260>.

Examples

```
data(msigdb)
head(msigdb)
```

omicsContrib	<i>Plot the omics contribution per MFA axis and the overall weighted contribution</i>
--------------	---------------------------------------------------------------------------------------

Description

Plot barplots indicating the percent contribution of each omics to each MFA dimension, as well as the overall weighted (by eigenvalue) percent contribution to the full analysis.

Usage

```
omicsContrib(
  padma_obj,
  max_dim = min(10, nrow(MFA_results(padma_obj)$eig)),
  ggplot = TRUE
)
```

Arguments

padma_obj	Output from running the padma function (with 'full_results = TRUE')
max_dim	Maximum dimension number of the MFA to be plotted
ggplot	If TRUE, use ggplot2 for plotting (and cowplot for combining ggplots)

Value

Barplots of percent variance contribution, optionally of class ggplot.

Examples

```
LUAD_subset <- padma::LUAD_subset
## Create MultiAssayExperiment object with LUAD data
omics_data <-
  list(rnaseq = as.matrix(LUAD_subset$rnaseq),
       methyl = as.matrix(LUAD_subset$methyl),
       mirna = as.matrix(LUAD_subset$mirna),
       cna = as.matrix(LUAD_subset$cna))
pheno_data <-
  data.frame(LUAD_subset$clinical,
             row.names = LUAD_subset$clinical$bcr_patient_barcode)
mae <-
  suppressMessages(
    MultiAssayExperiment::MultiAssayExperiment(
      experiments = omics_data, colData = pheno_data))

## Run padma
run_padma <-
  padma(mae, gene_map = padma::mirtarbase,
        pathway_name = "c2_cp_BIOCARTA_D4GDI_PATHWAY", verbose = FALSE)
```

```
summary(run_padma)

## padma plots
## Not run:
factorMap(run_padma, dim_x = 1, dim_y = 2)
factorMap(run_padma, dim_x = 1, dim_y = 2,
          partial_id = "TCGA-78-7536")
omicsContrib(run_padma, max_dim = 10)

## End(Not run)
```

padma

Calculate individualized deviation scores from multi-omic data

Description

This is the primary user interface for the padma package. Generic S4 methods are implemented to calculate individualized pathway deviation scores on the basis of matched, multi-omic data. The supported classes for input are `list` and `MultiAssayExperiment`. The output of padma is an S4 object of class `padmaResults`.

Usage

```
padma(object, ...)
```

```
## S4 method for signature 'list'
padma(
  object,
  colData,
  gene_map = padma::mirtarbase,
  base_ids = NULL,
  supp_ids = NULL,
  pathway_name = "c2_cp_BIOCARTA_D4GDI_PATHWAY",
  impute = FALSE,
  variance_threshold = 1e-04,
  full_results = TRUE,
  verbose = TRUE,
  ...
)
```

```
## S4 method for signature 'MultiAssayExperiment'
padma(
  object,
  gene_map = padma::mirtarbase,
  base_ids = NULL,
  supp_ids = NULL,
  pathway_name = "c2_cp_BIOCARTA_D4GDI_PATHWAY",
```

```

    impute = FALSE,
    variance_threshold = 1e-04,
    full_results = TRUE,
    verbose = TRUE,
    ...
  )

```

Arguments

<code>object</code>	Matched multi-omic data. May be provided as (1) a <code>MultiAssayExperiment</code> or (2) a named <code>list</code> , with each element corresponding to a <code>matrix</code> representing an omic, with biological entities in rows. Row names should include unique biological entity IDs (e.g., gene symbols, miRNA names); columns represent individuals. If more than one biological entity is used, a <code>gene_map</code> <code>data.frame</code> providing mappings between IDs and gene names should be provided if the default <code>mirtarbase</code> is not sufficient.
<code>...</code>	Optional additional arguments
<code>colData</code>	(optional) A <code>DataFrame</code> or <code>data.frame</code> of characteristics for all biological units, to be used in creating a <code>MultiAssayExperiment</code> from an object of class <code>list</code>
<code>gene_map</code>	(optional) Data frame mapping arbitrary biological entities (e.g. miRNAs) to genes. Contains two columns, where the first provides the IDs of the entity and the second provides the IDs of the corresponding target gene. By default, the miRNA-gene interactions of type 'Functional MTI' from <code>mirTarBase</code> are used (see the preloaded ' <code>mirtarbase</code> ' data in the package).
<code>base_ids</code>	(optional) Sample names to be used as reference base data. By default, all samples are used.
<code>supp_ids</code>	(optional) Sample names to be used as supplementary individuals to be projected onto the analysis based on the individuals identified in <code>base_ids</code> . By default, takes the value <code>NULL</code> , but should not overlap with <code>base_ids</code> if provided by the user.
<code>pathway_name</code>	Character of either a KEGG pathway identifier or MSigDB pathway names (e.g., see the pathway names in the ' <code>geneset</code> ' column of the preloaded <code>msigdb</code> data in the package), or a vector of gene symbols.
<code>impute</code>	If <code>TRUE</code> , impute missing values separately in base and supplementary data using MFA as implemented in the <code>missMDA</code> package; otherwise simple mean imputation is used (default).
<code>variance_threshold</code>	Minimal variance required across samples to retain a biological entity in the analysis
<code>full_results</code>	If <code>TRUE</code> (default), include full MFA results in function output; otherwise, provide concise output to save space.
<code>verbose</code>	If <code>TRUE</code> , provide verbose output.

Value

An S4 object of class `padmaResults`, where individualized pathway deviation scores are stored as the assay data, and the corresponding {pathway name, full MFA results, number of genes, and

names of imputed or filtered genes} are stored as slots that can be retrieved using the appropriate accessor functions.

Author(s)

Andrea Rau

Examples

```
LUAD_subset <- padma::LUAD_subset
## Create MultiAssayExperiment object with LUAD data
omics_data <-
  list(rnaseq = as.matrix(LUAD_subset$rnaseq),
       methyl = as.matrix(LUAD_subset$methyl),
       mirna = as.matrix(LUAD_subset$mirna),
       cna = as.matrix(LUAD_subset$cna))
pheno_data <-
  data.frame(LUAD_subset$clinical,
             row.names = LUAD_subset$clinical$bcr_patient_barcode)
mae <-
  suppressMessages(
    MultiAssayExperiment::MultiAssayExperiment(
      experiments = omics_data, colData = pheno_data))

## Run padma
run_padma <-
  padma(mae, gene_map = padma::mirtarbase,
        pathway_name = "c2_cp_BIOCARTA_D4GDI_PATHWAY", verbose = FALSE)

summary(run_padma)

## padma plots
## Not run:
factorMap(run_padma, dim_x = 1, dim_y = 2)
factorMap(run_padma, dim_x = 1, dim_y = 2,
          partial_id = "TCGA-78-7536")
omicsContrib(run_padma, max_dim = 10)

## End(Not run)
```

padmaResults-class *padmaResults* object and constructor

Description

`padmaResults` is a subclass of `RangedSummarizedExperiment`, used to store the individualized pathway deviation scores as well as some additional information useful about the pathway name (`pathway_name`), the gene-level contributions to each deviation score (`pathway_gene_deviation`), a full set of outputs related to the MFA (`MFA_results`, and the number of genes used in the analysis as well as the names of those for which data imputation or filtering was required (`ngenes`, `imputed_genes`, and `removed_genes`, respectively).

Usage

```
padmaResults(
  SummarizedExperiment,
  pathway_name = NULL,
  pathway_gene_deviation = NULL,
  MFA_results = NULL,
  ngenes = NULL,
  imputed_genes = NULL,
  removed_genes = NULL
)
```

Arguments

SummarizedExperiment	a RangedSummarizedExperiment of padma results
pathway_name	The name of the pathway, if applicable
pathway_gene_deviation	Per-gene contributions to each individualized pathway deviation score
MFA_results	List of all detailed results from the MFA
ngenes	Number of genes used in the pathway deviation score calculation
imputed_genes	Names of genes, per omic, for which data imputation was used to replace missing values
removed_genes	Names of genes, per omic, which were filtered from the analysis due to low variation

Details

This constructor function would not typically be used by 'end users'. This simple class extends the RangedSummarizedExperiment class of the SummarizedExperiment package to allow other packages to write methods for results objects from the padma package. It is used by [padmaRun](#) to wrap up the results table.

Value

a padmaResults object

padmaRun

Calculate individualized deviation scores from multi-omic data

Description

Calculate individualized deviation scores from multi-omic data

Usage

```
padmaRun(
  omics_data,
  gene_map = padma::mirtarbase,
  base_ids = NULL,
  supp_ids = NULL,
  pathway_name = "c2_cp_BIOCARTA_D4GDI_PATHWAY",
  impute = FALSE,
  variance_threshold = 1e-04,
  full_results = TRUE,
  verbose = TRUE,
  ...
)
```

Arguments

omics_data	Object of class 'MultiAssayExperiment' containing omics data from n matched individuals.
gene_map	(optional) Data frame mapping arbitrary biological entities (e.g. miRNAs) to genes. Contains two columns, where the first provides the IDs of the entity and the second provides the IDs of the corresponding target gene. By default, the miRNA-gene interactions of type 'Functional MTI' from miRTarBase are used (see the preloaded 'mirtarbase' data in the package).
base_ids	(optional) Sample names to be used as reference base data. By default, all samples are used.
supp_ids	(optional) Sample names to be used as supplementary individuals to be projected onto the analysis based on the individuals identified in base_ids. By default, takes the value NULL, but should not overlap with base_ids if provided by the user.
pathway_name	Character of either a KEGG pathway identifier or MSigDB pathway names (e.g., see the pathway names in the 'geneset' column of the preloaded msigdb data in the package), or a vector of gene symbols.
impute	If TRUE, impute missing values separately in base and supplementary data using MFA as implemented in the <i>missMDA</i> package; otherwise simple mean imputation is used (default).
variance_threshold	Minimal variance required across samples to retain a biological entity in the analysis
full_results	If TRUE (default), include full MFA results in function output; otherwise, provide concise output to save space.
verbose	If TRUE, provide verbose output.
...	Optional additional arguments

Value

An S4 object of class `padmaResults`, where individualized pathway deviation scores are stored as the assay data, and the corresponding {pathway name, full MFA results, number of genes, and

names of imputed or filtered genes} are stored as slots that can be retrieved using the appropriate accessor functions.

Examples

```

LUAD_subset <- padma::LUAD_subset
## Create MultiAssayExperiment object with LUAD data
omics_data <-
  list(rnaseq = as.matrix(LUAD_subset$rnaseq),
       methyl = as.matrix(LUAD_subset$methyl),
       mirna = as.matrix(LUAD_subset$mirna),
       cna = as.matrix(LUAD_subset$cna))
pheno_data <-
  data.frame(LUAD_subset$clinical,
             row.names = LUAD_subset$clinical$bcr_patient_barcode)
mae <-
  suppressMessages(
    MultiAssayExperiment::MultiAssayExperiment(
      experiments = omics_data, colData = pheno_data))

## Run padma
run_padma <-
  padma(mae, gene_map = padma::mirtarbase,
        pathway_name = "c2_cp_BIOCARTA_D4GDI_PATHWAY", verbose = FALSE)

summary(run_padma)

## padma plots
## Not run:
factorMap(run_padma, dim_x = 1, dim_y = 2)
factorMap(run_padma, dim_x = 1, dim_y = 2,
          partial_id = "TCGA-78-7536")
omicsContrib(run_padma, max_dim = 10)

## End(Not run)

```

pathway_name

Accessors for a padmaResults object.

Description

Accessors for a padmaResults object.

Usage

pathway_name(object, ...)

pathway_gene_deviation(object, ...)

MFA_results(object, ...)

```
ngenes(object, ...)  
  
imputed_genes(object, ...)  
  
removed_genes(object, ...)  
  
## S4 method for signature 'padmaResults'  
pathway_name(object)  
  
## S4 method for signature 'padmaResults'  
MFA_results(object)  
  
## S4 method for signature 'padmaResults'  
ngenes(object)  
  
## S4 method for signature 'padmaResults'  
imputed_genes(object)  
  
## S4 method for signature 'padmaResults'  
removed_genes(object)  
  
## S4 method for signature 'padmaResults'  
pathway_gene_deviation(object)  
  
## S4 method for signature 'padmaResults'  
show(object)
```

Arguments

object	a padmaResults object
...	Additional optional parameters

Value

Output varies depending on the method.

Author(s)

Andrea Rau

Examples

```
LUAD_subset <- padma::LUAD_subset  
## Create MultiAssayExperiment object with LUAD data  
omics_data <-  
  list(rnaseq = as.matrix(LUAD_subset$rnaseq),  
       methyl = as.matrix(LUAD_subset$methyl),  
       mirna = as.matrix(LUAD_subset$mirna),  
       cna = as.matrix(LUAD_subset$cna))
```

```
pheno_data <-
  data.frame(LUAD_subset$clinical,
            row.names = LUAD_subset$clinical$bcr_patient_barcode)
mae <-
  suppressMessages(
    MultiAssayExperiment::MultiAssayExperiment(
      experiments = omics_data, colData = pheno_data))

## Run padma
run_padma <-
  padma(mae, gene_map = padma::mirtarbase,
        pathway_name = "c2_cp_BIOCARTA_D4GDI_PATHWAY", verbose = FALSE)

summary(run_padma)

## padma plots
## Not run:
factorMap(run_padma, dim_x = 1, dim_y = 2)
factorMap(run_padma, dim_x = 1, dim_y = 2,
          partial_id = "TCGA-78-7536")
omicsContrib(run_padma, max_dim = 10)

## End(Not run)
```

summary,padmaResults-method

Summarize results from padma

Description

A function to summarize the pathway deviation results from padma, using the quantiles of the calculated multi-omic pathway deviation scores.

Usage

```
## S4 method for signature 'padmaResults'
summary(object, ...)
```

Arguments

object	An object of class 'padmaResults'
...	Additional arguments

Value

Summary of the padmaResults object.

Author(s)

Andrea Rau

References

Rau, A., Manansala, R., Flister, M. J., Rui, H., Jaffrézic, F., Laloë, D., and Auer, P. L. (2019) Individualized multi-omic pathway deviation scores using multiple factor analysis bioRxiv, <https://doi.org/10.1101/827022>.

See Also

[padma](#)

Examples

```
LUAD_subset <- padma::LUAD_subset
## Create MultiAssayExperiment object with LUAD data
omics_data <-
  list(rnaseq = as.matrix(LUAD_subset$rnaseq),
       methyl = as.matrix(LUAD_subset$methyl),
       mirna = as.matrix(LUAD_subset$mirna),
       cna = as.matrix(LUAD_subset$cna))
pheno_data <-
  data.frame(LUAD_subset$clinical,
            row.names = LUAD_subset$clinical$bcr_patient_barcode)
mae <-
  suppressMessages(
    MultiAssayExperiment::MultiAssayExperiment(
      experiments = omics_data, colData = pheno_data))

## Run padma
run_padma <-
  padma(mae, gene_map = padma::mirtarbase,
        pathway_name = "c2_cp_BIOCARTA_D4GDI_PATHWAY", verbose = FALSE)

summary(run_padma)

## padma plots
## Not run:
factorMap(run_padma, dim_x = 1, dim_y = 2)
factorMap(run_padma, dim_x = 1, dim_y = 2,
          partial_id = "TCGA-78-7536")
omicsContrib(run_padma, max_dim = 10)

## End(Not run)
```

Index

- * **datasets**
 - LUAD_subset, [3](#)
 - mirtarbase, [4](#)
 - msigdb, [5](#)
- * **methods**
 - padma, [7](#)
 - summary, padmaResults-method, [14](#)
- factorMap, [2](#)
- imputed_genes (pathway_name), [12](#)
- imputed_genes, padmaResults-method (pathway_name), [12](#)
- LUAD_subset, [3](#)
- MFA_results (pathway_name), [12](#)
- MFA_results, padmaResults-method (pathway_name), [12](#)
- mirtarbase, [4](#)
- msigdb, [5](#)
- ngenes (pathway_name), [12](#)
- ngenes, padmaResults-method (pathway_name), [12](#)
- omicsContrib, [6](#)
- padma, [7](#), [15](#)
- padma, list-method (padma), [7](#)
- padma, MultiAssayExperiment-method (padma), [7](#)
- padma-methods (padma), [7](#)
- padmaResults (padmaResults-class), [9](#)
- padmaResults-class, [9](#)
- padmaRun, [10](#), [10](#)
- pathway_gene_deviation (pathway_name), [12](#)
- pathway_gene_deviation, padmaResults-method (pathway_name), [12](#)
- pathway_gene_deviation-method (pathway_name), [12](#)
- pathway_name, [12](#)
- pathway_name, padmaResults-method (pathway_name), [12](#)
- removed_genes (pathway_name), [12](#)
- removed_genes, padmaResults-method (pathway_name), [12](#)
- show (pathway_name), [12](#)
- show, padmaResults-method (pathway_name), [12](#)
- summary (summary, padmaResults-method), [14](#)
- summary, padmaResults-method, [14](#)
- summary-methods (summary, padmaResults-method), [14](#)