

Package: scGraphVerse (via r-universe)

May 30, 2026

Title scGraphVerse: A Gene Network Analysis Package

Version 1.2.0

Description A package for inferring, comparing, and visualizing gene networks from single-cell RNA sequencing data. It integrates multiple methods (GENIE3, GRNBoost2, ZILGM, PCzinb, and JRF) for robust network inference, supports consensus building across methods or datasets, and provides tools for evaluating regulatory structure and community similarity. GRNBoost2 requires Python package 'arboreto' which can be installed using `init_py(install_missing = TRUE)`. This package includes adapted functions from ZILGM (Park et al., 2021), JRF (Petralia et al., 2015), and learn2count (Nguyen et al. 2023) packages with proper attribution under GPL-2 license.

License GPL-3 + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

biocViews GeneRegulation, NetworkInference, SingleCell, RNASeq, Visualization, Software, GraphAndNetwork, GeneSetEnrichment, NetworkEnrichment, Pathways, Sequencing, Reactome, Network, KEGG

URL <https://ngsFC.github.io/scGraphVerse>

BugReports <https://github.com/ngsFC/scGraphVerse/issues>

Depends R (>= 4.5.0)

Imports BiocBaseUtils, BiocParallel (>= 1.30.0), doParallel, doRNG, GENIE3, Matrix, MultiAssayExperiment, SingleCellExperiment, SummarizedExperiment, distributions3, dplyr, grDevices, graphics, httr, igraph, jsonlite, methods, parallel, reticulate, tidyr, glmnet, MASS, utils, stats, S4Vectors, graph, mpath

Suggests AnnotationDbi, BiocStyle, clusterProfiler, DOSE, enrichplot, fmsb, ggplot2, ggraph, gridExtra, INetTool, org.Hs.eg.db, org.Mm.eg.db, patchwork, pROC, RColorBrewer, ReactomePA, rentrez, robin, scales, Seurat, STRINGdb, testthat (>= 3.0.0), knitr, rmarkdown, tidyverse, magick, celldex, SingleR, TENxPBMCDData, scater, GenomeInfoDb, GenomicRanges,

VignetteBuilder knitr

LazyData false

SystemRequirements Python (>= 3.6) and arboreto Python package for GRNBoost2 method. Use `init_py(install_missing = TRUE)` for automated installation.

Config/pak/sysreqs libglpk-dev libicu-dev libpng-dev libxml2-dev libssl-dev python3 zlib1g-dev

Repository <https://bioc-release.r-universe.dev>

Date/Publication 2026-04-28 13:05:44 UTC

RemoteUrl <https://github.com/bioc/scGraphVerse>

RemoteRef RELEASE_3_23

RemoteSha 8776685bbd4cb1f79ee1351084bd5afbc8fe77d2

Contents

build_network_se	3
classify_edges	4
community_path	5
community_similarity	8
compare_consensus	9
compute_community_metrics	11
compute_topology_metrics	12
create_consensus	14
create_mae	16
cutoff_adjacency	17
download_Atlas	19
earlyj	19
edge_mining	20
generate_adjacency	22
infer_networks	23
init_py	25
PCzinb	26
plot_community_comparison	28
plot_network_comparison	30
plotg	31
plotROC	33
pscores	34
selgene	35
stringdb_adjacency	37
symmetrize	39

build_network_se 3

toy_adj_matrix 40
toy_counts 40
zinb_simdata 41

Index 43

build_network_se *Create a SummarizedExperiment for Network Storage*

Description

Constructs a SummarizedExperiment container for multiple gene regulatory network adjacency matrices with shared gene space (p×p matrices).

Usage

```
build_network_se(  
  networks,  
  networkData = NULL,  
  geneData = NULL,  
  metadata = list()  
)
```

Arguments

networks A list of adjacency matrices (all must have same dimensions)
networkData A DataFrame with metadata for each network
geneData Optional. A DataFrame with gene-level annotations
metadata Optional. List of global metadata

Value

A SummarizedExperiment object where each assay is a p×p network

Examples

```
# Example 1: Building SE from a list of adjacency matrices  
data("toy_adj_matrix")  
  
# Create a list of network matrices  
net_list <- list(  
  network1 = toy_adj_matrix,  
  network2 = toy_adj_matrix  
)  
  
# Build SummarizedExperiment  
network_se <- build_network_se(net_list)  
network_se
```

```
# Example 2: Using with inferred networks
data("toy_counts")

networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)

# generate_adjacency() internally uses build_network_se()
wadj_se <- generate_adjacency(networks)
wadj_se
```

classify_edges	<i>Classify Edges as TP, FP, or FN</i>
----------------	--

Description

Compares a consensus network to a reference network and classifies edges as True Positives (TP), False Positives (FP), or False Negatives (FN).

Usage

```
classify_edges(consensus_matrix, reference_matrix = NULL, use_stringdb = TRUE)
```

Arguments

consensus_matrix	A SummarizedExperiment object representing the consensus network.
reference_matrix	A SummarizedExperiment object representing the reference (ground truth) network. If NULL, STRINGdb is used to generate a high-confidence physical network.
use_stringdb	Logical. If TRUE and reference_matrix is NULL, queries STRINGdb for reference network. Default: TRUE.

Details

If reference_matrix is NULL and use_stringdb = TRUE, this function queries STRINGdb to generate a human high-confidence (score > 900) physical interaction network.

Value

A list containing:

- tp_edges: Character vector of True Positive edges
- fp_edges: Character vector of False Positive edges
- fn_edges: Character vector of False Negative edges

- consensus_graph: igraph object of consensus network
- reference_graph: igraph object of reference network
- edge_colors: Color vector for TP (red) and FN (blue) edges
- use_stringdb: Logical indicating if STRINGdb was used

Examples

```
data(toy_counts)
data(toy_adj_matrix)

# Infer networks (toy_counts is already a MultiAssayExperiment)
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)

# Generate and symmetrize adjacency matrices (returns SummarizedExperiment)
wadj_se <- generate_adjacency(networks)
swadj_se <- symmetrize(wadj_se, weight_function = "mean")

# Apply cutoff (returns SummarizedExperiment)
binary_se <- cutoff_adjacency(
  count_matrices = toy_counts,
  weighted_adjm_list = swadj_se,
  n = 1,
  method = "GENIE3",
  quantile_threshold = 0.95,
  nCores = 1
)

# Create consensus (returns SummarizedExperiment)
consensus <- create_consensus(binary_se, method = "union")

# Wrap reference matrix in SummarizedExperiment
ref_se <- build_network_se(list(reference = toy_adj_matrix))

# classify_edges expects SummarizedExperiment objects
edge_class <- classify_edges(consensus, ref_se)
```

Description

Detects gene communities within an adjacency network using one or two community detection methods, and performs pathway enrichment for each detected community.

Usage

```
community_path(
  adj_matrix,
  methods = "louvain",
  pathway_db = "KEGG",
  organism = c("human", "mouse"),
  genes_path = 5,
  plot = TRUE,
  verbose = TRUE,
  method_params = list(),
  comparison_params = list(),
  BPPARAM = BiocParallel::bpparam()
)
```

Arguments

adj_matrix	A square adjacency matrix or a SummarizedExperiment object containing a single adjacency matrix. Row and column names must correspond to gene symbols.
methods	A character vector of one or two community detection methods supported by robin . If two are given, performance is compared and the best is selected. Default: "louvain".
pathway_db	Character string specifying the pathway database to use: "KEGG" or "Reactome". Default: "KEGG".
organism	Character string specifying the organism: "human" or "mouse". Default: "human".
genes_path	Integer. Minimum number of genes per community to run enrichment analysis. Default: 5.
plot	Logical. If TRUE, generates a plot of detected communities. Default: TRUE.
verbose	Logical. If TRUE, shows progress messages. Default: TRUE.
method_params	List of parameters for community detection methods. Common parameters include: <ul style="list-style-type: none"> • resolution: Resolution parameter for Louvain/Leiden (default: 1) • steps: Number of steps for Walktrap (default: 4) • spins: Number of spins for Spinglass (default: 25) • nb.trials: Number of trials for Infomap (default: 10)
comparison_params	List of parameters for robin comparison: <ul style="list-style-type: none"> • measure: Stability measure ("vi", "nmi", "split.join", "adjusted.rand"). Default: "vi" • type: Robin construction type ("dependent", "independent"). Default: "independent" • rewire.w.type: Rewiring strategy for weighted graphs. Default: "Rewire"
BPPARAM	BiocParallel backend for parallel processing. Default: BiocParallel::bpparam().

Details

If two methods are provided, the function uses `robinCompare` and selects the method with higher AUC. Pathway enrichment is done via **clusterProfiler** (KEGG) or via **ReactomePA** (Reactome). Communities smaller than `genes_path` are excluded.

Value

A list with elements:

- `communities`: List with `best_method` and a named vector of community membership per gene.
- `pathways`: List of enrichment results per community (only for communities meeting size threshold).
- `graph`: The **igraph** object with community annotations.

Examples

```
data(toy_counts)

# Infer networks (toy_counts is already a MultiAssayExperiment)
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)
head(networks[[1]])

# Generate and symmetrize adjacency matrices (returns SummarizedExperiment)
wadj_se <- generate_adjacency(networks)
swadj_se <- symmetrize(wadj_se, weight_function = "mean")

# Apply cutoff (returns SummarizedExperiment)
binary_se <- cutoff_adjacency(
  count_matrices = toy_counts,
  weighted_adjm_list = swadj_se,
  n = 1,
  method = "GENIE3",
  quantile_threshold = 0.95,
  nCores = 1,
  debug = TRUE
)

# Create consensus (returns SummarizedExperiment)
consensus <- create_consensus(binary_se, method = "union")

# community_path now accepts SummarizedExperiment objects directly
comm_cons <- community_path(consensus)
```

community_similarity *Compare Community Assignments and Topological Properties*

Description

Convenience wrapper that computes community assignment metrics, topological properties, and optionally visualizes the comparison. For more control, use the individual functions: [compute_community_metrics](#), [compute_topology_metrics](#), and [plot_community_comparison](#).

Usage

```
community_similarity(control_output, predicted_list, plot = TRUE)
```

Arguments

control_output A list output from `community_path()` representing the ground truth network. Must contain a graph (igraph object) and `communities$membership`.

predicted_list A list of lists, each output from `community_path()` representing predicted networks to compare.

plot Logical. If TRUE, displays plots immediately. If FALSE, no plots are displayed. Default: TRUE.

Details

This function requires the **igraph** package. If `plot = TRUE`, the **fmsb** package is also required. Community similarity is measured using variation of information (VI), normalized mutual information (NMI), and adjusted Rand index (ARI).

Value

A list containing:

- `community_metrics`: A data frame with VI, NMI, and ARI scores for each prediction.
- `topology_measures`: A data frame with raw topological metrics for each prediction.
- `control_topology`: A list of raw topological metrics for the ground truth network.

See Also

[compute_community_metrics](#), [compute_topology_metrics](#), [plot_community_comparison](#)

Examples

```
data(toy_counts)
data(toy_adj_matrix)

# Infer networks (toy_counts is already a MultiAssayExperiment)
```

```

networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)
head(networks[[1]])

# Generate adjacency matrices
wadj_se <- generate_adjacency(networks)
swadj_se <- symmetrize(wadj_se, weight_function = "mean")

# Apply cutoff
binary_se <- cutoff_adjacency(
  count_matrices = toy_counts,
  weighted_adjm_list = swadj_se,
  n = 1,
  method = "GENIE3",
  quantile_threshold = 0.95,
  nCores = 1,
  debug = TRUE
)
head(binary_se[[1]])

consensus <- create_consensus(binary_se, method = "union")
comm_cons <- community_path(consensus)
comm_truth <- community_path(toy_adj_matrix)

sim_score <- community_similarity(comm_truth, list(comm_cons))

```

compare_consensus

Compare Consensus and Reference Graphs or STRINGdb Networks

Description

Convenience wrapper that classifies edges and visualizes the comparison between consensus and reference networks. For more control, use the individual functions: [classify_edges](#) and [plot_network_comparison](#).

Usage

```

compare_consensus(
  consensus_matrix,
  reference_matrix = NULL,
  false_plot = FALSE
)

```

Arguments

consensus_matrix

A [SummarizedExperiment](#) object representing the consensus network.

`reference_matrix` Optional. A [SummarizedExperiment](#) obj representing the reference network. If NULL, STRINGdb is queried.

`false_plot` Logical. If TRUE, displays False Positives plot. Default is FALSE.

Details

If no `reference_matrix` is provided, STRINGdb is queried to generate a high-confidence physical interaction network.

Value

A ggplot object visualizing the comparison.

Note

Requires **ggraph** and **ggplot2**. If `reference_matrix` is NULL, also requires **STRINGdb**. If `false_plot = TRUE`, requires **patchwork**.

See Also

[classify_edges](#), [plot_network_comparison](#)

Examples

```
data(toy_counts)
data(toy_adj_matrix)

# Infer networks (toy_counts is already a MultiAssayExperiment)
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)
head(networks[[1]])

# Generate adjacency matrices
wadj_se <- generate_adjacency(networks)
swadj_se <- symmetrize(wadj_se, weight_function = "mean")

# Apply cutoff
binary_se <- cutoff_adjacency(
  count_matrices = toy_counts,
  weighted_adjm_list = swadj_se,
  n = 1,
  method = "GENIE3",
  quantile_threshold = 0.95,
  nCores = 1,
  debug = TRUE
)
head(binary_se[[1]])
```

```
consensus <- create_consensus(binary_se, method = "union")

# Wrap reference matrix in SummarizedExperiment
ref_se <- build_network_se(list(reference = toy_adj_matrix))

# Compare consensus to reference
compare_consensus(
  consensus,
  reference_matrix = ref_se,
  false_plot = FALSE
)
```

`compute_community_metrics`*Compute Community Assignment Similarity Metrics*

Description

Calculates community assignment similarity between a reference community structure and one or more predicted structures using variation of information (VI), normalized mutual information (NMI), and adjusted Rand index (ARI).

Usage

```
compute_community_metrics(control_output, predicted_list)
```

Arguments

`control_output` A list output from `community_path()` representing the ground truth network. Must contain `communities$membership`.

`predicted_list` A list of lists, each output from `community_path()` representing predicted networks to compare.

Details

This function requires the **igraph** package. Lower VI values indicate better similarity (VI = 0 is perfect match). Higher NMI and ARI values indicate better similarity (both range 0-1).

Value

A data frame with columns VI, NMI, and ARI for each prediction. Row names indicate which prediction (e.g., "Predicted_1").

Examples

```
data(toy_counts)
data(toy_adj_matrix)

# Infer networks (toy_counts is already a MultiAssayExperiment)
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)

# Generate adjacency matrices
wadj_se <- generate_adjacency(networks)
swadj_se <- symmetrize(wadj_se, weight_function = "mean")

# Apply cutoff
binary_se <- cutoff_adjacency(
  count_matrices = toy_counts,
  weighted_adjm_list = swadj_se,
  n = 1,
  method = "GENIE3",
  quantile_threshold = 0.95,
  nCores = 1
)

consensus <- create_consensus(binary_se, method = "union")
comm_cons <- community_path(consensus)
comm_truth <- community_path(toy_adj_matrix)

metrics <- compute_community_metrics(comm_truth, list(comm_cons))
```

compute_topology_metrics

Compute Network Topological Properties

Description

Calculates topological properties (modularity, number of communities, density, transitivity) for one or more networks.

Usage

```
compute_topology_metrics(control_output, predicted_list)
```

Arguments

control_output A list output from `community_path()` representing the ground truth network. Must contain a graph (igraph object) and `communities$membership`.

`predicted_list` A list of lists, each output from `community_path()` representing predicted networks.

Details

This function requires the **igraph** package. Topological metrics include:

- Modularity: Quality of community division
- Communities: Number of detected communities
- Density: Proportion of actual vs. possible edges
- Transitivity: Clustering coefficient

Value

A list containing:

- `topology_measures`: A data frame with Modularity, Communities, Density, and Transitivity for each prediction.
- `control_topology`: A numeric vector of the same metrics for the control network.

Examples

```
data(toy_counts)
data(toy_adj_matrix)

# Infer networks (toy_counts is already a MultiAssayExperiment)
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)

# Generate adjacency matrices
wadj_se <- generate_adjacency(networks)
swadj_se <- symmetrize(wadj_se, weight_function = "mean")

# Apply cutoff
binary_se <- cutoff_adjacency(
  count_matrices = toy_counts,
  weighted_adjm_list = swadj_se,
  n = 1,
  method = "GENIE3",
  quantile_threshold = 0.95,
  nCores = 1
)

consensus <- create_consensus(binary_se, method = "union")
comm_cons <- community_path(consensus)
comm_truth <- community_path(toy_adj_matrix)

topo <- compute_topology_metrics(comm_truth, list(comm_cons))
```

create_consensus *Create a Consensus Adjacency Matrix from Multiple Networks*

Description

Builds a consensus adjacency matrix from networks stored in a [SummarizedExperiment](#) using one of three methods: "vote", "union", or "INet".

Usage

```
create_consensus(
  adj_matrix_list,
  method = c("vote", "union", "INet"),
  weighted_list = NULL,
  theta = 0.04,
  threshold = 0.5,
  ncores = 1,
  tolerance = 0.1,
  nitermax = 50,
  verbose = FALSE
)
```

Arguments

adj_matrix_list	A SummarizedExperiment object containing binary adjacency matrices (square, 0/1) with identical dimensions and matching row/column names, or a list of such matrices.
method	Character string specifying the consensus strategy. One of: <ul style="list-style-type: none"> "vote" (default): An edge is included if supported by at least threshold fraction of matrices. "union": An edge is included if present in any matrix. "INet": Combines normalized weighted matrices using consensusNet.
weighted_list	A SummarizedExperiment object containing weighted adjacency matrices (required if method = "INet"), or a list of such matrices.
theta	Numeric. Tuning parameter passed to consensusNet (default: 0.04).
threshold	Numeric between 0 and 1. Threshold for "vote" and "INet" methods. Default is 0.5.
ncores	Integer. Number of CPU cores to use when method = "INet". Default is 1.
tolerance	Numeric. Tolerance for differences between similar graphs in INet method. Default is 0.1.
nitermax	Integer. Maximum number of iterations for INet algorithm. Default is 50.
verbose	Logical. If TRUE, display verbose output for INet method. Default is FALSE.

Details

Consensus construction depends on the selected method:

vote Counts the presence of each edge across all matrices and includes edges supported by at least $\text{threshold} \times N$ matrices.

union Includes any edge that appears in any matrix.

INet Multiplies binary matrices by corresponding weighted matrices, normalizes the results, and applies consensusNet to generate a consensus network.

For "INet", both binary and weighted adjacency matrices must be provided with matching dimensions.

Value

A [SummarizedExperiment](#) object with a single assay containing the consensus adjacency matrix (binary or weighted, depending on the method). Metadata includes consensus method and parameters.

Examples

```
data(toy_counts)

# Infer networks (toy_counts is already a MultiAssayExperiment)
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)
head(networks[[1]])

# Generate adjacency matrices
wadj_se <- generate_adjacency(networks)
swadj_se <- symmetrize(wadj_se, weight_function = "mean")

# Apply cutoff
binary_se <- cutoff_adjacency(
  count_matrices = toy_counts,
  weighted_adjm_list = swadj_se,
  n = 1,
  method = "GENIE3",
  quantile_threshold = 0.95,
  nCores = 1,
  debug = TRUE
)
head(binary_se[[1]])

consensus <- create_consensus(binary_se, method = "union")
head(consensus)
```

`create_mae`*Create MultiAssayExperiment from Multiple Single-Cell Datasets*

Description

Converts a list of count matrices, Seurat objects, or SingleCellExperiment objects into a MultiAssayExperiment for integrated network inference.

Usage

```
create_mae(datasets, colData = NULL, ...)
```

Arguments

<code>datasets</code>	A named list of datasets. Each element can be: <ul style="list-style-type: none">• A matrix (genes \times cells)• A Seurat object• A SingleCellExperiment object
<code>colData</code>	Optional. A DataFrame with metadata for each experiment. If NULL, automatically generated from list names.
<code>...</code>	Additional arguments (currently unused)

Value

A MultiAssayExperiment object with:

- `experiments`: List of SingleCellExperiment objects
- `colData`: Metadata for each experiment/condition

Examples

```
# Load the example MAE
data("toy_counts")

# Extract the list of SingleCellExperiment objects
sce_list <- MultiAssayExperiment::experiments(toy_counts)
sce_list <- as.list(sce_list)

# Create a new MAE from the SCE list
mae <- create_mae(sce_list)
mae
```

cutoff_adjacency *Threshold Adjacency Matrices Based on Shuffled Network Quantiles*

Description

Applies a cutoff to weighted adjacency matrices using a percentile estimated from shuffled versions of the original expression matrices. Supports inference methods "GENIE3", "GRNBoost2", and "JRF".

Usage

```
cutoff_adjacency(
  count_matrices,
  weighted_adjm_list,
  n,
  method = c("GENIE3", "GRNBoost2", "JRF"),
  quantile_threshold = 0.99,
  weight_function = "mean",
  nCores = 1,
  grnboost_modules = NULL,
  debug = FALSE
)
```

Arguments

count_matrices A [MultiAssayExperiment](#) object containing expression data from multiple experiments or conditions.

weighted_adjm_list A [SummarizedExperiment](#) object containing weighted adjacency matrices (one per experiment) to threshold.

n Integer. Number of shuffled replicates generated per original expression matrix.

method Character string. One of "GENIE3", "GRNBoost2", or "JRF".

quantile_threshold Numeric. The quantile used to define the cutoff. Default is 0.99.

weight_function Character string or function used to symmetrize adjacency matrices ("mean", "max", etc.).

nCores Integer. Number of CPU cores to use for parallelization. Default is the number of workers in the current **BiocParallel** backend. Note: JRF uses C implementation and does not use this parameter.

grnboost_modules Python modules needed for GRNBoost2 if using reticulate.

debug Logical. If TRUE, prints detailed progress messages. Default is FALSE.

Details

For each input expression matrix, n shuffled versions are generated by randomly permuting each gene's expression across cells. Network inference is performed on the shuffled matrices, and a cutoff is determined as the specified quantile (`quantile_threshold`) of the resulting edge weights. The original weighted adjacency matrices are then thresholded using these estimated cutoffs.

Parallelization is handled via **BiocParallel**.

The methods are based on:

- **GENIE3**: Random Forest-based inference (Huynh-Thu et al., 2010).
- **GRNBoost2**: Gradient boosting trees using arboreto (Moerman et al., 2019).
- **JRF**: Joint Random Forests across multiple conditions (Petralia et al., 2015).

Value

A [SummarizedExperiment](#) object where each assay is a binary (thresholded) adjacency matrix corresponding to an input weighted matrix. Metadata includes cutoff values and method parameters.

Examples

```
data(toy_counts)

# Infer networks (toy_counts is already a MultiAssayExperiment)
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)
head(networks[[1]])

# Generate adjacency matrices
wadj_se <- generate_adjacency(networks)
swadj_se <- symmetrize(wadj_se, weight_function = "mean")

# Apply cutoff
binary_se <- cutoff_adjacency(
  count_matrices = toy_counts,
  weighted_adjm_list = swadj_se,
  n = 1,
  method = "GENIE3",
  quantile_threshold = 0.95,
  nCores = 1,
  debug = TRUE
)
head(binary_se[[1]])
```

download_Atlas	<i>Download and Load an RDS File from a URL</i>
----------------	---

Description

Downloads an RDS file from a specified URL and reads its contents into R. We used it for <https://www.singlecellatlas.org>

Usage

```
download_Atlas(file_url)
```

Arguments

file_url Character; URL of the RDS file to download.

Details

This function uses **httr** to perform the download. The RDS file is read directly from a raw connection without saving to disk. An internet connection is required.

If the download fails (e.g., invalid URL, server error), an informative error message is returned.

Value

An R object loaded from the downloaded RDS file.

Examples

```
url <- "https://zenodo.org/records/15511027/files/sce_obj.rds?download=1"
atlas_data <- download_Atlas(url)
```

earlyj	<i>Modify Cell Names and Combine Datasets</i>
--------	---

Description

Extracts expression data from a [MultiAssayExperiment](#) object, modifies cell identifiers by appending a unique experiment index (e.g., "-m1", "-m2", etc.), and merges the datasets into a single object.

Usage

```
earlyj(input_list, rowg = TRUE)
```

Arguments

input_list	A MultiAssayExperiment object containing expression data from multiple experiments or conditions.
rowg	Logical. If TRUE (default), genes are assumed to be rows and cells columns. If FALSE, matrices are transposed before renaming and combining.

Details

For matrices, this function optionally transposes the input before combining. For Seurat and SingleCellExperiment objects, only features (genes) common across all input datasets are retained before merging. The cell names are suffixed with "-m1", "-m2", etc., according to their original list position. The result is returned as a MultiAssayExperiment with a single merged experiment.

Value

A [MultiAssayExperiment](#) object containing a single merged experiment with modified (unique) cell names.

Examples

```
data(toy_counts)

merged_mae <- earlyj(toy_counts)
merged_mae
```

edge_mining

Edge Mining of Gene Interactions Using PubMed

Description

Query PubMed for literature evidence supporting predicted gene–gene interactions.

Usage

```
edge_mining(
  predicted_list,
  ground_truth,
  delay = 1,
  query_field = "Title/Abstract",
  query_edge_types = c("TP", "FP", "FN"),
  max_retries = 10,
  BPPARAM = BiocParallel::bpparam()
)
```

Arguments

predicted_list	A list of predicted adjacency matrices (row and column names are gene symbols), or a SummarizedExperiment object containing adjacency matrices.
ground_truth	A 0/1 adjacency matrix with row and column names.
delay	Numeric. Seconds to wait between consecutive queries (default = 1).
query_field	Character. PubMed search field. Options: "Title/Abstract" (default), "Title", "Abstract".
query_edge_types	Character vector. Edge types to query: c("TP", "FP", "FN") (default all).
max_retries	Integer. Max retries for PubMed queries (default = 10).
BPPARAM	A BiocParallel parameter object. Default = bpparam().

Details

This function compares predicted adjacency matrices against a ground truth matrix, identifies edge types (TP, FP, FN), and queries PubMed for each gene pair. Returns counts of hits, PMIDs, and query status.

Value

A named list of data.frames. Each data.frame has columns:

gene1	First gene in interaction
gene2	Second gene
edge_type	One of "TP", "FP", or "FN"
pubmed_hits	Number of PubMed hits
PMIDs	Comma-separated PubMed IDs or NA
query_status	One of "hits_found", "no_hits", or "error"

Examples

```
data(toy_counts)
data(toy_adj_matrix)

# Infer networks (toy_counts is already a MultiAssayExperiment)
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)
head(networks[[1]])

# Generate adjacency matrices
wadj_se <- generate_adjacency(networks)
swadj_se <- symmetrize(wadj_se, weight_function = "mean")
```

```

# Apply cutoff
binary_se <- cutoff_adjacency(
  count_matrices = toy_counts,
  weighted_adjm_list = swadj_se,
  n = 1,
  method = "GENIE3",
  quantile_threshold = 0.95,
  nCores = 1,
  debug = TRUE
)
head(binary_se[[1]])

consensus <- create_consensus(binary_se, method = "union")
head(consensus)
em <- edge_mining(consensus, toy_adj_matrix, query_edge_types = "TP")

```

generate_adjacency *Generate Adjacency Matrices from Gene Interaction Tables*

Description

Constructs adjacency matrices from a list of data frames (network edge lists) and returns them in a [SummarizedExperiment](#) object.

Usage

```
generate_adjacency(df_list, nCores = 1)
```

Arguments

df_list	A list of data frames. Each data frame must have three columns: Gene1 Character. First gene in the interaction. Gene2 Character. Second gene in the interaction. Weight Numeric. Weight or strength of the interaction from Gene1 to Gene2.
nCores	Integer. Number of CPU cores to use for parallel processing. Defaults to the number of available workers from the current BiocParallel backend.

Details

The function first identifies all unique genes across all data frames to define the matrix dimensions. For each interaction table, it places the corresponding weights at the appropriate gene-pair positions. Parallelization is handled by **BiocParallel** for improved performance on multiple datasets.

Missing weights (NA) are ignored during construction. Only gene pairs matching the global gene list are inserted.

Value

A [SummarizedExperiment](#) object where each assay is a square numeric adjacency matrix (p×p genes). Diagonal entries are set to zero (no self-interactions).

Examples

```

data("toy_counts")

# Infer networks (toy_counts is already a MultiAssayExperiment)
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)
head(networks[[1]])

# Generate adjacency matrices
wadj_se <- generate_adjacency(networks) # returns SummarizedExperiment
head(wadj_se[[1]])

```

infer_networks

*Infer Gene Regulatory Networks from Expression Matrices***Description**

Infers weighted gene regulatory networks (GRNs) from one or more expression matrices using different inference methods: "GENIE3", "GRNBoost2", "ZILGM", "JRF", or "PCzinb".

Usage

```

infer_networks(
  count_matrices_list,
  method = c("GENIE3", "GRNBoost2", "ZILGM", "JRF", "PCzinb"),
  adjm = NULL,
  nCores = 1,
  grnboost_modules = NULL,
  genie3_params = list(),
  grnboost2_params = list(),
  zilgm_params = list(),
  jrf_params = list(),
  pczinb_params = list(),
  verbose = FALSE
)

```

Arguments

count_matrices_list	A MultiAssayExperiment object containing expression data from multiple experiments or conditions.
method	Character string. Inference method to use. One of: "GENIE3", "GRNBoost2", "ZILGM", "JRF", or "PCzinb".
adjm	Optional. Reference adjacency matrix for matching dimensions when using "ZILGM" or "PCzinb".

nCores	Integer. Number of CPU cores to use for parallelization. Default: 1.
grnboost_modules	Python modules required for GRNBoost2 (created via reticulate).
genie3_params	List of parameters for GENIE3 method: <ul style="list-style-type: none"> • regulators: Vector of regulator gene names (default: all) • targets: Vector of target gene names (default: all genes) • treeMethod: "RF" or "ET" (default: "RF") • K: Number of candidate regulators (default: "sqrt") • nTrees: Number of trees per ensemble (default: 1000) • seed: Random seed for reproducibility (default: NULL)
grnboost2_params	List of parameters for GRNBoost2 method: <ul style="list-style-type: none"> • tf_names: Vector of transcription factor names (default:all) • gene_names: Vector of target gene names (default: all) • client_or_address: Dask client or address (default: NULL) • seed: Random seed for reproducibility (default: NULL)
zilgm_params	List of parameters for ZILGM method: <ul style="list-style-type: none"> • lambda: Regularization parameter (default: 0.1) • alpha: Elastic net mixing parameter (default: 1) • max_iter: Maximum iterations (default: 100) • tol: Convergence tolerance (default: 1e-4)
jrf_params	List of parameters for JRF method: <ul style="list-style-type: none"> • ntree: Number of trees (default: 1000) • mtry: Number of variables to sample at each split (default: sqrt(p))
pczinb_params	List of parameters for PCzinb method: <ul style="list-style-type: none"> • gamma: Regularization parameter (default: 0.1) • beta: Beta parameter (default: 0.1) • max_iter: Maximum iterations (default: 100) • tol: Convergence tolerance (default: 1e-4)
verbose	Logical. If TRUE, display messages. Default: FALSE.

Details

Each expression matrix is preprocessed automatically depending on its object type (Seurat, SingleCellExperiment, or plain matrix).

Parallelization behavior:

- **GENIE3**: No external parallelization; internal nCores parameter controls computation.
- **ZILGM**: Uses nCores parameter for internal parallelization.
- **GRNBoost2** and **PCzinb**: Parallelized across matrices using **BiocParallel**.
- **JRF**: Joint modeling of all matrices together using optimized C implementation.

Methods are based on:

- **GENIE3**: Random Forest-based inference (Huynh-Thu et al., 2010).
- **GRNBoost2**: Gradient boosting trees using arboreto (Moerman et al., 2019).
- **ZILGM**: Zero-Inflated Graphical Models for scRNA-seq (Zhang et al., 2021).
- **JRF**: Joint Random Forests across multiple conditions (Petralia et al., 2015).
- **PCzinb**: Pairwise correlation under ZINB models (Nguyen et al., 2023).

Value

A list of inferred networks:

- For "GENIE3", "GRNBoost2", "ZILGM", and "PCzinb", a list of inferred network objects (edge lists or adjacency matrices).
- For "JRF", a list of data frames with inferred edge lists for each condition or dataset.

Examples

```
data("toy_counts")

# Infer networks (toy_counts is already a MultiAssayExperiment)
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)
head(networks[[1]])
```

init_py

Initialize Python Environment for GRNBoost2

Description

Sets up the Python environment and lazily loads modules required for running GRNBoost2: arboreto, pandas, and numpy. Automatically installs missing Python packages if requested.

Usage

```
init_py(
  python_path = "/usr/bin/python3",
  required = TRUE,
  install_missing = FALSE,
  install_method = "auto",
  verbose = TRUE
)
```

Arguments

<code>python_path</code>	Character string. Path to the Python executable, e.g., <code>"/usr/bin/python3"</code> . For optimal GRNBoost2 compatibility, Python 3.8.x is strongly recommended.
<code>required</code>	Logical. If TRUE, errors if Python is not available or path is invalid. Default: TRUE.
<code>install_missing</code>	Logical. If TRUE, automatically installs missing Python packages. Default: FALSE.
<code>install_method</code>	Character string. Installation method when <code>install_missing = TRUE</code> . Options: <code>"auto"</code> , <code>"conda"</code> , <code>"pip"</code> . Default: <code>"auto"</code> .
<code>verbose</code>	Logical. If TRUE, shows installation progress. Default: TRUE.

Details

Uses **reticulate** to bind R to the specified Python interpreter and lazily import modules needed for GRNBoost2. If `install_missing = TRUE`, automatically installs the `'arboreto'` package using the specified method if not found.

Value

A list with three Python module objects:

- `arboreto`: GRNBoost2 algorithm module.
- `pandas`: Data handling module.
- `numpy`: Numerical operations module.

Examples

```
# Initialize Python environment (handles missing modules gracefully)
tryCatch(
  {
    modules <- init_py(required = FALSE)
  },
  error = function(e) {
    message("Python environment not available: ", e$message)
  }
)
```

Description

This function performs structure learning for count data using various PC algorithms adapted for different distributional assumptions including Poisson, Negative Binomial, and Zero-Inflated Negative Binomial models.

Usage

```

PCzinb(
  x,
  method = c("poi", "nb", "zinb0", "zinb1"),
  alpha = NULL,
  maxcard = 2,
  extend = TRUE,
  nCores = 1,
  whichAssay = "processed",
  ...
)

```

Arguments

x	A matrix of count data ($n \times p$), SummarizedExperiment, or SingleCellExperiment object. For matrix input, rows are samples and columns are genes.
method	The algorithm used to estimate the graph: poi (Poisson), nb (Negative Binomial), zinb0 (Zero-Inflated NB with structure only in mu), or zinb1 (Zero-Inflated NB with structure in both mu and pi).
alpha	The significance level of the tests. Default: $2 * pnorm(nrow(x)^{0.2}, lower.tail = FALSE)$.
maxcard	The upper bound of the cardinality of the conditional sets K. Default: 2.
extend	If TRUE, considers the union of the tests; if FALSE, considers the intersection. Default: TRUE.
nCores	Number of cores for parallel processing. Default: 1.
whichAssay	The assay to use as input (for SummarizedExperiment or SingleCellExperiment objects). Default: "processed".
...	Additional arguments (currently unused).

Details

PCzinb performs structure learning using PC algorithms for count data. Different methods handle different distributional assumptions:

- poi: Poisson distribution
- nb: Negative Binomial distribution
- zinb0: Zero-Inflated NB with structure only in mean parameter
- zinb1: Zero-Inflated NB with structure in both mean and zero-inflation parameters

For SummarizedExperiment and SingleCellExperiment inputs, if the specified whichAssay is "processed" but not found, the function will use the first assay and issue a warning recommending QPtransform().

Value

- If `x` is a matrix: the estimated adjacency matrix of the graph
- If `x` is a `SummarizedExperiment`: the object with adjacency matrix stored in metadata as `adj_mat`
- If `x` is a `SingleCellExperiment`: the object with adjacency matrix stored as `rowPair`

Examples

```
# Matrix input
mat <- matrix(rpois(50, 5), nrow = 10)
PCzinb(mat, method = "poi")

# SummarizedExperiment input
library(SummarizedExperiment)
se <- SummarizedExperiment(matrix(rpois(50, 5), ncol = 10))
se_result <- PCzinb(se, method = "poi")

# SingleCellExperiment input
library(SingleCellExperiment)
sce <- SingleCellExperiment(matrix(rpois(50, 5), ncol = 10))
sce_result <- PCzinb(sce, method = "poi")
rowPair(sce_result)
```

plot_community_comparison

Visualize Community and Topology Comparison

Description

Creates visualization plots for community assignment metrics and topological properties comparison.

Usage

```
plot_community_comparison(
  community_metrics,
  topology_measures,
  control_topology
)
```

Arguments

`community_metrics`

A data frame with VI, NMI, and ARI scores (output from `compute_community_metrics()`).

`topology_measures`

A data frame with Modularity, Communities, Density, and Transitivity (from `compute_topology_metrics()`).

`control_topology`

A named numeric vector of control network topology metrics (from `compute_topology_metrics()`).

Details

This function requires the **fmsb** package for radar chart visualization. The radar plot shows normalized community similarity metrics. The bar plots compare raw topological properties between predicted and control networks.

Value

Invisibly returns NULL. Displays a radar plot for community metrics and bar plots for topology comparison.

Examples

```
data(toy_counts)
data(toy_adj_matrix)

# Infer networks (toy_counts is already a MultiAssayExperiment)
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)

# Generate adjacency matrices
wadj_se <- generate_adjacency(networks)
swadj_se <- symmetrize(wadj_se, weight_function = "mean")

# Apply cutoff
binary_se <- cutoff_adjacency(
  count_matrices = toy_counts,
  weighted_adjm_list = swadj_se,
  n = 1,
  method = "GENIE3",
  quantile_threshold = 0.95,
  nCores = 1
)

consensus <- create_consensus(binary_se, method = "union")
comm_cons <- community_path(consensus)
comm_truth <- community_path(toy_adj_matrix)

comm_metrics <- compute_community_metrics(comm_truth, list(comm_cons))
topo_metrics <- compute_topology_metrics(comm_truth, list(comm_cons))

plot_community_comparison(
  comm_metrics,
  topo_metrics$topology_measures,
  topo_metrics$control_topology
)
```

`plot_network_comparison`*Visualize Network Comparison*

Description

Creates visualization plots comparing consensus and reference networks, showing True Positives (TP), False Negatives (FN), and optionally False Positives (FP) edges.

Usage

```
plot_network_comparison(edge_classification, show_fp = FALSE)
```

Arguments

<code>edge_classification</code>	A list output from <code>classify_edges()</code> containing edge classifications and graph objects.
<code>show_fp</code>	Logical. If TRUE, displays False Positive edges in a separate plot. Default: FALSE.

Details

This function requires the **ggraph** and **ggplot2** packages. If `show_fp = TRUE`, the **patchwork** package is also required.

The plots differentiate:

- TP/CE (True Positives/Confirmed Edges): Red edges present in both
- FN/ME (False Negatives/Missing Edges): Blue edges in reference only
- FP/EE (False Positives/Extra Edges): Edges in consensus only

If `STRINGdb` was used for reference, labels are CE/ME/EE. Otherwise, TP/FN/FP.

Value

A `ggplot` object visualizing the comparison. If `show_fp = TRUE`, a combined plot using `patchwork` is returned.

Examples

```
data(toy_counts)
data(toy_adj_matrix)

# Infer networks (toy_counts is already a MultiAssayExperiment)
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
```

```
    nCores = 1
  )

  # Generate and symmetrize adjacency matrices (returns SummarizedExperiment)
  wadj_se <- generate_adjacency(networks)
  swadj_se <- symmetrize(wadj_se, weight_function = "mean")

  # Apply cutoff (returns SummarizedExperiment)
  binary_se <- cutoff_adjacency(
    count_matrices = toy_counts,
    weighted_adjm_list = swadj_se,
    n = 1,
    method = "GENIE3",
    quantile_threshold = 0.95,
    nCores = 1
  )

  # Create consensus (returns SummarizedExperiment)
  consensus <- create_consensus(binary_se, method = "union")

  # Wrap reference matrix in SummarizedExperiment
  ref_se <- build_network_se(list(reference = toy_adj_matrix))

  # Classify edges
  edge_class <- classify_edges(consensus, ref_se)

  # Plot comparison
  plot_network_comparison(edge_class, show_fp = FALSE)
```

plotg

Visualize Graphs from Adjacency Matrices

Description

Generates and arranges multiple graph visualizations from a list of adjacency matrices. Each matrix is converted into an undirected **igraph** object and visualized using a force-directed layout via **ggraph**.

Usage

```
plotg(adj_matrix_list)
```

Arguments

adj_matrix_list

A list of square, symmetric adjacency matrices with zeros on the diagonal (no self-loops), or a [SummarizedExperiment](#) object containing such matrices as assays. Each matrix represents an undirected graph.

Details

Each adjacency matrix is validated to ensure it is square and symmetric. Disconnected nodes (degree zero) are removed prior to visualization. Graphs are visualized with a force-directed layout using **ggraph**, and multiple plots are arranged into a grid with **gridExtra**.

Each subplot title includes the graph index, number of nodes, and number of edges.

Value

A grid of plots displaying all valid graphs in the input list.

Note

This function requires the following packages: **igraph**, **ggraph**, and **gridExtra**. If any are missing, an informative error will be thrown.

Examples

```
data(toy_counts)

# Infer networks (toy_counts is already a MultiAssayExperiment)
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)
head(networks[[1]])

# Generate adjacency matrices
wadj_se <- generate_adjacency(networks)
swadj_se <- symmetrize(wadj_se, weight_function = "mean")

# Apply cutoff
binary_se <- cutoff_adjacency(
  count_matrices = toy_counts,
  weighted_adjm_list = swadj_se,
  n = 1,
  method = "GENIE3",
  quantile_threshold = 0.95,
  nCores = 1,
  debug = TRUE
)
head(binary_se[[1]])
plotg(binary_se)
```

`plotROC`*Plot ROC Curves for Inferred Networks*

Description

Computes and visualizes Receiver Operating Characteristic (ROC) curves for predicted adjacency matrices stored in a [SummarizedExperiment](#) object, compared against a binary ground truth network.

Usage

```
plotROC(predicted_se, ground_truth, plot_title, is_binary = FALSE)
```

Arguments

<code>predicted_se</code>	A SummarizedExperiment object containing predicted adjacency matrices as assays. Each matrix must share dimnames with <code>ground_truth</code> ; entries may be binary (0/1) or continuous weights.
<code>ground_truth</code>	A square binary matrix indicating true interactions (1) in the upper triangle. Must match dims and names of each assay in <code>predicted_se</code> .
<code>plot_title</code>	Character string. Title for the ROC plot.
<code>is_binary</code>	Logical. If TRUE, treat matrices as binary predictions. Default FALSE for weighted predictions.

Details

For binary matrices, a single TPR/FPR point is computed per matrix. For weighted ones, a full ROC curve is computed from continuous scores. Diagonals are ignored; symmetry is not enforced.

Value

A list with:
`auc`: data frame of AUC per matrix.
`plot`: the ROC plot (via `ggplot2`).

Examples

```
data(toy_counts)
data(toy_adj_matrix)

# Infer networks (toy_counts is already a MultiAssayExperiment)
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)
```

```

head(networks[[1]])

# Generate and symmetrize adjacency matrices (returns SummarizedExperiment)
wadj_se <- generate_adjacency(networks)
swadj_se <- symmetrize(wadj_se, weight_function = "mean")

# plotROC now accepts SummarizedExperiment directly
roc_res <- plotROC(
  swadj_se,
  toy_adj_matrix,
  plot_title = "ROC Curve: GENIE3",
  is_binary = FALSE
)
roc_res$plot
auc_joint <- roc_res$auc

```

pscores

Compute Performance Scores for Predicted Adjacency Matrices

Description

Computes classification metrics by comparing predicted adjacency matrices to a ground truth binary network and visualizes the performance via a radar (spider) plot.

Usage

```
pscores(ground_truth, predicted_list, zero_diag = TRUE)
```

Arguments

ground_truth	A square binary adjacency matrix representing the ground truth network. Values must be 0 or 1. Only the upper triangle is used for evaluation.
predicted_list	A list of predicted adjacency matrices to evaluate, or a SummarizedExperiment object containing such matrices as assays. Each matrix must have the same dimensions and row/column names as ground_truth.
zero_diag	Logical. If TRUE (default), sets the diagonal of ground_truth to zero before evaluation, removing self-loops.

Details

For each predicted matrix, the confusion matrix is computed using the upper triangle (non-self edges). Metrics including True Positive Rate (TPR), False Positive Rate (FPR), Precision, F1-score, and Matthews Correlation Coefficient (MCC) are calculated.

A radar plot is automatically generated summarizing the key scores across matrices.

Value

A list with one element:

Statistics: Data frame of evaluation metrics (TP, TN, FP, FN, TPR, FPR, Precision, F1, MCC) for each predicted matrix.

Note

Requires the **fmsb**, **dplyr**, and **tidyr** packages.

Examples

```
data(toy_counts)
data(toy_adj_matrix)

# Infer networks (toy_counts is already a MultiAssayExperiment)
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)

# Generate adjacency matrices
wadj_se <- generate_adjacency(networks)
swadj_se <- symmetrize(wadj_se, weight_function = "mean")

# Apply cutoff
binary_se <- cutoff_adjacency(
  count_matrices = toy_counts,
  weighted_adjm_list = swadj_se,
  n = 1,
  method = "GENIE3",
  quantile_threshold = 0.95,
  nCores = 1,
  debug = TRUE
)

pscores_data <- pscores(toy_adj_matrix, binary_se)
```

selgene

Select Top Expressed Genes from Single-Cell Data

Description

Identifies and returns the top n most highly expressed genes across all cells or within a specific cell type. Supports objects of class Seurat, [SingleCellExperiment](#), or a numeric expression matrix (genes × cells).

Usage

```
selgene(
  object,
  top_n,
  cell_type = NULL,
  cell_type_col = "cell_type",
  assay = NULL,
  remove_mt = FALSE,
  remove_rib = FALSE
)
```

Arguments

object	A Seurat object, SingleCellExperiment object, or numeric matrix (genes × cells).
top_n	Integer. Number of top expressed genes to return.
cell_type	Optional string. If provided, filters the expression matrix to only include cells of this type.
cell_type_col	Character. Name of the column in metadata (Seurat meta.data or SCE colData) containing cell type annotations. Default is "cell_type".
assay	Character. For SingleCellExperiment objects only. Name of the assay to use. If NULL, defaults to "logcounts".
remove_mt	Logical. If TRUE, remove mitochondrial genes matching "^MT-" (case-insensitive).
remove_rib	Logical. If TRUE, remove ribosomal genes matching "^RPL[SL]" (case-insensitive).

Details

The function assumes that log-normalized values are available in the "data" slot (for Seurat objects) or the "logcounts" assay (for SingleCellExperiment). If raw counts are provided as a matrix, no transformation is applied.

Optional filtering is available to exclude mitochondrial genes ("^MT-") and ribosomal genes ("^RPL[SL]"), which may otherwise dominate the top expressed genes.

Value

A character vector of the top n most highly expressed gene names.

Details

When using a Seurat object, the function retrieves the log-normalized data from the default assay's "data" slot. For SingleCellExperiment, it uses the specified assay (default is "logcounts"). For matrices, no checks or transformations are applied, and subsetting by cell type is not supported.

Mitochondrial and ribosomal gene removal is based on regular expressions matching gene names. These should follow standard naming conventions (e.g., MT-ND1, RPL13A, RPS6).

See Also

[SingleCellExperiment](#)

Examples

```

data(toy_counts)
genes <- selgene(
  object = toy_counts[[1]],
  top_n = 5,
  cell_type = "T_cells",
  cell_type_col = "CELL_TYPE",
  remove_rib = TRUE,
  remove_mt = TRUE,
  assay = "counts"
)

```

stringdb_adjacency	<i>Build Adjacency Matrices for Physical Interactions from STRING (POST API)</i>
--------------------	--

Description

Constructs weighted and binary adj matrices for physical protein-protein interactions using a POST request to the STRING database API.

Usage

```

stringdb_adjacency(
  genes,
  species = 9606,
  required_score = 400,
  keep_all_genes = TRUE,
  verbose = TRUE
)

```

Arguments

genes	A character vector of gene symbols or identifiers, e.g., c("TP53", "BRCA1", ...).
species	Integer. NCBI taxonomy ID of the species. Default is 9606 (human).
required_score	Integer in $\setminus[0,1000]$. Minimum confidence score for interactions. Default is 400.
keep_all_genes	Logical. If TRUE (default), includes all input genes in the final matrix even if unmapped.
verbose	Logical. If TRUE, displays progress messages. Default is TRUE.

Details

This function:

1. Maps input genes to STRING internal IDs.
2. Uses a POST request to retrieve physical protein-protein interactions from STRING.
3. Builds a weighted adjacency matrix using the STRING combined score.
4. Builds a binary adjacency matrix indicating presence/absence.

Genes not mapped to STRING are optionally retained as zero rows/columns if `keep_all_genes = TRUE`.

Value

A list containing:

- `weighted`: A square numeric adjacency matrix with scores as weights.
- `binary`: A corresponding binary (0/1) adjacency matrix.

Note

Requires packages: **STRINGdb**, **httr**, **jsonlite**.

Examples

```
data(toy_counts)
genes <- selgene(
  object = toy_counts[[1]],
  top_n = 5,
  cell_type = "T_cells",
  cell_type_col = "CELL_TYPE",
  remove_rib = TRUE,
  remove_mt = TRUE,
  assay = "counts"
)

str_res <- stringdb_adjacency(
  genes = genes,
  species = 9606,
  required_score = 900,
  keep_all_genes = FALSE
)
wadj_truth <- str_res$weighted
toy_adj_matrix <- str_res$binary
```

symmetrize

Symmetrize Adjacency Matrices in a SummarizedExperiment

Description

Symmetrizes each adjacency matrix in a [SummarizedExperiment](#) by ensuring entries (i, j) and (j, i) are identical, using a specified combination function.

Usage

```
symmetrize(matrix_list, weight_function = "mean", nCores = 1)
```

Arguments

matrix_list	A SummarizedExperiment object containing adjacency matrices to symmetrize.
weight_function	Character string or function. Method to combine entries (i, j) and (j, i). Options include "mean", "max", "min", or a user-defined function.
nCores	Integer. Number of CPU cores to use for parallel processing. Defaults to the number of available workers in the current BiocParallel backend.

Details

For each pair of off-diagonal elements (i, j) and (j, i):

- If one value is zero, the non-zero value is used.
- If both are non-zero, they are combined using the specified `weight_function`.

Diagonal entries are preserved as-is and not modified.

Parallelization is managed via **BiocParallel** for improved performance.

Value

A [SummarizedExperiment](#) object with symmetrized adjacency matrices, where for each matrix $A[i, j] = A[j, i]$ for all $i \neq j$.

Examples

```
data("toy_counts")

# Infer networks (toy_counts is already a MultiAssayExperiment)
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)
head(networks[[1]])
```

```
# Generate adjacency matrices
wadj_se <- generate_adjacency(networks)
swadj_se <- symmetrize(wadj_se, weight_function = "mean")
```

toy_adj_matrix	<i>Toy adjacency matrix for examples</i>
----------------	--

Description

An adjacency matrix generated using real dataset and STRINGdb for demonstrating functions in the scGraphVerse package.

Usage

```
data(toy_adj_matrix)
```

Format

A matrix of dimension 10x10.

Examples

```
data(toy_adj_matrix)
str(toy_adj_matrix)
```

toy_counts	<i>Toy MultiAssayExperiment for Network Inference</i>
------------	---

Description

A simulated dataset generated using zinb_simdata() for demonstrating network inference functions in the scGraphVerse package.

Usage

```
data(toy_counts)
```

Format

A [MultiAssayExperiment](#) object containing 3 SingleCellExperiment objects (experiments), each with 10 genes x 40 cells. The data was simulated using a known ground truth network (toy_adj_matrix) with zero-inflated negative binomial distributions.

Examples

```

data(toy_counts)
toy_counts

# Access individual experiments
MultiAssayExperiment::experiments(toy_counts)

# Use directly with infer_networks
networks <- infer_networks(
  count_matrices_list = toy_counts,
  method = "GENIE3",
  nCores = 1
)

```

zinb_simdata	<i>Simulate Zero-Inflated Negative Binomial (ZINB) Count Matrices with Sequencing Depth</i>
--------------	---

Description

Simulates one or more count matrices following a zero-inflated negative binomial (ZINB) distribution, incorporating gene-gene interaction structures and cell-specific sequencing depth variation.

Usage

```

zinb_simdata(
  n,
  p,
  B,
  mu_range,
  mu_noise,
  theta,
  pi,
  kmat = 1,
  depth_range = NA
)

```

Arguments

n	Integer. Number of cells (samples) in each simulated matrix.
p	Integer. Number of genes (features) in each simulated matrix.
B	A symmetric binary adjacency matrix (0/1) defining gene-gene connectivity. Row and column names correspond to gene names.
mu_range	List of numeric vectors (length 2 each). Range of gene expression means for each simulated matrix.
mu_noise	Numeric vector. Mean of background noise for each matrix.

theta	Numeric vector. Dispersion parameters of the negative binomial distribution for each matrix. Smaller theta implies higher overdispersion.
pi	Numeric vector. Probability of excess zeros ($0 < \pi < 1$) for each matrix.
kmat	Integer. Number of count matrices to simulate. Default is 1.
depth_range	Numeric vector of length 2 or NA. Range of total sequencing depth per cell. If NA, no depth adjustment is performed.

Details

Each simulated matrix:

1. Generates gene expression values based on a ZINB model.
2. Modulates expression using the adjacency matrix B.
3. Applies random sequencing depth scaling if depth_range is provided.

Useful for benchmarking single-cell RNA-seq network inference methods with dropout events and network structure.

Value

A list containing kmat matrices. Each matrix has:

- Rows representing cells (cell_1, ..., cell_n).
- Columns representing genes (rownames(B)).
- Count values following a ZINB distribution.

Examples

```
data(toy_adj_matrix)
nodes <- nrow(toy_adj_matrix)
sims <- zinb_simdata(
  n = 50,
  p = nodes,
  B = toy_adj_matrix,
  mu_range = list(c(1, 4), c(1, 7), c(1, 10)),
  mu_noise = c(1, 3, 5),
  theta = c(1, 0.7, 0.5),
  pi = c(0.2, 0.2, 0.2),
  kmat = 3,
  depth_range = c(0.8 * nodes * 3, 1.2 * nodes * 3)
)
```

Index

- * **datasets**
 - toy_adj_matrix, [40](#)
 - toy_counts, [40](#)
- build_network_se, [3](#)
- classify_edges, [4](#), [9](#), [10](#)
- community_path, [5](#)
- community_similarity, [8](#)
- compare_consensus, [9](#)
- compute_community_metrics, [8](#), [11](#)
- compute_topology_metrics, [8](#), [12](#)
- consensusNet, [14](#)
- create_consensus, [14](#)
- create_mae, [16](#)
- cutoff_adjacency, [17](#)
- download_Atlas, [19](#)
- earlyj, [19](#)
- edge_mining, [20](#)
- generate_adjacency, [22](#)
- infer_networks, [23](#)
- init_py, [25](#)
- MultiAssayExperiment, [17](#), [19](#), [20](#), [23](#), [40](#)
- PCzinb, [26](#)
- plot_community_comparison, [8](#), [28](#)
- plot_network_comparison, [9](#), [10](#), [30](#)
- plotg, [31](#)
- plotROC, [33](#)
- pscores, [34](#)
- selgene, [35](#)
- SingleCellExperiment, [35](#), [36](#)
- stringdb_adjacency, [37](#)
- SummarizedExperiment, [4](#), [6](#), [9](#), [10](#), [14](#), [15](#),
[17](#), [18](#), [21](#), [22](#), [31](#), [33](#), [34](#), [39](#)
- symmetrize, [39](#)
- toy_adj_matrix, [40](#)
- toy_counts, [40](#)
- zinb_simdata, [41](#)