Package: segmenter (via r-universe)

November 1, 2026

Type Package

Title Perform Chromatin Segmentation Analysis in R by Calling ChromHMM

Version 1.18.0

Description Chromatin segmentation analysis transforms ChIP-seq data into signals over the genome. The latter represents the observed states in a multivariate Markov model to predict the chromatin's underlying states. ChromHMM, written in Java, integrates histone modification datasets to learn the chromatin states de-novo. The goal of this package is to call chromHMM from within R, capture the output files in an S4 object and interface to other relevant Bioconductor analysis tools. In addition, segmenter provides functions to test, select and visualize the output of the segmentation.

License GPL-3

Encoding UTF-8

RoxygenNote 7.1.1

Depends R (>= 4.1)

BugReports https://github.com/MahShaaban/segmenter/issues

Suggests testthat, knitr, rmarkdown, TxDb.Hsapiens.UCSC.hg18.knownGene, Gviz

Imports ChIPseeker, GenomicRanges, SummarizedExperiment, IRanges, S4Vectors, bamsignals, ComplexHeatmap, graphics, stats, utils, methods, chromhmmData

VignetteBuilder knitr

biocViews Software, HistoneModification

LazyData True

Config/pak/sysreqs libcairo2-dev cmake libfontconfig1-dev libfreetype6-dev libglpk-dev make libbz2-dev libicu-dev liblzma-dev libpng-dev libuv1-dev libxml2-dev libssl-dev perl xz-utils zlib1g-dev

Repository Bioconductor 3.23

Date/Publication 2026-04-28 12:56:25 UTC

RemoteUrl https://github.com/bioc/segmenter

RemoteRef RELEASE_3_23

RemoteSha 25e9ac9b3889bd4a23f1ee6921b405c3cd7cd0b5

Contents

.Binarize . . . 3
.LearnModel . . . 3
accessors . . . 4
annotate_segments . . . 7
binarize_bam . . . 8
binarize_bed . . . 9
compare_models . . . 10
count_reads_ranges . . . 10
emissions_file . . . 11
enrichment_files . . . 11
get_frequency . . . 12
get_width . . . 13
learn_model . . . 13
merge_segments_bins . . . 15
methods . . . 16
model_file . . . 16
overlap_files . . . 17
plot_heatmap . . . 18
range_bins . . . 18
range_counts . . . 19
read_bam_file . . . 20
read_bins_file . . . 20
read_cellmark_file . . . 21
read_chromsize_file . . . 22
read_emissions_file . . . 22
read_enrichment_file . . . 23
read_model_file . . . 24
read_overlap_file . . . 24
read_segements_file . . . 25
read_transitions_file . . . 26
segmentation . . . 26
segments_files . . . 27
test_obj . . . 28
test_objs . . . 28
tidy_ranges . . . 29
transitions_file . . . 29

Index **31**

.Binarize *Call Java* BinarizeBed

Description

Call the Java module BinarizeBed which binarize a bed file of the aligned reads.

Usage

```
.Binarize(inputdir, cellmarkfiletable, chromsizefile, binsize, outputdir, type)
```

Arguments

inputdir	A string. The path to bed files.
cellmarkfiletable	A tab delimited files of three columns. The columns contains the cell, mark and the name or the bed file.
chromsizefile	A string. The path to the chromosomes sizes file.
binsize	An integer. The bin size to use. Default is 200.
outputdir	A string. The path to a directory where output will be written.
type	A string. The file type 'bam' or 'bed'.

Value

NULL. Output files are written to the output directory.

See Also

binarize_bed

.LearnModel *Call Java* LearnModel

Description

Call the Java module LearnModel which learns a multi-state model from ChIP-seq data.

Usage

```
.LearnModel(
  inputdir,
  outputdir,
  numstates,
  coordsdir,
  anchorsdir,
  chromsizefile,
  assembly,
  optional
)
```

Arguments

inputdir	A string. The path to binarized files.
outputdir	A string. The path to a directory where output will be written.
numstates	An integer. The number of desired states in the model.
coordsdir	A string. The path to genomic coordiantes files.
anchorsdir	A string. The path to the genomic anchors files.
chromsizefile	A string. The path to the chromosomes sizes file.
assembly	A string. The name of the genomic assembely.
optional	A string. Other optional arguments passed to the Java command.

Value

NULL. Output files are written to the output directory.

See Also

learn_model

---

accessors *Accessors for the* segmentation *objects*

Description

These functions can be used to access the contents of segmentation objects as well as modifying them.

Usage

```
model(object)

## S4 method for signature 'segmentation'
model(object)

emission(object)

## S4 method for signature 'segmentation'
emission(object)

transition(object)

## S4 method for signature 'segmentation'
transition(object)

overlap(object, ...)

## S4 method for signature 'segmentation'
overlap(object, cell)

TSS(object, ...)

## S4 method for signature 'segmentation'
TSS(object, cell)

TES(object, ...)

## S4 method for signature 'segmentation'
TES(object, cell)

segment(object, ...)

## S4 method for signature 'segmentation'
segment(object, cell)

bins(object, ...)

## S4 method for signature 'segmentation'
bins(object, cell)

counts(object, ...)

## S4 method for signature 'segmentation'
counts(object, cell)

likelihood(object)
```

```
## S4 method for signature 'segmentation'
likelihood(object)

cells(object)

## S4 method for signature 'segmentation'
cells(object)

states(object)

## S4 method for signature 'segmentation'
states(object)

markers(object)

## S4 method for signature 'segmentation'
markers(object)
```

Arguments

object	An object of class segmentation
...	Other argument passed to the accessors
cell	A string

Value

The data in the corresponding slot or a subset of it.

See Also

segmentation

Examples

```
model(test_obj)

emission(test_obj)

transition(test_obj)

overlap(test_obj)
overlap(test_obj, cell = 'K562')

TSS(test_obj)
TSS(test_obj, cell = 'K562')

TES(test_obj)
TES(test_obj, cell = 'K562')

segment(test_obj)
```

```
segment(test_obj, cell = 'K562')

bins(test_obj)

counts(test_obj)

likelihood(test_obj)

cells(test_obj)

states(test_obj)

markers(test_obj)
```

---

annotate_segments *Annotate segments*

Description

Annotate the GRanges objects of the segments using annotatePeak (see for details)

Usage

```
annotate_segments(segments, ...)
```

Arguments

segments	A GRanges object. Usually the output of calling segment on the the output object of lean_model.
...	Other arguments passed to annotatePeak

Value

A GRanges object which is identical to the input in addition to the annotations as metadata columns.

Examples

```
library(TxDb.Hsapiens.UCSC.hg18.knownGene)
txdb <- TxDb.Hsapiens.UCSC.hg18.knownGene
segs <- segment(test_obj)
segs_annotated <- annotate_segments(segs, TxDb = txdb, verbose = FALSE)
```

`binarize_bam` *Binarize the bam files*

Description

Transform the aligned reads into a binary format.

Usage

```
binarize_bam(
  inputdir,
  cellmarkfiletable,
  chromsizefile,
  binsize = 200,
  outputdir
)
```

Arguments

`inputdir`	A string. The dirctory of the bam files.
`cellmarkfiletable`	A string. The path to the input files table. Only
`chromsizefile`	A string. The path to the chromosomes sizes file.
`binsize`	An integer. The number in bp used to generate binarized files.
`outputdir`	A string. The path to a directory where output will be written.

Value

NULL. Write files to the outputdir

See Also

Binarize binarize_bed

Examples

```
# locate input and output files
inputdir <- system.file("extdata", package = "bamsignals")
cellmarkfiletable <- system.file('extdata',
                                 'cell_mark_table.tsv',
                                 package = 'segmenter')
chromsizefile <- system.file('extdata/CHROMSIZES',
                             'hg18.txt',
                              package = 'chromhmmData')
outputdir <- tempdir()

# run command
```

```
binarize_bam(inputdir,
             chromsizefile = chromsizefile,
             cellmarkfiletable = cellmarkfiletable,
             outputdir = outputdir)

# show output files
list.files(outputdir, pattern = '*_binary.txt')
```

`binarize_bed` *Binarize the bed files*

Description

Transform the aligned reads into a binary format.

Usage

```
binarize_bed(
  inputdir,
  cellmarkfiletable,
  chromsizefile,
  binsize = 200,
  outputdir
)
```

Arguments

`inputdir`	A string. The dirctory of the bam files.
`cellmarkfiletable`	A string. The path to the input files table. Only
`chromsizefile`	A string. The path to the chromosomes sizes file.
`binsize`	An integer. The number in bp used to generate binarized files.
`outputdir`	A string. The path to a directory where output will be written.

Value

NULL. Write files to the outputdir

See Also

Binarize binarize_bam

compare_models *Compare two or more models*

Description

Compare two or more models

Usage

```
compare_models(objs, type = "emission", plot = FALSE, ...)
```

Arguments

objs	A list of segmentation items
type	A string. What to compare. Default to 'emission'
plot	A logical.
...	Other arguments passed to plot

Value

A numeric vector or a plot with the same values.

Examples

```
compare_models(test_objs)
compare_models(test_objs, type = 'likelihood')
```

count_reads_ranges *Count reads in* GRanges *objects from bam files*

Description

Count reads in GRanges objects from bam files

Usage

```
count_reads_ranges(ranges, cellmarkfiletable, inputbamdir)
```

Arguments

ranges	A GRanges to count in.
cellmarkfiletable	A string. The path to the input files table.
inputbamdir	A string. The path to the input bam files directory.

Value

A SummarizedExperiment object with ranges as its rowRanges and the counts as the assay.

---

emissions_file *Make emissions file name*

Description

Make emissions file name

Usage

```
emissions_file(numstates)
```

Arguments

numstates	An integer

Value

A string

Examples

```
emissions_file(3)
```

---

enrichment_files *Make enrichment file names*

Description

Make enrichment file names

Usage

```
enrichment_files(numstates, cells, table = "RefSeq", annotation = "TSS")
```

Arguments

numstates	An integer
cells	A character vector
table	A string
annotation	A string

Value

A character vector

Examples

```
enrichment_files(3, 'K562')
```

`get_frequency` *Get the frequency of the segments in each cell type*

Description

Get the frequency of the segments in each cell type

Usage

```
get_frequency(segments, normalize = FALSE, tidy = FALSE, plot = FALSE, ...)
```

Arguments

`segments`	A `GRanges` object. Usually the output of calling `segment` on the the output object of `lean_model`.
`normalize`	A logical. Whether the frequency should be normalized by the total number of segments
`tidy`	A logical.
`plot`	A logical.
`...`	Other arguments passed to barplot

Value

A `data.frame` when tidy is TRUE otherwise a matrix or a plot

Examples

```
get_frequency(segment(test_obj))
get_frequency(segment(test_obj), normalize = TRUE)
```

get_width *Get the width of the segments in each cell type*

Description

Get the width of the segments in each cell type

Usage

```
get_width(segments, average = FALSE)
```

Arguments

segments	A GRanges object. Usually the output of calling segment on the the output object of lean_model.
average	A logical. Whether the width should be averaged across cells.

Value

A data.frame

Examples

```
get_width(segment(test_obj))
get_width(segment(test_obj), average = TRUE)
```

learn_model *Learn a multi-state model from chromatin data*

Description

Integrate multiple ChIP-seq chromatin datasets of histone modifications, transcription factors or other DNA binding proteins to build a multi-state model of the combinatorial and spatial frequently occurring patterns. The function uses as an input binarized ChIP-seq data and the genome annotations on which the states will be discovered.

Usage

```
learn_model(
  inputdir,
  outputdir,
  numstates,
  coordsdir,
  anchorsdir,
  chromsizefile,
```

```
  assembly,
  cells,
  annotation,
  binsize,
  inputbamdir,
  cellmarkfiletable,
  read_only = FALSE,
  read_bins = FALSE,
  counts = FALSE
)
```

Arguments

inputdir	A string. The path to binarized files.
outputdir	A string. The path to a directory where output will be written.
numstates	An integer. The number of desired states in the model.
coordsdir	A string. The path to genomic coordinates files.
anchorsdir	A string. The path to the genomic anchors files.
chromsizefile	A string. The path to the chromosomes sizes file.
assembly	A string. The name of the genomic assembely.
cells	A character vector. The names of the cells as they occur in the binarized files (first line).
annotation	A string. The name of the type of annotation as it occurs in the genomic annotation files.
binsize	An integer. The number in bp used to generate binarized files.
inputbamdir	A string. The path to the input bam files. Only used when count = TRUE.
cellmarkfiletable	A string. The path to the input files table. Only used when bins = TRUE.
read_only	A logical. Default is FALSE. Whether to look for and load output files or generate the model from scratch.
read_bins	A logical. Default is FALSE. Whether to load the binarized data into the output object.
counts	A logical. Default is FALSE. Whether to load the reads counts in bins data into the output object.

Details

By default, this functions runs the analysis commands, writes the output to files and loads it into an object of class segmentation. In addition, the binarized data and the reads counts in the bins can be loaded. When read_only is TRUE. The functions looks for previously generated files in the output directory and load them without rerunning the commands.

Value

An object of class segmentation (see for details) and the files written to the output directory.

See Also

LearnModel

Examples

```
# locate input and output files
inputdir <- system.file('extdata/SAMPLEDATA_HG18',
                        package = 'segmenter')
outputdir <- tempdir()
coordsdir <- system.file('extdata/COORDS',
                         package = 'chromhmmData')
anchorsdir <- system.file('extdata/ANCHORFILES',
                          package = 'chromhmmData')
chromsizefile <- system.file('extdata/CHROMSIZES',
                             'hg18.txt',
                             package = 'chromhmmData')

# run command
obj <- learn_model(inputdir = inputdir,
                   outputdir = outputdir,
                   coordsdir = coordsdir,
                   anchorsdir = anchorsdir,
                   chromsizefile = chromsizefile,
                   numstates = 3,
                   assembly = 'hg18',
                   cells = c('K562', 'GM12878'),
                   annotation = 'RefSeq',
                   binsize = 200)

# show the output
obj
```

---

merge_segments_bins *Merge segments and bins objects*

Description

Merge segments and bins objects

Usage

```
merge_segments_bins(segments, bins)
```

Arguments

segments	A GRanges object. Usually the output of calling segment on the the output object of lean_model.
bins	A SummarizedExperiment object. Usually the output of calling bins on the the output object of lean_model.

Value

A SummarizedExperiment object with the segment assignment added to the metadata of the rowRanges.

---

methods *Methods to interact with* segmentation *objects*

Description

These functions can be used to interact with segmentation objects for purposes other than accessing or modifying their contents.

Usage

```
## S4 method for signature 'segmentation'
show(object)
```

Arguments

object	An object of class segmentation

Value

Prints a summary of the segmentation object contents.

See Also

segmentation

accessors

Examples

```
show(test_obj)
```

---

model_file *Make model file name*

Description

Make model file name

Usage

```
model_file(numstates)
```

Arguments

numstates	An integer

Value

A string

Examples

```
model_file(3)
```

---

overlap_files *Make overlap file names*

Description

Make overlap file names

Usage

```
overlap_files(numstates, cells)
```

Arguments

numstates	An integer
cells	A character vector

Value

A character vector

Examples

```
overlap_files(3, 'K562')
```

plot_heatmap *Visualize the model output*

Description

Visualize the model output

Usage

```
plot_heatmap(obj, type = "emission", ...)
```

Arguments

obj	A segmentation object
type	A string. Which kind of parameter to print. Default is 'emission' and possible values are 'emission', 'transition', 'overlap', 'TSS' or 'TES'
...	Other arguments to path to Heatmap

Value

A heatmap

Examples

```
plot_heatmap(test_obj)
```

range_bins *Format the loaded binarized data*

Description

The function takes the `data.frames` of the loaded binarized data files and format them into `GRanges` or `SummarizedExperiment` objects.

Usage

```
range_bins(bins, chromsizefile, binsize, return = "GRanges", tidy = TRUE)
```

Arguments

bins	A `list` of the `read_bins_file` output.
chromsizefile	A string. The path to the chromosomes sizes file.
binsize	An integer. The number in bp used to generate binarized files.
return	A string. Possible values are `GRanges` (default) or `SummarizedExperiment`.
tidy	A `logical`. Default is `TRUE`. Whether to tidy the metadata columns of the `GRanges` object.

Value

GRanges (default) or SummarizedExperiment.

---

range_counts *Format the loaded counts data*

Description

The function takes the data.frames of the loaded counts data and format them into GRanges or SummarizedExperiment objects.

Usage

```
range_counts(
  counts,
  features,
  return = "GRanges",
  tidy = FALSE,
  average = FALSE,
  marks
)
```

Arguments

counts	A matrix of the read_bam_file output.
features	A GRanges. That was used to count the bam files.
return	A string. Possible values are GRanges (default) or SummarizedExperiment.
tidy	A logical. Default is TRUE. Whether to tidy the metadata columns of the GRanges object.
average	A logical. Default is FALSE. Whether to average the counts by marks before building the object.
marks	A character vector. The length shoud equal the numbe of columns in counts and is used for averaging and renaming the matrix columns.

Value

GRanges (default) or SummarizedExperiment.

read_bam_file *Read* bam *files*

Description

Count the reads in each range of the GRanges object

Usage

```
read_bam_file(file, features, ...)
```

Arguments

file	A string. The path to the file.
features	A GRanges object.
...	Other arguments passed to bamCount.

Value

A matrix

Examples

```
# locate the bam file
bam_file <- system.file("extdata", "randomBam.bam", package = "bamsignals")

# load a granges object
rand_anno <- system.file("extdata",
                         "randomAnnot.Rdata",
                         package = "bamsignals")
features <- GenomicRanges::promoters(get(load(rand_anno)))

# count reads in ranges
read_bam_file(bam_file, features)
```

read_bins_file *Read* bins *files*

Description

The files contain the cell and the chromosome info in the first line and the binarized data from all marks in the rest.

Usage

```
read_bins_file(file)
```

Arguments

file	A string. The path to the file.

Value

A list of 3 items: cell, seqname and binaries.

Examples

```
# locate the file
fl <- system.file('extdata/SAMPLEDATA_HG18/',
                  'GM12878_chr11_binary.txt.gz',
                  package = 'segmenter')

# read the file
read_bins_file(fl)
```

---

read_cellmark_file *Read* cellmarktable *file*

Description

The file should contain at least three columns: cell, mark and file for the names of the cells/conditions, the available marks and binarized data files.

Usage

```
read_cellmark_file(file)
```

Arguments

file	A string. The path to the file.

Value

A data.frame

Examples

```
# locate the file
fl <- system.file('extdata',
                  'cell_mark_table.tsv',
                  package = 'segmenter')

# read the file
read_cellmark_file(fl)
```

read_chromsize_file *Read* chromsizefile

Description

The file should contain exactly two columns. One for the name of the chromosome and the other for its length.

Usage

```
read_chromsize_file(file)
```

Arguments

file	A string. The path to the file.

Value

A data.frame

Examples

```
# locate the file
chromsizefile <- system.file('extdata/CHROMSIZES',
                             'hg18.txt',
                             package = 'chromhmmData')

# read the file
read_chromsize_file(chromsizefile)
```

read_emissions_file *Read* emissions *file*

Description

The segments files are the output of running learn_model and named emissions_3_segment.bed

Usage

```
read_emissions_file(file, states, marks)
```

Arguments

file	A string. The path to the file.
states	A character vector. The names of the states.
marks	A character vector. The names of the marks

Value

A matrix

Examples

```
# locate the file
fl <- file.path(tempdir(), 'emissions_3.txt')

# read the file
read_emissions_file(fl)
```

---

read_enrichment_file *Read* enrichment *files*

Description

The segments files are the output of running learn_model and named <cell>_3_TSS.txt or <cell>_3_TES.txt.

Usage

```
read_enrichment_file(file, states, regions)
```

Arguments

file	A string. The path to the file.
states	A character vector. The names of the states.
regions	A character vector. The names of the regions.

Value

A matrix

Examples

```
# locate the file
fl <- file.path(tempdir(), 'GM12878_3_RefSeqTSS_neighborhood.txt')

# read the file
read_enrichment_file(fl)
```

read_model_file *Read* modelfile

Description

The model file is the output of running learn_model and named model_#.txt

Usage

```
read_model_file(file)
```

Arguments

file	A string. The path to the file.

Value

A data.frame

Examples

```
# locate the file
modelfile <- file.path(tempdir(), 'model_3.txt')

# read the file
read_model_file(modelfile)
```

read_overlap_file *Read* segments *files*

Description

The segments files are the output of running learn_model and named <cell>_3_overlap.txt

Usage

```
read_overlap_file(file, states, regions)
```

Arguments

file	A string. The path to the file.
states	A character vector. The names of the states.
regions	A character vector. The names of the regions.

Value

A matrix

Examples

```
# locate the file
fl <- file.path(tempdir(), 'GM12878_3_overlap.txt')

# read the file
read_overlap_file(fl)
```

---

read_segements_file *Read* segments *files*

Description

The segments files are the output of running learn_model and named <cell>_3_segment.bed

Usage

```
read_segements_file(file, states)
```

Arguments

file	A string. The path to the file.
states	A character vector. The names of the states.

Value

A data.frame

Examples

```
# locate the file
segmentfile <- file.path(tempdir(), 'GM12878_3_segments.bed')

# read the file
segs <- read_segements_file(segmentfile)
head(segs)
```

read_transitions_file *Read* transitions *file*

Description

The segments files are the output of running learn_model and named transitions_3_segment.bed

Usage

```
read_transitions_file(file, states)
```

Arguments

file	A string. The path to the file.
states	A character vector. The names of the states.

Value

A matrix

Examples

```
# locate the file
fl <- file.path(tempdir(), 'transitions_3.txt')

# read the file
read_transitions_file(fl)
```

segmentation *segmentation objects*

Description

The segmentation class consists of matrices and lists. The components contain the output of the chromatin segmentation analysis. Loading the input data is optional. The object is returned as a result of calling learn_model or reading its already existing output.

Slots

model list. The list consists of 6 items corresponding to the contents of the model_#.txt file. These are number_states and number_marks for the numbers of states and marks in the model; likelihood and probinit for the likelihood and the initial probabilities of the multi-state model; transitionprobs and emissionprobs for the probabilities of the transitions and emissions parameters of the model. Can be accessed using model.

`emission` matrix. The `matrix` contains the emission parameters of n states (rows) for n marks (columns) corresponding to the contents of the `emission_#.txt` file. Can be accessed using `emission`.

`transition` matrix. The `matrix` contains the transition parameters of n by n states corresponding to the contents of the `transition_#.txt` file. Can be accessed using `transition`.

`overlap` list. A `list` of n number of cells/conditions items. Each item is a `matrix` of the overlap enrichment of n states (rows) at n genomic annotations (columns) corresponding to the contents of the `<cell>_#_overlap.txt` files. Can be accessed using `overlap`.

`TSS` list. A `list` of n number of cells/conditions items. Each item is a `matrix` of the overlap enrichment of n states (rows) at n locations around the transcription start site (TSS) (columns) corresponding to the contents of the `<cell>_#_TSS_neighborhood.txt` files. Can be accessed using `TSS`.

`TES` list. A `list` of n number of cells/conditions items. Each item is a `matrix` of the overlap enrichment of n states (rows) at n locations around the transcription end site (TES) (columns) corresponding to the contents of the `<cell>_#_TES_neighborhood.txt` files. Can be accessed using `TES`.

`segment` list. A `list` of n number of cells/conditions items. Each item is a `GRanges` object containing the segmentation and assigned states as a metadata column 'state'. These contents correspond to the `<cell>_#_segment.bed` files. Annotations of the ranges are optional. Can be accessed using `segment`.

`bins` list. A `list` of n number of cells/conditions items. Each item is a `SummarizedExperiment` object containing the binarized input data. The coordinates of the bins are saved as the `rowRanges` each assigned to a state and the binary data itself is saved as `assay`. Can be accessed using `bins`.

`counts` list. A `list` of n number of cells/conditions items. Each item is a `SummarizedExperiment` object containing the read counts in bins. The coordinates of the bins are saved as the `rowRanges` each assigned to a state and the counts data itself is saved as `assay`. Can be accessed using `counts`.

See Also

`learn_model`

`segments_files` *Make segments file names*

Description

Make segments file names

Usage

```
segments_files(numstates, cells)
```

Arguments

numstates	An integer
cells	A character vector

Value

A character vector

Examples

```
segments_files(3, 'K562')
```

---

test_obj *A segmentation object generated from the test data*

Description

A segmentation object generated by running lean_model on the test dataset in 'inst/extdata/ChromHMM/SAMPLEDATA_H
The source code to this run is in 'inst/script/test_obj.R'

Usage

```
test_obj
```

Format

An object of class segmentation of length 1.

---

test_objs *A a list of segmentation objects generated from the test data*

Description

A segmentation object generated by running lean_model on the test dataset in 'inst/extdata/ChromHMM/SAMPLEDATA_H
for 3 to 8 states. The source code to this run is in 'inst/script/test_objs.R'

Usage

```
test_objs
```

Format

An object of class list of length 6.

tidy_ranges *Tidy the metadata of a* GRanges *object*

Description

Tidy the metadata of a GRanges object

Usage

```
tidy_ranges(gr, columns, low = 0)
```

Arguments

gr	A GRanges object
columns	A character vectors. The names of columns to be tidied.
low	An integer. All values <= this integer will be removed.

Value

A GRanges object

Examples

```
tidy_ranges(segment(test_obj, cell = 'K562')[[1]])
```

transitions_file *Make transitions file name*

Description

Make transitions file name

Usage

```
transitions_file(numstates)
```

Arguments

numstates	An integer

Value

A string

Examples

```
transitions_file(3)
```

Index

∗ **datasets**
    test_obj, 28
    test_objs, 28
.Binarize, 3
.LearnModel, 3

accessors, 4
annotate_segments, 7
annotatePeak, *7*
assay, *27*

bamCount, *20*
binarize_bam, 8
binarize_bed, 9
bins, *27*
bins *(*accessors*)*, 4
bins,segmentation-method *(*accessors*)*, 4

cells *(*accessors*)*, 4
cells,segmentation-method *(*accessors*)*, 4
class:segmentation *(*segmentation*)*, 26
compare_models, 10
count_reads_ranges, 10
counts, *27*
counts *(*accessors*)*, 4
counts,segmentation-method *(*accessors*)*, 4

emission, *27*
emission *(*accessors*)*, 4
emission,segmentation-method *(*accessors*)*, 4
emissions_file, 11
enrichment_files, 11

get_frequency, 12
get_width, 13
GRanges, *27*

learn_model, 13, *26, 27*
likelihood *(*accessors*)*, 4
likelihood,segmentation-method *(*accessors*)*, 4

markers *(*accessors*)*, 4
markers,segmentation-method *(*accessors*)*, 4
merge_segments_bins, 15
methods, 16
model, *26*
model *(*accessors*)*, 4
model,segmentation-method *(*accessors*)*, 4
model_file, 16

overlap, *27*
overlap *(*accessors*)*, 4
overlap,segmentation-method *(*accessors*)*, 4
overlap_files, 17

plot_heatmap, 18

range_bins, 18
range_counts, 19
read_bam_file, 20
read_bins_file, 20
read_cellmark_file, 21
read_chromsize_file, 22
read_emissions_file, 22
read_enrichment_file, 23
read_model_file, 24
read_overlap_file, 24
read_segements_file, 25
read_transitions_file, 26
rowRanges, *27*

segment, *27*
segment *(*accessors*)*, 4
segment,segmentation-method *(*accessors*)*, 4
segmentation, *14*, 26
segmentation-class *(*segmentation*)*, 26

segments_files, 27
show,segmentation-method *(*methods*)*, 16
states *(*accessors*)*, 4
states,segmentation-method *(*accessors*)*, 4
SummarizedExperiment, *27*

TES, *27*
TES *(*accessors*)*, 4
TES,segmentation-method *(*accessors*)*, 4
test_obj, 28
test_objs, 28
tidy_ranges, 29
transition, *27*
transition *(*accessors*)*, 4
transition,segmentation-method *(*accessors*)*, 4
transitions_file, 29
TSS, *27*
TSS *(*accessors*)*, 4
TSS,segmentation-method *(*accessors*)*, 4